

## 151679-9 Product Details

[Share](#) [Print](#) [Email](#)

**151679-9**

TE Internal Number: 151679-9

[View 3D PDF](#)
**.200" Centerline, 250 V, 13 A max.**
[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)
**Product Highlights:**

- Commercial MATE-N-LOK Product Line
- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing

[View all Features](#)
**Quick Links**

- [Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[\[+\] Feedback](#)
[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)
**Documentation & Additional Information**
**Product Drawings:**

- [2 way mate-n-lok pin housing \(PDF, English\)](#)

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files: (CAD Format & Compression Information)**

- [2D Drawing \(DXF, Version S\)](#)
- [3D Model \(IGES, Version S\)](#)
- [3D Model \(STEP, Version S\)](#)

[List all Documents](#)
**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

**Product Features (Please use the Product Drawing for all design activity)**
**Product Type Features:**

- Product Line = Commercial MATE-N-LOK
- Product Type = Connector
- Connector Type = Housing
- Sealed = No
- UL File Number = E28476
- CSA File Number = LR 16455

**Mechanical Attachment:**

- Mating Retention Type = Positive Lock
- Panel Mount Retention = Without

**Electrical Characteristics:**

- Operating Voltage Reference = AC
- Operating Voltage (VAC) = 250

**Body Features:**

- Mating Retention = With

**Contact Features:**

- Contact Type = Pin
- Contact Layout = In-Line

**Housing Features:**

- Connector Style = Pin (Cap)
- Housing Color = Black
- Centerline (mm [in]) = 3.56 [0.140]
- Mating Alignment = With
- Mating Alignment Type = Polarization
- Housing Material = Nylon 66
- UL Flammability Rating = UL 94V-0

**Configuration Features:**

- Number of Positions = 2
- Number of Rows = 1

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant
- [VDE Tested](#) = No
- [Agency/Standard](#) = UL, CSA
- [UL Rating](#) = Certified, Recognized

**Identification Marking:**

- Circuit Identification Feature = With

**Environmental:**

- Operating Temperature (°C [°F]) = -55 - +105 [-67 - +221]

**Conditions for Usage:**

- Applies To = Wire/Cable
- For Use With = Socket (Plug) Housing

**Operation/Application:**

- Application Use = Wire-to-Wire

**Packaging Features:**

- Packaging Method = Bag
- Packaging Quantity = 500

**Other:**

- Brand = AMP

**Corporate Information**
[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
**Quick Links**
[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)
**Customer Support**
[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)
**Keep Me Informed**
