

Product data sheet

Characteristics

NSYTBS11116

ABS box IP66 IK07 RAL7035

Int.H105W105D55 Ext.H116W116D62 Opaque
cover H10



Main

Range	Thalassa
Product name	Thalassa TBS
Device application	Multi-purpose
Category	Industrial box
Height	4.57 in (116 mm)
Maximum Width	4.57 in (116 mm)
Depth	2.44 in (62 mm)
Internal height	4.13 in (105 mm)
Internal width	4.13 in (105 mm)
Internal depth	2.17 in (55 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Quantity per set	Set of 5
Body type	One piece moulded
Type of front cover	Low plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Color	Grey (RAL 7035)
Standards	IEC 62208
Product certifications	TÜV
Electrical insulation class	Class II
IP degree of protection	IP66 NEMA 4.4X
IK degree of protection	IK07 conforming to IEC 62262
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11
Ambient air temperature for storage	5...104 °F (-15...40 °C)
Operating temperature	-13...140 °F (-25...60 °C)
Net Weight	0.33 lb(US) (0.151 kg)

Ordering and shipping details

Category	80033 - ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	03606480165252
Nbr. of units in pkg.	5
Package weight(Lbs)	0.34 lb(US) (0.15 kg)
Returnability	No
Country of origin	HU

Packing Units

Package 1 Height	4.92 in (125.000 mm)
Package 1 width	4.80 in (122.000 mm)
Package 1 Length	13.03 in (331.000 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------