




REVISION RECORD			
REV.	CONTENT	MOD.	DATE
	新发行		



NOTES:

1. Voltage Rating: 300V, Current Rating: 8A
2. PITCH: 3.81mm
3. Insulation Withstands Voltage: AC2500V/min
4. Using Temperature Range: -40°C - $+105^{\circ}\text{C}$
5. Suitable Electric Wire: 28-16AWG
6. Screw Torque Value: 0.2Nm

技术要求:

1. 额定电压: 300V, 额定电流: 8A
2. 间距: 3.81mm
3. 耐电压值: AC 2500V/min
4. 使用条件: -40° - $+105^{\circ}$
5. 适用线规: 28-16AWG
6. 螺丝扭力: 0.2Nm

	pitch dimension			Nominal dimension					
	over 0 to 6	over 6 to 10	over 10 to 24	over 0 to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	
variable range	0 to 6	6 to 10	10 to 24	0 to 30	30 to 60	60 to 100	100 to 150	150	
Tolerance	± 0.1	± 0.15	± 0.25	± 0.2	± 0.3	± 0.5	± 0.7	± 1.0	0.05/10

5	LC1-3.81-螺丝	SP0YA204801V	5	碳钢	三价铬钝化彩锌
4	LC1-3.81-夹子	1002B0001AV	5	磷青铜	镀锡
3	LC1-3.81-铜方块	F1A0BLC3813V	5	黄铜	镀镍
2	LC1-3.81-盖子	1002C0YXXAV	1	PA66-V0	
1	LC1-3.81-本体	1002A0YXXAV	1	PA66-V0	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	ARKINE	DATE	2010/5/8	UNITS	mm
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
DWG NO.				SP-2-1002002	REV: V0
TITILE				LC1-3.81-3P-1Y-00A	
				LC1-3.81-成品	



上海联捷电气有限公司
Shanghai Elinker Electric CO., LTD