



RoHs Have HF

VER	MARK	PR. BY	ECR/ECN DESCRIPTION	DATE
A	△	LRB	新图纸发行	2021. 11. 02
B	△	LRB	更新工程图框	2023. 12. 11
C	△	LRB	依实物修改尺寸公差	2024. 12. 12

- NOTES:
- ELECTRONIC:
CONTACT RESISTANCE: 30mohm MAX
INSULATION RESISTANCE: 1000 Mohm MIN
WITHSTAND VOLTAGE: AC 500V,1min.
 - MECHANICAL:
MATING FORCE: 35N MAX.
UNMATED FORCE: 10N MIN.
DURABILITY: 1500 CYCLE.
 - ENVIRONMENT CHARACTERISTICS:
OPERTING TEMPERATURE: -25°C TO +85°C

NO.	PART NAME	Q' TY	MATERIAL	FINISH
3	Shell	1	Copper Aiioy	Nickel Plating
2	Contact	8	Copper Aiioy	Gold plating on contact area and Tin plating on welding area
1	Housing	1	Hing Temperature	BLACK

TITLE:
 双层USB2.0 AF 板上15.40mm DIP 外壳无卷边 弯脚
CST 深圳市科新成电子有限公司
Shenzhen Cosantra Electronics CO.,LTD

TOLERANCE		APPROVAL:		UNIT:	PART NO:
LINEAR:	ANGLE:	Eric.Zhu		mm	CSTU-1714-1912
X. ±0.30	X° ±4°	CHECK:		SIZE:	DWG.NO:
X.X ±0.25	X.X° ±3°	Rick		A4	-----
X.XX ±0.20	X.XX° ±2.5°	REV:	DRAWN:	SCALE:	PRJ.:
CUSTOMER	C	C	LRB	1:1	⊙
				SHEET:	1/2