





RoHS

SPECIFICATIONS

Rated Current:3.0AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°C to +105°C

Contact Material:Brass
 Contact Plating:Au Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)



Dimension antitheses list					
ITEM	PB	PC	PW	H	W
001	9.0		7.1	8.5	5.0
002					

深圳市连盛精密连接器有限公司

				OPERATION		DRAW		SCALE		FIT	
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM	TOL	APPROVE	PROJ.	UNIT	SHEET	
A0	2012.03.28	NEW DRAWING			X.X	±0.30			mm	1/1	
					X.XX	±0.20	CHECK				
					X.XXX	±0.10			A4		
					Angle	±3'					

PART NO.		1020300860
TITLE:		2.54FH H=8.5 W=5.0 2*13P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T