




TM25H03DF

N+N-Channel Enhancement Mosfet

General Description • Low $R_{DS(ON)}$ • RoHS and Halogen-Free Compliant Applications • Load switch • PWM	General Features $V_{DS} = 30V$ $I_D = 25A$ $R_{DS(ON)} = 14\text{ m}\Omega$ (Typ.) @ $V_{GS} = 10V$ 100% UIS Tested 100% R_g Tested 																																																							
D1 D1 D2 D2  S1 G1 S2 G2 Marking:304 DF:DFN3x3-8L  																																																								
Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise noted) <table><tr><th>Symbol</th><th>Parameter</th><th>Rating</th><th>Units</th></tr><tr><td>V_{DS}</td><td>Drain-Source Voltage</td><td>30</td><td>V</td></tr><tr><td>V_{GS}</td><td>Gate-Source Voltage</td><td>± 20</td><td>V</td></tr><tr><td>$I_D @ T_C = 25^\circ\text{C}$</td><td>Continuous Drain Current, $V_{GS} @ 10V^1$</td><td>25</td><td>A</td></tr><tr><td>$I_D @ T_C = 100^\circ\text{C}$</td><td>Continuous Drain Current, $V_{GS} @ 10V^1$</td><td>14</td><td>A</td></tr><tr><td>I_{DM}</td><td>Pulsed Drain Current²</td><td>76</td><td>A</td></tr><tr><td>EAS</td><td>Single Pulse Avalanche Energy³</td><td>12.1</td><td>mJ</td></tr><tr><td>$P_D @ T_C = 25^\circ\text{C}$</td><td>Total Power Dissipation⁴</td><td>6.0</td><td>W</td></tr><tr><td>T_{STG}</td><td>Storage Temperature Range</td><td>-55 to 150</td><td>$^\circ\text{C}$</td></tr><tr><td>T_J</td><td>Operating Junction Temperature Range</td><td>-55 to 150</td><td>$^\circ\text{C}$</td></tr></table> Thermal Data <table><tr><th>Symbol</th><th>Parameter</th><th>Typ.</th><th>Max.</th><th>Unit</th></tr><tr><td>$R_{\theta JA}$</td><td>Thermal Resistance Junction-Ambient ¹</td><td>---</td><td>62</td><td>$^\circ\text{C/W}$</td></tr><tr><td>$R_{\theta JC}$</td><td>Thermal Resistance Junction-Case¹</td><td>---</td><td>3.6</td><td>$^\circ\text{C/W}$</td></tr></table>		Symbol	Parameter	Rating	Units	V_{DS}	Drain-Source Voltage	30	V	V_{GS}	Gate-Source Voltage	± 20	V	$I_D @ T_C = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10V^1$	25	A	$I_D @ T_C = 100^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10V^1$	14	A	I_{DM}	Pulsed Drain Current ²	76	A	EAS	Single Pulse Avalanche Energy ³	12.1	mJ	$P_D @ T_C = 25^\circ\text{C}$	Total Power Dissipation ⁴	6.0	W	T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$	T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$	Symbol	Parameter	Typ.	Max.	Unit	$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	---	62	$^\circ\text{C/W}$	$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	---	3.6	$^\circ\text{C/W}$
Symbol	Parameter	Rating	Units																																																					
V_{DS}	Drain-Source Voltage	30	V																																																					
V_{GS}	Gate-Source Voltage	± 20	V																																																					
$I_D @ T_C = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10V^1$	25	A																																																					
$I_D @ T_C = 100^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10V^1$	14	A																																																					
I_{DM}	Pulsed Drain Current ²	76	A																																																					
EAS	Single Pulse Avalanche Energy ³	12.1	mJ																																																					
$P_D @ T_C = 25^\circ\text{C}$	Total Power Dissipation ⁴	6.0	W																																																					
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$																																																					
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$																																																					
Symbol	Parameter	Typ.	Max.	Unit																																																				
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	---	62	$^\circ\text{C/W}$																																																				
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	---	3.6	$^\circ\text{C/W}$																																																				



TM25H03DF

N+N-Channel Enhancement Mosfet

Electrical Characteristics (T_J=25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V	-	-	1	μA
I _{GSS}	Gate to Body Leakage Current	V _{DS} =0V, V _{GS} =±20V	-	-	±100	nA
On Characteristics						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	0.9	1.2	1.5	V
R _{DS(on)}	Static Drain-Source on-Resistance note2	V _{GS} =10V, I _D =5A	-	14	17	mΩ
		V _{GS} =4.5V, I _D =3A	-	18	26	mΩ
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =15V, V _{GS} =0V, f=1.0MHz	-	520	-	pF
C _{oss}	Output Capacitance		-	79	-	pF
C _{rss}	Reverse Transfer Capacitance		-	61	-	pF
Q _g	Total Gate Charge	V _{DS} =15V, I _D =5.8A, V _{GS} =10V	-	5.2	-	nC
Q _{gs}	Gate-Source Charge		-	0.9	-	nC
Q _{gd}	Gate-Drain(“Miller”) Charge		-	1.3	-	nC
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time	V _{DS} =15V, I _D =3A, V _{GS} =10V, R _{REN} =3Ω	-	4.5	-	ns
t _r	Turn-on Rise Time		-	2.5	-	ns
t _{d(off)}	Turn-off Delay Time		-	14.5	-	ns
t _f	Turn-off Fall Time		-	3.5	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I _S	Maximum Continuous Drain to Source Diode Forward Current		-	-	25	A
I _{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	48	A
V _{SD}	Drain to Source Diode Forward Voltage	V _{GS} =0V, I _S = 12A	-	-	1.2	V

Note :

1. The data tested by surface mounted on a 1 inch² FR-4 board with 20Z copper.
2. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
3. The EAS data shows Max. rating . The test condition is V_{DD}=25V, V_{GS}=10V, L=0.1mH, I_{AS}=21A
4. The power dissipation is limited by 150°C junction temperature
5. The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.

TM25H03DF

N+N-Channel Enhancement Mosfet

Typical Performance Characteristics

Figure1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics





Figure 6: Capacitance Characteristics



TM25H03DF

N+N-Channel Enhancement Mosfet

Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature






Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



TM25H03DF

N+N-Channel Enhancement Mosfet

Package Mechanical Data:DFN3x3-8L




Symbol	Common		
	Mm		
	Min	Nom	Max
A	0.70	0.75	0.85
A1	/	/	0.05
b	0.25	0.30	0.39
c	0.14	0.152	0.20
D	3.20	3.30	3.45
D1	3.05	3.15	3.25
D2	0.84	1.04	1.24
D3	2.30	2.45	2.60
E	3.20	3.30	3.40
E1	2.95	3.05	3.15
E2	1.60	1.74	1.90
E3	0.28	0.48	0.65
E4	0.37	0.57	0.77
E5	0.10	0.20	0.30
e	0.60	0.65	0.70
K	0.50	0.69	0.80
K1	0.30	0.38	0.53
K2	0.15	0.25	0.35
L	0.30	0.40	0.50
L1	0.06	0.125	0.20
L2	0.27	0.42	0.57
t	0	0.075	0.13
Φ	10°	12°	14°

TM25H03DF

N+N-Channel Enhancement Mosfet

PDFN3×3-8L Embossed Carrier Tape




Packaging Description:

SOP-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 2,500 units per 13" or 33cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).


ALL DIM IN mm

Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
PDFN3×3-8L	6.40	5.40	2.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

PDFN3×3-8L Tape Leader and Trailer



PDFN3×3-8L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
13"Dia	Ø330.00	100.00	13.00	R135.00	R55.00	R6.50	12.00	14.00

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
5,000 pcs	13 inch	10,000 pcs	370×355×52	50,000 pcs	400×360×368	

TM25H03DF**N+N-Channel Enhancement Mosfet****Important Notices and Disclaimers**

- Tritech-MOS Technology Corp. reserves the right to change this document, its products, and specifications at any time without prior notice.
- Before final design, purchase, or use, customers should obtain and confirm the latest product information and specifications.
- Tritech-MOS Technology Corp. makes no warranties, representations or warranties regarding the suitability of its products for any specific purpose, and Tritech-MOS Technology Corp. does not assume any responsibility for application assistance or customer product design.
- Tritech-MOS Technology Corp. does not guarantee or assume any responsibility for the purchase or use of any unexpected or unauthorized products.
- Any intellectual property rights of Tritech-MOS Technology Corp. are not licensed through implicate or other means.
- Products of Tritech-MOS Technology Corp. are not included as critical components in life support equipment or systems without explicit written approval from Tritech-MOS Technology Corp.

Revision history:

Date	Rev	Description	Page
2023.05.14	23.05	Original	