


NOTES:

- 1.HUOSING: PA9T HIGH-TEMP THERMOPLASTIC UL94V-0 COLOR:BLACK
 2.TERMINAL:PHOSPHOR BRONZE
 PLATING:1µ"GOLD FLASH OVERALL 50~100µ"NICEL UNDER PLATED.
 3.CODING INFORMATION: LB250-GxxP-B0R



PLATING: G:GOLD FLASH
 PIN
 PLUG
 COLOR:BLACK
 STANDARD TYPE
 PACKING: R: CARRIER REEL
 0.5 BTB
 MATING HEIGHT: 30--3.0H;35--3.5H;
 40--4.0H;45--4.5H;
 50--5.0H;55--5.5H;

— xxlconn BTB CONNECTOR SERIES



MATING HEIGHT	PLUG (H.)	SOCKET (H.)	E	No.of contac- ts	Dimensions				No.of contac- ts	Dimensions			
					A.	B.	C.	D.		A.	B.	C.	D.
3.0	0.8	2.2	1.6	4	3.70	0.50	1.50	2.40	54	16.20	13.00	14.00	14.90
3.5	1.3	2.2	1.6	6	4.20	1.00	2.00	2.90	56	16.70	13.50	14.50	15.40
4.0	1.0	3.0	1.9	8	4.70	1.50	2.50	3.40	58	17.20	14.00	15.00	15.90
4.5	1.0	3.5	1.9	10	5.20	2.00	3.00	3.90	60	17.70	14.50	15.50	16.40
5.0	1.0	4.0	1.9	12	5.70	2.50	3.50	4.40	62	18.20	15.00	16.00	16.90
5.5	1.0	4.5	1.9	14	6.20	3.00	4.00	4.90	64	18.70	15.50	16.50	17.40
6.0	2.0	4.0	1.9	16	6.70	3.50	4.50	5.40	66	19.20	16.00	17.00	17.90
6.5	2.0	4.5	1.9	18	7.20	4.00	5.00	5.90	68	19.70	16.50	17.50	18.40
				20	7.70	4.50	5.50	6.40	70	20.20	17.00	18.00	18.90
				22	8.20	5.00	6.00	6.90	72	20.70	17.50	18.50	19.40
				24	8.70	5.50	6.50	7.40	74	21.20	18.00	19.00	19.90
				26	9.20	6.00	7.00	7.90	76	21.70	18.50	19.50	20.40
				28	9.70	6.50	7.50	8.40	78	22.20	19.00	20.00	20.90
				30	10.20	7.00	8.00	8.90	80	22.70	19.50	20.50	21.40
				32	10.70	7.50	8.50	9.40	82	23.20	20.00	21.00	21.90
				34	11.20	8.00	9.00	9.90	84	23.70	20.50	21.50	22.40
				36	11.70	8.50	9.50	10.40	86	24.20	21.00	22.00	22.90
				38	12.20	9.00	10.00	10.90	88	24.70	21.50	22.50	23.40
				40	12.70	9.50	10.50	11.40	90	25.20	22.00	23.00	23.90
				42	13.20	10.00	11.00	11.90	92	25.70	22.50	23.50	24.40
				44	13.70	10.50	11.50	12.40	94	26.20	23.00	24.00	24.90
				46	14.20	11.00	12.00	12.90	96	26.70	23.50	24.50	25.40
				48	14.70	11.50	12.50	13.40	98	27.20	24.00	25.00	25.90
				50	15.20	12.00	13.00	13.90	100	27.70	24.50	25.50	26.40

东莞市洋瀚实业有限公司

				一般公差 GENERAL TOLERANCE	Kavin 制图 (DR) : 2016.07.05	品名(TITLE): 0.5mm 双槽BTB PLUG
				X ± 0.25		
				XX ± 0.15		
				XXX ± 0.05		
				ANGLES $\pm 1^\circ$	审核 (CHKD) :	料号(PART NO): LB250-GxxP-B0R
修订 SER	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE	版本 (REV) A 	比例(SCALE) 核准(APPD): 1:8	单位(UNITS) mm 张数(SHEET) 1 OF 1 图幅(SIZE) A4