

1	2	3	4	5	6	7																									
						修正(标记)	描述	日期																							
A							<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td colspan="2">主要技术性能</td><td>公 差</td></tr> <tr><td>额定电负荷</td><td>DC 30V\0.5A</td><td>X.±0.20</td></tr> <tr><td>接触电阻</td><td>≤0.03Ω</td><td>.X±0.10</td></tr> <tr><td>绝缘电阻</td><td>≥100MΩ</td><td>.XX±0.05</td></tr> <tr><td>耐 压</td><td>AC500V(50Hz)/min</td><td>.XXX±0.02</td></tr> <tr><td>插 拔 力</td><td>3-20N</td><td>X°±5°</td></tr> <tr><td>使 用 温 度 范 围</td><td>-30-70°C</td><td>X°±2°</td></tr> <tr><td>使 用 寿 命</td><td>5000次</td><td>.XX°±1°</td></tr> </table>	主要技术性能		公 差	额定电负荷	DC 30V\0.5A	X.±0.20	接触电阻	≤0.03Ω	.X±0.10	绝缘电阻	≥100MΩ	.XX±0.05	耐 压	AC500V(50Hz)/min	.XXX±0.02	插 拔 力	3-20N	X°±5°	使 用 温 度 范 围	-30-70°C	X°±2°	使 用 寿 命	5000次	.XX°±1°
主要技术性能		公 差																													
额定电负荷	DC 30V\0.5A	X.±0.20																													
接触电阻	≤0.03Ω	.X±0.10																													
绝缘电阻	≥100MΩ	.XX±0.05																													
耐 压	AC500V(50Hz)/min	.XXX±0.02																													
插 拔 力	3-20N	X°±5°																													
使 用 温 度 范 围	-30-70°C	X°±2°																													
使 用 寿 命	5000次	.XX°±1°																													
B							线路板开孔尺寸																								
C																															
D							<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>PIN</td><td>φ 1.65</td><td>φ 2.0</td><td>φ 2.5</td></tr> <tr><td>APPO</td><td></td><td></td><td></td></tr> </table>	PIN	φ 1.65	φ 2.0	φ 2.5	APPO																			
PIN	φ 1.65	φ 2.0	φ 2.5																												
APPO																															
E	7						产品名称: DC 电源插座																								
6	DC-005	弹 片	1	锰钢(磷铜)	T=0.25	锡 锡	产品型号: DC-005小脚																								
5	DC-005	插 片	1	H62黄铜带	T=0.30	铜 锡																									
4	DC-005	平 片	1	H62黄铜带	T=0.35	铜 锡																									
3	DC-005	中心针	1	H62黄铜棒		铜 锡																									
2	DC-005	盖 板	1	PBT	黑色		图片编号: ZJF/SZL-DC-005-01128-2017																								
1	DC-005	基 座	1	PBT	黑色																										
序号	产品编号	产品名称	数量	材 料	规 格	电 镀																									
	'1		'2		'3																										
				'4		'5	'6																								
							'7																								

**KKG** 東莞市洋瀚實業有限公司  
TEL : 86-769-82036866 FAX : 86-769-82076788