





RoHS Compliant

REVISIONS							
Rev	DESCRIPTION	DATE	DRAWER	Rev	DESCRIPTION	DATE	DRAWER
A	Initial Drawing	2017.12.11	Jane Shen	C			
B				D			
SPECIFICATIONS							
RATING		DC12V 50mA		TIMING			
CONTACT RESISTANCE		100mΩ MAX.		OPERATION (TORQUE)		160±50 gf	
INSULATION RESISTANCE		DC500V – 100MΩ MIN.		STROKE (ANGLE)		0.25±0.15 mm	
WITHSTAND VOLTAGE		AC250V – 1 MINUTE.		LIFE		100,000 CYCLES	
REMARKS:							




⑧ ⑧ ⑧

SCHEMATIC



P.C.B MOUNTING PLAN



HATCHED AREA SHOWS SOLDERING LAND

TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.2			SIGNATURES		DATE	MODEL
			DRAWER	Jane Shen	2017.12.11	TITLE TACT SWITCH
			CHECKED			
			REVIEWED			NO. ETC014-AA1U-H160TJ
			APPROVALS			
TAIWAN MISAKI ELECTRONICS CO., LTD.						


Standby Shu
Dennis Jfung
2017.12.11

ALL TERMINALS TO BE
PLANAR WITHIN 0.1mm

THE PACKING SPECIFICATIONS


RoHS Compliant

1.STRUCTURE AND MATERIALS



③	COVER TAPE	POLYESTER
②	CARRIER TAPE	POLYSTYRENE
①	REEL	POLYSTYRENE
NO.	PARTS NAME	MATERIALS

- PACKAGING QUANTITY : 400 PCS/REEL
- MORE THAN 10 EMPTY POCKETS SHOULD BE REMAINED AT BOTH ENDS OF THE CARRIER TAPE FOR EACH REEL.
- SHORTAGE LESS THAN 10 PCS A REEL IS ACCETABLE BUT MORE THAN 3 RUNNING POCKETS SHORTAGE IS NOT ALLOWED.
- STRIPPING STRENGTH OF COVER TAPE IS BETWEEN 10 gf TO 130 gf AND STRIPPING ANGLE SHOULD BE WITHIN 165° ~ 180° .
- THE PRODUCT IN THE POCKET OF CARRIER TAPE SHOULD BE PLACED IN A SPECIFIED CORRECT POSITION.
- TAPE AND REEL PER EIA-481.
- DIMENSIONS :



				APPROVED BY	REVIEWED BY	CHECKED BY	DESIGNED BY	MODEL NO.
							Jane Shen	NTC014-AA1U-H
							2011.12.24	PAGINATE.
								1/1
								SPEC NO.
								P-693
SYM	DISCRPTION	DATE	APPROVED					

TAIWAN MISAKI ELECTRONICS CO.,LTD.