






WTC01A05BB


- 1、极数 Number of poles: 2-16
- 2、工作温度 Working Temperature: -40°C $\rightarrow$ $+85^{\circ}\text{C}$
- 3、额定电压 Voltage rating : 125V AC
- 4、额定电流 Rated current : 1A
- 4、接触电阻 Contact resistance: $\leq 30\text{m}\Omega$
- 5、绝缘电阻 Insulation resistance: $\geq 100\text{M}\Omega$
- 6、耐压 Withstand voltage : 250V AC
- 7、端子 Terminal : 黄铜 Brass
外壳 Housing : LCP

PCB. 焊接图
PCB. WELDING DRAWING

	A	B	C
2P	1.25	4.30	7.30
3P	2.50	5.55	8.55
4P	3.75	6.80	9.80
5P	5.00	8.05	11.05
6P	6.25	9.30	12.30
7P	7.50	10.55	13.55
8P	8.75	11.80	14.80
9P	10.00	13.05	16.05
10P	11.25	14.30	17.30
nP	...	...	...
16P	18.75	21.8.	24.80

WT C01A B

极数:
02、03、04、
... 16电镀方式:
B: 亮锡包装方式:
A: 散装
B: 加盖编带
C: 管装

					第一视角 FIRST VIEW 		
标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比例 SCALE	1:1	一般公差 GENERAL TOLERANCE
设计 DESIGN		朱元隆	2022. 12. 01		单位 UNIT	mm	≥0~2< ±0.20
审核 CHECKED		赵晓峰	2022. 12. 01		重量 WEIGHT		≥2~5< ±0.30
批准 APPROVED		陈乐峰	2022. 12. 01				≥5 ±0.50
							角度 ANGLE ±0.5°

名称/NAME:

板上连接器

型号/MODEL:

WTC01A05BB



		Page	1/5								
		MODEL	WTC01XXXXX								
SPECIFICATION											
1、 适用范围											
APPLICATION											
此规格书适用于线对板连接器的相关要求											
This specification is applicable to relevant requirements of wire to board connector											
2、 使用条件											
SERVICE CONDITIONS											
2.1 环境温度：-40℃～+85℃											
Ambient temperature Range: -40℃～+85℃											
3、外观及尺寸											
Appearance and Dimension											
3.1 产品表面不应有对制品有害的缺陷、污垢、裂痕及机械损伤；接触件无锈蚀、镀层氧化、脱落等现象											
Appearance:Product surface without defect、dirt、crack、and mechanical damang,											
Contact without rust,plating not oxided and not peeled											
3.2 外形尺寸：参考图纸											
Dimension:According to drawings											
4、材料											
Material											
<table><tr><td>名 称 NAME</td><td>材 质 MATERIALS</td></tr><tr><td>主体 Main body</td><td>LCP（本色）</td></tr><tr><td>端子 Sit uip</td><td>黄铜</td></tr><tr><td>焊护耳 Solder tabs</td><td>黄铜</td></tr></table>				名 称 NAME	材 质 MATERIALS	主体 Main body	LCP（本色）	端子 Sit uip	黄铜	焊护耳 Solder tabs	黄铜
名 称 NAME	材 质 MATERIALS										
主体 Main body	LCP（本色）										
端子 Sit uip	黄铜										
焊护耳 Solder tabs	黄铜										
5、 电气性能											
Electrical Performance											
NO.	项目 ITEM	试验条件 TEST CONDITIONS	要求 REQUIREMENTS								
5.1	接触电阻 Contact Resistance	适合嵌合状态；开放电压20mV 以下；短路电流 10mA的状态下测定。 Mate applicable and measure by dry circuit, 30mΩ MAX, 10mA	≤ 30mΩ MAX								



SPECIFICATION

5.2

绝缘电阻
Insulation
Resistance

适合嵌合状态；相邻端子间或端子与地面间加DC 100V
下测定。
Mate applicable and apply 100V DC between
adjacent terminal or ground.

 $\geq 100M\Omega$

5.3

耐电压
Dielectric

适合嵌合状态；相邻端子间或端子与地面间加AC250V
（有效值）历时1分钟下测定。
Mate applicable and apply 250V AC(rms)for
lminute between adjacent terminal or ground.

无击穿、无飞弧
There should be no
breakdown and flashover

6、机械性能：

MECHANICAL SPECIFICATION

NO.

项目
ITEM试验条件
TEST CONDITIONS要求
REQUIREMENTS

6.1

端子保持力
Terminal
Retention Force

单一端子；以每分钟 $25\pm 3mm$ 的速度平行向外拉
Pull the terminal at the speed rate of
 $25\pm 3mm$ per minute

 $\geq 1.96N$



SPECIFICATION

7、 环境和其他性能:

ENVIRONMENTAL PERFORMANCE AND OTHERS

NO.	项目 ITEM	试验条件 TEST CONDITIONS	要求 REQUIREMENTS
7.1	重复拔插 Repeated Insertion and Withdrawal	无通电状态; 以10次/分钟的速度插拔20次 Insertion and withdrawal catuator up to 20 cycles at the speed rate of less than 10 cyclea/minute	试验后接触电阻 $\leq 60\text{m}\Omega$
7.2	耐热性 Heat Resistance	适合嵌合状态; $85\pm 2^{\circ}\text{C}$ 的空气中; 放置 96 小时; 再回到室温中放置 1-2 小时 $85\pm 2^{\circ}\text{C}$, 96 hour	试验后外观无损坏, 接触电阻 $\leq 60\text{m}\Omega$

SPECIFICATION

7.4

耐寒性
Cold
Resistance

适合嵌合状态： $-40\pm 2^{\circ}\text{C}$ 的空气中；放置 96 小时；
再回到室温中放置 1-2 小时
 $-40\pm 2^{\circ}\text{C}$ ， 96 hour

试验后外观无损坏，
接触电阻 $\leq 60\text{m}\Omega$

7.5

耐湿性
Humidity

适合嵌合状态； $40\pm 2^{\circ}\text{C}$ 、 相对湿度90-95%的空气中；放置 96 小时； 再回到室温中 0.5 小时内测定
Temperature: $40\pm 2^{\circ}\text{C}$
Relative Humidity: 90-95%
Duration: 96 Hours

试验后外观无损坏，
接触电阻 $\leq 60\text{m}\Omega$
满足耐电压测试，
绝缘电阻 $\geq 20\text{M}\Omega$

7.6

温度循环
Temperature
Cycling

适合嵌合状态； $-40\pm 3^{\circ}\text{C}$ 30 分钟； $85\pm 2^{\circ}\text{C}$ 30 分钟；温度转换时间30分钟，循环5次。
5 cycles of:
a) $-40\pm 3^{\circ}\text{C}$ 30 minutes
B) $85\pm 2^{\circ}\text{C}$ 30 minutes

试验后外观无损坏，
接触电阻 $\leq 60\text{m}\Omega$

SPECIFICATION

7.6	盐雾试验 Salt Mist (铁材质不做盐雾要求)	在嵌合状态以下列设定条件下进行测量: The switch shall be checked after following test: (1) 温度: $35^{\circ}\text{C} \pm 2^{\circ}\text{C}$ temperature: $35^{\circ}\text{C} \pm 2^{\circ}\text{C}$ (2) 盐溶液浓度: $5 \pm 1\%$ (质量百分比) salt solution : $5 \pm 1\%$ (solids by mass) (3) 时间: 8 h Time: 8 h 实验后的盐沉积物后水冲掉 After test, salt deposit shall be removed by running water.	金属件上明显的腐蚀斑点 No remarkable corrosion shall be recognized in metal part.
7.7	可焊性 Solderability	端子前端侵入 $235 \pm 5^{\circ}\text{C}$ 的锡槽中; 历时 2 ± 0.5 sec。 Soldering Time: 2 ± 0.5 sec. Soldering Temperature: $235 \pm 5^{\circ}\text{C}$ 0.2 mm from terminal tip	除边缘外涂层应均匀覆盖 90% 以上 Except for the edge, the coating should cover a minimum 90%

下图为所推荐的回流焊温度曲线图

The following diagram shows the recommended reflow soldering temperature profile.

