

产品规格承认书

Specification For Approval

客户名称:

CUSTOMER:

产品名称:

PRODUCT NAME:

贴片保险丝 SMD FUSE

型号规格:

MODEL DETAIL: 12H (RoHS Compliant) 4A 63V 抗浪涌型(High Inrush Current Withstand)

料号:

PART NO.:

12H1400C

供应商:

深圳市良胜电子有限公司

惠州市良胜电子有限公司

SUPPLIER:

SHENZHEN LANSON ELECTRONICS CO., LTD.

HUIZHOU LANSON ELECTRONICS CO., LTD.

地址:

惠州仲恺高新区沥林镇英光村惠州仲恺中集智城产业园 12 号厂房

ADDRESS:

Factory Building No.12, Zhongji Wisdom City Industrial Park, Zhongkai District, Huizhou.

TEL:0752-3339907

FAX:0755-29929812

Http:www.lansonfuse.com

E-mail:lanson@lansonfuse.com

编制 PREPARED BY	审核 CHECKED BY	批准 APPROVED BY
		

承认 SIGNATURE	审核 CHECKED BY	批准 APPROVED BY

供方签章:

SUPPLIER:

日期:

DATE: 2025.01.20



需方签章:

CUSTOMER:

日期:

DATE:

SHENZHEN LANSON ELECTRONICS CO., LTD.	PRODUCT	EDITION NO.	A/6
	SPECIFICATION	FILE NO.	LS/C-005-34
	MODEL: 12H	PAGE	PAGE 1 OF 4

1. 适用范围 Scope of Application

本产品适用于各种电子电路中起过电流保护作用。
This product is suitable for various kinds of electronic machines to work for over current protection.

2. 相关标准及认证 Relevant Standards and Certification


2.1 执行标准 Standard: UL248-1、UL248-14

2.2 认证 Certification

认证 Certification	认证范围 Scope of Certification	证书编号 Certification No.
UL	100mA~30A	E221465

3. 结构尺寸及原材料明细 Structure Size and Material Detail

3.1 结构尺寸 Structure Size (unit: mm)



3.2 原材料明细 Material Detail

编号 No.	零件名称 Part Name	材质 Material
①	电极 Electrode	银 Silver
②	涂层 Coating	玻璃浆 Glass cover
③	端头 End Termination	镀银 Silver plated
④	熔丝 Fuse element	银 Silver
⑤	基片 Substrate	陶瓷 Ceramic

SHENZHEN LANSON ELECTRONICS CO., LTD.	PRODUCT	EDITION NO.	A/6
	SPECIFICATION	FILE NO.	LS/C-005-34
	MODEL: 12H	PAGE	PAGE 2 OF 4

4. 标示 Mark

4.1 保险丝上需有下列标示:

The fuse shall have the following marking:

额定电流 Ampere Rating	产品标示 Marking
1A	H
1.5A	K
2A	N
2.5A	O
3A	P
3.5A	R
4A	S
5A	T
6A	F
7A	7
8A	V
10	U
12A	W
15A	Y
20A	Q
25A	L
30A	Z

5. 电气特性 Electrical Characteristics

5.1 实验条件: 所有测试环境温度为 25±5℃。

Test Condition: All electrical characteristics tests are conducted at an ambient temperature of 25±5℃.

5.2 时间-电流特性

Time-Current Characteristics

额定电流 Ampere Rating	额定电流的% % of Ampere Rating	熔断时间 Opening Time
1A~5A	100%	4 hours Min(大于 4 小时)
1A~5A	250%	5 S Max(小于 5 秒)
1A~5A	300%	0.1 S~3 S
1A~5A	1000%	0.2 ms~20 ms
6A~30A	100%	4 hours Min(大于 4 小时)
6A~30A	350%	5 S Max(小于 5 秒)

5.3 额定分断能力:

Interrupting Rating:

50 Amperes at 63V DC (100mA~5A)

100 Amperes at 32V DC (6A~10A)

300 Amperes at 24V DC (12A~30A)

SHENZHEN LANSON ELECTRONICS CO., LTD.	PRODUCT	EDITION NO.	A/6
	SPECIFICATION	FILE NO.	LS/C-005-34
	MODEL: 12H	PAGE	PAGE 3 OF 4

6. 环境特性 Environmental Characteristics

6.1 使用温度范围 Operating Temperature
-40℃~125℃。

6.2 保存条件 Storage Conditions
相对湿度≤75%，可以存放 3 年。
Relative humidity≤75%, store 3 years.

6.3 库存产品超过 1 年后需对产品可焊性和产品熔断性能进行验证。
The solderability and performance of the products in stock shall be verified after more than 1 year.

7. 可靠性试验 Reliability Test


7.1 冷热冲击试验 Thermal Shock Test
MIL-STD-202G, Method 107G。

7.2 防潮湿试验 Moisture Resistance Test
MIL-STD-202G, Method 106G。

7.3 振动试验 Vibration Test
MIL-STD-202G, Method 201A。

7.4 可焊性试验 Solderability Test
MIL-STD-202G, Method 208H, IEC60127-2, IEC60068-2。

8. 时间-电流曲线图 Time-Current Curve




SHENZHEN LANSON ELECTRONICS CO., LTD.	PRODUCT	EDITION NO.	A/6
	SPECIFICATION	FILE NO.	LS/C-005-34
	MODEL: 12H	PAGE	PAGE 4 OF 4

9. 焊锡参数 Soldering Parameters

- 9.1 回流焊 Reflow Slodering
- 9.1.1 温度 Temperature 260℃
- 9.1.2 时间 Time ≤10 seconds
- 9.1.3 最大可以承受三次回流焊
Capable for three times reflow
- 9.2 手工焊锡 Hand Soldering
- 9.2.1 温度 Temperature 380℃
- 9.2.2 时间 Time ≤3 seconds

10. 包装 Packing

- 10.1 自动机器包装 3000PCS/卷。Automaton taped 3000PCS per reel.
- 10.2 包装尺寸 Packing Size (unit: mm)





JDYX2.E221465 - Fuses, Supplemental - Component

Fuses, Supplemental - Component

SHENZHEN LANSON ELECTRONICS CO LTD

E221465

A18TH BLDG

3 INDUSTRIAL ZONE

FUQIAO FUYONG TOWN, BAO'AN DISTRICT

SHENZHEN, GUANGDONG 518133 China

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
Supplemental fuses				
5D	5.2 x 20 (0.20 x 0.79)	4-7	125Vac	100
		4-7	250Vac	100
		8-10	125Vac	100
		8-10	250Vac	100
5F	5.2 x 20 (0.20 x 0.79)	0.125-0.315	125Vac	35
		0.125-0.315	250Vac	35
		0.4-0.8	125Vac	35
		0.4-0.8	250Vac	35
		1-6.3	125Vac	35
		1-6.3	250Vac	35
5K	5.2 x 20 (0.20 x 0.79)	0.2-0.8	125Vac	35
		0.2-0.8	250Vac	35
		1-6.3	125Vac	63
		1-6.3	250Vac	63
		8-15	125Vac	50
		8-15	250Vac	50
5M	5.2 x 20 (0.20 x 0.79)	0.5-0.8	250Vac	1500
		1.0-3.15	250Vac	1500

12H	3.2 x 1.6 x 0.65 (0.13 x 0.06 x 0.03)	0.1-5	125Vac	50
		0.1-5	125Vdc	50
		0.1-5	63Vdc	50
		6-10	32Vdc	100
		12-30	24Vdc	300
Supplemental micro fuses: surface mount, cartridge enclosed				
24E	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.1-20	350Vac	50
		0.1-20	300Vac	50
		0.1-20	250Vac	50
		0.1-20	125Vac	50
		0.1-20	125Vdc	50
24F	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.1-7	125Vac	50
		0.1-7	250Vac	50
		0.1-7	125Vdc	50
32E	10.25 x 3.2 x 3.2 (0.40 x 0.13 x 0.13)	0.05-60	250Vac	100
		0.05-60	125Vac	100
		0.05-60	100Vdc	600
		0.05-60	72Vdc	600
		0.05-60	60Vdc	600
		0.05-60	32Vdc	1000

Marking: Company name and model designation.

Last Updated on 2022-02-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



JDYX8.E221465 - Fuses, Supplemental Certified for Canada - Component

Fuses, Supplemental Certified for Canada - Component

SHENZHEN LANSON ELECTRONICS CO LTD
A18TH BLDG
3 INDUSTRIAL ZONE
FUQIAO FUYONG TOWN, BAO'AN DISTRICT
SHENZHEN, GUANGDONG 518133 China

E221465

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
Supplemental fuses				
5D	5.2 x 20 (0.20 x 0.79)	4-7	125Vac	100
		4-7	250Vac	100
		8-10	125Vac	100
		8-10	250Vac	100
5F	5.2 x 20 (0.20 x 0.79)	0.125-0.315	125Vac	35
		0.125-0.315	250Vac	35
		0.4-0.8	125Vac	35
		0.4-0.8	250Vac	35
		1-6.3	125Vac	35
		1-6.3	250Vac	35
5K	5.2 x 20 (0.20 x 0.79)	0.2-0.8	125Vac	35
		0.2-0.8	250Vac	35
		1-6.3	125Vac	63
		1-6.3	250Vac	63
		8-15	125Vac	50
		8-15	250Vac	50
5M	5.2 x 20 (0.20 x 0.79)	0.5-0.8	250Vac	1500

12H	3.2 x 1.6 x 0.65 (0.13 x 0.06 x 0.03)	0.1-5	125Vac	50
		0.1-5	125Vdc	50
		0.1-5	63Vdc	50
		6-10	32Vdc	100
		12-30	24Vdc	300
Supplemental micro fuses: surface mount, cartridge enclosed				
24E	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.1-20	350Vac	50
		0.1-20	300Vac	50
		0.1-20	250Vac	50
		0.1-20	125Vac	50
		0.1-20	125Vdc	50
24F	6.1 x 2.6 x 2.6 (0.24 x 0.10 x 0.10)	0.1-7	125Vac	50
		0.1-7	250Vac	50
		0.1-7	125Vdc	50
32E	10.25 x 3.2 x 3.2 (0.40 x 0.13 x 0.13)	0.05-60	250Vac	100
		0.05-60	125Vac	100
		0.05-60	100Vdc	600
		0.05-60	72Vdc	600
		0.05-60	60Vdc	600
		0.05-60	32Vdc	1000

Marking: Company name, model designation and the Recognized Component Mark for Canada,



Last Updated on 2022-02-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"