

RoHS

SPECIFICATIONS

Rated Current:3.0AMP

Contact Resistance:20mΩ Max

Withstand Voltage:1000V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:-40°C to +105°C

Contact Material:Brass





Contact Plating:Au Or Tin Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PA6T

Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Ordering Information

P	3	D	2	06	1	5	00	X	0037
产品类型 P=排针	间距 3=2.54	塑胶高度 D=2.5	排数 2=双排	单排PIN数 1~40P	产品形态 1=DIP	塑胶材料 1=PB 2=LCP 5=PA6T	电镀厚度 00=常规 01=1u" 02=2u" 03=3u"	包装方式 1=管装 2=卷装 3=盒装 4=袋装 5=直装	序列号

Dimension antitheses list								
ITEM	PA	PW	PC	L1	L2	L3	H	W
001	6.0		3.0	11.5			2.5	5.0
Alternate								

						OPERATION		DRAW				SCALE	FIT	深圳市连盛精密连接器有限公司	
						X.X	±0.30					UNIT	mm		
						X.XX	±0.20	CHECK				SIZE	A4	PART NO.	
						X.XXX	±0.10					SHEET	1/1		
						Angle	±3°	APPROVE				PROJ.	☞	TITLE:	
						DIM	TOL								
A0	2012.03.28	NEW DRAWING													1010300046
REV	DATE	MODIFICATION DESCRIPTION			CHANGE										2.54PH H=2.5 2*6P DIP PA6.0 PC3.0 L=11.5 AU0.6U PA6T