

	2	3	4	5	6	7	8	9					
G	RoHS												
F	SPECIFICATIONS						Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)						
	Rated Current:3.0AMP												
F	Contact Resistance:20mΩ Max												
	Withstand Voltage:1000V AC/DC												
	Insulation Resistance:1000MΩ Min												
	Operation Temperature:-40℃ to +105℃												
	Contact Material:Brass												
	Contact Plating:Au Over Ni												
	Insulator Material:Polyester(UL94V-0)												
E	Standard: PA6T												
	Max.Processing Temp: 230℃ for 30-60 seconds (260℃ for 10 seconds)												
D													
C	Ordering Information												
B	F	3	N	2	08	3	5	01	X	1027			
	产品类型 F=排母	间距 3=2.54	塑胶高度 N=8.5	排数 2=双排	单排PIN数 1~40P	产品形态 3=SMT	塑胶材料 5=PA6T	电镀厚度 00=常规 01=1u" 02=2u" 03=3u"	包装方式 1=管装 2=卷装 3=盒装 4=袋装 5=盒装	序列号			
A													
						OPERATION				SCALE	FIT	深圳市连盛精密连接器有限公司	
						X.X	±0.30	DRAW		UNIT	mm		
						X.XX	±0.20	CHECK		SIZE	A4		
						X.XXX	±0.10			SHEET	1/1		
	A0					Angle	±3°	APPROVE				PART NO.	1020300759
	REV	DATE	MODIFICATION DESCRIPTION			CHANGE	DIM	TOL		PROJ.		TITLE:	2.54FH H=8.5 W=5.0 2*8P SMT=7.1 总高9.0 U-A型 AU1U 青铜 PA6T
	1		2	3	4	5	6	7	8	9			