


TRANSISTOR (PNP)	SOT-23 Plastic-Encapsulate Transistors																																				
<u>SOT-23</u>  COLLECTOR 3 BASE 1 EMITTER 2 1.BASE 2.EMITTER 3.COLLECTOR Marking :2L	Features ※ Complimentary to MMBT5551 ※ Collector Current: Ic=0.6A ※ Ideal for Medium Power Amplification and Switching																																				
MAXIMUM RATINGS (Ta=25℃ unless otherwise noted) <table><tr><th>Parameter</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Collector-Base Voltage</td><td>VCBO</td><td>-160</td><td>V</td></tr><tr><td>Collector-Emitter Voltage</td><td>VCEO</td><td>-150</td><td>V</td></tr><tr><td>Emitter-Base Voltage</td><td>VEBO</td><td>-6</td><td>V</td></tr><tr><td>Collector Current</td><td>IC</td><td>-600</td><td>mA</td></tr><tr><td>Collector Power Dissipation</td><td>PC</td><td>300</td><td>mW</td></tr><tr><td>Thermal Resistance From Junction To Ambient</td><td>ROJA</td><td>417</td><td>℃/W</td></tr><tr><td>Junction Temperature</td><td>Tj</td><td>150</td><td>℃</td></tr><tr><td>Storage Temperature</td><td>Tstg</td><td>-55~+150</td><td>℃</td></tr></table>		Parameter	Symbol	Value	Unit	Collector-Base Voltage	VCBO	-160	V	Collector-Emitter Voltage	VCEO	-150	V	Emitter-Base Voltage	VEBO	-6	V	Collector Current	IC	-600	mA	Collector Power Dissipation	PC	300	mW	Thermal Resistance From Junction To Ambient	ROJA	417	℃/W	Junction Temperature	Tj	150	℃	Storage Temperature	Tstg	-55~+150	℃
Parameter	Symbol	Value	Unit																																		
Collector-Base Voltage	VCBO	-160	V																																		
Collector-Emitter Voltage	VCEO	-150	V																																		
Emitter-Base Voltage	VEBO	-6	V																																		
Collector Current	IC	-600	mA																																		
Collector Power Dissipation	PC	300	mW																																		
Thermal Resistance From Junction To Ambient	ROJA	417	℃/W																																		
Junction Temperature	Tj	150	℃																																		
Storage Temperature	Tstg	-55~+150	℃																																		

ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Collector-base breakdown voltage	V(BR)CBO	IC= -100μA, IE=0	-160	-255	-500	V
Collector-emitter breakdown voltage	V(BR)CEO	IC= -1mA, IB=0	-150	-251	-500	V
Emitter-base breakdown voltage	V(BR)EBO	IE= -10μA, IC=0	-6	-11	-30	V
Collector cut-off current	ICBO	VCB= -120 V , IE=0			-0.1	μA
Collector cut-off current	ICEO	VCB= -150V , IE=0			-1.8	μA
Emitter cut-off current	IEBO	VEB= -4V , IC=0			-0.1	μA
DC current gain	hFE	VCE=-5V, IC= -1mA	80			
	hFE	VCE=-5V, IC= -10mA	100		200	
	hFE	VCE=-5V, IC= -50mA	50			
Collector-emitter saturation voltage	VCE(sat)	IC= -50 mA, IB= -5mA			-0.5	V
Base-emitter saturation voltage	VBE(sat)	IC= -50 mA, IB= -5mA			-1.	V
Transition frequency	fT	VCE=6V, IC= 20mA f=30MHz	100		300	MHz

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

