



TRANSI STOR (PNP)	SOT-23 Plastic-Encapsulate Transistors																																				
SOT-23  1.BASE 2.EMITTER 3.COLLECTOR  1.BASE 2.EMITTER 3.COLLECTOR Marking :2T1 Features ※ Complimentary to S9013 ※ Collector Current: Ic=0.5A ※ Ecxellent Hfe Linearity																																					
MAXIMUM RATINGS (Ta=25℃ unless otherwise noted) <table><tr><th>Parameter</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Collector-Base Voltage</td><td>VCBO</td><td>-40</td><td>V</td></tr><tr><td>Collector-Emitter Voltage</td><td>VCEO</td><td>-25</td><td>V</td></tr><tr><td>Emitter-Base Voltage</td><td>VEBO</td><td>-5</td><td>V</td></tr><tr><td>Collector Current</td><td>IC</td><td>-500</td><td>mA</td></tr><tr><td>Collector Power Dissipation</td><td>PC</td><td>300</td><td>mW</td></tr><tr><td>Thermal Resistance From Junction To Ambient</td><td>RΘJA</td><td>417</td><td>℃/W</td></tr><tr><td>Junction Temperature</td><td>Tj</td><td>150</td><td>℃</td></tr><tr><td>Storage Temperature</td><td>Tstg</td><td>-55~+150</td><td>℃</td></tr></table>		Parameter	Symbol	Value	Unit	Collector-Base Voltage	VCBO	-40	V	Collector-Emitter Voltage	VCEO	-25	V	Emitter-Base Voltage	VEBO	-5	V	Collector Current	IC	-500	mA	Collector Power Dissipation	PC	300	mW	Thermal Resistance From Junction To Ambient	RΘJA	417	℃/W	Junction Temperature	Tj	150	℃	Storage Temperature	Tstg	-55~+150	℃
Parameter	Symbol	Value	Unit																																		
Collector-Base Voltage	VCBO	-40	V																																		
Collector-Emitter Voltage	VCEO	-25	V																																		
Emitter-Base Voltage	VEBO	-5	V																																		
Collector Current	IC	-500	mA																																		
Collector Power Dissipation	PC	300	mW																																		
Thermal Resistance From Junction To Ambient	RΘJA	417	℃/W																																		
Junction Temperature	Tj	150	℃																																		
Storage Temperature	Tstg	-55~+150	℃																																		

ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Collector-base breakdown voltage	V (BR) CBO	IC= -100 μ A, IE=0	-40			V
Collector-emitter breakdown voltage	V (BR) CEO	IC= -1mA, IB=0	-25			V
Emitter-base breakdown voltage	V (BR) EBO	IE=-100 μ A, IC=0	-5			V
Collector cut-off current	ICBO	VCB=-40 V , IE=0			-0.1	μ A
Collector cut-off current	ICEO	VCB=-25V , IE=0			-0.1	μ A
Emitter cut-off current	IEBO	VEB= -5V , IC=0			-0.1	μ A
DC current gain	hFE	VCE=-1V, IC= -50mA	200		350	
	hFE	VCE=-1V, IC= -500mA	40			
Collector-emitter saturation voltage	VCE(sat)	IC=-500 mA, IB= -50mA			-0.6	V
Base-emitter saturation voltage	VBE(sat)	IC=-500 mA, IB= -50mA			-1.2	V
Transition frequency	fT	VCE=-6V, IC= -20mA f=30MHz	150			MHz

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

