



TRANSI STOR (NPN)		SOT-23 Plastic-Encapsulate Transistors																																					
<u>SOT-23</u>  1.BASE 2.EMITTER 3.COLLECTOR Marking :J6		Features ※ Complimentary to S9015 ※ Collector Current: Ic=0.1A																																					
MAXIMUM RATINGS (Ta=25℃ unless otherwise noted) <table><tr><th>Parameter</th><th>Symbol</th><th>Value</th><th>Unit</th></tr><tr><td>Collector-Base Voltage</td><td>VCBO</td><td>50</td><td>V</td></tr><tr><td>Collector-Emitter Voltage</td><td>VCEO</td><td>45</td><td>V</td></tr><tr><td>Emitter-Base Voltage</td><td>VEBO</td><td>6</td><td>V</td></tr><tr><td>Collector Current</td><td>IC</td><td>100</td><td>mA</td></tr><tr><td>Collector Power Dissipation</td><td>PC</td><td>250</td><td>mW</td></tr><tr><td>Thermal Resistance From Junction To Ambient</td><td>RθJA</td><td>625</td><td>℃/W</td></tr><tr><td>Junction Temperature</td><td>Tj</td><td>150</td><td>℃</td></tr><tr><td>Storage Temperature</td><td>Tstg</td><td>-55~+150</td><td>℃</td></tr></table>				Parameter	Symbol	Value	Unit	Collector-Base Voltage	VCBO	50	V	Collector-Emitter Voltage	VCEO	45	V	Emitter-Base Voltage	VEBO	6	V	Collector Current	IC	100	mA	Collector Power Dissipation	PC	250	mW	Thermal Resistance From Junction To Ambient	RθJA	625	℃/W	Junction Temperature	Tj	150	℃	Storage Temperature	Tstg	-55~+150	℃
Parameter	Symbol	Value	Unit																																				
Collector-Base Voltage	VCBO	50	V																																				
Collector-Emitter Voltage	VCEO	45	V																																				
Emitter-Base Voltage	VEBO	6	V																																				
Collector Current	IC	100	mA																																				
Collector Power Dissipation	PC	250	mW																																				
Thermal Resistance From Junction To Ambient	RθJA	625	℃/W																																				
Junction Temperature	Tj	150	℃																																				
Storage Temperature	Tstg	-55~+150	℃																																				

ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Collector-base breakdown voltage	V(BR)CBO	IC= 100μA, IE=0	50			V
Collector-emitter breakdown voltage	V(BR)CEO	IC= 1mA, IB=0	45			V
Emitter-base breakdown voltage	V(BR)EBO	IE= 100μA, IC=0	5			V
Collector cut-off current	ICBO	VCB= 50 V , IE=0			0.1	μ A
Collector cut-off current	ICEO	VCE= 35V , IB=0			1	μ A
Emitter cut-off current	IEBO	VEB= 3V , IC=0			0.1	μ A
DC current gain	hFE	VCE=5V, IC= 1mA	200		450	
Collector-emitter saturation voltage	VCE(sat)	IC=100 mA, IB= 5mA			0.3	V
Base-emitter saturation voltage	VBE(sat)	IC=100 mA, IB= 5mA			1.0	V
Transition frequency	fT	VCE=5V, IC= 10mA f=30MHz	150			MHz

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

