



| Model No. | POS.1 | POS.2 | POS.3 |
|-------------|---|---|---|
| |  |  |  |
| 2AS3 | ON | OFF | ON |
| Term. Comm. | 2-3 | | 2-1 |
| SCHEMATIC |  | OPEN |  |

SWITCH FUNCTION

G : Gold,tin-lead
S : Silver,tin-lead
C : Gold over silver
K : Gold over silver,tin-lead

SPECIFICATIONS

MECHANICAL LIFE: 50,000 make-and-break cycles

CONTACT RESISTANCE: 20m Ω max. initial @ 2-4VDC
100mA for both silver and gold plated contacts

INSULATION RESISTANCE: 1,000MΩ min

DIELECTRIC STRENGTH: 1,000 V RMS@sea level.

OPERATING TEMPERATURE: -30°C to 85°C.

MATERIALS

CASE & BUSHING - Glass filled nylon 6/6 , retardant , heat stabilized(UL94V-0)

ACTUATOR - Brass, chrome plated. Internal O-ring seal. standard for all actuators.

SWITCH SUPPORT - Brass , tin plated.

TERMINALS/CONTACT - Silver or gold plated copper.

RATING :

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)

Q : 1Amp @250VAC
3Amps @120 VAC or 28 VDC

Jicten Electronics Co.,Ltd.
东莞市久晨电子有限公司

| 符號 | 原尺寸 | 修改後尺寸 | 變更日期 |
|-------|-----|-------|------|
| 1 (A) | | | |
| 2 (B) | | | |
| 3 (C) | | | |
| 4 (D) | | | |
| 5 (E) | | | |

SCALE (比例) : 3 : 2

TOLERANCE (公差) :

0.00 mm \pm 0.25mm

0.0 mm ± 0.

ANGULAR : $\pm 5^\circ$
FILE NAME : 2ASP0200

| | | | | | | |
|------------------|--|------------|-----------------|-----|-------------|------------|
| TITLE 圖名 | Sealed Sub - Miniature Toggle Switches | | | | SIZE 圖紙 | A4 |
| DWG NO. 圖號 | 2AS3T1A1VS2CES | | | | UNIT 單位 | inch mm |
| REV. 版本 | A | DATE 日期 | JUL - 21 - 2006 | | SHEET 張數 | 1 of 1 |
| CHECKED BY 審核 | RICHARD | | DRAWN BY 繪圖 | ODA | | |