




YAZAKI PART NO. AND CH. CODE		W1	R1	W2	R2	WIRE SIZE
1	7116-1466-02, A	4.05	1.20	1.95	0.50	CAVS 0.3~0.5 CAVUS 0.3~0.5
3	(7B16-1466-02, A)					
1	7116-1466-08, A					
2	(7B16-1466-08, A)					
1	7116-1469-02, A	4.20	1.25	2.60	0.70	CAVS 0.85 CAVUS 0.85
3	(7B16-1469-02, A)					
1	7116-1469-08, A					
2	(7B16-1469-08, A)					

NOTES

- MATING TERMINAL PART NO. : 7114-1466-02 ETC.
- APPLICABLE RUBBER STOPPER NO. : 7158-3120-90 ETC.
- PART NUMBERS IN PARENTHESIS SHALL BE USED FOR AIR BAG (A/B)
CIRCUITS AND OTHER CIRCUITS DESIGNATED FOR SPECIAL MONITORING.
- INDENTATION (SIDE OUT) MAY BE ADDED ON CARRIER.

注記

- かん合相手端子品番 : 7114-1466-02 ETC.
- 適用ゴム栓品番 : 7158-3120-90 ETC.
- ()内の品番は、エアバック (A/B)回路及び特別管理回路に
使用する時に適用すること。
- キャリア部へのサイドカットによる食い込み追加を可とする。



SEC. A-A

4	2018/03/07	ADDED NOTES	C18-P083	Y. M
3	2008/01/23	ADDED AIR BAG PART NO.	C08-Z502	J. S
2	2000/04/05	CHANGED NOTES, ETC.	C00-L507	T. K
1	1998/11/20	CHANGED FORM. A	C98-M874	M. F
	1998/02/04	NEW	C98-L246	M. T
LET	DATE	REVISION RECORD	NO.	CHKD
GENERAL TOLERANCE				
	10MAX	50MAX	100MAX	250MAX
	±0.15	±0.2	±0.3	±0.5
A	±0.2	±0.3	±0.55	±0.95
B	±0.3	±0.5	±0.8	±1.4
C	±0.3	±0.5	±0.8	±1.4
SPECIFIED				
MASS				
g				
2018/03/07				
R				
APPROVED				
M. NAKAMURA				
CHECKED				
NEW				
DWG SOURCE				
1998/02/04				
UNIT				
mm				
SCL				
5:1				
ANGLE				
3				
DRAWN				
Y. MAEDA				
2018/03/07				
1996/02/19				
PART NO. 7116-1466-02 (7B16-1466-02) ETC.				
CH. CODE				
7116-1466-02:R				
SET DWG NO.				
7116-1466-02:R				
NAME RK-TYPE TERMINAL FEMALE				
MATERIAL: COPPER ALLOY SPEC: t=0.2				
TREAT. & FIN.				
ISSUE MARK				

YAZAKI Corporation