





PART NO. AND CH. CODE	△W ₁ ±0.4	△H ₁	H ₂	X	WIRE SIZE
7114-4025, △					AVS 0.3~AVS 0.5 EQUIVALENT
△(7B14-4025, △)	2. 60	△(2. 44)	△(4. 13)	0. 50	
7114-4026, △					AVS 0.5~AVS 1. 25 EQUIVALENT
△(7B14-4026, △)	3. 30	△(3. 06)	△(4. 00)	0. 80	
7114-4027, △					AVSS 2 EQUIVALENT
△(7B14-4027, △)	4. 30	△(4. 12)	△(5. 02)	1. 00	



SEC. P-P



SEC. Q-Q



注記

- △ 1. 適用ゴム検品番 : 7158-3006-90 ETC.
- △ 2. () 内品番は、エアバック (A/B) 回路及び特別管理回路に使用する時に適用すること。

NOTES

- △ 1. APPLICABLE RUBBER STOPPER NO. : 7158-3006-90 ETC.
- △ 2. PART NUMBERS IN PARENTHESIS SHALL BE USED FOR AIR BAG (A/B) CIRCUITS AND OTHER CIRCUITS DESIGNATED FOR SPECIAL MONITORING.

A

B

A

B

LET	DATE	REVISION RECORD	NO.	CHKD
△	09. 08. 19	CHANGED PART NAME, ETC.	C09-Z596	C. T
△	04. 03. 03	ADDED A/B PART NO.	C04-X114	S. N
△	01. 06. 06	ADDED A/B PART NO.	C01-X536	E. F
△	98. 07. 14	CHANGED DIMENSION	C97-N455	H. K
△	97. 06. 03	CHANGED FORM, △	C97-L889	H. K
	88. 07. 18	NEW	8MC-0810	Y. S

GENERAL TOLERANCE				
10MAX	50MAX	100MAX	250MAX	2500VR
A ±0. 15	±0. 2	±0. 3	±0. 5	±0. 75
B ±0. 2	±0. 3	±0. 55	±0. 95	±1. 4
C ±0. 3	±0. 5	±0. 8	±1. 4	±2
SPECIFIED				
MASS				

CUSTOMER	CUSTOMER PART NO.	CUSTOMER DWG NO.	MATL. SPEC.	△ BRASS (t=0. 30)	TREAT. & FIN.	ISSUE MARK
OFFICE	TRIAL PART NO.		NAME	△ 2. 3 II SEALED		
VENDOR				TERMINAL MALE		

PART NO.	△ 7114-4025 ETC. △(7B14-4025 ETC.)	CH. CODE	△ 7114-4025 ETC. △(7B14-4025 ETC.)
APPROVED	NEW	CHECKED	DESIGN
M. YAMANASHI	S. SUZUKI	C. TORII	M. TSUJI
09. 08. 19	09. 08. 19	09. 08. 19	09. 08. 19

09. 08. 19	09. 08. 19	09. 08. 19	09. 08. 19
------------	------------	------------	------------