

Coaxial Panel Connector 22_MMBX-50-0-2/111_N

Description

Straight bulkhead receptacle jack

Interface standards
SUHNER-MMBX



Technical Data

Electrical Data

| | |
|--------------------------|----------|
| Impedance | 50 Ω |
| Interface frequency max. | 12.4 GHz |

Mechanical Data

| | |
|-------------------|-----------|
| Number of matings | 100 |
| Weight | 0.0011 kg |

Environmental Data

| | |
|---|------------------|
| Operating temperature | -55 °C to 155 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------|-----------------------------------|
| Centre contact | Brass | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPRO Plating |
| Body | Brass | SUCOPRO Plating |
| Insulator | PTFE / LCP | |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00017333 |
| Catalogue drawing | DCA-00086279 |
| Mounting hole | DCA-00086278 |

Ordering Information

| | |
|--------------|-----------------------|
| Tray package | 22_MMBX-50-0-2/111_NY |
|--------------|-----------------------|