

1	2	3	4	5	6	7																																													
E				<table><tr><td>SIGN</td><td>DATE</td><td>DESCRIPTION</td><td>APPROVER</td></tr><tr><td>△</td><td>10/20'08</td><td>Add APPROVAL: : CQC</td><td>Kind</td></tr><tr><td>△</td><td>12/05'12</td><td>Change the screw plating specification</td><td>Jacky</td></tr><tr><td>△</td><td>12/05'12</td><td>Change the dimensional tolerance</td><td>Jacky</td></tr><tr><td>△</td><td>12/12'13</td><td>Add the view</td><td>Jacky</td></tr><tr><td>△</td><td>12/12'13</td><td>Change the withstand voltage and current</td><td>Jacky</td></tr><tr><td colspan="4"></td><td colspan="3">THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!</td></tr></table>		SIGN	DATE	DESCRIPTION	APPROVER	△	10/20'08	Add APPROVAL: : CQC	Kind	△	12/05'12	Change the screw plating specification	Jacky	△	12/05'12	Change the dimensional tolerance	Jacky	△	12/12'13	Add the view	Jacky	△	12/12'13	Change the withstand voltage and current	Jacky					THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!																	
				SIGN	DATE	DESCRIPTION	APPROVER																																												
				△	10/20'08	Add APPROVAL: : CQC	Kind																																												
				△	12/05'12	Change the screw plating specification	Jacky																																												
				△	12/05'12	Change the dimensional tolerance	Jacky																																												
△	12/12'13	Add the view	Jacky																																																
△	12/12'13	Change the withstand voltage and current	Jacky																																																
				THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!																																															
D				MATERIALS ELECTRICAL		cULus	CQC																																												
				RATED VOLTAGE & CURRENT:		250 V, 10 A	/ 250 V, 9A△5																																												
				WITHSTAND VOLTAGE:		AC 2000 V/Min																																													
				INSULATION RESISTANCE:		1000 MΩ OR MORE AT DC 500 V																																													
				OPERATING TEMPERATURE RANG:		-40 °C ~ +115 °C																																													
C				SCREW TORQUE VALUE:		5.3 Lb-In.																																													
				WIRE RANGE:		22 - 18 AWG																																													
				1) MOLDED PARTS:		Thermoplastic, UL 94 V-0 BLACK																																													
				2) TERMINAL:		BRASS, 0.8t, Tin PLATED																																													
				△ 3) TERMINAL SCREWS:		STEEL, M3																																													
B				△ APPROVAL:		cULus CQC																																													
				PART NO.:																																															
				Critical dimension:		▽																																													
				YK 223 xx 0 x x 00G																																															
				NO. OF POLES		G: RoHS compliant (lead<4%) In copper Alloy																																													
A	<table><tr><td>02: 2 POLES</td><td rowspan="5">MARK</td><td rowspan="5">0: "0" MARK</td><td rowspan="5">1: "ANY" MARK</td></tr><tr><td>03: 3 POLES</td></tr><tr><td>04: 4 POLES</td></tr><tr><td>...</td></tr><tr><td>30: 30 POLES</td></tr></table>			02: 2 POLES	MARK	0: "0" MARK	1: "ANY" MARK	03: 3 POLES	04: 4 POLES	...	30: 30 POLES	0: TERMINAL & SCREW PLATED																																							
				02: 2 POLES				MARK	0: "0" MARK	1: "ANY" MARK																																									
				03: 3 POLES																																															
				04: 4 POLES																																															
				...																																															
30: 30 POLES																																																			
0: TERMINAL & SCREW: G/F		△ 1: TERMINAL: G/F, SCREW: Zinc																																																	
2: TERMINAL: Sn, SCREW: G/F		△ 3: TERMINAL: Sn, SCREW: Zinc																																																	
N = Number of poles△																																																			
Dim A=Nx6.35+1.0																																																			
Dim B=(N-1)x6.35																																																			
<table><tr><td>Poles</td><td>Tol.</td><td>Dim A&B</td></tr><tr><td>2-5p</td><td>±0.20</td><td></td></tr><tr><td>6-10p</td><td>±0.25</td><td></td></tr><tr><td>11-16p</td><td>±0.35</td><td></td></tr><tr><td>17-24p</td><td>±0.40</td><td></td></tr><tr><td>25-30p</td><td>±0.50</td><td></td></tr></table>		Poles	Tol.	Dim A&B	2-5p	±0.20		6-10p	±0.25		11-16p	±0.35		17-24p	±0.40		25-30p	±0.50																																	
Poles	Tol.	Dim A&B																																																	
2-5p	±0.20																																																		
6-10p	±0.25																																																		
11-16p	±0.35																																																		
17-24p	±0.40																																																		
25-30p	±0.50																																																		
<table><tr><td colspan="4">TITLE</td><td colspan="4">YK-223 Series</td></tr><tr><td colspan="2">PART NO.</td><td colspan="2">YK223xx0xx00G</td><td colspan="2">DWG NO.</td><td colspan="2">8YK0001-223</td></tr><tr><td colspan="2">APPROVED</td><td>CHECKED</td><td>DESIGNED</td><td colspan="2">DRAWN</td><td colspan="2">CUST NO.</td></tr><tr><td colspan="2"></td><td></td><td>Jacky</td><td colspan="2">Jacky</td><td colspan="2"></td></tr><tr><td colspan="2"></td><td></td><td>2013.12.12</td><td colspan="2">2013.12.12</td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">SHEET: 01/01</td><td colspan="2">REV.: F</td></tr></table>		TITLE				YK-223 Series				PART NO.		YK223xx0xx00G		DWG NO.		8YK0001-223		APPROVED		CHECKED	DESIGNED	DRAWN		CUST NO.					Jacky	Jacky							2013.12.12	2013.12.12								SHEET: 01/01		REV.: F			
TITLE				YK-223 Series																																															
PART NO.		YK223xx0xx00G		DWG NO.		8YK0001-223																																													
APPROVED		CHECKED	DESIGNED	DRAWN		CUST NO.																																													
			Jacky	Jacky																																															
			2013.12.12	2013.12.12																																															
				SHEET: 01/01		REV.: F																																													
						Tolerance																																													
						X. ±0.50																																													
						X.X ±0.30																																													
						X.XX ±0.10																																													
						X° ±1°																																													