

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

'90A, 'LS90 . . . Decade Counters

'92A, 'LS92 . . . Divide By-Twelve Counters

'93A, 'LS93 . . . 4-Bit Binary Counters

| TYPES               | TYPICAL<br>POWER DISSIPATION |
|---------------------|------------------------------|
| '90A                | 145 mW                       |
| '92A, '93A          | 130 mW                       |
| 'LS90, 'LS92, 'LS93 | 45 mW                        |

## description


Each of these monolithic counters contains four master-slave flip-flops and additional gating to provide a divide-by-two counter and a three-stage binary counter for which the count cycle length is divide-by-five for the '90A and 'LS90, divide-by-six for the '92A and 'LS92, and the divide-by-eight for the '93A and 'LS93.

All of these counters have a gated zero reset and the '90A and 'LS90 also have gated set-to-nine inputs for use in BCD nine's complement applications.

To use their maximum count length (decade, divide-by-twelve, or four-bit binary) of these counters, the CKB input is connected to the  $Q_A$  output. The input count pulses are applied to CKA input and the outputs are as described in the appropriate function table. A symmetrical divide-by-ten count can be obtained from the '90A or 'LS90 counters by connecting the  $Q_D$  output to the CKA input and applying the input count to the CKB input which gives a divide-by-ten square wave at output  $Q_A$ .


SN5490A, SN54LS90 . . . J OR W PACKAGE  
SN7490A . . . N PACKAGE  
SN74LS90 . . . D OR N PACKAGE

(TOP VIEW)




SN5492A, SN54LS92 . . . J OR W PACKAGE  
SN7492A . . . N PACKAGE  
SN74LS92 . . . D OR N PACKAGE

(TOP VIEW)



SN5493A, SN54LS93 . . . J OR W PACKAGE  
SN7493 . . . N PACKAGE  
SN74LS93 . . . D OR N PACKAGE


(TOP VIEW)



**SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS**

SDLS940A – MARCH 1974 – REVISED MARCH 1988

**logic symbols†**



†These symbols are in accordance with ANSI/IEEE Std. 91-1984 and IEC Publication 617-12.

SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

'90A, 'LS90  
 BCD COUNT SEQUENCE  
 (See Note A)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | L              | H              | L              | H              |
| 6     | L              | H              | H              | L              |
| 7     | L              | H              | H              | H              |
| 8     | H              | L              | L              | L              |
| 9     | H              | L              | L              | H              |

'90A, 'LS90  
 BI-QUINARY (5-2)  
 (See Note B)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>A</sub> | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | H              | L              | L              | L              |
| 6     | H              | L              | L              | H              |
| 7     | H              | L              | H              | L              |
| 8     | H              | L              | H              | H              |
| 9     | H              | H              | L              | L              |

'92A, 'LS92  
 COUNT SEQUENCE  
 (See Note C)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | L              | H              | L              | H              |
| 6     | H              | L              | L              | L              |
| 7     | H              | L              | L              | H              |
| 8     | H              | L              | H              | L              |
| 9     | H              | L              | H              | H              |
| 10    | H              | H              | L              | L              |
| 11    | H              | H              | L              | H              |

'90A, 'LS90  
 RESET/COUNT FUNCTION TABLE

| RESET INPUTS       |                    |                    |                    | OUTPUT         |                |                |                |
|--------------------|--------------------|--------------------|--------------------|----------------|----------------|----------------|----------------|
| R <sub>0</sub> (1) | R <sub>0</sub> (2) | R <sub>9</sub> (1) | R <sub>9</sub> (2) | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| H                  | H                  | L                  | X                  | L              | L              | L              | L              |
| H                  | H                  | X                  | L                  | L              | L              | L              | L              |
| X                  | X                  | H                  | H                  | H              | L              | L              | H              |
| X                  | L                  | X                  | L                  | COUNT          |                |                |                |
| L                  | X                  | L                  | X                  | COUNT          |                |                |                |
| L                  | X                  | X                  | L                  | COUNT          |                |                |                |
| X                  | L                  | L                  | X                  | COUNT          |                |                |                |

'93A, 'LS93  
 COUNT SEQUENCE  
 (See Note C)

| COUNT | OUTPUT         |                |                |                |
|-------|----------------|----------------|----------------|----------------|
|       | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| 0     | L              | L              | L              | L              |
| 1     | L              | L              | L              | H              |
| 2     | L              | L              | H              | L              |
| 3     | L              | L              | H              | H              |
| 4     | L              | H              | L              | L              |
| 5     | L              | H              | L              | H              |
| 6     | L              | H              | H              | L              |
| 7     | L              | H              | H              | H              |
| 8     | H              | L              | L              | L              |
| 9     | H              | L              | L              | H              |
| 10    | H              | L              | H              | L              |
| 11    | H              | L              | H              | H              |
| 12    | H              | H              | L              | L              |
| 13    | H              | H              | L              | H              |
| 14    | H              | H              | H              | L              |
| 15    | H              | H              | H              | H              |

'92A, 'LS92, '93A, 'LS93  
 RESET/COUNT FUNCTION TABLE


| RESET INPUTS       |                    | OUTPUT         |                |                |                |
|--------------------|--------------------|----------------|----------------|----------------|----------------|
| R <sub>0</sub> (1) | R <sub>0</sub> (2) | Q <sub>D</sub> | Q <sub>C</sub> | Q <sub>B</sub> | Q <sub>A</sub> |
| H                  | H                  | L              | L              | L              | L              |
| L                  | X                  | COUNT          |                |                |                |
| X                  | L                  | COUNT          |                |                |                |

- NOTES: A. Output Q<sub>A</sub> is connected to input CKB for BCD count.  
 B. Output Q<sub>D</sub> is connected to input CKA for bi-quinary count.  
 C. Output Q<sub>A</sub> is connected to input CKB.  
 D. H = high level, L = low level, X = irrelevant

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS


SDLS940A – MARCH 1974 – REVISED MARCH 1988

## logic diagrams (positive logic)



The J and K inputs shown without connection are for reference only and are functionally at a high level.  
Pin numbers shown in ( ) are for the 'LS93 and '93A and pin numbers shown in [ ] are for the 54L93.

## schematics of inputs and outputs




SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

schematics of inputs and outputs (continued)

'LS90, 'LS92, 'LS93



# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

|                                                                 |                |
|-----------------------------------------------------------------|----------------|
| Supply voltage, $V_{CC}$ (see Note 1)                           | 7 V            |
| Input voltage                                                   | 5.5 V          |
| Interemitter voltage (see Note 2)                               | 5.5 V          |
| Operating free-air temperature range: SN5490A, SN5492A, SN5493A | –55°C to 125°C |
| SN7490A, SN7492A, SN7493A                                       | 0°C to 70°C    |
| Storage temperature range                                       | –65°C to 150°C |

NOTES: 1. Voltage values, except interemitter voltage, are with respect to network ground terminal.

2. This is the voltage between two emitters of a multiple-emitter transistor. For these circuits, this rating applies between the two  $R_0$  inputs, and for the '90A circuit, it also applies between the two  $R_0$  inputs.

## recommended operating conditions

|                                             |              | SN5490A, SN5492A<br>SN5493A |     |      | SN7490A, SN7492A<br>SN7493A |     |      | UNIT    |
|---------------------------------------------|--------------|-----------------------------|-----|------|-----------------------------|-----|------|---------|
|                                             |              | MIN                         | NOM | MAX  | MIN                         | NOM | MAX  |         |
| Supply voltage, $V_{CC}$                    |              | 4.5                         | 5   | 5.5  | 4.75                        | 5   | 5.25 | V       |
| High-level output current, $I_{OH}$         |              |                             |     | –800 |                             |     | –800 | $\mu$ A |
| Low-level output current, $I_{OL}$          |              |                             |     | 16   |                             |     | 16   | mA      |
| Count frequency, $f_{count}$ (see Figure 1) | A input      | 0                           |     | 32   | 0                           |     | 32   | MHz     |
|                                             | B input      | 0                           |     | 16   | 0                           |     | 16   |         |
| Pulse width, $t_w$                          | A input      | 15                          |     |      | 15                          |     |      | ns      |
|                                             | B input      | 30                          |     |      | 30                          |     |      |         |
|                                             | Reset inputs | 15                          |     |      | 15                          |     |      |         |
| Reset inactive-state setup time, $t_{SU}$   |              | 25                          |     |      | 25                          |     |      | ns      |
| Operating free-air temperature, $T_A$       |              | –55                         |     | 125  | 0                           |     | 70   | °C      |

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER <sup>¶</sup> |                                           | TEST CONDITIONS <sup>†</sup>                                                                                 |                                               | '90A |                  |      | '92A |                  |      | '93A |                  |      | UNIT    |
|------------------------|-------------------------------------------|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------|------|------------------|------|------|------------------|------|------|------------------|------|---------|
|                        |                                           |                                                                                                              |                                               | MIN  | TYP <sup>‡</sup> | MAX  | MIN  | TYP <sup>‡</sup> | MAX  | MIN  | TYP <sup>‡</sup> | MAX  |         |
| $V_{IH}$               | High-level input voltage                  |                                                                                                              |                                               | 2    |                  |      | 2    |                  |      | 2    |                  |      | V       |
| $V_{IL}$               | Low-level input voltage                   |                                                                                                              |                                               |      |                  | 0.8  |      |                  | 0.8  |      |                  | 0.8  | V       |
| $V_{IK}$               | Input clamp voltage                       | $V_{CC} = \text{MIN}$ , $I_I = -12 \text{ mA}$                                                               |                                               |      |                  | –1.5 |      |                  | –1.5 |      |                  | –1.5 | V       |
| $V_{OH}$               | High-level output voltage                 | $V_{CC} = \text{MIN}$ , $V_{IH} = 2 \text{ V}$ ,<br>$V_{IL} = 0.8 \text{ V}$ , $I_{OH} = -800 \mu\text{A}$   |                                               | 2.4  | 3.4              |      | 2.4  | 3.4              |      | 2.4  | 3.4              |      | V       |
| $V_{OL}$               | Low-level output voltage                  | $V_{CC} = \text{MIN}$ , $V_{IH} = 2 \text{ V}$ ,<br>$V_{IL} = 0.8 \text{ V}$ , $I_{OL} = 16 \text{ mA}^{\S}$ |                                               |      | 0.2              | 0.4  |      | 0.2              | 0.4  |      | 0.2              | 0.4  | V       |
| $I_I$                  | Input current at maximum input voltage    | $V_{CC} = \text{MAX}$ , $V_I = 5.5 \text{ V}$                                                                |                                               |      |                  | 1    |      |                  | 1    |      |                  | 1    | mA      |
| $I_{IH}$               | High-level input current                  | Any reset                                                                                                    | $V_{CC} = \text{MAX}$ , $V_I = 2.4 \text{ V}$ |      |                  | 40   |      |                  | 40   |      |                  | 40   | $\mu$ A |
|                        |                                           | CKA                                                                                                          |                                               |      |                  | 80   |      |                  | 80   |      |                  | 80   |         |
|                        |                                           | CKB                                                                                                          |                                               |      |                  | 120  |      |                  | 120  |      |                  | 80   |         |
| $I_{IL}$               | Low-level input current                   | Any reset                                                                                                    | $V_{CC} = \text{MAX}$ , $V_I = 0.4 \text{ V}$ |      |                  | –1.6 |      |                  | –1.6 |      |                  | –1.6 | mA      |
|                        |                                           | CKA                                                                                                          |                                               |      |                  | –3.2 |      |                  | –3.2 |      |                  | –3.2 |         |
|                        |                                           | CKB                                                                                                          |                                               |      |                  | –4.8 |      |                  | –4.8 |      |                  | –3.2 |         |
| $I_{OS}$               | Short-circuit output current <sup>§</sup> | $V_{CC} = \text{MAX}$                                                                                        | SN54'                                         | –20  |                  | –57  | –20  |                  | –57  | –20  |                  | –57  | mA      |
|                        |                                           |                                                                                                              | SN74'                                         | –18  |                  | –57  | –18  |                  | –57  | –18  |                  | –57  |         |
| $I_{CC}$               | Supply current                            | $V_{CC} = \text{MAX}$ , See Note 3                                                                           |                                               |      | 29               | 42   |      | 26               | 39   |      | 26               | 39   | mA      |

<sup>†</sup> For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

<sup>‡</sup> All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

<sup>§</sup> Not more than one output should be shorted at a time.

<sup>¶</sup>  $I_{OH}$  outputs are tested at  $I_{OL} = 16 \text{ mA}$  plus the limit value for  $I_{IL}$  for the CKB input. This permits driving the CKB input while maintaining full fan-out capability.

NOTE 3:  $I_{CC}$  is measured with all outputs open, both  $R_0$  inputs grounded following momentary connection to 4.5 V, and all other inputs grounded.



SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

switching characteristics,  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$

| PARAMETER†       | FROM<br>(INPUT) | TO<br>(OUTPUT)                  | TEST CONDITIONS                                                    | '90A |     |     | '92A |     |     | '93A |     |     | UNIT |
|------------------|-----------------|---------------------------------|--------------------------------------------------------------------|------|-----|-----|------|-----|-----|------|-----|-----|------|
|                  |                 |                                 |                                                                    | MIN  | TYP | MAX | MIN  | TYP | MAX | MIN  | TYP | MAX |      |
| f <sub>max</sub> | CKA             | Q <sub>A</sub>                  | C <sub>L</sub> = 15 pF,<br>R <sub>L</sub> = 400 Ω,<br>See Figure 1 | 32   | 42  |     | 32   | 42  |     | 32   | 42  |     | MHz  |
|                  | CKB             | Q <sub>B</sub>                  |                                                                    | 16   |     |     | 16   |     |     | 16   |     |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>A</sub>                  |                                                                    | 10   | 16  |     | 10   | 16  |     | 10   | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                    | 12   | 18  |     | 12   | 18  |     | 12   | 18  |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>D</sub>                  |                                                                    | 32   | 48  |     | 32   | 48  |     | 46   | 70  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                    | 34   | 50  |     | 34   | 50  |     | 46   | 70  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>B</sub>                  |                                                                    | 10   | 16  |     | 10   | 16  |     | 10   | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                    | 14   | 21  |     | 14   | 21  |     | 14   | 21  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>C</sub>                  |                                                                    | 21   | 32  |     | 10   | 16  |     | 21   | 32  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                    | 23   | 35  |     | 14   | 21  |     | 23   | 35  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>D</sub>                  |                                                                    | 21   | 32  |     | 21   | 32  |     | 34   | 51  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                    | 23   | 35  |     | 23   | 35  |     | 34   | 51  |     |      |
| t <sub>PHL</sub> | Set-to-0        | Any                             |                                                                    | 26   | 40  |     | 26   | 40  |     | 26   | 40  |     | ns   |
| t <sub>PLH</sub> | Set-to-9        | Q <sub>A</sub> , Q <sub>D</sub> |                                                                    | 20   | 30  |     |      |     |     |      |     |     | ns   |
| t <sub>PHI</sub> |                 | Q <sub>B</sub> , Q <sub>C</sub> |                                                                    | 26   | 40  |     |      |     |     |      |     |     |      |

†  $f_{\max}$  = maximum count frequency

$t_{PLH}$  = propagation delay time, low-to-high-level output

$t_{PHL}$  = propagation delay time, high-to-low-level output

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

|                                                        |                |
|--------------------------------------------------------|----------------|
| Supply voltage, $V_{CC}$ (see Note 1)                  | 7 V            |
| Input voltage: R inputs                                | 7 V            |
| A and B inputs                                         | 5.5 V          |
| Operating free-air temperature range: SN54LS* Circuits | –55°C to 125°C |
| SN74LS* Circuits                                       | 0°C to 70°C    |
| Storage temperature range                              | –65°C to 150°C |

NOTE 1: Voltage values are with respect to network ground terminal.

recommended operating conditions

|                                             |              | SN54LS90<br>SN54LS92<br>SN54LS93 |     |     | SN74LS90<br>SN74LS92<br>SN74LS93 |     |      | UNIT    |
|---------------------------------------------|--------------|----------------------------------|-----|-----|----------------------------------|-----|------|---------|
|                                             |              | MIN                              | NOM | MAX | MIN                              | NOM | MAX  |         |
| Supply voltage, $V_{CC}$                    |              | 4.5                              | 5   | 5.5 | 4.75                             | 5   | 5.25 | V       |
| High-level output current, $I_{OH}$         |              | –400                             |     |     | –400                             |     |      | $\mu$ A |
| Low-level output current, $I_{OL}$          |              | 4                                |     |     | 8                                |     |      | mA      |
| Count frequency, $f_{count}$ (see Figure 1) | A input      | 0                                |     | 32  | 0                                |     | 32   | MHz     |
|                                             | B input      | 0                                |     | 16  | 0                                |     | 16   |         |
| Pulse width, $t_w$                          | A input      | 15                               |     |     | 15                               |     |      | ns      |
|                                             | B input      | 30                               |     |     | 30                               |     |      |         |
|                                             | Reset inputs | 30                               |     |     | 30                               |     |      |         |
| Reset inactive-state setup time, $t_{su}$   |              | 25                               |     |     | 25                               |     |      | ns      |
| Operating free-air temperature, $T_A$       |              | –55                              |     | 125 | 0                                |     | 70   | °C      |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER |                                        | TEST CONDITIONS†                                                                                                                 |                                            | SN54LS90<br>SN54LS92 |      |      | SN74LS90<br>SN74LS92 |      |      | UNIT    |
|-----------|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|----------------------|------|------|----------------------|------|------|---------|
|           |                                        |                                                                                                                                  |                                            | MIN                  | TYP‡ | MAX  | MIN                  | TYP‡ | MAX  |         |
| $V_{IH}$  | High-level input voltage               |                                                                                                                                  |                                            | 2                    |      |      | 2                    |      |      | V       |
| $V_{IL}$  | Low-level input voltage                |                                                                                                                                  |                                            |                      |      | 0.7  |                      |      | 0.8  | V       |
| $V_{IK}$  | Input clamp voltage                    | $V_{CC} = \text{MIN}, I_I = -18 \text{ mA}$                                                                                      |                                            |                      |      | –1.5 |                      |      | –1.5 | V       |
| $V_{OH}$  | High-level output voltage              | $V_{CC} = \text{MIN}, V_{IH} = 2 \text{ V}, V_{IL} = V_{IL \text{ max}}, I_{OH} = -400 \mu\text{A}$                              |                                            | 2.5                  | 3.4  |      | 2.7                  | 3.4  |      | V       |
| $V_{OL}$  | Low-level output voltage               | $V_{CC} = \text{MIN}, V_{IH} = 2 \text{ V}, V_{IL} = V_{IL \text{ max}}, I_{OL} = 4 \text{ mA}^{\S}, I_{OL} = 8 \text{ mA}^{\P}$ |                                            | 0.25                 | 0.4  |      | 0.25                 | 0.4  |      | V       |
| $I_I$     | Input current at maximum input voltage | Any reset                                                                                                                        | $V_{CC} = \text{MAX}, V_I = 7 \text{ V}$   |                      |      | 0.1  |                      |      | 0.1  | mA      |
|           |                                        | CKA                                                                                                                              | $V_{CC} = \text{MAX}, V_I = 5.5 \text{ V}$ |                      |      | 0.2  |                      |      | 0.2  |         |
|           |                                        | CKB                                                                                                                              | $V_{CC} = \text{MAX}, V_I = 5.5 \text{ V}$ |                      |      | 0.4  |                      |      | 0.4  |         |
| $I_{IH}$  | High-level input current               | Any reset                                                                                                                        | $V_{CC} = \text{MAX}, V_I = 2.7 \text{ V}$ |                      |      | 20   |                      |      | 20   | $\mu$ A |
|           |                                        | CKA                                                                                                                              | $V_{CC} = \text{MAX}, V_I = 2.7 \text{ V}$ |                      |      | 40   |                      |      | 40   |         |
|           |                                        | CKB                                                                                                                              | $V_{CC} = \text{MAX}, V_I = 2.7 \text{ V}$ |                      |      | 80   |                      |      | 80   |         |
| $I_{IL}$  | Low-level input current                | Any reset                                                                                                                        | $V_{CC} = \text{MAX}, V_I = 0.4 \text{ V}$ |                      |      | –0.4 |                      |      | –0.4 | mA      |
|           |                                        | CKA                                                                                                                              | $V_{CC} = \text{MAX}, V_I = 0.4 \text{ V}$ |                      |      | –2.4 |                      |      | –2.4 |         |
|           |                                        | CKB                                                                                                                              | $V_{CC} = \text{MAX}, V_I = 0.4 \text{ V}$ |                      |      | –3.2 |                      |      | –3.2 |         |
| $I_{OS}$  | Short-circuit output current $^{\S}$   | $V_{CC} = \text{MAX}$                                                                                                            |                                            | –20                  |      | –100 | –20                  |      | –100 | mA      |
| $I_{CC}$  | Supply current                         | $V_{CC} = \text{MAX},$ See Note 3                                                                                                | 'LS90                                      |                      |      | 9    |                      |      | 15   | mA      |
|           |                                        |                                                                                                                                  | 'LS92                                      |                      |      | 9    |                      |      | 15   |         |

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡ All typical values are at  $V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}$ .

$^{\S}$  Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

$^{\P}$   $I_{QA}$  outputs are tested at specified  $I_{OL}$  plus the limit value of  $I_{IL}$  for the CKB input. This permits driving the CKB input while maintaining full fan-out capability.

NOTE 3:  $I_{CC}$  is measured with all outputs open, both  $R_O$  inputs grounded following momentary connection to 4.5 V, and all other inputs grounded.



SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93  
SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93  
DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER       |                                        |            | TEST CONDITIONS†                                                                                               | SN54LS93 |      |      | SN74LS93 |      |     | UNIT |
|-----------------|----------------------------------------|------------|----------------------------------------------------------------------------------------------------------------|----------|------|------|----------|------|-----|------|
|                 |                                        |            |                                                                                                                | MIN      | TYP‡ | MAX  | MIN      | TYP‡ | MAX |      |
| V <sub>IH</sub> | High-level input voltage               |            |                                                                                                                | 2        |      |      | 2        |      |     | V    |
| V <sub>IL</sub> | Low-level input voltage                |            |                                                                                                                | 0.7      |      |      | 0.8      |      |     | V    |
| V <sub>IK</sub> | Input clamp voltage                    |            | V <sub>CC</sub> = MIN, I <sub>I</sub> = -18 mA                                                                 | -1.5     |      |      | -1.5     |      |     | V    |
| V <sub>OH</sub> | High-level output voltage              |            | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V, V <sub>IL</sub> = V <sub>IL</sub> max, I <sub>OH</sub> = -400 µA | 2.5      | 3.4  |      | 2.7      | 3.4  |     | V    |
| V <sub>OL</sub> | Low-level output voltage               |            | V <sub>CC</sub> = MIN, V <sub>IH</sub> = 2 V, I <sub>OL</sub> = 4 mA¶                                          | 0.25     |      | 0.4  | 0.25     |      | 0.4 | V    |
|                 |                                        |            | V <sub>IL</sub> = V <sub>IL</sub> max, I <sub>OL</sub> = 8 mA¶                                                 |          |      | 0.35 |          | 0.5  |     |      |
| I <sub>I</sub>  | Input current at maximum input voltage | Any reset  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 7 V                                                                    | 0.1      |      |      | 0.1      |      |     | mA   |
|                 |                                        | CKA or CKB | V <sub>CC</sub> = MAX, V <sub>I</sub> = 5.5 V                                                                  | 0.2      |      |      | 0.2      |      |     |      |
| I <sub>IH</sub> | High-level input current               | Any reset  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 2.7 V                                                                  | 20       |      |      | 20       |      |     | µA   |
|                 |                                        | CKA or CKB |                                                                                                                | 40       |      |      | 80       |      |     |      |
| I <sub>IL</sub> | Low-level input current                | Any reset  | V <sub>CC</sub> = MAX, V <sub>I</sub> = 0.4 V                                                                  | -0.4     |      |      | -0.4     |      |     | mA   |
|                 |                                        | CKA        |                                                                                                                | -2.4     |      |      | -2.4     |      |     |      |
|                 |                                        | CKB        |                                                                                                                | -1.6     |      |      | -1.6     |      |     |      |
| I <sub>OS</sub> | Short-circuit output current§          |            | V <sub>CC</sub> = MAX                                                                                          | -20      | -100 |      | -20      | -100 |     | mA   |
| I <sub>CC</sub> | Supply current                         |            | V <sub>CC</sub> = MAX, See Note 3                                                                              | 9        |      | 15   | 9        |      | 15  | mA   |

†For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

‡All typical values are at V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C.

§Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

¶Q<sub>A</sub> outputs are tested at specified I<sub>OL</sub> plus the limit value for I<sub>IL</sub> for the CKB input. This permits driving the CKB input while maintaining full fan-out capability.

NOTE 3: I<sub>CC</sub> is measured with all outputs open, both R<sub>Q</sub> inputs grounded following momentary connection to 4.5 V, and all other inputs grounded.

switching characteristics, V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C

| PARAMETER#       | FROM<br>(INPUT) | TO<br>(OUTPUT)                  | TEST CONDITIONS                                                  | 'LS90 |     |     | 'LS92 |     |     | 'LS93 |     |     | UNIT |
|------------------|-----------------|---------------------------------|------------------------------------------------------------------|-------|-----|-----|-------|-----|-----|-------|-----|-----|------|
|                  |                 |                                 |                                                                  | MIN   | TYP | MAX | MIN   | TYP | MAX | MIN   | TYP | MAX |      |
| f <sub>max</sub> | CKA             | Q <sub>A</sub>                  | C <sub>L</sub> = 15 pF,<br>R <sub>L</sub> = 2 kΩ<br>See Figure 1 | 32    | 42  |     | 32    | 42  |     | 32    | 42  |     | MHz  |
|                  | CKB             | Q <sub>B</sub>                  |                                                                  | 16    |     |     | 16    |     |     | 16    |     |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>A</sub>                  |                                                                  | 10    | 16  |     | 10    | 16  |     | 10    | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                  | 12    | 18  |     | 12    | 18  |     | 12    | 18  |     |      |
| t <sub>PLH</sub> | CKA             | Q <sub>D</sub>                  |                                                                  | 32    | 48  |     | 32    | 48  |     | 46    | 70  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                  | 34    | 50  |     | 34    | 50  |     | 46    | 70  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>B</sub>                  |                                                                  | 10    | 16  |     | 10    | 16  |     | 10    | 16  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                  | 14    | 21  |     | 14    | 21  |     | 14    | 21  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>C</sub>                  |                                                                  | 21    | 32  |     | 10    | 16  |     | 21    | 32  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                  | 23    | 35  |     | 14    | 21  |     | 23    | 35  |     |      |
| t <sub>PLH</sub> | CKB             | Q <sub>D</sub>                  |                                                                  | 21    | 32  |     | 21    | 32  |     | 34    | 51  |     | ns   |
| t <sub>PHL</sub> |                 |                                 |                                                                  | 23    | 35  |     | 23    | 35  |     | 34    | 51  |     |      |
| t <sub>PHL</sub> | Set-to-0        | Any                             |                                                                  | 26    | 40  |     | 26    | 40  |     | 26    | 40  |     | ns   |
| t <sub>PLH</sub> | Set-to-9        | Q <sub>A</sub> , Q <sub>D</sub> |                                                                  | 20    | 30  |     |       |     |     |       |     |     | ns   |
| t <sub>PHI</sub> |                 | Q <sub>B</sub> , Q <sub>C</sub> |                                                                  | 26    | 40  |     |       |     |     |       |     |     |      |

#f<sub>max</sub> = maximum count frequency

t<sub>PLH</sub> = propagation delay time, low-to-high-level output

t<sub>PHL</sub> = propagation delay time, high-to-low-level output



TEXAS  
INSTRUMENTS

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

# SN5490A, SN5492A, SN5493A, SN54LS90, SN54LS92, SN54LS93 SN7490A, SN7492A, SN7493A, SN74LS90, SN74LS92, SN74LS93 DECADE, DIVIDE-BY-TWELVE AND BINARY COUNTERS

SDLS940A – MARCH 1974 – REVISED MARCH 1988

## PARAMETER MEASUREMENT INFORMATION



NOTES: A. Input pulses are supplied by a generator having the following characteristics:

for '90A, '92A, '93A,  $t_r \leq 5$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms;  
for 'LS90, 'LS92, 'LS93,  $t_r \leq 15$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms.

B.  $C_L$  includes probe and jig capacitance.

C. All diodes are 1N3064 or equivalent.

D. Each reset input is tested separately with the other reset at 4.5 V.

E. Reference waveforms are shown with dashed lines.

F. For '90A, '92A, and '93A;  $V_{ref} = 1.5$  V. For 'LS90, 'LS92, and 'LS93;  $V_{ref} = 1.3$  V.

FIGURE 1A

## PARAMETER MEASUREMENT INFORMATION



LOAD CIRCUIT

- NOTES: A. Input pulses are supplied by a generator having the following characteristics:  
 for '90A, '92A, '93A,  $t_r \leq 5$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms;  
 for 'LS90, 'LS92, 'LS93,  $t_r \leq 15$  ns,  $t_f \leq 5$  ns, PRR = 1 MHz, duty cycle = 50%,  $Z_{out} \approx 50$  ohms.
- B.  $C_L$  includes probe and jig capacitance.
- C. All diodes are 1N3064 or equivalent.
- D. Each reset input is tested separately with the other reset at 4.5 V.
- E. Reference waveforms are shown with dashed lines.
- F. For '90A, '92A, and '93A;  $V_{ref} = 1.5$  V. For 'LS90, 'LS92, and 'LS93;  $V_{ref} = 1.3$  V.

FIGURE 1B

**PACKAGING INFORMATION**

| Orderable part number            | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)     |
|----------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|-------------------------|
| <a href="#">7603201CA</a>        | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7603201CA<br>SNJ54LS90J |
| <a href="#">7700101CA</a>        | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7700101CA<br>SNJ54LS93J |
| <a href="#">7700101DA</a>        | Active        | Production           | CFP (W)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7700101DA<br>SNJ54LS93W |
| <a href="#">JM38510/31501BCA</a> | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31501BCA    |
| JM38510/31501BCA.A               | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31501BCA    |
| <a href="#">JM38510/31502BCA</a> | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31502BCA    |
| JM38510/31502BCA.A               | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31502BCA    |
| <a href="#">JM38510/31502BDA</a> | Active        | Production           | CFP (W)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31502BDA    |
| JM38510/31502BDA.A               | Active        | Production           | CFP (W)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31502BDA    |
| <a href="#">M38510/31501BCA</a>  | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31501BCA    |
| <a href="#">M38510/31502BCA</a>  | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31502BCA    |
| <a href="#">M38510/31502BDA</a>  | Active        | Production           | CFP (W)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | JM38510/<br>31502BDA    |
| <a href="#">SN54LS90J</a>        | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54LS90J               |
| SN54LS90J.A                      | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54LS90J               |
| <a href="#">SN54LS93J</a>        | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54LS93J               |
| SN54LS93J.A                      | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54LS93J               |
| <a href="#">SN74LS90D</a>        | Obsolete      | Production           | SOIC (D)   14  | -                     | -           | Call TI                              | Call TI                           | 0 to 70      | LS90                    |
| <a href="#">SN74LS90DR</a>       | Active        | Production           | SOIC (D)   14  | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS90                    |
| SN74LS90DR.A                     | Active        | Production           | SOIC (D)   14  | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS90                    |
| <a href="#">SN74LS90N</a>        | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS90N               |

| Orderable part number       | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)     |
|-----------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|-------------------------|
| SN74LS90N.A                 | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS90N               |
| SN74LS90NE4                 | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS90N               |
| <a href="#">SN74LS92D</a>   | Active        | Production           | SOIC (D)   14  | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS92                    |
| SN74LS92D.A                 | Active        | Production           | SOIC (D)   14  | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS92                    |
| <a href="#">SN74LS92N</a>   | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS92N               |
| SN74LS92N.A                 | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS92N               |
| <a href="#">SN74LS92NSR</a> | Active        | Production           | SOP (NS)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 74LS92                  |
| SN74LS92NSR.A               | Active        | Production           | SOP (NS)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | 74LS92                  |
| <a href="#">SN74LS93D</a>   | Active        | Production           | SOIC (D)   14  | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS93                    |
| SN74LS93D.A                 | Active        | Production           | SOIC (D)   14  | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LS93                    |
| <a href="#">SN74LS93N</a>   | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS93N               |
| SN74LS93N.A                 | Active        | Production           | PDIP (N)   14  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74LS93N               |
| <a href="#">SNJ54LS90J</a>  | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7603201CA<br>SNJ54LS90J |
| SNJ54LS90J.A                | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7603201CA<br>SNJ54LS90J |
| <a href="#">SNJ54LS93J</a>  | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7700101CA<br>SNJ54LS93J |
| SNJ54LS93J.A                | Active        | Production           | CDIP (J)   14  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7700101CA<br>SNJ54LS93J |
| <a href="#">SNJ54LS93W</a>  | Active        | Production           | CFP (W)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7700101DA<br>SNJ54LS93W |
| SNJ54LS93W.A                | Active        | Production           | CFP (W)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 7700101DA<br>SNJ54LS93W |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN54LS90, SN54LS93, SN74LS90, SN74LS93 :**

- Catalog : [SN74LS90](#), [SN74LS93](#)
- Military : [SN54LS90](#), [SN54LS93](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

## TAPE AND REEL INFORMATION



\*All dimensions are nominal


| Device      | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LS90DR  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LS92NSR | SOP          | NS              | 14   | 2000 | 330.0              | 16.4               | 8.1     | 10.4    | 2.5     | 12.0    | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device      | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LS90DR  | SOIC         | D               | 14   | 2500 | 356.0       | 356.0      | 35.0        |
| SN74LS92NSR | SOP          | NS              | 14   | 2000 | 356.0       | 356.0      | 35.0        |

**TUBE**


\*All dimensions are nominal

| Device             | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|--------------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 7700101DA          | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| JM38510/31502BDA   | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| JM38510/31502BDA.A | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| M38510/31502BDA    | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| SN74LS90N          | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS90N          | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS90N.A        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS90N.A        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS90NE4        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS90NE4        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS92D          | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LS92D.A        | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LS92N          | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS92N          | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS92N.A        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS92N.A        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS93D          | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LS93D.A        | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LS93N          | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS93N          | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS93N.A        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74LS93N.A        | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SNJ54LS93W         | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| SNJ54LS93W.A       | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |

**D0014A****PACKAGE OUTLINE****SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



4220718/A 09/2016

**NOTES:**

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm, per side.
5. Reference JEDEC registration MS-012, variation AB.

# EXAMPLE BOARD LAYOUT


D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
SCALE:8X



SOLDER MASK DETAILS

4220718/A 09/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:8X

4220718/A 09/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK



## NOTES:

- All linear dimensions are in inches (millimeters).
- This drawing is subject to change without notice.
- This package can be hermetically sealed with a ceramic lid using glass frit.
- Index point is provided on cap for terminal identification only.
- Falls within MIL STD 1835 GDFP1-F14

**J 14**

## GENERIC PACKAGE VIEW

**CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4040083-5/G

**J0014A****PACKAGE OUTLINE****CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



4214771/A 05/2017

**NOTES:**

1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.

# EXAMPLE BOARD LAYOUT

J0014A

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



LAND PATTERN EXAMPLE  
NON-SOLDER MASK DEFINED  
SCALE: 5X



4214771/A 05/2017

## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



14/18 Pin Only  
20 Pin vendor option

4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated