




GENERAL TOLERANCE											
	10 MAX	50 MAX	100 MAX	250 MAX	250 OVR	R5 MAX	R10 MAX	R20 MAX	R20 OVR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.2	±0.3	±0.5	±2.5	±3°	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4					±3°	0.1
C	±0.3	±0.5	±0.8	±1.4	±2					±3°	0.15



PART NO. AND CH. CODE	COLOR
7183-1616, [B]	NATURAL
7183-1616-30, [B]	BLACK
7183-1616-40, [B]	LIGHT GRAY
7183-1616-90, [B]	BLUE

①

②

注記

1. 材質 : PBT

色 : 色品番表参照

2. かん合相手品番 : 7282-1025 ETC.

② 3. 取扱説明書No. YPES-15-618

NOTES

1. MATERIAL : PBT

COLOR : SEE TABLE

2. MATING PART NO. : 7282-1025 ETC.

② 3. HANDLING MANUAL No. YPES-15-618

ISSUE MARK

								CUSTOMER				MATL. SPEC.				SEE NOTES		TREAT. & FIN.		TOSSE MARK		
②	11/01/21	CHANGED PART NAME, ETC.			C11-ZA40	J. G	CUSTOMER PART NO.			CUSTOMER DWG NO.			NAME ② HLC 4.8 2P HOUSING FEMALE									
①	06/02/20	ADDED COLOR NO., ETC.			C06-Z170	H. T																
	03/08/06	NEW, [B]			C03-X492	E. F	OFFICE			TRIAL PART NO.												
LET	DATE	REVISION RECORD			NO.	CHKD	VENDOR															
GENERAL TOLERANCE							VENDOR NO.															
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE		DWG DATE	UNIT	SCL	ANGLE	PART NO.		7183-1616 ETC.					
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW		03/08/06	mm	2:1	3	CH. CODE							
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN			DWG NO.		7183-1616:R				SET DWG NO.	
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	M. FUKUDA	O. SUGIYAMA		K. KIDA	K. WATANABE		J. GALLARES		YAZAKI CORPORATION						
SPECIFIED						MASS		11/01/21	11/01/21	11/01/21	02/12/25		11/01/21									