


APHC-03103-S

Peltier cooler module

Data sheet



Features

- RoHs and Reach I 6I compliant
- Solid-state reliability
- Built with high temperature solder with the ability to withstand <200°C assembly processing temperatures for short periods of time
- High integrity nickel diffusion barriers on elements
- High strength for rugged environments
- Porched style for enhanced leadwire strength
- Sealed & lapped for multi-module applications

I _{max}	[A]	2.5
V _{max}	[V _{dc}]	3.6
P _c max	[W]	6
ACR	[Ω]	1.2
ΔT _{max}	[°C]	65
A	[mm]	16
AI	[mm]	16
B	[mm]	20.5
H	[mm]	3.94
L	[mm]	100
Wire	AWG	20





- (At hot side temperature $T_h = 27^\circ\text{C} / 300\text{K}$, under dry N_2)
- $P_c \text{ max}$ = Cooling power at $\Delta T = 0$ and $I = I_{\text{max}}$
- ΔT_{max} = Temperature difference at $I = I_{\text{max}}$ and $P_c = 0$
- Max hot side temperature $T_h = 200^\circ\text{C}$ for best long term performance
- Max mounting pressure: 1.5MPa
- Wires: UL-style 1569, 105oC (Unstripped)



APHC-03 I03-S

Peltier cooler module





Data sheet - At hot side temperature 25°C



APHC-03103-S

Peltier cooler module

Data sheet - At hot side temperature 50°C



APHC-03103-S

Peltier cooler module

Data sheet - At hot side temperature 75°C

