UR

UNI-ROYAL

厚聲集團

2019~2020

# 厚聲電阻




**Our Mission:**

Create value for customers, business associates and partners by providing reliable products and quality services.

**我们的使命：**

通过提供可信赖的产品和服务，为顾客、企业成员和合作伙伴创造价值。

**Our Vision:**

Become an excellent global supplier of passive components.

Be a respectable corporation to customers, business associates and partners.

**我们的愿景：**

以产品和服务成为电子制造业卓越的全球供货商。

做客户、企业成员、合作伙伴尊敬的企业。

厚声集团・昆山总部（Kunshan HQ)

UNI-ROYAL Group, founded in Hsinchu, Taiwan in 1978, has become a global leader in CHIP and DIP resistors industry. With more than 40 years of manufacturing experience, UNI-ROYAL has a profound industry insight and innovation leadership for the global electronics industry. UNI-ROYAL has a complete R&D team, manufacturing plants, global sales team and marketing service network located in Taiwan, Kunshan, Shenzhen, Xiamen, and Southeast Asia (Thailand). The group's four well-known brands: **ROYALOHM, UNIOHM, FOSS, AEON**, has become the world's favorite passive components suppliers and preferred partners.

UNI-ROYAL has successively been awarded many international standard system certifications such as QS9000, ISO14001, TL9000 and IATF16949. Products are widely used in microelectronics, mobile terminals, industrial equipment, automotive electronics, the Internet and other emerging civil and military high-tech industries. With the continuous development of the global economy, the iterative update of modern technology, especially the ever-changing application and innovation in the field of electronics, UNI-ROYAL has always provided cutting-edge technology, excellent products and leading solutions to supply a full range of products and services to well-known companies in the global industry.

厚声集团，始创于 1978 年台湾新竹，迄今已经成为全球晶片电阻和插件电阻的行业领导者。凭借逾四十年的制造经验，厚声对全球电子行业拥有深刻的行业洞察与创新领导能力。集团在台湾、昆山、深圳、厦门与东南亚（泰国）拥有完善的电阻研发团队、制造工厂及遍布全球的销售团队和营销服务网络。集团旗下四大著名品牌：**ROYALOHM**、**UNIOHM**、**FOSS**、**AEON**，已成为全球各行业备受青睐的被动元器件重要供货商和首选合作伙伴。

厚声先后获得 QS9000、ISO14001、TL9000、IATF16949 等多项国际标准体系认证。产品广泛应用于微电子、移动终端、工業設備、汽车电子、物联网等新兴民用与军工众多高科技领域。随着全球经济的不断发展、现代化技术的迭代更新，特别是电子领域日新月异的应用革新，厚声始终以前沿的技术、出色的产品和领先的解决方案，向全球行业知名企业提供全方位的产品和服务。

## Milestone

| | | |
|---|---|---|
| 1978 | Hsinchu, Taiwan | Uniroyal Taiwan |
| 1988 | Bangkok, Thailand | Royal Electronic Factory (Thailand) Co., Ltd. |
| 1992 | Kunshan, China | Uniroyal Electronics Industry Co., Ltd |
| 2003 | Kunshan, China | FOSS Electronics Material |
| 2009 | Xiamen, China | Aeon Technology (Xiamen) Corportation |
| 2014 | Kunshan, China | Uniroyal Electronics Industry Co., Ltd - New Area |
| 2016 | Kunshan, China | Uniroyal Electronics Global Co., Ltd.: KS HQ, Shenzhen Branch, Xiamen Branch |

## 厚声集团沿革

| | | |
|---|---|---|
| 1978 | 台湾新竹 | 台湾厚声 |
| 1988 | 泰国曼谷 | 泰国厚声 |
| 1992 | 中国昆山 | 昆山厚声 |
| 2003 | 中国昆山 | 昆山福仕电材 |
| 2009 | 中国厦门 | 厦门翔声科技 |
| 2014 | 中国昆山 | 昆山厚声 - 新厂区 |
| 2016 | 中国昆山 | 厚声国际贸易：昆山总公司、深圳分公司、厦门分公司 |

(Thailand 1988)

0 (Xiamen 2009)

(Kunshan 2003)

(Thailand 2015)

UNI-ROYAL 厚聲集團

# Metal Glaze Film Fixed Resistors
## 金属玻璃釉膜固定电阻器

ROYALOHM
www.royalohm.com



## Feature (特性)

- Provide high stable performance against environment conditions & overload voltage
  耐高压，稳定性强，抗湿热高温环境
- Can withstand High Surge Voltage 可承受高浪涌电压
- Wide resistance range & low TCR 阻值范围宽，温度系数低
- VDE items available (File NO:40003686、A414、D708、A759)
  产品VDE 认证（认证号：40003686、A414、D708、A759）
- UL items available (File NO:20130925-E364163、E244546)
  产品UL安规 认证（认证号：20130925-E364163、E244546）

The tolerance ±5% has five color codes, and the last one is marked in black
公差 ±5% 有五道色码，最后一道以黑色标示

Tolerance ±1% with 5 color codes
公差 ±1% 有 5 道色码

## Dimension
## (尺寸) mm




## Surge Withstanding Voltage
## (承受浪涌电压)




## Derating Curve
## (降功率曲线)




- Normal size: The discharge cycle is repeated in above circuit: 2.5 seconds"ON",2.5"OFF",50 cycles, C=0.001uf.
  正常尺寸：右图中充放电回路 :2.5 秒 " 通 "，2.5 秒 " 断 "，50 次循环，电容容值 C=0.001uf.
- Small Size: The discharge cycle is repeated in above circuit: 2.5 seconds"ON",2.5 seconds "OFF",10 cycles, C=0.01uf.
  小型化产品：右图中充放电回路 :2.5 秒 " 通 "，2.5S" 断 "，10 次循环，电容容值 C=0.01uf.
- The applied DC source voltage is shown as below table. 电路中的直流电压如下表 " 承受浪涌电压 " 所述 .

## Specification(性能)

| Part No 料号 | Type 类型 | Power Rating 功率 70 °C | Dimension ( 尺寸 )(mm) | | | | MAX. Working Voltage 最大工作电压 | MAX. Overlaod Voltage 最大过负荷电压 | Dielectric Withstanding Voltage 绝缘耐压 | Surge Withstanding Voltage 浪涌电压 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | D | L | d ±0.05 | H±3 | | | | | |
| **Normal Size( 正常尺寸)** | | | | | | | | | | | |
| **MGR0W4** | MGR-25 | 1/4W | 2.2±0.5 | 6.5±1.0 | 0.60 | 28 | 1,600V | 2,000V | 700V | ≥100KΩ 10000V | 1KΩ~510MΩ (±5%,±10%) ≤10MΩ(±1%) 10M~100M(±2%) |
| **MGR0W2** | MGR-50 | 1/2W | 3.5±0.6 | 9.5±1.0 | 0.60 | 28 | 3,500V | 4,000V | 700V | | |
| **MGR01W** | MGR-100 | 1W | 4.0±0.6 | 11.5±1.0 | 0.75 | 25 | 3,500V | 4,000V | 1000V | | 1KΩ~1GΩ (±5%,±10%) ≤10MΩ:±1% 10M~100M(±2%) |
| **MGR02W** | MGR-200 | 2W | 5.0±0.6 | 15.5±1.0 | 0.80 | 28 | 3,500V | 4,000V | 1000V | | |
| **MGR03W** | MGR-300 | 3W | 6.0±0.6 | 17.5±1.0 | 0.80 | 28 | 3,500V | 4,000V | 1000V | | 1KΩ~100MΩ (±5%,±10%) 100K~1M(±1%) |
| **Small Size&Ultra Small Size( 小型尺寸)** | | | | | | | | | | | |
| **MGR0S2** | MGR-50-S | 1/2W-S | 2.2±0.5 | 6.5±1.0 | 0.60 | 28 | 500V | 700V | 500V | 100KΩ~1M:3000V 1M1~6M2: 4000V ≥6M8: 6000V | 1KΩ~33MΩ (±5%,±10%) 100KΩ~1MΩ (±1%) |
| **MGR01S** | MGR-100-S | 1W-S | 3.5±0.6 | 9.5±1.0 | 0.60 | 28 | 700V | 1000V | 700V | 100KΩ~1M:4000V 1M1~6M2: 5000V ≥6M8: 8000V | |
| **MGR02S** | MGR-200-S | 2W-S | 4.5±0.6 | 11.5±1.0 | 0.75 | 25 | 1000V | 1400V | 700V | 100KΩ~1M:5000V 1M1~6M2: 6000V ≥6M8: 9000V | |
| **MGR03U** | MGR-300-SS | 3W-SS | 4.5±0.6 | 11.5±1.0 | 0.75 | 25 | 1000V | 1400V | 700V | | |
| **MGR03S** | MGR-300-S | 3W-S | 5.0±0.6 | 15.5±1.0 | 0.80 | 28 | 1000V | 1400V | 700V | 100KΩ~1M:8000V 1M1~6M2: 9000V ≥6M8: 10000V | |

## Performance Specification(性能)

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | ≤±200PPM°C |
| **Short-time Overload** | 短时间过负荷 | ΔR/R ≤ ±(1%+0.05 Ω),with no evidence of mechanical damage ( 无可见机械损伤) |
| **Dielectric withstanding voltage** | 绝缘耐压 | With no evidence of flashover,mechanical damage,arcing or insulation breakdown ( 无击穿 · 飞弧及可可见机械损伤 ) |
| **Pulse Overload** | 脉冲过负荷 | ΔR/R ≤ ± (2%+0.05),with no evidence of mechanical damage ( 无可见机械损伤) |
| **Terminal strength** | 端子强度 | No evidence of mechanical damage ( 无可见机械损伤 ) |
| **Soldering heat** | 耐焊接热 | ΔR/R ≤ ±(1%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Resistance to solvent** | 耐熔剂 | No deterioration of protective coating and marking ( 包封层，色码完整) |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R ≤ ±(1%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤) |
| **Load life in humidity** | 湿度寿命 | ΔR/R ≤ ±(5%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤) |
| **Load life** | 负载寿命 | ΔR/R ≤ ±(5%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤) |
| **Surge Withstanding Voltage** | 尖峰脉冲 | ΔR/R ≤ ±(20%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤) |

## Ordering Procedure (Example: MGR 1W 5% 27MΩ T/B-1000)

## 订购方式 (例如: MGR 1W 5% 27MΩ T/B-1000)

**M G R 0 1 W J 0 2 7 6 A 1 0**

**Product Type (产品类型):**
MGR=Metal Glaze Film Fixed Resistors
(金属玻璃釉膜固定电阻器)

**Special Feature (特征):**
O=Standard( 标准品)

**Wattage (功率):**

| | | |
|---|---|---|
| W4=1/4W | S2=1/2W-S | W2=1/2W |
| 1S=1W-S | 1W=1W | 2S=2W-S |
| 2W=2W | 3U=3W-SS | 3S=3W-S |
| 3W=3W | | |

**Tolerance (公差):**
F=±1% G=±2% J=±5%

**Resistance Value (阻值):**
**5% & 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**5%,10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.
**1%(E-24,E-96 Series)**
The 1st to 3rd digits are for the significant figures of the resistance and the 4th digit denotes number of zeros following:
**1% 产品 (E-24,E-96 系列阻值)**
第 1~3 位表示阻值的有效数，第 4 位表示有几个 0.

**Packing Type( 包装类型 ):**
A=Tape/Box ( 编带 / 盒装 )
T=Tape/Reel ( 编带 / 卷装 )
B=Bulk/Box ( 散装 / 盒装 )
P=Tape/Box of PT-26 product
编带 (PT-26 产品) / 盒装

**Packing Qty. (包装数量):**
1=1,000pcs
2=2,000pcs
3=3,000pcs
4=4,000pcs
5=5,000pcs
A=500pcs
B=2,500pcs
0=Bulk/Box
( 散装 / 盒装 )

**Additional Information( 注 ):**
0=NIL( 标准品 )
P=Panasert type 1=Avisert type 1
2=Avisert type 2 3=Avisert type 3
8=PT-58mm 9=PT-64mm
7=Lead wire(H)38mm
A=PT-83mm C=PT-73mm
D=PT-71mm

## New/Old Part.no Contrast (新旧料号对照)

| New Part.no 新料号 | Old Part.no 旧料号 |
|---|---|
| **MGR0**J******* | HMGR**J******* |
| **MGR0**J******* | HVR0**J******* |
| **MGR*S2******** | MGR*U2******** |

**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

# Fusible Resistors
## 保险丝电阻器



## Feature (特性)

- Ideal circuit opening controller,disconnecting units from overload rating specified .
  理想的电流过负荷保护组件
- Too low or too high ohmic value can be supplied on a case to case to case basis.
  超高或超低阻值也能特别生产
- UL items available (File NO:E306074、E245468)
  产品UL安规认证 (认证号：E306074、E245468)

## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




## Specification(性能)

| Part No 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | | Dielectric Withstanding Voltage 绝缘耐压 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|
| | | | D | L | d ±0.05 | H±3 | PT | | |
| **FRN0W4** | FRN-25 | 1/4W | 2.2±0.5 | 6.5±1.0 | 0.60 | 28 | 52 | 300V | 0.22Ω~10KΩ |
| **FRN0S2** | FRN-50-S | 1/2W-S | 2.2±0.5 | 6.5±1.0 | 0.60 | 28 | 52 | 300V | 0.22Ω~10KΩ |
| **FRN004** | FRN-40 | 0.4W | 2.2±0.5 | 6.5±1.0 | 0.60 | 28 | 52 | 300V | 0.22Ω~10KΩ |
| **FRN0W2** | FRN-50 | 1/2W | 3.0±0.5 | 9.0±1.0 | 0.60 | 28 | 52 | 350V | 0.22Ω~10KΩ |
| **FRN075** | FRN-75 | 3/4W | 3.5±0.6 | 9.5±1.0 | 0.54 | 28 | 52 | 350V | 0.22Ω~10KΩ |
| **FRN01W** | FRN-100 | 1W | 3.5±0.6 | 9.5±1.0 | 0.54 | 28 | 52 | 350V | 0.22Ω~10KΩ |
| **FRN01A** | FRN-150 | 1.5W | 4.5±0.6 | 11.5±1.0 | 0.70 | 25 | 52 | 600V | 0.22Ω~10KΩ |
| **FRN02W** | FRN-200 | 2W | 4.5±0.6 | 11.5±1.0 | 0.70 | 25 | 52 | 600V | 0.22Ω~10KΩ |
| **FRN03W** | FRN-300 | 3W | 5.0±0.6 | 15.5±1.0 | 0.80 | 28 | 64 | 600V | 0.22Ω~10KΩ |

## Fusing Characteristics (熔断特性)

| Resistance Value ( 阻值 ) | Test Wattage ( 测试功率 ) | Fusing Time ( 熔断时间 ) |
|---|---|---|
| ≤2.2Ω | 32 X Power Rating ( 额定功率 ) | ≤ 60 seconds ( 秒 ) |
| >2.2Ω | 16 X Power Ratring ( 额定功率 ) | ≤ 60 seconds ( 秒 ) |

The fusing test current or voltage should be stable, change within 5%. ( 测试电流或电压必须稳定变化率不超过 5%)

## Performance Specification(性能)

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | ±350PPM/℃ |
| **Short-time Overload** | 短时间过负荷 | ΔR/R ≤ ±(2%+0.05 Ω),with no evidence of mechanical damage ( 无可见机械损伤) |
| **Dielectric withstanding voltage** | 绝缘耐压 | With no evidence of flashover,mechanical damage,arcing or insulation breakdown ( 无击穿 · 飞弧及可可见机械损伤 ) |
| **Terminal strength** | 端子强度 | No evidence of mechanical damage （无可见机械损伤 ) |
| **Soldering heat** | 耐焊接热 | ΔR/R ≤ ±(1%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R ≤ ±(2%+0.05 Ω） with no evidence of mechanical damage （无可见机械损伤） |
| **Load life in humidity** | 湿度寿命 | ΔR/R ≤ ±(5%+0.05 Ω） with no evidence of mechanical damage （无可见机械损伤） |
| **Load life** | 负载寿命 | ΔR/R ≤ ±(5%+0.05 Ω） with no evidence of mechanical damage （无可见机械损伤） |
| **Flame retardant** | 阻燃 | Resistor insulation is self-extinguishing within 10 seconds after externally applied flame is removed （火焰移开后 10S 内，电阻自动绝燃，无可见火焰） |

## Ordering Procedure (Example: FRN 1W 5% 1Ω T/B-1000)

### 订购方式 (例如: FRN 1W 5% 1Ω T/B-1000 )

**F R N 0 1 W J 0 1 0 J A 1 0**

**Product Type (产品类型):**
FRN=Fusible Resistors
(保险丝电阻器)

**Special Feature (特征):**
O=Standard(标准品)

**Wattage (功率):**
W4=1/4W W2=1/2W
1W=1W 2W=2W
3W=3W S2=1/2WS
04 = 0.4W 75=3/4W
1A=1.5W

**Tolerance (公差):**
G=±2% J=±5%
K=±10%

**Resistance Value (阻值):**
**2%, 5%, 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**2%, 5%, 10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.
**≤1% (E-96 series):**
the 1st to 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following.
**≤1% 产品 (E-96 系列阻值 ):**
第 1~3 位表示阻值的有效数 , 第 4 位表示有几个 0.

**Packing Type( 包装类型 ):**
A=Tape/Box ( 编带 / 盒装 )
T=Tape/Reel ( 编带 / 卷装 )
B=Bulk/Box ( 散装 / 盒装 )

**Packing Qty.**
**(包装数量):**
1=1,000pcs
2=2,000pcs
3=3,000pcs
4=4,000pcs
5=5,000pcs
A=500pcs
B=2,500pcs
0=Bulk/Box
( 散装 / 盒装 )

**Additional Information( 注 ):**
0=NIL( 标准品 )
P=Panasert type 1=Avisert type 1
2=Avisert type 2 3=Avisert type 3
8=PT-58mm 9=PT-64mm
7=Lead wire(H)38mm
A=PT-83mm C=PT-73mm
D=PT-71mm

**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

# Wire-Wound Fixed Resistors
## 绕线型固定电阻器



## Feature (特性)

- Excellent flame retardant coating 优异不燃性涂装
- Too low or too high ohmic value can be supplied on a case to basis
  超低阻值或超高阻值都可特别提供
- Non-inductive type available
  可特别提供无感型产品

## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




## Specification(性能)

| Part No 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|
| | | | D±1 | L±1 | d ±0.05 | H±3 | PT | |
| **KNP0W4** | KNP-25 | 1/4W | 2.5 | 6.5 | 0.54 | 28 | 52 | 0.01Ω~200Ω |
| **KNP0S2** | KNP-50-S | 1/2WS | 2.5 | 6.5 | 0.54 | 28 | 52 | 0.01Ω~200Ω |
| **KNP0W2** | KNP-50 | 1/2W | 3.0 | 9.5 | 0.54 | 28 | 52 | 0.01Ω~390Ω |
| **KNP01S** | KNP-100-S | 1W-S | 3.0 | 9.5 | 0.54 | 28 | 52 | 0.01Ω~390Ω |
| **KNP01W** | KNP-100 | 1W | 4.5 | 11.5 | 0.70 | 25 | 52 | 0.01Ω~1.2KΩ |
| **KNP02S** | KNP-200-S | 2W-S | 4.5 | 11.5 | 0.70 | 25 | 52 | 0.01Ω~1.2KΩ |
| **KNP02W** | KNP-200 | 2W | 5.5 | 15.5 | 0.70 | 28 | 64 | 0.01Ω~3.0KΩ |
| **KNP03S** | KNP-300-S | 3W-S | 5.5 | 15.5 | 0.70 | 28 | 64 | 0.01Ω~3.0KΩ |
| **KNP03W** | KNP-300 | 3W | 6.5 | 17.5 | 0.75 | 28 | 64 | 0.039Ω~3.9KΩ |
| **KNP05S** | KNP-500-S | 5W-S | 6.5 | 17.5 | 0.75 | 28 | 64 | 0.039Ω~3.9KΩ |
| **KNP05W** | KNP-500 | 5W | 8.5 | 24.5 | 0.75 | 38 | 90 | 0.082Ω~5.6KΩ |
| **KNP07S** | KNP-700-S | 7W-S | 8.5 | 24.5 | 0.75 | 38 | 90 | 0.082Ω~5.6KΩ |
| **KNP07W** | KNP-700 | 7W | 8.5 | 29.5 | 0.75 | 38 | B/B | 0.1Ω~8.2KΩ |
| **KNP08S** | KNP-800-S | 8W-S | 8.5 | 29.5 | 0.75 | 38 | B/B | 0.1Ω~8.2KΩ |
| **KNP08W** | KNP-800 | 8W | 8.5 | 39.5 | 0.75 | 38 | B/B | 0.15Ω~12KΩ |
| **KNP09S** | KNP-900-S | 9W-S | 8.5 | 39.5 | 0.75 | 38 | B/B | 0.15Ω~12KΩ |
| **KNP09W** | KNP-900 | 9W | 8.5 | 52.5 | 0.75 | 38 | B/B | 0.22Ω~15KΩ |
| **KNP0AS** | KNP-1000-S | 10W-S | 8.5 | 52.5 | 0.75 | 38 | B/B | 0.22Ω~15KΩ |

## KNS Type (KNS型)




## Derating Curve (降功率曲线)



| Part No 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|
| | | | D±1 | L±1.5 | P ±1.0 | H±1.0 | h±1.0 | B±0.5 | |
| **KNS02W** | KNS-200 | 2W | 7.0 | 19.0 | 8 | 19 | 12 | 4.5 | 0.05Ω~470Ω |
| **KNS03W** | KNS-300 | 3W | 7.0 | 21.0 | 10 | 19 | 13 | 4.5 | 0.068Ω~470Ω |
| **KNS05W** | KNS-500 | 5W | 9.0 | 26.0 | 15 | 21.5 | 13 | 6.5 | 0.01Ω~750Ω |
| **KNS07W** | KNS-700 | 7W | 9.0 | 31.0 | 20 | 21.5 | 13 | 6.5 | 0.1Ω~1.1KΩ |
| **KNS08W** | KNS-800 | 8W | 9.0 | 41.0 | 32.5 | 21.5 | 13 | 6.5 | 0.2Ω~2.2KΩ |
| **KNS0AW** | KNS-1000 | 10W | 9.0 | 54.0 | 43 | 21.5 | 13 | 6.5 | 0.3Ω~3.3KΩ |

## KNH Type (KNH型)




## KNHA Type (KNHA型)



| Part No 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|
| | | | A±1.5 | B±1.5 | C ±3 | D±1 | |
| **KNH020** | KNH-20W | 20W | 19 | 50 | 19 | 5 | 0.4Ω~10KΩ |
| **KNH025** | KNH-25W | 25W | 19 | 60 | 19 | 5 | 0.4Ω~10KΩ |
| **KNH030** | KNH-30W | 30W | 19 | 75 | 19 | 5 | 0.5Ω~15KΩ |
| **KNH040** | KNH-40W | 40W | 19 | 90 | 19 | 5 | 0.6Ω~20KΩ |
| **KNH050** | KNH-50W | 50W | 31<br>28 | 75 | 31 | 8 | 3Ω~25KΩ |
| **KNH060** | KNH-60W | 60W | 31<br>28 | 90 | 31 | 8 | 3Ω~30KΩ |
| **KNH080** | KNH-80W | 80W | 31<br>28 | 115 | 31 | 8 | 3Ω~40KΩ |
| **KNH.....100** | KNH-100W | 100W | 31<br>28 | 140 | 31 | 8 | 3Ω~50KΩ |
| **KNHA25** | KNHA-25W | 25W | 21 | 41 | 24 | 5 | 0.4Ω~10KΩ |
| **KNHA30** | KNHA-30W | 30W | 21 | 42 | 24 | 5 | 0.4Ω~10KΩ |

# Wire-Wound Non-inductive Fixed Resistors

## 绕线无感电阻器



## Feature (特性)

- Excellent flame retardant coating 优异不燃性漆
- Too low or too high ohmic value can be supplied on a case to case basis
  超低或超高阻值都可特别提供
- Non-inductive production process 无感的制作工艺

## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




| Part No 料号 | Type 类型 | Dimension ( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|
| | | D±1 | L±1 | d±0.05 | H±3 | PT | |
| **KNPNW2** | KNPN-50 | 3.0 | 9.5 | 0.54 | 28 | 52 | 0.01Ω~30Ω |
| **KNPN1S** | KNPN-100-S | 3.0 | 9.5 | 0.54 | 28 | 52 | |
| **KNPN1W** | KNPN-100 | 4.0 | 11.5 | 0.70 | 25 | 52 | 0.01Ω~62Ω |
| **KNPN2S** | KNPN-200-S | 4.0 | 11.5 | 0.70 | 25 | 52 | |
| **KNPN2W** | KNPN-200 | 5.5 | 15.5 | 0.70 | 28 | 64 | 0.018Ω~120Ω |
| **KNPN3S** | KNPN-300-S | 5.5 | 15.5 | 0.70 | 28 | 64 | |
| **KNPN3W** | KNPN-300 | 6.5 | 17.5 | 0.75 | 28 | 64 | 0.024Ω~150Ω |
| **KNPN5S** | KNPN-500-S | 6.5 | 17.5 | 0.75 | 28 | 64 | |
| **KNPN5W** | KNPN-500 | 8.5 | 24.5 | 0.75 | 38 | 90 | 0.043Ω~430Ω |
| **KNPN7S** | KNPN-700-S | 8.5 | 24.5 | 0.75 | 38 | 90 | |
| **KNPN7W** | KNPN-700 | 8.5 | 29.5 | 0.75 | 38 | B/B | 0.047Ω~430Ω |
| **KNPN8S** | KNPN-800-S | 8.5 | 29.5 | 0.75 | 38 | B/B | |
| **KNPN8W** | KNPN-800 | 8.5 | 39.5 | 0.75 | 38 | B/B | 0.091Ω~620Ω |
| **KNPN9S** | KNPN-900-S | 8.5 | 39.5 | 0.75 | 38 | B/B | |
| **KNPN9W** | KNPN-900 | 8.5 | 52.5 | 0.75 | 38 | B/B | 0.13Ω~820Ω |
| **KNPNAS** | KNPN-1000-S | 8.5 | 52.5 | 0.75 | 38 | B/B | |

## Performance Specification( 性能 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | ≥20 Ω：±300PPM/℃； ＜ 20Ω：±400PPM/℃ |
| **Short-time Overload** | 短时间过负荷 | ΔR/R ≤ ±(2%+0.05 Ω)Max,with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Terminal strength** | 端子强度 | No evidence of mechanical damage （无可见机械损伤 ) |
| **Soldering heat** | 耐焊接热 | ΔR/R ≤ ±(1%+0.05 Ω)Max, with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Load life in humidity** | 湿度寿命 | ΔR/R≤ ±(5%+0.05 Ω)Max，with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life** | 负载寿命 | ΔR/R≤ ±(5%+0.05 Ω)Max，with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Resistance to solvent** | 耐溶剂 | No evidence of mechanical damage ( 无可见机械损伤 ) |

## Ordering Procedure (Example: KNP 3WS 5% 12Ω T/B-1000)

### 订购方式 (例如: KNP 3WS 5% 12Ω T/B-1000 )



# Wire-Wound Anti-Surge Fixed Resistors

## 绕线耐脉冲电阻器



## Feature (特性)

- Excellent flame retardant coating ( 优异不燃性涂装 )
- According to IEC 61000-4-5 ( 符合 IEC61000-4-5 标准 )
- Applies to electricity meters, home appliance and ballast ( 适用于电表、家电及整流器产品 )

## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




## KNPA Pulses Energy Curve (KNPA耐脉冲能量曲线)




## KNPA Pulses Voltage Curve (KNPA耐脉冲电压曲线)




| Part No 料号 | Type 类型 | Dimension ( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|
| | | D±1 | L±1 | d±0.05 | H±3 | PT | |
| **KNPAW2,01S** | KNPA-50,KNPA-100-S | 3.5 | 9.5 | 0.54 | 28 | 52 | 10Ω~820Ω |
| **KNPA1W,02S** | KNPA-100,KNPA-200-S | 4.5 | 11.5 | 0.70 | 25 | 52 | 10Ω~1.2KΩ |
| **KNPA2W,03S** | KNPA-200,KNPA-300-S | 5.5 | 15.5 | 0.70 | 28 | 64 | 10Ω~3.0KΩ |
| **KNPA3W,05S** | KNPA-300,KNPA-500-S | 6.5 | 17.5 | 0.75 | 28 | 64 | 10Ω~3.9KΩ |
| **KNPA5W,07S** | KNPA-500,KNPA-700-S | 8.5 | 24.5 | 0.75 | 38 | 90 | 10Ω~5.6KΩ |
| **KNPA7W,08S** | KNPA-700,KNPA-800-S | 8.5 | 29.5 | 0.75 | 38 | B/B | 10Ω~8.2KΩ |
| **KNPA8W,09S** | KNPA-800,KNPA-900-S | 8.5 | 39.5 | 0.75 | 38 | B/B | 10Ω~10KΩ |
| **KNPA9W,AS** | KNPA-900,KNPA-1000-S | 8.5 | 52.5 | 0.75 | 38 | B/B | 10Ω~15KΩ |

## Performance Specification( 性能 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | ±200PPM/°C |
| **Short-time Overload** | 短时间过负荷 | ΔR/R±(2%+0.05Ω)MAX，with no evidence of mechanical damage ( 无可见机械损伤) |
| **Terminal strength** | 端子强度 | No evidence of mechanical damage ( 无可见机械损伤 ) |
| **Soldering heat** | 耐焊接热 | ΔR/R±(1%+0.05Ω)) MAX，with no evidence of mechanical damage ( 无可见机械损伤) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R±(2%+0.05Ω) MAX，with no evidence of mechanical damage ( 无可见机械损伤) |
| **Load life in humidity** | 湿度寿命 | ΔR/R±(5%+0.05Ω) MAX，with no evidence of mechanical damage ( 无可见机械损伤) |
| **Load life** | 负载寿命 | ΔR/R±(5%+0.05Ω) MAX，with no evidence of mechanical damage ( 无可见机械损伤) |
| **Surge Immunity** | 脉冲测试 | ΔR/R±(5%+0.05Ω) MAX |
| **Resistance to solvent** | 耐溶剂 | No evidence of mechanical damage ( 无可见机械损伤 ) |

## Surge Rating( 脉冲标准 )

| Type 类型 | Low Resistance Range 低阻值范围 | Maximum Surge Voltage 最大脉冲电压 | Medium Resistance Range 中阻值范围 | Maximum Surge Voltage 最大脉冲电压 | High Resistance Range 高阻值范围 | Maximum Surge Voltage 最大脉冲电压 |
|---|---|---|---|---|---|---|
| KNPA1/2W、1WS | 10Ω~40Ω | 2KV | 43Ω~240Ω | 3KV | 270Ω~820Ω | 4KV |
| KNPA1W、2WS | 10Ω~50Ω | 3KV | 51Ω~240Ω | 4KV | 270Ω~1.2KΩ | 5KV |
| KNPA2W、3WS | 10Ω~100Ω | 4KV | 110Ω~240Ω | 5KV | 270Ω~3.0KΩ | 6KV |
| KNPA3W、5WS | 10Ω~100Ω | 6KV | 110Ω~680Ω | 7KV | 750Ω~3.9KΩ | 8KV |
| KNPA5W、7WS | 10Ω~160Ω | 7KV | 180Ω~680Ω | 8KV | 750Ω~5.6KΩ | 9KV |
| KNPA7W、8WS | 10Ω~160Ω | 8KV | 180Ω~680Ω | 9KV | 750Ω~8.2KΩ | 10KV |
| KNPA8W、9WS | 10Ω~160Ω | 9KV | 180Ω~680Ω | 10KV | 750Ω~10KΩ | 10KV |
| KNPA9W、10WS | 10Ω~160Ω | 10KV | 180Ω~680Ω | 10KV | 750Ω~15KΩ | 10KV |

## Ordering Procedure (Example: KNPA 3WS 5% 12Ω T/B-1000)

## 订购方式 (例如: KNPA3WS 5% 12Ω T/B-1000 )




## New/Old Part.no Contrast (新旧料号对照)

| New Part.no 新料号 | Old Part.no 旧料号 |
|---|---|
| KNPA**J******* | KSR0**J******* |

# Wire-wound Fusible Resistors
## 绕线保险丝型电阻器



## Feature (特性)

- Suitable for all kinds of protection circuit 适用各种保护电路
- Non-flammable coating,could withstand High Temperature
  优异不燃性涂装，耐高温
- Common resistor with additional safety function , no flame or smoke, no explosion or coating crack when fusing
  常见的电阻器具有额外的安全性能，无火焰或烟，无爆炸或涂层裂纹
- UL items available (File NO:E306074)
  产品 UL 安规认证 (认证号：E306074)

## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




## Fuseing Curve (熔断曲线)




| Part No 料号 | Type 类型 | Power Rating 功率 70 °C | Dimension ( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|
| | | | D(Max) | L(Max) | H±3 | d±0.05 | PT | |
| **KNPU1U** | KNPU1W-SS | 1W-SS | 3.0 | 8.5 | 28 | 0.54 | 52 | 10Ω |
| **KNPU1S** | KNPU1W-S | 1W-S | 4.3 | 9.0 | 28 | 0.60 | 52 | 0.47Ω~240Ω |
| **KNPU1S** | KNPU1W-S | 1W-S | 4.3 | 10.0 | 28 | 0.75 | 52 | 0.47Ω~240Ω |
| **KNPU1W** | KNPU100 | 1W | 5.0 | 12.0 | 25 | 0.70 | 52 | 0.47Ω~240Ω |
| **KNPU2S** | KNPU2W-S | 2W-S | 5.0 | 12.0 | 25 | 0.70 | 52 | 0.47Ω~240Ω |
| **KNPU2W** | KNPU200 | 2W | 5.5 | 16.0 | 28 | 0.70 | 64 | 0.47Ω~240Ω |
| **KNPU3S** | KNPU3W-S | 3W-S | 5.5 | 16.0 | 28 | 0.70 | 64 | 0.47Ω~240Ω |
| **KNPU3W** | KNPU300 | 3W | 6.5 | 17.5 | 28 | 0.75 | 64 | 0.47Ω~240Ω |
| **KNPU5W** | KNPU500 | 5W | 8.0 | 20.0 | 38 | 0.75 | B/B | 0.47Ω~240Ω |
| **KNPU7W** | KNPU700 | 7W | 8.5 | 25.0 | 38 | 0.75 | B/B | 0.47Ω~47Ω |

## Performance Specification( 性能 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | ≥20 Ω: ±300PPM/℃<br><20 Ω: ±400PPM/℃ |
| **Short-time Overload** | 短时间过负荷 | ΔR/R ≤±(2%±0.05Ω), with no evidence of mechanical damage ( 无可 见机械损伤 ) |
| **Dielectric withstanding voltage** | 绝缘耐压 | No evidence of flashover, mechanical damage.(1000V).<br>无击穿、飞弧及可见机械损伤 (1000V) |
| **Terminal strength** | 端子强度 | No evidence of mechanical damage ( 无可见机械损伤 ) |
| **Soldering heat** | 耐焊接热 | ΔR/R ≤±(1%±0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Load life in humidity** | 湿度寿命 | ΔR/R ≤±(5%±0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life** | 负载寿命 | ΔR/R ≤±(5%±0.05Ω),<br>witn no evidence of mechanical damage ( 无可见机械损伤 ) |

## Ordering Procedure (Example: KNPU 3WS 5% 12Ω T/B-1000)

### 订购方式 (例如: KNPU3WS 5% 12Ω T/B-1000 )



## Feature (特性)

- Small body size 体积小
- High power 功率大
- Excellent flame retardant coating 优异的阻燃封装
- Provides stable performance in various environments
  在各种环境中提供优异的稳定性



## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




## Surge Withstanding Curve ( 脉冲曲线 )

100ms Single Pulse Power-Value Chart (100ms 单脉冲曲线 )




| Part No 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|
| | | | D±1 | L±1 | d±0.05 | H±3 | Max Working Voltage 最大工作电压 | Dieletric Withstand Voltage 绝缘耐压 | |
| **WPR01W** | WPR-100 | 1W | 2.5 | 6.2 | 0.60 | 28 | 50V | 250V | 0.1Ω~300Ω |
| **WPR02W** | WPR-200 | 2W | 3.5 | 9.0 | 0.75 | 28 | 50V | 250V | 0.1Ω~1KΩ |
| **WPR03W** | WPR-300 | 3W | 4.5 | 10.5 | 0.75 | 25 | 50V | 350V | 0.1Ω~1KΩ |
| **WPR04W** | WPR-400 | 4W | 5.5 | 15.5 | 0.75 | 28 | 50V | 350V | 0.1Ω~1.8KΩ |
| **WPR0AU** | WPR-1000-SS | 10W-SS | 8.5 | 39.5 | 0.75 | 38 | 50V | 350V | 1Ω~5KΩ |

## Performance Specification( 性能 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | ±200PPM/°C |
| **Short-time Overload** | 短时间过负荷 | ΔR/R≤±(5.0%+0.05Ω) with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Terminal strength** | 端子强度 | No evidence of mechanical damage ( 无可见机械损伤 ) |
| **Soldering heat** | 耐焊接热 | ΔR/R≤±(1.0%+0.05Ω) with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R≤±(2.0%+0.05Ω) with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Humidity (Steady State)** | 恒定湿热 | ΔR/R≤±(2.0%+0.05Ω) with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Pulse test** | 脉冲测试 | ΔR/R≤±(5.0%+0.05Ω) |
| **Resistance to solvent** | 耐溶剂 | No deterioration of protective coating and markings ( 包封层，色码完整 ) |
| **Load life in humidity** | 湿度寿命 | ΔR/R≤±(5.0%+0.05Ω) Max. with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life** | 负载寿命 | ΔR/R≤±(5.0%+0.05Ω) Max. with no evidence of mechanical damage ( 无可见机械损伤 ) |

## Ordering Procedure (Example: WPR1W 5% 100Ω T/B-1000)

## 订购方式 (例如: WPR1W 5% 100Ω T/B-1000 )




## New/Old Part.no Contrast (新旧料号对照)

| New Part.no 新料号 | Old Part.no 旧料号 |
|---|---|
| **WPR01WJ****A*0** | KNP01UJ****A*0 |
| **WPR02WJ****A*0** | KNP02UJ****A*0 |
| **WPR03WJ****A*0** | KNP03UJ****A*0 |
| **WPR04WJ****A*0** | KNP04UJ****A*0 |
| **WPR0AUJ****A*0** | KNP0AUJ****A*0 |

# Thermal Fusing Wire-wound Fixed Resistors

## 绕线型温度保险丝电阻器



## Feature (特性)

- Low resistance value with higher power dissipation 低阻值高功耗
- Wire-wound resistor with thermal fuse protection 绕线电阻热熔断保护
- Used in Electronic ballast ,other lighting applications
  一般用在电子整流器及其它照明用途

## Dimension(尺寸) mm




## Derating Curve (降功率曲线)




| Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | | | | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | D | L | H (Min) | h1 (Min) | d±0.02 | Current Rating | TF (°C) | TH/TC (°C) | TM (°C) | Ir | Ur | |
| TFR | 1W | 5.5±0.5 | 14±1 | 12 | 3.5 | 0.53 | 2A | 130 | 102 | 180 | 2 | 250 | 2.2Ω~4.7Ω |
| TFR | 1W | 5.5 $^{+1}_{-0.5}$ | 11(Max) | 12 | 3.5 | 0.53 | 1A | 130 | 102 | 180 | 1 | 250 | |

## Ordering Procedure (Example: TFR1W 5% 4.7Ω B/B)

## 订购方式 (例如: TFR1W 5% 4.7Ω B/B )

**T F R 0 1 W J 0 4 7 J B 0 0**

**Product Type (产品类型):**
TFR0=TFR

**Wattage (功率):**
1W=1W

**Tolerance (公差):**
J=±5% K=±10%

**Resistance Value (阻值):**
**5% & 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**5%,10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.

**Packing Type( 包装类型 ):**
B=Bulk/Box ( 散装 / 盒装 )

**Packing Qty. (包装数量):**
0=Bulk/Box
( 散装 / 盒装 )

**Additional Information( 注 ):**
0=Standard

## ZW Type (ZW 型)



| Part No 料号 | Type 类型 | L±3 | d±0.05 | O±1 | |
|---|---|---|---|---|---|
| **ZWA0** | ZW-A | 60/34 | 0.45 | 52 | 26 |
| **ZWB0** | ZW-B | 60/34 | 0.54 | 52 | 26 |
| **ZWB1** | ZW-B1 | 60/34 | 0.60 | 52 | 26 |
| **ZWC0** | ZW-C | 60/34 | 0.70 | 52 | 26 |
| **ZWD0** | ZW-D | 60/34 | 0.75 | 52 | 26 |
| **ZWE0** | ZW-E | 60/34 | 1.00 | 52 | 26 |

## ZO Type (ZO 型)




ZOC



ZOT

| Part No 料号 | Type | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | Resistance Range 阻值范围 (≤mΩ ) |
|---|---|---|---|---|---|---|---|
| | | | D±0.3 | L | d±0.05 | H±3 | |
| **ZOT0W8/ZOCOW8** | ZO-12 | 1/8W | 1.9 | 3.3±0.3 | 0.45 | 28 | ZOT：10<br>ZOC：50 |
| **ZOT0W4/ZOCOW4** | ZO-25 | 1/4W | 2.2 | 6.5±1.0 | 0.54 | 28 | |

## Performance Specification( 性能 )

| | | |
|---|---|---|
| **Lead material** | 引线材料 | Tin-Plated copper（镀锡铜线） |
| **Insulation resistance** | 绝缘阻值 | Dry( 干态 )-10,000MΩ,Wet( 湿态 )-100MΩ |
| **Dielectric withstanding voltage** | 绝缘耐压 | Atmospheric（正常气压）-500V RMS; Reduced（减压）-325VRMS; |
| **Rated current** | 额定电流 | 1/8W70°C 1.5A，1/4W 70°C 2.5A Derating to 0 Amps at 150°C<br>1/8W70°C 1.5A，1/4W 70°C 2.5A 150°C时，电流降低到 0A |

## Ordering Procedure (Example: ZOC 1/4W 0Ω T/R-5000)

## 订购方式 (例如: ZOC 1/4W 0Ω T/R-5000 )

**Z O C 0 W 4 0 0 0 0 0 0 T 5 0**

**Product Type (产品类型):**
Zero Ohm Resistors(0Ω电阻)
ZOT0=0Ω(铁棒涂漆0Ω电阻)
ZOC0=0Ω(镀铜瓷棒0Ω电阻)
Jumper Wire(跳线）:
ZWA0=0.45mm ZWB0=0.54mm
ZWB1=0.60mm ZWC0=0.70mm
ZWD0=0.75mm ZWE0=1.0mm

**Wattage (功率):**
Zero Ohm Resistors(0Ω 电阻)
W8=1/8W
W4=1/4W
Jumper Wire(跳线):
00=NIL

**Tolerance (公差):**
0=NIL

**Resistance Value (阻值):**
Fill-in these 4digits with "0" specially 填 4 个 0 表示 0 阻值

**Packing Type( 包装类型 ):**
A=Tape/Box ( 编带 / 盒装 )
T=Tape/Reel ( 编带 / 卷装 )
B=Bulk/Box ( 散装 / 盒装 )
P=Tape/Box of PT-26 product
编带 /（PT-26 产品）盒装

**Packing Qty. (包装数量):**
5=5,000pcs
7=7,000pcs
8=8,000pcs
C=10,000pcs
0=Bulk/Box
（散装 / 盒装）

**Additional Information( 注 ):**
0=NIL( 标准品 )

## New/Old Part.no Contrast (新旧料号对照)

| New Part.no 新料号 | Old Part.no 旧料号 |
|---|---|
| **ZOC0**00000A*0** | CFR0**00000A*0 |
| **ZOT0**00000A*0** | ZO00**00000A*0 |

| New Part.no 新料号 | Old Part.no 旧料号 |
|---|---|
| **ZWB10000000A*0** | ZWF00000000A*0 |
| **ZWE00000000A*0** | ZWF00000000A*0 |

*M-type jumpers can be customized on request *M型跳線可特別提供

## Copper Plated Steel Wire [铜包钢 (CP型) ]

## Tin Plated Copper Steel Lead Wire[镀锡铜包钢 (CT型) ]




| Part No 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | MAX.Working Voltage 最大工作电压 | MAX.Overlaod Voltage 最大过负荷电压 | Dielectric Withstanding Voltage 绝缘耐压 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | D | L | d ±0.05 | H±3 | | | | |
| **CPXXW8/CTXXW8** | CP/CT12 | 1/8W | 1.9±0.3 | 3.3±0.3 | 0.54 | 28 | 200V | 400V | 400V | 1Ω~10MΩ |
| **CPXXW4/CTXXW4** | CP/CT25 | 1/4W | 2.2±0.5 | 6.5±1.0 | 0.54 | 28/38 | 250V | 500V | 500V | 1Ω~10MΩ |
| **CPXXS3/CTXXS3** | CP/CT33-S | 1/3W-S | 2.2±0.5 | 6.5±1.0 | 0.54 | 28/38 | 300V | 600V | 500V | 1Ω~10MΩ |
| **CPXXW3/CTXXW3** | CP/CT33 | 1/3W | 3±0.5 | 9.0±1.0 | 0.54 | 28 | 300V | 600V | 700V | 1Ω~10MΩ |
| **CPXXS2/CTXXS2** | CP/CT50-S | 1/2W-S | 3±0.5 | 9.0±1.0 | 0.54 | 28 | 350V | 700V | 700V | 1Ω~10MΩ |

## Cutting Type (CO) [切割半成品型 (CO) 型]




| Part No. 料号 | Type 类型 | Power Rating 功率 70°C | Dimension ( 尺寸 )(mm) | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|
| | | | D | L | |
| **CO...W8** | CO-12 | 1/8W | 1.6 +0.10 -0.00 | 3.2 ±0.10 | 1Ω ~ 10MΩ |
| **CO...W4** | CO-25 | 1/4W | 2.1 +0.09 -0.00 | 5.6 +0.10 -0.20 | 1Ω ~ 10MΩ |
| **CO...W4...A** | CO-25-A | 1/4W | 2.1 +0.09 -0.00 | 5.9 +0.10 -0.15 | 1Ω ~ 10MΩ |
| **CO...W4...B** | CO-25-B | 1/4W | 2.1 +0.09 -0.01 | 6.4 +0.10 -0.15 | 1Ω ~ 10MΩ |

- Cutting type resistors are produced without lead-wire and without coating
  切割型半成品型电阻无导线，无涂装
- Cap plated option: 1. Tin-plated 2. Nickel-Plated
  铁帽：1 镀锡 2 镀镍

## Ordering Procedure (Example: CTO 1/4W 5% 10Ω T/B-5000, CTO lead wire)

## 订购方式 (例如: CTO 1/4W 5% 10Ω T/B-5000, CTO导线)

**C T O O W 4 J 0 1 0 0 A 5 0**

**Product Type (产品类型):**
CPO=Copper plated steel lead wire
铜包钢线 (H=28mm)
CPL=Copper plated steel lead wire
铜包钢线 (H=38mm)
CTO=Tin Plated copper steel lead wire
镀锡铜包钢线 (H=28mm)
CTL=Tin Plated copper steel lead wire
镀锡铜包钢线(H=38mm)
COT= Cutting type (Tin-Plated Cap)
[切割型 (镀锡铁帽) ]
CON= Cutting type (Nickel-Plated Cap)
[切割型 (镀镍铁帽) ]

**Special Feature (特征):**
O=Standard(标准品)
F=Flame Retardant (阻燃型)
I=Non-Inductive (无感型)

**Wattage (功率):**
W8=1/8W
W4=1/4W
W3=1/3W
S3=1/3WS
S2=1/2WS

**Tolerance (公差):**
G = ±2%
J = ±5%
K = ±10%

**Resistance Value (阻值):**
**2%, 5%, 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**2%, 5%, 10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.

**≤1% (E-96 series):**
the 1st to 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following.
**≤1% 产品 (E-96 系列阻值 ):**
第 1~3 位表示阻值的有效数 , 第 4 位表示有几个 0.

**Packing Type( 包装类型 ):**
A=Tape/Box ( 编带 / 盒装 )
T=Tape/Reel ( 编带 / 卷装 )
B=Bulk/Box ( 散装 / 盒装 )
P=Tape/Box of PT-26 product
编带 (PT-26 产品) / 盒装

**Packing Qty. (包装数量):**
1=1,000pcs,
2=2,000pcs
3=3,000pcs,
4=4,000pcs
5=5,000pcs,
A=500pcs
B=2,500pcs
0=Bulk/Box
( 散装 / 盒装 )

**Additional Information( 注 ):**
0=CP/CT Type
A=Co-25-A,
B=CO-25-B

## Feature (特性)

- This specification is applicable for CFR 1/4W,1/2W,1WS&CPR1/2W&MF1/4W,1/2WS,1/2W,1WS,2WS&MOR1/4W,1WS,2WS, KNP1/4W,1/2WS,1WS,2WS product only. KNP2WS product only; For other product (size), please consult factory for the available specification and drawing..

  下图规格适用于 CFR1/4W,1/2W,1WS&CPR1/2W&MF1/4W,1/2WS,1/2W,1WS,2WS&MOR1/4W,1WS,2WS,KNP1/4W,1/2WS,1WS,2WS. 其它产品的立 式加工，可洽询工厂以取得可生产的 规格图样。
- Standard product is insulated lead wire, insulated coating length 1/4W: 9.5±1mm; 1WS:13±1mm; 2WS:15±1mm
  标准品为绝缘引线，绝缘涂层长度为:
  1/4W: 9.5±1mm
  1WS: 13±1mm
  2WS: 15±1mm

Panasert Type 1:




Panasert Type 1:




Panasert Type 2:




| Items( 项目) | Symbol | Dimension 尺寸 (mm) | | | |
|---|---|---|---|---|---|
| | | 1/4W | 1/2WS | 1WS | 2WS |
| Body diameter 本体直径 | D | 2.5 (Max) | 3±0.5 | 3.5±0.5 | 4±0.5 |
| Body length 本体长度 | L | 6.8 (Max) | 9±1 | 9±1 | 11.5±1 |
| Body height 本体高度 | H | 12 (Max) | 17 (Max) | 19 (Max) | 21 (Max) |
| Lead-wire diameter 导线直径 | d | 0.60±0.05 | 0.60±0.05 | 0.70±0.05 | 0.70±0.05 |
| Pitch of component 零件间距 | p | 12.7±1 | 12.7±1 | 12.7±1 | 12.7±1 |
| Feed hole pitch 孔距 | P0 | 12.7±0.3 | 12.7±0.3 | 12.7±0.3 | 12.7±0.3 |
| Hole center to lead 中心测量 | P1 | 3.85±0.7 | 3.85±0.7 | 3.85±0.7 | 3.85±0.7 |
| Hole center to body 孔心至本体 | P2 | 6.35±1.3 | 6.35±1.3 | 6.35±1.3 | 6.35±1.3 |
| Lead to lead distance 两脚导线中心测量 | F | 5±1 | 5±1 | 5±1 | 5±1 |
| Component aligment 零件偏移 | Δh | 0±1 | 0±1 | 0±1 | 0±1 |
| Tape width 纸带宽度 | W | 18±1 | 18+1/-1.5 | 18+1/-1.5 | 18+1/-1.5 |
| Sticky tape width 热熔胶带宽 | W0 | 12.5 (Min) | / | 12.5 (Min) | 12.5 (Min) |
| | | 6 (min) | 6±0.2 | 6±0.2 | 6±0.2 |
| Hole position 孔位 | W1 | 9±0.5 | 9+0.75/-0.5 | 9+0.75/-0.5 | 9+0.75/-0.5 |
| Uncovered paper tape width 纸带露出宽度 | W2 | 1.5 (Max) | 1.5 (Max) | 1.5 (Max) | 1.5 (Max) |
| Lead –wire clinch height 导线固定高度 | H0 | 16.5 (Max) | 16±0.5 | 16±0.5 | 16±0.5 |
| Length of snipped lead 导线剪断高度 | H1 | 11 (Max) | 11 (Max) | 11 (Max) | 11 (Max) |
| Feed hole diameter 孔径 | D0 | 4±0.3 | 4±0.3 | 4±0.3 | 4±0.3 |
| Total tape thickness 胶带厚度 | t | 0.5±0.2 | 0.5±0.2 | 0.5±0.2 | 0.5±0.2 |
| Lead wire protrusion 导线露出 | i | 1Max | - | - | - |
| Length of lead cut 切脚的长度 | H1-w1 | 2±0.5 | 2±0.5 | 2±0.5 | 2±0.5 |

## Avisert(1) Type【Avisert(1)型】

- This specification is applicable for CFR1/4W,CPR1/2W&MF1/4W,1/2WS,0.6WS,MOR1/4W,1/2WS,product only; For other product (size), please consult factory for the specification and drawing.
  适用于 CFR1/4W, CPR1/2W & MF1/4W, 1/2WS, 0.6WS, MOR1/4W, 1/2WS 固定电阻。其它产品的立式加工，可洽询工厂以取得可生产的规格图样。
- Standard product is insulated lead wire,insulated coating length 9.5±1mm
  标准品为绝缘引线，绝缘涂层长度为 : 9.5±1mm。




| Items ( 项目) | Symbol | Dimension 尺寸 (mm) 1/4W |
|---|---|---|
| Body diameter 本体直径 | D | 2.5 (Max) |
| Body length 本体长度 | L | 6.8 (Max) |
| Lead-wire diameter 导线直径 | d | 0.60±0.05 |
| Pitch of component 零件间距 | p | 12.7±1 |
| Feed hole pitch 孔距 | P0 | 12.7±0.3 |
| Hole center to lead 中心测量 | P1 | 3.85±0.7 |
| Lead to lead distance 两脚导线中心测量 | F | 5±1 |
| Tape width 纸带宽度 | W | 18±1 |
| Sticky tape width 热熔胶带宽 | W0 | 12.5 (Min) |
| | | 6 (min) |
| Hole position 孔位 | W1 | 9.5±0.5 |
| Uncovered paper tape width 纸带露出宽度 | W2 | 3.0 (Max) |
| Height of component from tape center 零件至纸带中间的宽度 | H | 17.3±0.5 |
| Lead –wire clinch height 导线固定高度 | H0 | 16.5 (Max) |
| Component height 零件高度 | H1 | 34.5 (Max) |
| Length of snipped lead 导线剪断高度 | H2 | 11 (Max) |
| Feed hole diameter 孔径 | D0 | 4±0.3 |
| Total tape thickness 胶带厚度 | t | 0.5±0.2 |
| Lead wire protrusion 导线露出 | i | 1 (Max) |

## Avisert(2) Type【Avisert(2)型】

- This specification is applicable for CFR1/8W, 1/4WS&MF1/8W, 1/4WS product only; For other product avaiable forming products, please consult factory for the specification and drawing.
  适用于 CFR1/8W, 1/4WS&MF1/8W, 1/4WS 固定电阻。其它产品的立式加工，可洽询工厂以取得可生产的规格图样。




| Items ( 项目) | Symbol | Dimension 尺寸 (mm) 1/8W |
|---|---|---|
| Body diameter 本体直径 | D | 1.85 (Max) |
| Body length 本体长度 | L | 3.5 (Max) |
| Lead-wire diameter 导线直径 | d | 0.45±0.05 |
| Pitch of component 零件间距 | p | 12.7±1 |
| Feed hole pitch 孔距 | P0 | 12.7±0.3 |
| Hole center to lead 中心测量 | P1 | 3.85±0.7 |
| Hold center to component center 孔心至零件中心距离 | P2 | 6.35±1.3 |
| Lead to lead distance 两脚导线中心测量 | F | 5±1 |
| Tape width 纸带宽度 | W | 18±1 |
| Sticky tape width 热熔胶带宽 | W0 | 6 (Min) |
| Hole position 孔位 | W1 | 9.0±0.5 |
| Uncovered paper tape width 纸带露出宽度 | W2 | 3.0 (Max) |
| Lead wire protrusion 打弯处到纸带中心位置 | H | 21.25 (Max) |
| Component height 零件高度 | H1 | 32.25 (Max) |
| Length of snipped lead 导线剪断高度 | H2 | 11 (Max) |
| Feed hole diameter 孔径 | D0 | 4±0.3 |
| Total tape thickness 胶带厚度 | t | 0.5±0.2 |
| Lead wire protrusion 导线露出 | i | 1 (Max) |

## Avisert(3) Type【Avisert(3)型】

- This specification is applicable for CFR1/8W, CFR1/4WS, MF1/8W, MF1/4WS, MF1/4W, MF1/2WS, MF0.6WS, MOR1/4W, MOR1/2WS. For other product (size), please consult factory for the specification and drawing.
  下图规格适用于 CFR1/8W,CFR1/4WS,MF1/8W,MF1/4WS,MF1/4W,MF1/2WS,MF0.6WS,MOR1/4W,MOR1/2WS ; 其它产品的立式加工，可洽询工厂以取得可生产的规格图样 .
- Standard product is insulated lead wire,insulated coating length 9.5±1mm.
  标准品为绝缘引线，绝缘涂层长度为：9.5±1mm.




| Items ( 项目) | Symbol | Dimension 尺寸 (mm) | |
|---|---|---|---|
| | | 1/8W | 1/4W |
| Body diameter 本体直径 | D | 2.0 (Max) | 2.5 (Max) |
| Body length 本体长度 | L | 4.2 (Max) | 6.8 (Max) |
| Lead-wire diameter 导线直径 | d | 0.45±0.05 | 0.60±0.05 |
| Pitch of component 零件间距 | p | 12.7±1 | 12.7±1 |
| Feed hole pitch 孔距 | P0 | 12.7±0.3 | 12.7±0.3 |
| Hole center to lead 中心测量 | P1 | 3.85±0.7 | 3.85±0.7 |
| Lead to lead distance 两脚导线中心测量 | F | 2.5±1 | 5±1 |
| Tape width 纸带宽度 | W | 18±1 | 18±1 |
| Sticky tape width 热熔胶带宽 | W0 | 6min | 6min |
| Hole position 孔位 | W1 | 9.0±0.5 | 9.0±0.5 |
| Uncovered paper tape width 纸带露出宽度 | W2 | 3.0 (Max) | 3.0 (Max) |
| Body height 本体高度 | H | 7.0 (Max) | 10.0 (Max) |
| Lead –wire clinch height 导线固定高度 | H0 | 20.0 (Max) | 16.0 (Max) |
| Component aligment 零件偏移 | Δh | 0±1 | 0±1 |
| Length of snipped lead 导线剪断高度 | H1 | 11 (Max) | 11 (Max) |
| Feed hole diameter 孔径 | D0 | 4±0.3 | 4±0.3 |
| Total tape thickness 胶带厚度 | t | 0.5±0.2 | 0.5±0.2 |
| Lead wire protrusion 导线露出 | i | 1 (Max) | 1 (Max) |

## Ordering Procedure (Example: CFR1/4W 5% 100KΩ T/B-2000 PANASERT Type)

## 订购方式 (例如: CFR1/4W 5% 100KΩ T/B-2000 PANASERT Type)

C F R 0 W 4 J 0 1 0 4 A 2 P

**Product Type (产品类型):**
CFR = Carbon Film Fixed Resistors (碳膜固定电阻器)
MF = Metal Film Fixed Resistors (金属膜固定电阻器)
MOR= Metal Oxide Film Fixed Resistors (金属氧化膜固定电阻器)

**Special Feature (特征):**
O=Standard(标准品)
I=Non-Inductive (无感型)

**Wattage (功率):**
W8=1/8W
W4=1/4W
W2=1/2W
S4=1/4W-S
S2=1/2W-S
06=0.6W-S

**Tolerance (公差):**
G=2% J=±5%
K=±10%

**Resistance Value (阻值):**
**2%, 5%, 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**2%, 5%, 10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.
**≤1% (E-96 series):**
the 1st to 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following.
**≤1% 产品 (E-96 系列阻值 ):**
第 1~3 位表示阻值的有效数 , 第 4 位表示有几个 0.

**Packing Type( 包装类型 ):**
A=Tape/Box ( 编带 / 盒装 )
T=Tape/Reel ( 编带 / 卷装 )

**Packing Qty. (包装数量):**
2=2,000pcs(T/B only)( 限 T/B)
5=5,000pcs(T/R only)( 限 T/R)
T/R is 2500PCS per reel &2reels per box (T/R 是每卷 2,500pcs, 每盒 2 卷)

**Additional Information( 注 ):**
P=Panasert type 1
Q=Panasert type 2
1= Avisert type 1
2= Avisert type 2
3= Avisert type 3

## F Forming Type (F 型)




F Type (F 型)

F1 Type (F1 型)

F2 Type (F2 型)

F3 Type (F3 型)



## Dimension (尺寸) (mm)

| Power Rating 功率 | L Max. L 最大 | D Max. D 最大 | d ± 0.05 | P +1 -3 | H ± I | E ± 0.5 |
|---|---|---|---|---|---|---|
| I W (2W-S) | 12 | 5.0 | 0.70 | 8 | 6 | 2.5 |
| 2 W (3W-S) | 16 | 5.5 | 0.70 | 8 | 6 | 2.5 |

## M Forming Type (M 型)

MB Type (MB 型)




MC Type (MC 型)




MK Type (MK 型)




M Type (M 型)







| Power Rating 功率 70°C | L(Max) | D(Max) | d±0.05 | H±2 | P±1.5 |
|---|---|---|---|---|---|
| 1/2W & 1WS | 10 | 4 | 0.70 | 14 | 13 |
| 1W & 2WS | 12 | 5 | 0.70 | 14 | 15 |
| 2W & 3W-S | 16 | 5.5 | 0.70 | 18 | 20 |
| 3W & 5WS | 17.5 | 6.5 | 0.75 | 20 | 25 |
| 5W | 26 | 8.5 | 0.75 | 20 | 31 |

## T Forming Type (T 型)

| Power Rating 功率 70°C | L(Max) | D(Max) | d±0.05 | P(Max) | H +1 -0 |
|---|---|---|---|---|---|
| 1W-S | 10 | 3.5 | 0.70 | 12.5 | 8 |
| 1W(2W-S) | 12 | 5.0 | 0.70 | 15 | 8 |
| 2W(3W-S) | 16 | 55 | 0.70 | 20 | 9 |




## Ordering Procedure (Example: MOR1WS 5% 10Ω B/B M Type with flattened lead wire)

## 订购方式 (例如: MOR1WS 5% 10Ω B/B M 型导线打扁)

**M O R 0 1 S J 0 1 0 0 B M F**

**Product Type (产品类型):**
MOR=Metal Oxide Film Fixed Resistors (金属氧化膜固定电阻器)
CFR=Carbon Film Fixed Resistors (碳膜固定电阻器)

**Special Feature (特征):**
O=Standard(标准品)
I=Non-Inductive (无感型)

**Wattage (功率):**
W2=1/2W 1W=1W
2W=2W 3W=3W
5W=5W 1S=1W-S
2S=2W-S 3S=3W-S
5W=5W-S

**Tolerance (公差):**
G=2% J=±5% K=±10%

**Resistance Value (阻值):**
**5% & 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**5%,10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.
**2% (E-96 series):**
the 1st to 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following.
**2% 产品 (E-96 系列阻值 ):**
第 1~3 位表示阻值的有效数 , 第 4 位表示有几个 0.

**Packing Type( 包装类型 ):**
B=Bulk/Box ( 散装 / 盒装 )

**Additional Information( 注 ):**
F0=F Type (F 型) F1=F1 Type (F1 型)
F2=F2Type (F2 型) F3=F3 Type (F3 型)
T0=T Type (T 型)
MF=M Type with flattened lead wire M 型导线打扁
MC=M Type with bending lead wire M 型导线打弯曲
MK=M Type with kinked lead wire M 型导线打弯折
ML=M Type with normal lead wire M 型导线直线

## Feature (特性)

- Used for insulation protection and fusing protection of wire-wound (fusible) resistor.
  用于涂装产品的绝缘防护及绕线 ( 保险丝 ) 电阻的熔断防护。
- This specification is applicable for KNP、KNPU product only. For the other products (size), please consult factory for the available specification and drawing..
  适用于 KNP、KNPU 的产品，其他产品请洽谈工厂取得可生产的规格图样。

## TZ Forming Type (TZ 轴向套管)

**TZ-1 Wrapped resistor body only**
**TZ-1套管包电阻本体**




**TZ-2 Wrapped resistor body and lead one side only**
**TZ-2套管包电阻本体及一边导线**




**TZ-3 Wrapped resistor body and lead both two side**
**TZ-3套管包电阻本体及两边导线**




## Dimension (尺寸) (mm)

| Type 类型 | Forming type 加工形态 | Dimension ( 尺寸 )(mm) (L1、L2、L3 Adjustable range 可调范围 ) | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | D±1 | L±1 | L1 | L2 | L3 | Ød±0.05 | A (Max.) | C (Max.) |
| 1/4W、1/2W、1WSS | TZ-1 | 2.5 | 6.5 | 38 | 25 | / | 0.54 | / | Max.68mm |
| | TZ-2 | | | 38 | 2Min. | 40Max. | | / | |
| | TZ-3 | | | 2Min. | 2Min. | 40Max. | | 33 | |
| 1/2W、1WS、2WSS | TZ-1 | 3.5 | 9.5 | 38 | 25 | / | 0.54 | / | Max.71mm |
| | TZ-2 | | | 38 | 2Min. | 40Max. | | / | |
| | TZ-3 | | | 2Min. | 2Min. | 40Max. | | 30 | |
| 1W、2WS、3WSS | TZ-1 | 4.5 | 11.5 | 38 | 25 | / | 0.70 | / | Max.73mm |
| | TZ-2 | | | 38 | 2Min. | 40Max. | | / | |
| | TZ-3 | | | 2Min. | 2Min. | 40Max. | | 28 | |
| 2W、3WS、4WSS | TZ-1 | 5.5 | 15.5 | 38 | 25 | / | 0.70 | / | Max.77mm |
| | TZ-2 | | | 38 | 2Min. | 40Max. | | / | |
| | TZ-3 | | | 2Min. | 2Min. | 40Max. | | 25 | |

## Feature (特性)

- Made by Cu/Ni or Mn/Cu Alloy resistance wire materials
  由铜 / 镍或锰 / 铜合金电阻线制成
- Excellent Solderability 优越的焊接性能
- Suitable for all kinds of Current sense application
  适用于各种类型的电流感应器应用
- Application: Power Supply 电源供应



**CSRA Type- CSRA 型**




**CSRB Type- CSRB 型**




**CSRC Type- CSRC 型**




**CSRD Type- CSRD 型**




**CSRE Type- CSRE 型**




## Specification(性能)

| Type 类型 | ΦD 线径 | Rated Current 额定电流 | Resistance Range 阻值范围 | TCR | Remark 备注 |
|---|---|---|---|---|---|
| CSRA CSRB CSRC CSRD | Φ0.8mm | 4.5A | 5mΩ~50mΩ | ±100PPM/℃ | *P&H could be design by customer's requirement<br>P 值和 H 值可根据客户的要求进行设计<br>*Temperature coefficient of resistor could be design by customer's requirement<br>温度系数可根据客户的要求进行设计 |
| | Φ0.9mm | 5.0A | 5mΩ~40mΩ | | |
| | Φ1.0mm | 5.5A | 3mΩ~30mΩ | | |
| | Φ1.1mm | 6.0A | 3mΩ~20mΩ | | |
| | Φ1.2mm | 7.0A | 3mΩ~20mΩ | | |
| | Φ1.3mm | 7.5A | 3mΩ~20mΩ | | |
| | Φ1.4mm | 8.0A | 3mΩ~20mΩ | | |
| | Φ1.5mm | 9.0A | 3mΩ~20mΩ | | |
| | Φ1.6mm | 9.5A | 3mΩ~15mΩ | | |
| | Φ1.8mm | 11A | 3mΩ~10mΩ | | |
| | Φ2.0mm | 12A | 3mΩ~10mΩ | | |
| | Φ2.3mm | 14A | 3mΩ~7mΩ | | |
| CSRE | Φ1.0mm | 50A | 1mΩ | | |

## Feature (特性)

- Made by Cu/Ni or Mn/Cu Alloy resistance wire materials
  由铜 / 镍或锰 / 铜合金电阻线制成
- Excellent Solderability 优越的焊接性能
- Suitable for all kinds of Current sense application
  适用于各种类型的电流感应器应用
- Application: Power Supply 电源供应

**CSSA Type- CSSA 型**




**CSSB Type- CSSB 型**




**CSSC Type- CSSC 型**




| Type 类型 | ΦD 线径 | Rated Current 额定电流 | Resistance Range 阻值范围 | Remark 备注 |
|---|---|---|---|---|
| CSSA CSSB CSSC | Φ0.8mm | 4.5A | 5mΩ~50mΩ | *P&H could be design by customer's requirement<br>*P 值和 H 值可根据客户的要求进行设计 |
| | Φ1.0mm | 5.5A | 3mΩ~30mΩ | |
| | Φ1.6mm | 9.5A | 3mΩ~15mΩ | |
| | Φ2.0mm | 12A | 3mΩ~10mΩ | |

## Ordering Procedure (Example: CSRC Φ1.5mm 10mΩ±5% B/B)

## 订购方式 (例如: CSRC Φ1.5mm 10mΩ±5% B/B)

C S R C 1 5 J 0 1 0 L B 0 0

**Type ( 产品类型 ):**
CSRA = CSRA type
CSRB = CSRB type
CSRC = CSRC type
CSRD = CSRD type
CSRE = CSRE type
CSSA = CSSA type
CSSB = CSSB type
CSSC = CSSC type

**Wire Ø ( 线径 Ø):**
08=Ø0.8 10=Ø1.0
12=Ø1.2 15=Ø1.5
16=Ø1.6 20=Ø2.0
23=Ø2.3

**Tolerance ( 公差 ):**
J=±5% K=±10%

**Resistance Value (阻值):**
**2%, 5% (E-24 series):** the 1st digit is "0"; the 2nd & 3rd digits are for the significant figures of the resistance and the 4th digit denotes number of zeros following.
**2%, 5%产品 (E-24系列电阻):** 第1位是0，第2,3位表示阻值的有效数，第4位表示有几个0.
**≤1%(E-96 Series)**
the 1st to 3rd digits are for the significant figures of the resistance and the 4th digit denotes number of zeros following:
**≤1% 产品 (E-96系列阻值)**
第1~3位表示阻值的有效数，第4位表示有几个0.

**Packing Type (包装类型):**
**B=Bulk/Box ( 散装 / 盒装 )**

**Packing Qty. ( 包装数量 )**
0=Bulk/Box
0= 散装 / 盒装

**Additional Information ( 注 ):**
0=NIL ( 标准品 )

**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明。

## Tape in Box Packing (Ammo Pack) (编带盒装)







*L1-L2=1.0 Max. 最大
ZW: 0
**S=0.5 Max. 最大
PT-26: 0.8 Max. 最大

| Part No 料号 | Type 类型 | Dimension of T/B( 尺寸) (mm) | | | | | Qty./Box 数量 / 盒 |
|---|---|---|---|---|---|---|---|
| | | O | P | A±5 | B±5 | C±5 | |
| **Carbon Film Fixed Resistors( 碳膜固定电阻器)** | | | | | | | |
| **CFR0W8** | CFR-12 | 52±1 | 5±0.3 | 75 | 70 | 255 | 5,000 |
| **CFR0S4** | CFR-25-S | 52±1 | 5±0.3 | 75 | 70 | 255 | 5,000 |
| **CFR0W4** | CFR-25 | 52±1 | 5±0.3 | 75 | 98 | 255 | 5,000 |
| **CFR0W2** | CFR-50 | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **CFR01S** | CFR-100-S | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **CFR01W** | CFR-100 | 64±5 | 10±0.5 | 94 | 88 | 255 | 1,000 |
| **CFR02S** | CFR-200-S | 64±5 | 10±0.5 | 94 | 88 | 255 | 1,000 |
| **CFR02W** | CFR-200 | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **CFR03S** | CFR-300-S | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **CPR0W2** | CPR-50 | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **CPR01W** | CPR-100 | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **CPR02W** | CPR-200 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **Precision Metal Film Lilm Fixed Resistors ( 金属膜固定电阻器)** | | | | | | | |
| **MF0W8** | MF-12 | 52±1 | 5±0.3 | 75 | 70 | 255 | 5,000 |
| **MF0S4** | MF-25-S | 52±1 | 5±0.3 | 75 | 70 | 255 | 5,000 |
| **MF004** | MF-40-SS | 52±1 | 5±0.3 | 75 | 70 | 255 | 5,000 |
| **MF0W4** | MF-25 | 52±1 | 5±0.3 | 75 | 98 | 255 | 5,000 |
| **MF0S2** | MF-50-S | 52±1 | 5±0.3 | 75 | 98 | 255 | 5,000 |
| **MF006** | MF-60-S | 52±1 | 5±0.3 | 75 | 98 | 255 | 5,000 |
| **MF0W2** | MF-50 | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **MF01S** | MF-100-S | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **MF01W** | MF-100 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MF02S** | MF-200-S | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MF02W** | MF-200 | 64±5 | 10±0.5 | 94 | 88 | 255 | 1,000 |
| **MF03S** | MF-300-S | 64±5 | 10±0.5 | 94 | 88 | 255 | 1,000 |
| **MF03W** | MF-300 | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **Metal Film Power Resistors (高功率金属膜电阻器)** | | | | | | | |
| **PMR01S** | PMR-100-S | 52±1 | 5±0.3 | 75 | 98 | 255 | 5,000 |
| **PMR02S** | PMR-200-S | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **PMR03S** | PMR-300-S | 64±5 | 10±0.5 | 90 | 88 | 255 | 1,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
**注:** 以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Tape in Box Packing (Ammo Pack) (编带盒装)







*L1-L2=1.0 Max. 最大
ZW: 0
**S=0.5 Max. 最大
PT-26: 0.8 Max. 最大

| Part No 料号 | Type 类型 | Dimension of T/B( 尺寸) (mm) | | | | | Qty./Box 数量 / 盒 |
|---|---|---|---|---|---|---|---|
| | | O | P | A±5 | B±5 | C±5 | |
| **Metal Oxide Film Fixed Resistors ( 金属氧化膜固定电阻器)** | | | | | | | |
| **MOR0W4** | MOR-25 | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **MOR0S2** | MOR-50-S | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **MOR0W2** | MOR-50 | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **MOR01S** | MOR-100-S | 52±1 | 5±0.3 | 75 | 70 | 255 | 1,000 |
| **MOR01W** | MOR-100 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MOR02S** | MOR-200-S | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MOR02W** | MOR-200 | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |
| **MOR03S** | MOR-300-S | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |
| **MOR03W** | MOR-300 | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **MOR05S** | MOR-500-S | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **MOR05W** | MOR-500 | 90±5 | 10±0.5 | 115 | 124 | 500 | 500 |
| **Metal Glaze Film Fixed Resistors (精密玻璃釉膜固定电阻器)** | | | | | | | |
| **MGR0W4** | MGR-25 | 52±1 | 5±0.3 | 75 | 116 | 255 | 4,000 |
| **MGR0W2** | MGR-50 | 52±1 | 5±0.3 | 75 | 70 | 255 | 1,000 |
| **MGR01W** | MGR-100 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MGR02W** | MGR-200 | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |
| **MGR03W** | MGR-300 | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **MGR0S2** | MGR-50-S | 52±1 | 5±0.3 | 75 | 116 | 255 | 4,000 |
| **MGR01S** | MGR-100-S | 52±1 | 5±0.3 | 75 | 70 | 255 | 1,000 |
| **MGR02S** | MGR-200-S | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MGR03U** | MGR-300-SS | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **MGR03S** | MGR-300-S | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |
| **Fusible Resistors( 保险丝电阻器)** | | | | | | | |
| **FRN0W4** | FRN-25 | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **FRN0S2** | FRN-50-S | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **FRN004** | FRN-40 | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **FRN0W2** | FRN-50 | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **FRN075** | FRN-75 | 52±1 | 5±0.3 | 80 | 70 | 255 | 1,000 |
| **FRN01W** | FRN-100 | 52±1 | 5±0.3 | 80 | 70 | 255 | 1,000 |
| **FRN01A** | FRN-150 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **FRN02W** | FRN-200 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **FRN03W** | FRN-300 | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Tape in Box Packing (Ammo Pack) (编带盒装)







*L1-L2=1.0 Max. 最大
ZW: 0
**S=0.5 Max. 最大
PT-26: 0.8 Max. 最大

| Part No 料号 | Type 类型 | Dimension of T/B( 尺寸) (mm) | | | | | Qty./Box 数量 / 盒 |
|---|---|---|---|---|---|---|---|
| | | O | P | A±5 | B±5 | C±5 | |
| **Wire Wound Fixed Resistors KNP (with Non-inductive KNPN & Anti-surge KNPA) 绕线固定器 ( 含无感型 KNPN 与耐脉冲型 KNPA)** | | | | | | | |
| **KNP*W4** | KNP*-25 | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **KNP*S2** | KNP*-50-S | 52±1 | 5±0.3 | 75 | 116 | 255 | 5,000 |
| **KNP*W2** | KNP*-50 | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **KNP*1S** | KNP*-100-S | 52±1 | 5±0.3 | 75 | 45 | 255 | 1,000 |
| **KNP*1W** | KNP*-100 | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **KNP*2S** | KNP*-200-S | 52±1 | 5±0.3 | 86 | 82 | 255 | 1,000 |
| **KNP*2W** | KNP*-200 | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |
| **KNP*3S** | KNP*-300-S | 64±5 | 10±0.5 | 90 | 119 | 255 | 1,000 |
| **KNP*3W** | KNP*-300 | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **KNP*5S** | KNP*-500-S | 64±5 | 10±0.5 | 90 | 88 | 255 | 500 |
| **KNP*5W** | KNP*-500 | 90±5 | 10±0.5 | 115 | 124 | 500 | 500 |
| **KNP*7S** | KNP*-700-S | 90±5 | 10±0.5 | 115 | 124 | 500 | 500 |
| **Jumper Wires & Zero Ohm Resistors( 跳线和零欧姆固定电阻器)** | | | | | | | |
| **ZWA0** | ZW-A | 52±1 | 5±0.3 | 75 | 98 | 255 | 10,000 |
| **ZWB0** | ZW-B | 52±1 | 5±0.3 | 75 | 116 | 255 | 10,000 |
| **ZWB-1** | ZW-B1 | 52±1 | 5±0.3 | 75 | 116 | 255 | 10,000 |
| **ZWC0** | ZW-C | 52±1 | 5±0.3 | 75 | 116 | 255 | 8,000 |
| **ZWD0** | ZW-D | 52±1 | 5±0.3 | 75 | 116 | 255 | 8,000 |
| **ZWE0** | ZW-E | 52±1 | 5±0.3 | 75 | 116 | 255 | 7,000 |
| **ZOT0W8**<br>**ZOC0W8** | ZOT-12<br>ZOC-12 | 52±1 | 5±0.3 | 75 | 70 | 255 | 5,000 |
| **ZOT0W4**<br>**ZOC0W4** | ZOT-25<br>ZOC-25 | 52±1 | 5±0.3 | 75 | 98 | 255 | 5,000 |
| **PT-26Type (PT-26 类型)** | | | | | | | |
| **CFR0W8**<br>**MF0W8** | CFR-12<br>MF-12 | 26 $^{+1.5}_{-1.0}$ | 5±0.5 | 50 | 66 | 255 | 5,000 |
| **CFR0S4**<br>**MF0S4** | CFR-25-S<br>MF-25-S | 26 $^{+1.5}_{-1.0}$ | 5±0.5 | 50 | 66 | 255 | 5,000 |
| **MF004** | MF-40-SS | 26 $^{+1.5}_{-1.0}$ | 5±0.5 | 50 | 66 | 255 | 5,000 |
| **CFR0W4**<br>**MF0W4**<br>**FRN0W4** | CFR-25<br>MF-25<br>FRN-25 | 26 $^{+1.5}_{-0}$ | 5±0.5 | 50 | 100 | 255 | 5,000 |
| **MF0S2**<br>**MOR0S2** | MF-50-S<br>MOR-50-S | 26 $^{+1.5}_{-0}$ | 5±0.5 | 50 | 100 | 255 | 5,000 |
| **MF006** | MF-60-S | 26 $^{+1.5}_{-0}$ | 5±0.5 | 50 | 100 | 255 | 5,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Tape in Reel (编带卷装)







| Part No 料号 | Type 类型 | Dimension of T/R( 尺寸) (mm) | | | | | Qty./Box 数量 / 盒 |
|---|---|---|---|---|---|---|---|
| | | O | A | W±5 | H±5 | L±5 | |
| **Carbon Film Fixed Resistors( 碳膜固定电阻器)** | | | | | | | |
| **CFR0W8** | CFR-12 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **CFR0S4** | CFR-25-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **CFR0W4** | CFR-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **CFR0W2** | CFR-50 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **CFR01S** | CFR-100-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **CFR01W** | CFR-100 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **CFR02S** | CFR-200-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **CFR02W** | CFR-200 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **CFR03S** | CFR-300-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **CPR0W2** | CPR-50 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **CPR01W** | CPR-100 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **CPR02W** | CPR-200 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **Precision Metal Film Fixed Resistors ( 金属膜固定电阻器)** | | | | | | | |
| **MF0W8** | MF-12 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MF0S4** | MF-25-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MF004** | MF-40-SS | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MF0W4** | MF-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MF0S2** | MF-50-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MF0W2** | MF-50 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MF006** | MF-60-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MF01S** | MF-100-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MF01W** | MF-100 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MF02S** | MF-200-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MF02W** | MF-200 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MF03S** | MF-300-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MF03W** | MF-300 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **Metal Film Power Resistors (高功率金属膜电阻器)** | | | | | | | |
| **PMR01S** | PMR-100-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **PMR02S** | PMR-200-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **PMR03S** | PMR-300-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

# Standard Packing of Coated Type Resistors

## 涂装型电阻器包装标准



## Tape in Reel (编带卷装)




| Part No 料号 | Type 类型 | Dimension of T/R( 尺寸) (mm) | | | | | Qty./Box 数量 / 盒 |
|---|---|---|---|---|---|---|---|
| | | O | A | W±5 | H±5 | L±5 | |
| **Metal Oxide Film Fixed Resistors ( 金属氧化膜固定电阻器)** | | | | | | | |
| **MOR0W4** | MOR-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MOR0S2** | MOR-50-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MOR0W2** | MOR-50 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MOR01S** | MOR-100-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MOR01W** | MOR-100 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MOR02S** | MOR-200-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MOR02W** | MOR-200 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MOR03S** | MOR-300-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MOR03W** | MOR-300 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MOR05S** | MOR-500-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MOR05W** | MOR-500 | 90±5 | 115±5 | 121 | 310 | 310 | 700 |
| **Metal Glaze Film Fixed Resistors (精密玻璃釉膜固定电阻器)** | | | | | | | |
| **MGR0W4** | MGR-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MGR0W2** | MGR-50 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MGR01W** | MGR-100 | 52±1 | 73±2 | 85 | 295 | 293 | 1,000 |
| **MGR02W** | MGR-200 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MGR03W** | MGR-300 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **MGR0S2** | MGR-50-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **MGR01S** | MGR-100-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **MGR02S** | MGR-200-S | 52±1 | 73±2 | 85 | 295 | 293 | 1,000 |
| **MGR03U** | MGR-300-SS | 52±1 | 73±2 | 85 | 295 | 293 | 1,000 |
| **MGR03S** | MGR-300-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **Fusible Resistors( 保险丝电阻器)** | | | | | | | |
| **FRN0W4** | FRN-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **FRN0S2** | FRN-50-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **FRN004** | FRN-40 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **FRN0W2** | FRN-50 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **FRN075** | FRN-75 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **FRN01W** | FRN-100 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **FRN01A** | FRN-150 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **FRN02W** | FRN-200 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **FRN03W** | FRN-300 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Tape in Reel (编带卷装)




| Part No 料号 | Type 类型 | Dimension of T/R( 尺寸) (mm) | | | | | Qty./Box 数量 / 盒 |
|---|---|---|---|---|---|---|---|
| | | O | A | W±5 | H±5 | L±5 | |
| **Wire Wound Fixed Resistors KNP (with Non-inductive KNPN & Anti-surge KNPA) 绕线固定器 ( 含无感型 KNPN 与耐脉冲型 KNPA)** | | | | | | | |
| **KNP*W4** | KNP*-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **KNP*S2** | KNP*-50-S | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **KNP*W2** | KNP*-50 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **KNP*1S** | KNP*-100-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **KNP*1W** | KNP*-100 | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **KNP*2S** | KNP*-200-S | 52±1 | 73±2 | 85 | 295 | 293 | 2,500 |
| **KNP*2W** | KNP*-200 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **KNP*3S** | KNP*-300-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **KNP*3W** | KNP*-300 | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **KNP*5S** | KNP*-500-S | 64±5 | 80±5 | 95 | 295 | 293 | 1,000 |
| **KNP*5W** | KNP*-500 | 90±5 | 115±5 | 121 | 310 | 310 | 700 |
| **KNP*7S** | KNP*-700-S | 90±5 | 115±5 | 121 | 310 | 310 | 700 |
| **Jumper Wires & Zero Ohm Resistors( 跳线和零欧姆固定电阻器)** | | | | | | | |
| **ZWA0** | ZW-A | 52±1 | 73±2 | 85 | 295 | 293 | 10,000 |
| **ZWB0** | ZW-B | 52±1 | 73±2 | 85 | 295 | 293 | 10,000 |
| **ZWB-1** | ZW-B1 | 52±1 | 73±2 | 85 | 295 | 293 | 10,000 |
| **ZWC0** | ZW-C | 52±1 | 73±2 | 85 | 295 | 293 | 10,000 |
| **ZWD0** | ZW-D | 52±1 | 73±2 | 85 | 295 | 293 | 10,000 |
| **ZWE0** | ZW-E | 52±1 | 73±2 | 85 | 295 | 293 | 10,000 |
| **ZOT0W8 ZOC0W8** | Z0-12 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |
| **ZOT0W4 ZOC0W4** | ZO-25 | 52±1 | 73±2 | 85 | 295 | 293 | 5,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

# Standard Packing of Coated Type Resistors

## 涂装型电阻器包装标准



### Bulk in Box Packing (散装盒装)







| Part No 料号 | Type 类型 | Dimension of B/B( 尺寸) (mm) | | | Qty.of Bag/Box 袋数量 / 盒数量 |
|---|---|---|---|---|---|
| | | A±5 | B±5 | C±5 | |
| **Carbon Film Fixed Resistors( 碳膜固定电阻器)** | | | | | |
| **CFR0W8** | CFR-12 | 140 | 80 | 240 | 1,000/20,000 |
| **CFR0S4** | CFR-25-S | 140 | 80 | 240 | 1,000/20,000 |
| **CFR0W4** | CFR-25 | 140 | 80 | 240 | 500/10,000 |
| **CFR0W2** | CFR-50 | 140 | 80 | 240 | 250/5,000 |
| **CFR01S** | CFR-100-S | 140 | 80 | 240 | 100/2,500 |
| **CFR01W** | CFR-100 | 140 | 80 | 240 | 100/1,500 |
| **CFR02S** | CFR-200-S | 140 | 80 | 240 | 100/1,500 |
| **CFR02W** | CFR-200 | 140 | 80 | 240 | 100/1,000 |
| **CFR03S** | CFR-300-S | 140 | 80 | 240 | 100/1,000 |
| **CPR0W2** | CPR-50 | 140 | 80 | 240 | 500/10,000 |
| **CPR01W** | CPR-100 | 140 | 80 | 240 | 250/5,000 |
| **CPR02W** | CPR-200 | 140 | 80 | 240 | 100/2,500 |
| **Precision Metal Film Fixed Resistors ( 金属膜固定电阻器)** | | | | | |
| **MF0W8** | MF-12 | 140 | 80 | 240 | 1,000/20,000 |
| **MF0S4** | MF-25-S | 140 | 80 | 240 | 1,000/20,000 |
| **MF004** | MF-40-SS | 140 | 80 | 240 | 1,000/20,000 |
| **MF0W4** | MF-25 | 140 | 80 | 240 | 500/10,000 |
| **MF0S2** | MF-50-S | 140 | 80 | 240 | 500/10,000 |
| **MF0W2** | MF-50 | 140 | 80 | 240 | 250/5,000 |
| **MF006** | MF-60-S | 140 | 80 | 240 | 500/10,000 |
| **MF01S** | MF-100-S | 140 | 80 | 240 | 250/5,000 |
| **MF01W** | MF-100 | 140 | 80 | 240 | 100/2,500 |
| **MF02S** | MF-200-S | 140 | 80 | 240 | 100/2,500 |
| **MF02W** | MF-200 | 140 | 80 | 240 | 100/1,500 |
| **MF03S** | MF-300-S | 140 | 80 | 240 | 100/1,500 |
| **MF03W** | MF-300 | 140 | 80 | 240 | 100/1,500 |
| **Metal Film Power Resistors (高功率金属膜电阻器)** | | | | | |
| **PMR01S** | PMR-100-S | 140 | 80 | 240 | 500/10,000 |
| **PMR02S** | PMR-200-S | 140 | 80 | 240 | 100/2,500 |
| **PMR03S** | PMR-300-S | 140 | 80 | 240 | 100/1,500 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Bulk in Box Packing (散装盒装)







| Part No 料号 | Type 类型 | Dimension of B/B( 尺寸) (mm) | | | Qty.of Bag/Box 袋数量 / 盒数量 |
|---|---|---|---|---|---|
| | | A±5 | B±5 | C±5 | |
| **Metal Oxide Film Fixed Resistors ( 金属氧化膜固定电阻器)** | | | | | |
| **MOR0W4** | MOR-25 | 140 | 80 | 240 | 500/10,000 |
| **MOR0S2** | MOR-50-S | 140 | 80 | 240 | 500/10,000 |
| **MOR0W2** | MOR-50 | 140 | 80 | 240 | 250/5,000 |
| **MOR01S** | MOR-100-S | 140 | 80 | 240 | 250/5,000 |
| **MOR01W** | MOR-100 | 140 | 80 | 240 | 100/2,500 |
| **MOR02S** | MOR-200-S | 140 | 80 | 240 | 100/2,500 |
| **MOR02W** | MOR-200 | 140 | 80 | 240 | 100/1,500 |
| **MOR03S** | MOR-300-S | 140 | 80 | 240 | 100/1,500 |
| **MOR03W** | MOR-300 | 140 | 80 | 240 | 100/1,000 |
| **MOR05S** | MOR-500-S | 140 | 80 | 240 | 100/1,000 |
| **MOR05W** | MOR-500 | 140 | 80 | 240 | 25/400 |
| **MOR07W** | MOR-700 | 140 | 80 | 240 | 25/300 |
| **MOR08W** | MOR-800 | 140 | 80 | 240 | 25/200 |
| **MOR09W** | MOR-900 | 140 | 80 | 240 | 25/200 |
| **Metal Glaze Film Fixed Resistors (精密玻璃釉膜固定电阻器)** | | | | | |
| **MGR0W4** | MGR-25 | 140 | 80 | 240 | 500/10,000 |
| **MGR0W2** | MGR-50 | 140 | 80 | 240 | 250/5,000 |
| **MGR01W** | MGR-100 | 140 | 80 | 240 | 100/2,500 |
| **MGR02W** | MGR-200 | 140 | 80 | 240 | 100/1,500 |
| **MGR03W** | MGR-300 | 140 | 80 | 240 | 100/1,000 |
| **MGR0S2** | MGR-50-S | 140 | 80 | 240 | 500/10,000 |
| **MGR01S** | MGR-100-S | 140 | 80 | 240 | 250/5,000 |
| **MGR02S** | MGR-200-S | 140 | 80 | 240 | 100/2,500 |
| **MGR03U** | MGR-300-SS | 140 | 80 | 240 | 100/2,500 |
| **MGR03S** | MGR-300-S | 140 | 80 | 240 | 100/1,500 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

# Standard Packing of Coated Type Resistors
# 涂装型电阻器包装标准

## Bulk in Box Packing (散装盒装)







| Part No 料号 | Type 类型 | Dimension of B/B( 尺寸) (mm) | | | Qty.of Bag/Box 袋数量 / 盒数量 |
|---|---|---|---|---|---|
| | | A±5 | B±5 | C±5 | |
| **Fusible Resistors( 保险丝电阻器)** | | | | | |
| **FRN0W4** | FRN-25 | 140 | 80 | 240 | 500/10,000 |
| **FRN0S2** | FRN-50-S | 140 | 80 | 240 | 500/10,000 |
| **FRN004** | FRN-40 | 140 | 80 | 240 | 500/10,000 |
| **FRN0W2** | FRN-50 | 140 | 80 | 240 | 250/5,000 |
| **FRN075** | FRN-75 | 140 | 80 | 240 | 250/5,000 |
| **FRN01W** | FRN-100 | 140 | 80 | 240 | 250/5,000 |
| **FRN01A** | FRN-150 | 140 | 80 | 240 | 100/2,500 |
| **FRN02W** | FRN-200 | 140 | 80 | 240 | 100/2,500 |
| **FRN03W** | FRN-300 | 140 | 80 | 240 | 100/1,500 |
| **Wire Wound Fixed Resistors KNP (with Non-inductive KNPN & Anti-surge KNPA) 绕线固定器 ( 含无感型 KNPN 与耐脉冲型 KNPA)** | | | | | |
| **KNP*W4** | KNP*-25 | 140 | 80 | 240 | 500/10,000 |
| **KNP*S2** | KNP*-50-S | 140 | 80 | 240 | 500/10,000 |
| **KNP*W2** | KNP*-50 | 140 | 80 | 240 | 250/5,000 |
| **KNP*1S** | KNP*-100-S | 140 | 80 | 240 | 250/5,000 |
| **KNP*1W** | KNP*-100 | 140 | 80 | 240 | 100/2,500 |
| **KNP02S** | KNP*-200-S | 140 | 80 | 240 | 100/2,500 |
| **KNP*2W** | KNP*-200 | 140 | 80 | 240 | 100/1,500 |
| **KNP*3S** | KNP*-300-S | 140 | 80 | 240 | 100/1,500 |
| **KNP*3W** | KNP*-300 | 140 | 80 | 240 | 100/1,000 |
| **KNP*5S** | KNP*-500-S | 140 | 80 | 240 | 100/1,000 |
| **KNP*5W** | KNP*-500 | 140 | 80 | 240 | 25/400 |
| **KNP*7S** | KNP*-700-S | 140 | 80 | 240 | 25/400 |
| **KNP*7W** | KNP*-700 | 140 | 80 | 240 | 25/300 |
| **KNP*8S** | KNP*-800-S | 140 | 80 | 240 | 25/300 |
| **KNP*8W** | KNP*-800 | 140 | 80 | 240 | 25/200 |
| **KNP*9S** | KNP*-900-S | 140 | 80 | 240 | 25/200 |
| **KNP*9W** | KNP*-900 | 140 | 80 | 240 | 25/200 |
| **KNP*AS** | KNP*-1000-S | 140 | 80 | 240 | 25/200 |
| **Zero Ohm Resistors( 零欧姆固定电阻器 )** | | | | | |
| **ZOT0W8 ZOCOW8** | ZO-12 | 140 | 80 | 240 | 1,000/20,000 |
| **ZOT0W4 ZOCOW4** | ZO-25 | 140 | 80 | 240 | 500/10,000 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Feature (特性)

- Miniature, high density packaging
  小型高密度封装
- High reliability $R_uO_2$ paste
  使用高稳定性 $R_uO_2$ 电阻材料

## Application (应用)

- Control circuit V.C.R. (V.C.R.控制电路)
- Air-conditioner (空调)
- Computer, color TV (计算机，彩电)
- Facsimile (传真机)

## Dimension (尺寸) (mm)




"●" indicate the 1st pin (表示第一脚位置)

## Derating Curve (降功率曲线)




| Type 类型 | Dimension of L(Max.) L 的最大尺寸 | | | | | | | | | | | H max | C +0.5 -0.3 | T max | t±0.05 | P±0.2 | D±0.1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 4pin | 5pin | 6pin | 7pin | 8pin | 9pin | 10 pin | 11 pin | 12 pin | 13 pin | 14 pin | | | | | | |
| RNL | 10.2 | 12.7 | 15.3 | 17.8 | 20.4 | 22.9 | 25.4 | 28.0 | 30.5 | 33.1 | 35.6 | 5.08 | 3.3 | 2.5 | 0.25 | 2.54 | 0.5 |
| RPL | 10.2 | 12.7 | 15.3 | 17.8 | 20.4 | 22.9 | 25.4 | 28.0 | 30.5 | 33.1 | 35.6 | 5.08 | 3.3 | 2.5 | 0.25 | 2.54 | 0.5 |
| RNM | 10.2 | 12.7 | 15.3 | 17.8 | 20.4 | 22.9 | 25.4 | 28.0 | 30.5 | 33.1 | 35.6 | 6.35 | 3.3 | 2.5 | 0.25 | 2.54 | 0.5 |
| RPH | 10.2 | 12.7 | 15.3 | 17.8 | 20.4 | 22.9 | 25.4 | 28.0 | 30.5 | 33.1 | 35.6 | 8.89 | 3.3 | 2.5 | 0.25 | 2.54 | 0.5 |

## Circuit Structure (电路结构)

| A | B | C | D | E |
|---|---|---|---|---|
| RNL/RPL/RNM/RPH | RNL/RPL/RNM/RPH | RNL | RNL | RNL |
| R1=R2=.....Rn | R1=R2=.....Rn | R1=R2=$R_n$ | R1=R2=.....Rn<br>$R_1 \neq R_2 \neq$.....Rn | R1=R2 or R1≠R2 |

| G | H | L | P | R |
|---|---|---|---|---|
| RNL | RNL | RNL | RNL | RNL/RPL/RNM/RPH |
| R1=R2=.....Rn | | | | R1=R2 or R1≠R2 |

* Custom Design Circuit could be available on a case to case basis. (可按客户特殊要求定制)

## Package Power Ratings (封装功率等级)

| Type 类型 | 4PIN | 5PIN | 6PIN | 7PIN | 8PIN | 9PIN | 10PIN | 11PIN | 12PIN | 13PIN | 14PIN |
|---|---|---|---|---|---|---|---|---|---|---|---|
| RPL | 0.5W | 0.63W | 0.75W | 0.88W | 1.0W | 1.13W | 1.25W | 1.38W | 1.5W | 1.63W | 1.75W |
| RNM | 0.6W | 0.75W | 0.9W | 1.05W | 1.20W | 1.35W | 1.50W | 1.65W | 1.80W | 1.95W | 2.10W |
| RPH | 0.8W | 1.0W | 1.2W | 1.4W | 1.6W | 1.8W | 2.0W | 2.2W | 2.4W | 2.6W | 2.8W |

| Type 类型 | Power Rating ( 功率 )70℃ | Max .Working Voltage 最大工作电压 | Max. Overload Voltage 最大过负荷电压 | Dielectric Withstanding Voltage 绝缘耐压 | Resistance Range 阻值范围 | Tolerance 公差 | Operating Temperature 工作温度范围 |
|---|---|---|---|---|---|---|---|
| RNL | B type(B 型 ): 0.2W<br>Others( 其它类型 ): 0.125W | 100V | 150V | 200V | R Type(R 型 ):<br>100Ω~10K<br>Others( 其它类型 ):<br>10Ω~1MΩ | ±2%<br>±5% | -55℃~+155℃ |
| RPL | A:0.2W | 100V | 150V | 200V | 10Ω~1MΩ | ±2%<br>±5% | -55℃~+155℃ |
| | B:0.3W | | | | 10Ω~1MΩ | | |
| | R:0.2W | | | | 100Ω~10KΩ | | |
| RNM | A:0.25W | 100V | 150V | 200V | 10Ω~1MΩ | ±2%<br>±5% | -55℃~+155℃ |
| | B:0.4W | | | | 10Ω~1MΩ | | |
| | R:0.25W | | | | 100Ω~10KΩ | | |
| RPH | A:0.3W | 100V | 150V | 200V | 10Ω~1MΩ | ±2%<br>±5% | -55℃~+155℃ |
| | B:0.5W | | | | 10Ω~1MΩ | | |
| | R:0.3W | | | | 100Ω~10KΩ | | |

## Marking (Single Value) [标示(单个阻值)]:







## Marking(Dual Value)[标示(双阻类型)]:




## Dual Value (双阻型阻值系列)(R1/R2)(Ohm)

| | |
|---|---|
| 160 / 240 | 330 / 390 |
| 180 / 390 | 330 / 470 |
| 220 / 270 | 1.5K / 3.5K |
| 220 / 330 | 3.0K / 6.2K |

* Special Value available on a case to case basis. (另可按客户特殊要求订做)

## Performance Specification( 性能 )

| Test Item 试验项目 | | Evaluation Criteria 判定标准 | | | |
|---|---|---|---|---|---|
| | | RNL | RPL | RNM | RPH |
| Temperature | 温度系数 | 50Ω~1MΩ：±200PPM/°C<br><50Ω&>1MΩ：±250PPM/°C | 50Ω~1MΩ：±100PPM/°C<br><50Ω&>1MΩ：±250PPM/°C | | |
| Short-time overload | 短时间过负荷 | ΔR/R≤±(0.5%+0.1Ω) | ΔR/R≤±(0.25%+0.1Ω) | | |
| Insulation resistance | 绝缘电阻 | ≥10,000MΩ | | | |
| Dielectric withstanding voltage | 绝缘耐压 | No Evidence of flashover,arcing or insulation breakdown( 无击穿、飞弧及可见机械损伤 ) | | | |
| Terminal strength | 端子强度 | ΔR/R≤±(0.5%+0.1Ω) | ΔR/R≤±(0.25%+0.1Ω) | | |
| Soldering heat | 耐焊接热 | ΔR/R≤±(0.5%+0.1Ω) | | | |
| Solderability | 可焊性 | Coverage must be over 95%. | | | |
| Thermal shock | 热冲击 | ΔR/R≤±(0.5%+0.1Ω) | ΔR/R≤±(0.25%+0.1Ω) | | |
| Rapid change of temperature | 温度快速变化 | ΔR/R≤±(0.5%+0.1Ω) | | | |
| Load life in humidity | 湿度寿命 | ΔR/R≤±(3%+0.1Ω) | ΔR/R≤±(0.5%+0.1Ω) | | |
| Load life | 负载寿命 | ΔR/R≤±(3%+0.1Ω) | ΔR/R≤±(1%+0.1Ω) | | |

## Ordering Procedure (Example: RNL A type 10 PIN 2% 10KΩ B/B)

## 订购方式 (例如: RNL A 型 10 PIN 2% 10KΩ B/B)




**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明。

## Standard Packing of Resistor Network (网络电阻器的标准包装)




| Type 类型 | Pins Pins 数 | Weight of 1,000pcs 1,000 只 重量 (g) | Qty.per Bag 每袋数量 | Qty.per Box 每盒数量 | Qty.per Carton 每箱数量 |
|---|---|---|---|---|---|
| RNL RPL | 4 | 210 | 200 | 1,000 | 30,000 |
| RNM | | 240 | 100 | | |
| RPH | | 330 | | | |
| RNL RPL | 5 | 250 | 200 | 1,000 | 30,000 |
| RNM | | 300 | 100 | | |
| RPH | | 410 | | | |
| RNL RPL | 6 | 320 | 200 | 1,000 | 30,000 |
| RNM | | 360 | 100 | | |
| RPH | | 490 | | | |
| RNL RPL | 7 | 360 | 200 | 1,000 | 30,000 |
| RNM | | 420 | 100 | | |
| RPH | | 570 | | | |
| RNL RPL | 8 | 430 | 200 | 1,000 | 30,000 |
| RNM | | 480 | 100 | | |
| RPH | | 660 | 50 | 500 | 15,000 |
| RNL RPL | 9 | 450 | 200 | 1,000 | 30,000 |
| RNM | | 540 | 50 | 500 | 15,000 |
| RPH | | 760 | | | |

| Type 类型 | Pins Pins 数 | Weight of 1,000pcs 1,000 只 重量 (g) | Qty.per Bag 每袋数量 | Qty.per Box 每盒数量 | Qty.per Carton 每箱数量 |
|---|---|---|---|---|---|
| RNL RPL | 10 | 530 | 200 | 1,000 | 30,000 |
| RNM | | 610 | 50 | 500 | 15,000 |
| RPH | | 870 | | | |
| RNL RPL | 11 | 600 | 100 | 500 | 15,000 |
| RNM | | 670 | 50 | | |
| RPH | | 950 | | | |
| RNL RPL | 12 | 650 | 100 | 500 | 15,000 |
| RNM | | 730 | 50 | | |
| RPH | | 1030 | | | |
| RNL RPL | 13 | 710 | 100 | 500 | 15,000 |
| RNM | | 790 | 50 | | |
| RPH | | 1130 | | | |
| RNL RPL | 14 | 770 | 100 | 500 | 15,000 |
| RNM | | 850 | 50 | | |
| RPH | | 1210 | | | |

## Ammo Pack of Resistor Network (网络电阻器编带包装)




* … n=Pin Count




| Dimension 尺寸 (mm) | | Dimension 尺寸 (mm) | |
|---|---|---|---|
| H1 | Max 5.08 | t0 | 2.0Max |
| L | Max 2.54*n | t1 | 18.99±0.5 |
| a | 2.54±0.25 | t2 | 9.0±0.5 |
| d1 | 0.5±0.1 | t3 | 24.46Max |
| P | 25.4±1.0 | t4 | 1.5max |
| W | 18±0.5 | I | φ4.0±0.3 |
| w | 5.0min | h2 | 3.0±0.5 |
| P1 | 6.35±0.7 | a1 | 2.54±0.25 |
| P2 | 12.7±0.3 | a2 | 5.08±0.3 |
| B | Max 2.49 | d3 | 2.0Max |
| T | 16±0.5 | / | / |

## Packing quantity (包装数量)




The inner box sizes 内盒尺寸 :
4~9pin: 320(L) × 207(W) × 40(H)mm
10pin:315(L) × 295(W) × 40(H)mm

| Pins Pins 数 | Qty.per Box 每盒数量 | Qty.per Carton 每箱数量 |
|---|---|---|
| 4~10 | 1,000 | 12,000 |

## Special Network-SIP Series
## 特殊网络电阻器 SIP 系列




"●" indicate the 1st pin (表示第一脚位置)

| Type( 类型) | SN0001 | SN0002 | SN0003 | SN0004 |
|---|---|---|---|---|
| Circuit Structure ( 电路结构 ) | R1=500Ω ±5% R2=40K ±5% (TO: R3: ±1%) R3=10K ±5% R4=R5=75K ±5% R6=R7=100K ±5% (R6 TO R7: ±1%) |  R1=33KΩ ±5% R2=22KΩ ±5% |  R3=9K1 R1=120K R14=24K R4=36K R9=14K R15=1K5 R5=R6=7K5 R10=R11=R12=20K R13=2K R7=52K5 R13=11K | R1=52Ω3 R2=70Ω7 R3=121Ω R4=249Ω R5=1K33 R6=619K R7=174Ω R8=75Ω |
| Dimension of L(max) 尺寸 L( 最大 ) | 10PINS:25.4mm | 10PINS:25.4mm | 10PINS:43.2mm | 9PINS:22.9mm |
| H(max) H( 最大 ) | 5.08mm | 5.08mm | 6.35mm | 5.08mm |
| Power Rating at 70°C 功率 70°C | 0.2W | 0.2W | 0.125W | 0.125W |
| Max Working Voltage 最大工作电压 | 100V | 100V | 100V | 100V |
| Max Overload Voltage 最大过负荷电压 | 150V | 150V | 200V | 150V |
| Operating Temperature 工作温度 | -55~+155 °C | -55~+155°C | -55~+155 °C | -55~+155 °C |

* Custom Design Circuit could be available on a case to case basis (可提供客户特殊要求之线路产品)

## Resistor/Capacitor Network - SIP Series
## 网络阻容器 - SIP 系列




"●" indicate the 1st pin (表示第一脚位置)

| A | B |
|---|---|
|  |  |

### Electrical Characteristics- Capacitor (电容特性)

| Capacitance Dielectric 电容介质 | Capacitance Range 电容范围 | Capacitance Tolerance 电容公差 | Capacitance Voltage 电容电压 |
|---|---|---|---|
| NPO | 39pF~270pF | ±10% | 50V |
| X7R | >270pF~0.1μF | ±20% | |

### Dimension (尺寸) (mm):

| Type 类型 | H (mm) | F (mm) |
|---|---|---|
| RCH | 7.62 Max. | 3.81 Max. |
| RCN | 8.89 Max. | 3.81 Max. |

### Dimension (尺寸) (mm):

| L | |
|---|---|
| 4 PIN: 10.2mm | 10 PIN: 25.4mm |
| 5 PIN: 12.7mm | 11 PIN: 28.0mm |
| 6 PIN: 15.3mm | 12 PIN: 30.5mm |
| 7 PIN: 17.8mm | 13 PIN: 33.1mm |
| 8 PIN: 20.4mm | 14 PIN: 35.6mm |
| 9 PIN: 22.9mm | |

* Custom Design Circuit could be available on a case to case basis （可提供客户特殊要求之线路产品）

## Capacitor Network-SIP Series
## 网络电容器 SIP 系列




"●" indicate the 1st pin (表示第一脚位置)




Circuit Structure (电路结构)

### Electrical Characteristics- Capacitor (电容特性)

| Capacitance Dielectric 电容介质 | Capacitance Range 电容范围 | Capacitance Tolerance 电容公差 | Capacitance Voltage 电容电压 |
|---|---|---|---|
| NPO | 39pF~270pF | ±10% | 50V |
| X7R | >270pF~0.1μF | ±20% | |

### Dimension (尺寸) (mm):

| Type 类型 | H (mm) | F (mm) |
|---|---|---|
| CNM | 6.35 Max. | 3.81 Max. |
| CNH | 7.62 Max. | 3.81 Max. |

### Dimension (尺寸) (mm):

| L | |
|---|---|
| 4 PIN: 10.2mm | 10 PIN: 25.4mm |
| 5 PIN: 12.7mm | 11 PIN: 28.0mm |
| 6 PIN: 15.3mm | 12 PIN: 30.5mm |
| 7 PIN: 17.8mm | 13 PIN: 33.1mm |
| 8 PIN: 20.4mm | 14 PIN: 35.6mm |
| 9 PIN: 22.9mm | |

* Custom Design Circuit could be available on a case to case basis （可提供客户特殊要求之线路产品）

# High Voltage Flat Resistors
## 高压扁平式电阻器



## Feature (特性)

- Small size, Light weight 小尺寸，重量轻
- High stability, Reliability 高稳定性，高可靠性
- Max working voltage 10KV 最大工作电压可达10KV
- Used in Microwave Ovens, Induction Cooker, High Voltage Power Supply, Laser light control circuit and other applications
  用于微波炉、电磁炉、高压电源、激光控制电路及其它产品

## Dimension (尺寸) (mm)




## Derating Curve & Specification (降功率曲线和性能)




| Part No. 料号 | Type 类型 | Power rating 功率 70°C | Dimension ( 尺寸 )(mm) | | | | | | Max Working Voltage 最大工作电压 | Dielectronic Withstanding Voltage 绝缘耐压 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | P±0.5 | L(max) L 最大 | d1±0.1 | d2 +0.5 -0.2 | H(max) H 最大 | T(max) T 最大 | | | |
| **HFR0W2** | HFR-50 | 0.5W | 17.8 | 20.4 | 0.5 | 3.5 | 5.08 | 2.5 | 5KV | 500V | 1M~1GΩ |
| **HFR007** | HFR-75 | 0.75W | 22.9 | 25.4 | 0.5 | 3.5 | 5.08 | 2.5 | 10KV | 500V | 1M~1GΩ |
| **HFR01W** | HFR-100 | 1W | 27.9 | 30.5 | 0.5 | 3.5 | 5.08 | 2.5 | 10KV | 500V | 1M~1GΩ |

## Performance Specification (性能)

| | | | | | |
|---|---|---|---|---|---|
| **Temperature coefficient** | 温度系数 | ±200PPM/°C | **Humidity (Steady State)** | 恒定湿热 | ΔR/R±(1.0%+0.1 Ω) |
| **Terminal strength** | 端子强度 | ΔR/R≤±(1%+0.1Ω) | **Load life in humidity** | 湿度寿命 | ΔR/R±(3.0%+0.1Ω) |
| **Soldering heat** | 耐焊接热 | ΔR/R±(1%+0.1 Ω) | **Load life** | 负载寿命 | ΔR/R±(3.0%+0.1Ω) |
| **Solderability** | 可焊性 | Min.95% coverage ( 最少 95% 覆盖率 ) | **Insulation resistance** | 绝缘电阻 | ≥10,000MΩ |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R±(1%+0.1 Ω) | **Thermal shock** | 热冲击 | ΔR/R±(1%+0.1Ω) |

## Ordering Procedure (Example: HFR 0.75W 10% 10M B/B)
## 订购方式 (例如: HFR 0.75W 10% 10M B/B)

**H F R 0 0 7 K 0 1 0 6 B 0 E**

**Product Type ( 产品类型 ):**
High Voltage Flat Resistors
高压扁平式电阻器

**Wattage ( 功率 ):**
W2 = 1/2W
07= 0.75W
1W = 1W

**Tolerance ( 公差 ):**
J =±5%
K=±10%
M=±20%

**Resistance Value ( 阻值 ):**
**5%,10%,20%(E-24 series)**
The 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the number of zeros following
**5%,10%,20% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数，第 4 位表示有几个 0.

**Packing Type:**
B = Bulk / Box
包装类型:
B = 散装 / 盒装

**Special Feature ( 特征 ):**
0 =For Bulk/Box packing ( 散装 / 盒装 )
E =lead-free ( 无铅标准品 )

**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

## Feature (特性)

- Small size and light weight (体积小，重量轻)
- Lighting application (照明应用)
- Too low/high ohmic value can be supplied case to case basis (可特别提供过低/过高的欧姆值)
- Patent No:1581275 (专利号:1581275)

## Dimension (尺寸) (mm)







## Derating Curve (降功率曲线)




| Type | Power 功率 at 70°C | D ±1 | L ±1 | H1 ±1.5 | H2 ±1 | h ±1 | d ±0.05 | t ±1 | Tolerance 精度 % | Resistance Range 阻值範圍 | Max Working Voltage 最大工作电压 | Max Overload Voltage 最大过负荷电压 | Dielectric Withstanding Voltage 绝缘耐压 | Standard Color 标准色 | Operating Temperature 工作温度 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| RC06 | 0.25W (1/4W) | 5.5 | 6 | 13.5 | 4.5 | 3.5 | 0.68 | 3.5 | Jumper | <50mΩ | 200V | 400V | 500V | Brown | -55 ~ +155°C |
| | | | | | | | | | 1% | 10Ω ~ 1MΩ | | | | | |
| RC06-1 | 0.25W (1/4W) | 5.5 | 7.5 | 13.5 | 4.5 | 3.5 | 0.68 | 4.5 | 5% | 1Ω ~ 10MΩ | 200V | 400V | 500V | Blue | |

## Performance Specification (性能)

| | |
|---|---|
| **Temperature Coefficient 温度系数** | 1Ω ~ 10Ω : ±400PPM/°C<br>11Ω ~ 100Ω: ±200PPM /°C<br>>100Ω: ±100PPM /°C |
| **Short Time Overload 短时间过负荷** | ±1% ; ±(1.0%+0.1Ω)<br>±5%; ±(2.0%+0.1Ω) |
| **Solderability 可焊性** | Min. 95%coverage |
| **Resistance to Soldering Heat 耐焊接热** | ±(1.0%+0.05Ω) |
| **Temperature Cycling 温度循环** | ±1% ; ±(0.5.0%+0.05Ω)<br>±5%; ±(1.0%+0.05Ω) |
| **Insulation Resistance 绝缘电阻** | 1,000 MΩ or more |
| **Load Life in Humidity 湿度寿命** | ±1% ; ±(1.0%+0.1Ω)<br>±5%; ±(3.0%+0.1Ω) |
| **Load Life 负载寿命** | ±1% ; ±(1.0%+0.1Ω)<br>±5%; ±(3.0%+0.1Ω) |

## Ordering Procedure (Example: RC06 1/4W 1% 10Ω)

## 订购方式 (例如: RC06 1/4W 1% 10Ω

**R C 0 6 W 4 F 1 0 0 J B 3 0**

**Product Type ( 产品类型 ):**
RC06= Special Metal Glaze film (non-flame)
RC16= RC06-1 Special Metal Glaze film

**Wattage ( 功率 ):**
W4= 1/4W

**Tolerance ( 公差 ):**
F= 1%  J= 5%

**Resistance Value (阻值):**
**5% & 10% (E-24 series):**
the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbers of zeros following;
**5%,10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0.
**1%(E-96 Series)**
The 1st to 3rd digits are for the significant figures of the resistance and the 4th digit denotes number of zeros following:
**1% 产品 (E-96 系列阻值)**
第 1~3 位表示阻值的有效数，第 4 位表示有几个 0.

**Color: ( 色标 ):**
1= Blue ( 蓝 )
3= Brown (综)

**Special Feature ( 特征 ):**
0 =For Bulk/Box packing ( 散装 / 盒装 )

**Packing Type:**
B = Bulk / Box
包装类型:
B = 散装 / 盒装

**Remark:** Please refer to page 141 for ordering guide.  注：下单请详见 P141 页说明 。

# Axial Leaded Type Cement Fixed Resistors
## 轴向导线型水泥固定电阻器



## Feature (特性)

- Self-extinguishing 完全不燃性
- Extremely small & sturdy mechanically safe 体积小且坚固安全
- Non-inductive type available 无感也可提供
- Excellent flame & moisture resistance 卓越抗湿性
- Too low or too high values on Wire-wound & Power-film type can be supplied on a case to case basis 过低或过高的阻值，绕线或切割型都可以特别提供



## Derating Curve (降功率曲线)




## Heat Rise Chart (表面温升)




## Axial Leaded Type-PRW Series( 轴向导线型 -PRW 系列 )




| Part No. 料号 | Type 类型 | Dimension( 尺寸 )(mm) | | | | | Max. working voltage 最大工作电压 | Max. Overload voltage 最大过负荷电压 | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | W±1 | D±1 | L±1 | H | d±0.05 | | | Wire-wound 绕线型 | Power Film 膜层型 |
| **PRW01W** | PRW1W | 6 | 6 | 13.5 | 25±3 | 0.70 | 200V | 400V | 0.1Ω~27Ω | 28Ω~100KΩ |
| **PRW02W** | PRW2W | 7 | 7 | 18 | 28±5 | 0.70 | 250V | 500V | 0.1Ω~27Ω | 28Ω~120KΩ |
| **PRW03W** | PRW3W | 8 | 8 | 22 | 32±5 | 0.70 | 300V | 600V | 0.1Ω~39Ω | 40Ω~150KΩ |
| **PRW05W** | PRW5W | 10 | 9 | 22 | 35±5 | 0.75 | 350V | 700V | 0.1Ω~47Ω | 48Ω~150KΩ |
| **PRW07W** | PRW7W | 10 | 9 | 35 | 35±5 | 0.75 | 500V | 1000V | 0.1Ω~680Ω | 681Ω~200KΩ |
| **PRW0AW** | PRW10W | 10 | 9 | 49 | 35±5 | 0.75 | 700V | 1400V | 0.1Ω~910Ω | 911Ω~200KΩ |
| **PRW0FW** | PRW15W | 12.5 | 11.5 | 49 | 35±5 | 0.75 | 700V | 1400V | 1Ω~1.0KΩ | 1.1KΩ~200KΩ |
| **PRW020** | PRW20W | 14.5 | 13.5 | 60 | 35±5 | 0.75 | 750V | 1500V | 2Ω~1.2KΩ | 1.3KΩ~200KΩ |
| **PRW025** | PRW25W | 14.5 | 13.5 | 64 | 35±5 | 0.75 | 750V | 1500V | 2Ω~1.2KΩ | 1.3KΩ~200KΩ |

## Axial Leaded Type-PRWC Series( 轴向导线型 -PRWC 系列 )




| Part No. 料号 | Type 类型 | Dimension( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|
| | | W±1 | D±1 | L±1 | H | d±0.05 | Wire-wound 绕线型 | Power Film 膜层型 |
| **PRWC1W** | **PRWC-1W** | 6 | 6 | 12 | 25±3 | 0.70 | 1Ω~27Ω | 28Ω~33KΩ |
| **PRWC2W** | **PRWC-2W** | 6 | 6 | 18 | 28±5 | 0.70 | 1Ω~27Ω | 28Ω~33KΩ |
| **PRWC3W** | **PRWC-3W** | 6 | 6 | 20 | 28±5 | 0.70 | 1Ω~27Ω | 28Ω~120KΩ |
| **PRWC5W** | **PRWC-5W** | 6 | 6 | 25 | 35±5 | 0.75 | 1Ω~200Ω | 201Ω~150KΩ |
| **PRWC7W** | **PRWC-7W** | 9 | 9 | 25 | 35±5 | 0.75 | 1Ω~200Ω | 201Ω~150KΩ |

## Axial Leaded Type-PRWC Series( 轴向导线型 -PRWC 系列 )




| Part No. 料号 | Type 类型 | Dimension( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|
| | | W±1 | D±1 | L±1 | H±5 | d±0.05 | Wire-wound 绕线型 | Power Film 膜层型 |
| **PRC14W** | PRWC-1 4W | 6.4 | 6.4 | 20 | 28 | 0.70 | 1Ω~200Ω | 201Ω~100KΩ |
| **PRC15W** | PRWC-1 5W | 6.4 | 6.4 | 25 | 28 | 0.70 | 1Ω~200Ω | 201Ω~100KΩ |
| **PRC16W** | PRWC-1 6W | 6.4 | 6.4 | 38 | 35 | 0.75 | 1Ω~200Ω | 201Ω~100KΩ |

## Axial Leaded Type-PRWA Series( 轴向导线型 -PRWA 系列 )




| Part No. 料号 | Type 类型 | Dimension( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|
| | | W±1 | D±1 | L±1 | H±5 | d±0.05 | Wire-wound 绕线型 | Power Film 膜层型 |
| **PRWA2W** | PRWA-2W | 7 | 7 | 18 | 28 | 0.70 | 0.1Ω~27Ω | 28Ω~120KΩ |
| **PRWA5W** | PRWA-5W | 10 | 9 | 22 | 35 | 0.75 | 0.1Ω~47Ω | 48Ω~150KΩ |
| **PRWA7W** | PRWA-7W | 10 | 9 | 35 | 35 | 0.75 | 0.1Ω~680Ω | 681Ω~200KΩ |
| **PRWAAW** | PRWA-10W | 10 | 9 | 49 | 35 | 0.75 | 0.1Ω~910Ω | 911Ω~200KΩ |

*Max. working voltage&Max. Overloadvoltage Reference to PRW Type 最大工作电压、最大过负荷电压参考 PRW 规格

## Radial Leaded Type-PRM Series(立式导线型-PRM系列)







| Part No. 料号 | Type 类型 | Dimension( 尺寸 )(mm) | | | | | Max. working voltage 最大工作电压 | Max. Overload voltage 最大过负荷电压 | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | W±1 | D±1 | L±1 | P±1 | d ±0.05 | | | Wire-wound 绕线型 | Power Film 膜层型 |
| **PRM02W** | PRM-2W | 11.5 | 7.5 | 20 | 5 | 0.70 | 250V | 500V | 0.1Ω~27Ω | 28Ω~120KΩ |
| **PRM03W** | PRM-3W | 12.5 | 8.5 | 25 | 5 | 0.70 | 300V | 600V | 0.1Ω~39Ω | 40Ω~150KΩ |
| **PRM05W** | PRM-5W | 13 | 9 | 25 | 5 | 0.75 | 350V | 700V | 0.1Ω~47Ω | 48Ω~150KΩ |
| **PRM07W** | PRM-7W | 13 | 9 | 38 | 5 | 0.75 | 500V | 1000V | 0.1Ω~680Ω | 681Ω~200KΩ |
| **PRM0AW** | PRM-10W | 13 | 9 | 50 | 5 | 0.75 | 700V | 1400V | 0.1Ω~910Ω | 911Ω~200KΩ |
| **PRMA5W** | PRMA-5W | 13 | 9 | 25 | 7.5 | 0.75 | 350V | 700V | 0.1Ω~47Ω | 48Ω~100KΩ |
| **PRMAAW** | PRMA-10W | 16 | 12 | 35 | 7.5 | 0.75 | 700V | 1400V | 0.1Ω~560Ω | 561Ω~100KΩ |
| **PRMB7W** | PRMB-7W | 12.5 | 9 | 38 | 5 | 0.75 | 500V | 1000V | 0.1Ω~680Ω | 681Ω~200KΩ |

## Radial Terminal Type-PRMT Series(轴向导线型-PRMT系列)



| Part No. 料号 | Type | Dimension( 尺寸 )(mm) | | | | | Max. working voltage 最大工作电压 | Max. Overload voltage 最大过负荷电压 | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | W±1 | D±0.5 | L±1 | P±1 | d ±0.05 | | | Wire-wound 绕线型 | Power Film 膜层型 |
| **PRMT15** | PRMT15W | 20 | 13 | 38 | 7.5 | 0.5 | 700V | 1400V | 0.1Ω~560Ω | 561Ω~200KΩ |
| **PRMT20** | PRMT20W | 20 | 13 | 45 | 7.5 | 0.4 | 750V | 1500V | | |

## Performance Specification ( 特性 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | < 20Ω：±400PPM； ≥20Ω：±350PPM |
| **Short-time Overload** | 短时间过负荷 | ΔR/R±(5%+0.05 Ω)，no evidence of mechanical damage( 无可见机械损伤 ) |
| **Dielectric withstanding voltage** | 绝缘耐压 | no evidence of mechanical damage( 无可见机械损伤 ) |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R±(2%+0.05 Ω),no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life in humidity** | 湿度寿命 | Wire-wound type( 绕线型 ):ΔR/R=±5%<br>Power Film type( 膜层型 ):<100KΩ:ΔR/R=±5%; ≥100KΩ:ΔR/R=±10% |
| **Load life** | 负载寿命 | Wire-wound type( 绕线型 ):ΔR/R=±5%<br>Power Film type( 膜层型 ):<100KΩ:ΔR/R=±5%; ≥100KΩ:ΔR/R=±10% |

## Ordering Procedure (Example: PRW 1W 5% 100Ω B/B)

## 订购方式 (例如: PRW 1W 5% 100Ω B/B )




**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

## Feature (特性)

- Low indutance 低电感量
- Safety flameroof construction 耐高温
- Thin& lightweight body save the PCB space cosiderably
  体积小轻薄, 节省PCB空间



## Derating Curve (降功率曲线)




## Heat Rise Chart (表面温升)




## PFAS (Single circuit-S Type) Dimension(mm)

### PFAS( 单电路 -S 型 ) 尺寸 (mm)




| Type 类型 | A±1.0 | B±1.0 | C±0.5 | d±0.05 | P±1 | H±1 | Resistance Range 阻值范围 (±5%、±10%) |
|---|---|---|---|---|---|---|---|
| PFAS2W | 13 | 8.5 | 5 | 0.75 | 9 & 10 | 13 | 0.01Ω~1Ω |
| PFAS3W | 14 | 13.5 | 5 | 0.75 | | 13 | 0.01Ω~1Ω |
| PFAS5W | 14 | 18 | 5 | 0.75 | | 13 | 0.01Ω~1Ω |
| PFAS10W | 26 | 18 | 5 | 0.75 | 20 | 13 | 0.01Ω~3.3Ω |

## PFAP (Single circuit-P Type) Dimension(mm)

### PFAP( 单电路 -P 型 ) 尺寸 (mm)




| Type 类型 | A±1.0 | B±1.0 | C±0.5 | d±0.05 | P±1 | H±1 | Resistance Range 阻值范围 (±5%、±10%) |
|---|---|---|---|---|---|---|---|
| PFAP2W | 13 | 8.5 | 5 | 0.75 | 9 & 10 | 4 & 10 | 0.01Ω~1Ω |
| PFAP3W | 14 | 13.5 | 5 | 0.75 | | | 0.01Ω~1Ω |
| PFAP5W | 14 | 18 | 5 | 0.75 | | | 0.01Ω~1Ω |
| PFAP10W | 26 | 18 | 5 | 0.75 | 20 | | 0.01Ω~3.3Ω |

## PFAT (Twin circuit-S Type) Dimension(mm)

### PFAT( 双电路 -S 型 ) 尺寸 (mm)




| Type 类型 | A±1.0 | B±1.0 | C±0.5 | d±0.05 | P±1 | H±1 | Resistance Range 阻值范围 (±5%、±10%) |
|---|---|---|---|---|---|---|---|
| PFAT2W | 26 | 9 | 5 | 0.75 | 10 | 13 | 0.05Ω~1Ω |
| PFAT3W | 26 | 13 | 5 | 0.75 | | | 0.05Ω~1Ω |
| PFAT5W | 26 | 18 | 5 | 0.75 | | | 0.05Ω~1Ω |
| PFAT7W | 26 | 20 | 5 | 0.75 | | | 0.1Ω~1Ω |

## Performance Specification ( 特性 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | 0.01Ω~0.1Ω Please contact Uniroyal，≥0.1Ω:±350PPM |
| **Short-time Overload** | 短时间过负荷 | ΔR/R≤±(2%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Dielectric withstanding voltage** | 绝缘耐压 | 2000V |
| **Operating temperature** | 工作温度范围 | -55℃~+200℃ |
| **Resistance to soldering heat** | 耐焊接热 | ΔR/R±(1%+0.05 Ω) with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Solderability** | 可焊性 | Coverage must be over 95%. |
| **Resistance to solvent** | 耐溶剂 | No deterioration of protective coating and markings ( 包封层，色码完整 ) |
| **Humidity (Steady State)** | 恒定湿热 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life in humidity** | 湿度寿命 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life** | 负载寿命 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |

## Ordering Procedure (Example: PFAS 5W ±5% 0.68Ω B/B)

## 订购方式 (例如: PFAS 5W ±5% 0.68Ω B/B )




**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

## Derating Curve (降功率曲线)




## Heat Rise Chart (表面温升)






## Radial Terminal Type - PRT (With metal mounting bracket)/PRU Series

## 立式端片型 PRT (带金属安装支架)/PRU

**PRT0**




**PRTA**




**PRU0**




**PRUA**




| Type 类型 | | W ±1 | D ±1 | L ±1.5 | P ±1 | H ±1 | A ±0.5 | H1 ±0.4 | C ±0.5 | F ±0.5 | G ±0.5 | E ±1 | Φ1 ±0.2 | Φ2 ±0.2 | W1 ±0.08 | Resistance Range 阻值范围 | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Wire-wound 绕线型 | Power Film 膜层型 |
| 10W | PRT0 PRUO | 10 | 9 | 48 | 32 | 18 | 12 | 5.5 | 3 | 8.7 | 5 | 3 | 4.1 | 2.5 | 0.5 | 1Ω~820Ω | 821Ω~200KΩ |
| | PRTA PRUA | | | | | 19 | | 8.0 | | | | | | 1.6 | 0.8 | | |
| 15W | PRT0 PRUO | 12.5 | 11.5 | 48 | 32 | 21 | 12 | 6.2 | 3 | 8.0 | 6 | 3 | 4.1 | 2.5 | 0.5 | 1Ω~1KΩ | 1.1KΩ~200KΩ |
| | PRTA PRUA | | | | | 23.5 | | 7.6 | | | | | | 1.6 | 0.8 | | |
| 20W | PRT0 PRUO | 12.5 | 13.5 | 63 | 44 | 21 | 12 | 6.2 | 3 | 10 | 6 | 3 | 4.1 | 2.5 | 0.5 | 2Ω~1.2KΩ | 1.3KΩ~200KΩ |
| | PRTA PRUA | | | | | 25 | | 7.6 | | | | | | 1.6 | 0.8 | | |
| 30W | PRT0 PRUO | 19 | 19 | 75 | 54 | 32 | 18 | 7.6 | 3 | 9.5 | 7.5 | 4 | 4.1 | 3.2 | 0.5 | 3Ω~1.5KΩ | - |
| | PRTA PRUA | | | | | 30 | | 7.6 | | | | | 6.0 | 1.6 | 0.8 | | |
| 40W | PRT0 PRUO | 19 | 19 | 90 | 70 | 32 | 18 | 7.6 | 3 | 9.5 | 7.5 | 4 | 4.1 | 3.2 | 0.5 | 6Ω~1.5KΩ | - |
| | PRTA PRUA | | | | | 30 | | 8.0 | | | | | 6.0 | 1.6 | 0.8 | | |
| 50W | PRT0 PRUO | 19 | 19 | 90 | 70 | 32 | 18 | 7.6 | 3 | 9.5 | 7.5 | 4 | 4.1 | 3.2 | 0.5 | 6Ω~1.5KΩ | - |
| | PRTA PRUA | | | | | 30 | | 8.0 | | | | | 6.0 | 1.6 | 0.8 | | |

## Performance Specification ( 特性 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | < 20Ω：±400PPM； ≥20Ω：±350PPM |
| **Short-time Overload** | 短时间过负荷 | ΔR/R±(5%+0.05 Ω)，no evidence of mechanical damage( 无可见机械损伤 ) |
| **Dielectric withstanding voltage** | 绝缘耐压 | no evidence of mechanical damage( 无可见机械损伤 ) |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R±(2%+0.05 Ω),no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life in humidity** | 湿度寿命 | Wire-wound type( 绕线型 ):ΔR/R=±5%<br>Power Film type( 膜层型 ):<100KΩ:ΔR/R=±5%; ≥100KΩ:ΔR/R=±10% |
| **Load life** | 负载寿命 | Wire-wound type( 绕线型 ):ΔR/R=±5%<br>Power Film type( 膜层型 ):<100KΩ:ΔR/R=±5%; ≥100KΩ:ΔR/R=±10% |

## Ordering Procedure (Example: PRT 50W 5% 100Ω B/B)

## 订购方式 (例如: PRT 50W 5% 100Ω B/B)

**P R T 0 5 0 J W 1 0 1 B 0 0**

**Product Type ( 产品类型 ):**
PRT0=PRT
PRU0=PRU
PRTA=PRTA
PRUA=PRUA

**Wattage ( 功率 ):**
AW=10W
FW=15W
20=20W
30=30W
40=40W
50=50W

**Tolerance (公差):**
J = ± 5%
K = 10%

**Resistance Value (阻值):**
**5%,10%(E-24 series):**
The 1st digit to denote production type: W=Wire-wound type P=Power film type, the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the number of zeros following

**5%, 10% 产品 (E-24 系列阻值 ):**
第 1 位用 "W" 或 "P" 来表示产品是 " 绕线型 " 还是 " 切割型 "; 第 2, 3 位为阻值的有效数 , 第 4 位则表示有效数后有几个 0.

**Packing Type (包装类型):**
B = Bulk/Box
散装 / 盒装

**Packing Qty. ( 包装数量 ):**
0 = Bulk/Box
散装 / 盒装

**Additional Information (注):**
0=NIL( 标准品 )
N=Non-Inductive ( 无感性)

**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

# Radial Terminal Type Cement Fixed Resistors

## 立式端片型水泥固定电阻器



## Feature (特性)

- Self-extinguishing 完全不燃性
- Extremely small & sturdy mechanically safe 体积小且坚固安全
- Excellent flame & moisture resistance 卓越抗湿性
- Too low or too high values on Wire-wound & Power-film type can be supplied on a case to case basis
  过低或过高的阻值，绕线或切割型都可以特别提供

## Radial Terminal Type-PRVA Series

## (立式端片型-PRVA系列)




## Radial Terminal Type - PRVB Series

## 立式端片型-PRVB系列




| 类型 Type | W±1 | D±1 | L ±1 | P±1 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|
| PRVA-3W<br>PRVB-3W | 10 | 9 | 22 | 9.5 | 0.1Ω~150KΩ |
| PRVA-5W<br>PRVB-5W | 10 | 9 | 27/25 | 15/9.5 | 0.1Ω~200KΩ |
| PRVA-7W<br>PRVB-7W | 10 | 9 | 35 | 22 | 0.1Ω~200KΩ |
| PRVA-10W<br>PRVB-10W | 10 | 9 | 48 | 35/32 | 1Ω~200KΩ |
| PRVA-15W<br>PRVB-15W | 12.5 | 11.5 | 48 | 32 | 1Ω~200KΩ |
| PRVA-20W<br>PRVB-20W | 12.5 | 13.5 | 63 | 42 | 1Ω~200KΩ |

## Radial Terminal Type-PRZ Series

## (立式端片型-PRZ系列)




| Type | W±1 | D±1 | L | P±1.5 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|
| PRZA-1/PRZA-2 /PRZC/PRZD 3 W | 10 | 9 | 22±1 | 9.5 | 0.1~150KΩ |
| PRZA-1/PRZA-2/PRZA-3/PRZC/PRZD 5W | 10 | 9 | 25/27±1 | 9.5/15 | 0.1Ω~200KΩ |
| PRZA-1/PRZA-2/PRZC/PRZD 7W | 10 | 9 | 35±1 | 22 | 0.1Ω~200KΩ |
| PRZA-1/PRZA-2/PRZC/PRZD 10W | 10 | 9 | 48±1.5 | 32/35 | 1Ω~200KΩ |
| PRZA-1/PRZA-2/PRZC/ 15W | 12.5 | 11.5 | 48±1.5 | 32 | 1Ω~200KΩ |
| PRZA-1/PRZA-2/PRZC/ 20W | 12.5 | 13.5 | 63±1.5 | 42/45 | 2Ω~200KΩ |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## Feature (特性)

- Self-extinguishing 完全不燃性
- Extremely small & sturdy mechanically safe 体积小且坚固安全
- Excellent flame & moisture resistance 卓越抗湿性
- Too low or too high values on Wire-wound & Power-film type can be supplied on a case to case basis
  过低或过高的阻值，绕线或切割型都可以特别提供



## Radial Leaded Type-PRS Series(立式导线型-PRS系列)




| Part No. 料号 | Type | Dimension( 尺寸 )(mm) | | | | | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|
| | | W±1 | D±1 | L±1 | P±1 | d ±0.05 | |
| PRS05W | PRS-5W | 10 | 9 | 22 | 5 | 0.75 | 0.1Ω~150KΩ |
| PRS07W | PRS-7W | 10 | 9 | 35 | 10 | 0.75 | 0.1Ω~200KΩ |
| PRS0AW | PRS-10W | 10 | 9 | 45 | 10 | 0.75 | 0.1Ω~200KΩ |
| PRS0FW | PRS-15W | 12.5 | 13.5 | 49 | 11 | 0.75 | 0.1Ω~200KΩ |
| PRS020 | PRS-20W | 14.5 | 13.5 | 60 | 10 | 0.75 | 0.1Ω~200KΩ |
| PRS025 | PRS-25W | 14.5 | 13.5 | 64 | 10 | 0.75 | 0.1Ω~200KΩ |

## Radial Terminal Type Resistors (立式端片型电阻器)






| Type 类型 | W±1 | D±1 | L±1.5 | H±1 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|
| PRTC/PRTD10W | 10 | 9 | 48 | 18/19 | 1Ω~200KΩ |
| PRTC/PRTD15W | 12.5 | 11.5 | 48 | 21/23.5 | 1Ω~200KΩ |
| PRTC/PRTD20W | 12.5 | 13.5 | 63 | 21/25 | 2Ω~200KΩ |
| PRTC/PRTD30W | 19 | 19 | 75 | 32/30 | 3Ω~1.5KΩ |
| PRTC/PRTD40W | 19 | 19 | 90 | 32/30 | 6Ω~1.5KΩ |
| PRTC/PRTD50W | 19 | 19 | 90 | 32/30 | 6Ω~1.5KΩ |

## Resistors of Capacitor Voltage Balance (电容电压平衡电阻器)




| Type 类型 | Dimension( 尺寸 ) (mm) | | | | Resistance Range 阻阻值范围 |
|---|---|---|---|---|---|
| | W±1.0 | D±1.5 | L±1.5 | P±1.5 | Power Film 切割型 |
| PRTM4W | 12.5 | 12.5 | 48.0 | 27.0 | 1.3KΩ~200KΩ |
| PRTM7W | 12.5 | 12.5 | 63.0 | 27.0 | |
| PRTM20W | 12.5 | 13.5 | 63.0 | 35.0 | |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

# Lead Type Cement Fixed Resistors
## 导线型水泥固定电阻器



## Feature (特性)

- Square porcelain tube 方形瓷管外壳
- Excellent insulation and moisture resistance优良的绝缘性和耐湿性
- Winding process, good resistance to load绕线工艺，良好的耐负荷能力
- Application：Power supply of frequency converter 应用：变频器的电源

PHF1type 卧式1型




PHF2type 卧式2型




PHF3 type 卧式3型




## PHF1、PHF2、PHF3 Series

| Type 类型 | H±1.5 | H1±0.5 | D±0.5 | D1±0.5 | L | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|
| PHF1/PHF2 4W | - | 8.5 | - | 7.5 | 20±1 | 1Ω~1KΩ |
| PHF1/PHF2 5W | - | 8.5 | - | 7.5 | 25±1 | 1Ω~2.2KΩ |
| PHF1/PHF2 7W | - | 9.5 | - | 7.5 | 38±1 | 1Ω~6.2KΩ |
| PHF1/PHF2 9W | 10 | - | 9 | - | 38±1 | 1Ω~6.2KΩ |
| PHF1/PHF2/ PHF3 11W | 10 | - | 9 | - | 50±1 | 1Ω~6.2KΩ |
| PHF1/PHF2/ PHF3 17W | 10 | - | 9 | - | 75±2 | 1Ω~10KΩ |

## PRWI Series




| Type 类型 | W±1 | D | L±1 | H±1 | d±0.05 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|
| PRWI 4W | 7.0 | 8±1 | 20 | 56 | 0.75 | 0.1Ω~6.8KΩ |
| PRWI 5W | 7.5 | 8.5±1 | 25 | 60 | 0.75 | 0.1Ω~6.8KΩ |
| PRWI 7W | 7.0 | 8±1 | 38 | 70 | 0.75 | 0.33Ω~22KΩ |
| PRWI 11W | 9.0 | 10±1.5 | 50 | 85 | 0.75 | 0.33Ω~22KΩ |
| PRWI 17W | 9.0 | 10±1.5 | 75 | 110 | 0.75 | 1Ω~39KΩ |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## Feature (特性)

- With Aluminum Shell for a good heat dissipation, suitable for board mount
  铝外壳散热性能好，适用于散热板安装
- Thin & lightweight body with big power rating 本体小而轻，功率大
- Application: Power Supply, Adapter, Machine 应用：设备电源类




## Derating Curve (降功率曲线)







PDM5W~50W




(PDM1 75W、100W)




(PDMS 25W~50W)

| Type | L1±1 | L2 | L3 | L4±1.5 | W±1 | H±1 | D±1 | d±0.2 | D1 | D2±0.5 | D3 | Resistance range 阻值范围 | Special high value 特殊最高值 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **PDM 5W** | 15.5 | 11±0.5 | 12±0.5 | 32.5 | 16±0.5 | 8.0 | 8.0 | 0.3 | 2.0+0.5/-0.2 | 1.3 | 1±0.05 | 0.5Ω~1KΩ | 1.8KΩ |
| **PDM10W** | 20.5 | 15.2±0.5 | 17.2±0.5 | 40.5 | 22.3±0.5 | 12.2 | 11.0 | 0.8 | 2.5+0.5/-0.2 | 2.0 | 2±0.1 | 1Ω~1.5KΩ | 5KΩ |
| **PDM25W** | 28.0 | 18.2±0.5 | 20.2±0.5 | 45.5 | 30.3±0.5 | 16.0 | 13.5 | 0.8 | 3.0+0.5/-0.2 | 2.0 | 2±0.1 | 5.1Ω~8.2KΩ | 12KΩ |
| | 28.0 | 18±0.5 | 19.0±0.5 | 49.0 | 27±1 | 14.0 | 13.5 | 0.8 | 4+0.5/-0.2 | / | 2±0.1 | 5.1Ω~8.2KΩ | 12KΩ |
| **PDM35W** | 34.5 | 24.2±0.5 | 20.2±0.5 | 56.5 | 30±0.5 | 16.3 | 16.3 | 0.8 | 3.0+0.5/-0.2 | 2.0 | 2±0.1 | 5.1Ω~8.2KΩ | 15KΩ |
| **PDM50W** | 50.5 | 40.2±0.5 | 20.2±0.5 | 75.0 | 30.3±0.5 | 15.7 | 15.5 | 0.8 | 3.0+0.5/-0.2 | 2.0 | 2±0.1 | 5.1Ω~20KΩ | 35KΩ |
| | 50.0 | 40±1 | 21.5±0.5 | 78.5 | 30±1 | 16.0 | 15.5 | 0.8 | 3.5±0.5 | / | 2±0.1 | 5.1Ω~20KΩ | 35KΩ |
| **PDMS25W** | 28.0 | 18±0.5 | 19±1 | 49.0 | 27±0.5 | 14.0 | 13.5 | 0.8 | 4±0.5 | 2.0 | 2±0.1 | 5.1Ω~8.2KΩ | 22KΩ |
| **PDMS50W** | 50.0 | 40±0.5 | 21.5±1 | 75.0 | 30±0.5 | 16.0 | 15.5 | 0.8 | 3.5±0.5 | 2.0 | 2±0.1 | 5.1Ω~20KΩ | 35KΩ |
| **PDM-1 75W** | 66.0 | 36±0.5 | 37±1 | 88.0 | 47.5±1 | 26.0 | 27.0 | 1.1 | 4.5±0.5 | 2.0 | 2.3±0.2 | 1Ω~20KΩ | - |
| **PDM-1 85W** | 75.5 | 40±0.5 | 20.5±1 | 100 | 29±1 | 15.5 | 15.5 | 0.8 | 3.5±0.5 | 2.0 | 2±0.1 | 1Ω~20KΩ | - |
| **PDM-1 100W** | 98.0 | 72±1 | 37±1 | 120 | 48±1 | 26.0 | 27.0 | 0.8 | 4.5±0.5 | 2.0 | 2±0.1 | 1Ω~20KΩ | - |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

# High Power Wire-wound Aluminum Case Resistors
## 高功率绕线铝壳电阻器



## Feature (特性)

- Anti-vibration, high stability 优异的抗震性和稳定性
- Excellent transient current impact capability, suitable for the start of the inverter under harsh conditions
  优良的瞬间电流冲击能力，适合变频器严苛条件下的启动
- Application: Frequency Conversion Equipment, such as Elevator, Freezer, Crane, Lift etc.
  应用: 各类变频设备中, 如电梯,冷柜, 起重机, 升降机等

## Derating Curve (降功率曲线)






60W - 600W



1000W

| Type 类型 | L1±2 | L2±2 | L3±2 | L4±10 | W1±2 | W2±5 | H±2 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|---|---|
| HEWR60W | 115 | 100 | 80 | 190 | 40 | 15 | 20 | 2Ω~2.5KΩ |
| HEWR80W | 140 | 125 | 105 | 200 | 40 | 15 | 20 | 1Ω~3KΩ |
| HEWR100W | 140 | 125 | 100 | 240 | 60 | 25 | 30 | 1Ω~4KΩ |
| HEWR100WS | 165 | 150 | 125 | 240 | 40 | 15 | 20 | 1Ω~4KΩ |
| HEWR120W | 190 | 175 | 150 | 240 | 40 | 15 | 20 | 1Ω~5KΩ |
| HEWR150W | 215 | 200 | 175 | 240 | 40 | 15 | 20 | 1Ω~6KΩ |
| HEWR200W | 165 | 150 | 125 | 255 | 60 | 25 | 30 | 1Ω~7KΩ |
| HEWR300W | 215 | 200 | 175 | 255 | 60 | 25 | 30 | 1Ω~8KΩ |
| HEWR400W | 265 | 250 | 225 | 255 | 60 | 25 | 30 | 0.5Ω~10KΩ |
| HEWR500W | 335 | 320 | 295 | 255 | 60 | 25 | 30 | 0.5Ω~12KΩ |
| HEWR600W | 335 | 320 | 295 | 255 | 60 | 25 | 30 | 0.5Ω~12KΩ |
| HEWR1000W | 400 | 385 | 340 | 255 | 100 | 25 | 50 | 1Ω~15KΩ |

## HBWR Lead Type-HBWR 引线型




| Type 类型 | L1±2 | L2±2 | L3±2 | W1±2 | H±2 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|
| **HBWR200W** | 190 | 160 | 165 | 30 | 60 | 1Ω~7KΩ |
| **HBWR300W** | 240 | 210 | 215 | 30 | 60 | 1Ω~8KΩ |
| **HBWR400W** | 290 | 260 | 265 | 30 | 60 | 0.5Ω~10KΩ |
| **HBWR500W** | 360 | 330 | 335 | 30 | 60 | 0.5Ω~12KΩ |
| **HBWR600W** | 360 | 330 | 335 | 30 | 60 | 0.5Ω~12KΩ |

## Performance Specification ( 特性 )

| | | |
|---|---|---|
| **Temperature coefficient** | 温度系数 | <20Ω:±400PPM； ≥20Ω:±350PPM |
| **Short-time Overload** | 短时间过负荷 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Dielectric withstanding voltage** | 绝缘耐压 | No evidence of flashover, mechanical damage.( 无击穿、飞弧及可见机械损伤 ) |
| **Rapid change of temperature** | 温度快速变化 | ΔR/R≤±(2%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Humidity (Steady State)** | 恒定湿热 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |
| **Load life in humidity** | 湿度寿命 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 |
| **Load life** | 负载寿命 | ΔR/R≤±(5%+0.05Ω), with no evidence of mechanical damage ( 无可见机械损伤 ) |

## Ordering Procedure (Example: HEWR200W ±5% 10Ω B/B)

## 订购方式 (例如: HEWR200W±5% 10Ω B/B)

**H E W R A 0 J 0 1 0 0 2 0 0**

**Product Type ( 产品类型 ):**
HEWR=HEWR
HBWR=HBWR

**Wattage ( 功率 ):**
00=for power rating over 100W, please indicate the power rating at the last 3 digits of the part No. (00 = 功率超过 100 瓦 , 但请注明功率于料号最后三位数 )
A0=Terminal Type
B0=Cable Type

**Tolerance (公差):**
J = ± 5%
K = 10%

**Resistance Value (阻值):**
**5%,10%(E-24 series):**
The 1st digit is "0", the 2nd & 3rd digits are for the signifcant fgures of the resistance and the 4th indicate the numbers of zeros following;
**5%, 10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0

**Additional information( 注 ):**
200=200W，300=300W，
400=400W，500=500W，
600=600W

## New/Old Part.no Contrast (新旧料号对照)

| New Part.no 新料号 | Old Part.no 旧料号 |
|---|---|
| **HEWR**J******* | HPAR**J******* |

**Remark:** Please refer to page 141 for ordering guide. 注：下单请详见 P141 页说明 。

## Feature (特性)

- Multi-terminal types & variable types available多端子和多可调阻方式都可提供
- Small in size but capable of carrying high power load小体型负载大功率
- Resistance value unchanged after long use, good resistivity to short time overload
  长年使用不变阻值，短时间过负荷表现良好
- High resistivity to heat, small resistance temperature coefficient and the change in resistance with temperature being linear
  抗热，温度系数低，温度变化小
- Too low or high ohmic value can be supplied on a case to case basis
  超低或超高阻值都可特别提供
- Adjustable & Multi-Resistor type is available
  可调型与多阻型可提供
- Non-Inductive type is available可提供无感型

## Derating Curve (降功率曲线)




## Power Wire-wound Resistors-QH&QL Type
## 功率绕线型 – -QH&QL Type

QH Type (QH 型)




(QH Type 20W~40W)




(QH Type 50W~600W)

QL Type (QL 型)




(QL Type 20W~40W)




(QL Type 50W~600W)

| Type 类型 | Dimension ( 尺寸 )(mm) | | | | | | | | | | Resistance range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | A±2 | B | C±2 | E | F | H1±2 | H2±2 | J±1 | K±1 | Φd±0.05 | |
| QH/QL20W | 22 | 50±2 | 70 | 75±2 | 102±2 | 25 | 50 | 5 | 19 | 4 | 1Ω~10KΩ |
| QH/QL25W | 22 | 60±2 | 81 | 84±2 | 110±2 | 25 | 50 | 5 | 19 | 4 | 2Ω~12KΩ |
| QH/QL30W | 22 | 75±2 | 95 | 99±2 | 126±2 | 25 | 50 | 5 | 19 | 4 | 2Ω~15KΩ |
| QH/QL40W | 22 | 90±2 | 112 | 114±2 | 141±2 | 25 | 50 | 5 | 19 | 4 | 2Ω~20KΩ |
| QH/QL50W | 30 | 75±2 | 110 | 103±2 | 133±2 | 34 | 64 | 6.3 | 27 | 5 | 3Ω~25KΩ |
| QH/QL60W | 30 | 90±2 | 126 | 117±2 | 147±2 | 34 | 64 | 6.3 | 27 | 5 | 3Ω~30KΩ |
| QH/QL80W | 30 | 115±2 | 150 | 143±2 | 173±2 | 34 | 64 | 6.3 | 27 | 5 | 3Ω~40KΩ |
| QH/QL100W | 30 | 140±2 | 173 | 166±2 | 197±2 | 34 | 64 | 6.3 | 27 | 5 | 3Ω~50KΩ |
| QH/QL120W | 30 | 165±2 | 200 | 193±2 | 223±2 | 34 | 64 | 6.3 | 27 | 5 | 4Ω~60KΩ |
| QH/QL150W | 30 | 195±2 | 230 | 224±2 | 254±2 | 34 | 64 | 6.3 | 27 | 5 | 4Ω~70KΩ |
| QH/QL200W | 30 | 254±2 | 289 | 282±2 | 312±2 | 34 | 64 | 6.5 | 27 | 5 | 5Ω~100KΩ |
| QH/QL300W | 42 | 254±2 | 292 | 285±2 | 332±2 | 45 | 87 | 6.5 | 39 | 5 | 8Ω~150KΩ |
| QH/QL400W | 42 | 330±3 | 364 | 364±3 | 410±3 | 45 | 87 | 6.5 | 39 | 5 | 10Ω~200KΩ |
| QH/QL600W | 42 | 420±3 | 458 | 451±3 | 498±3 | 45 | 87 | 6.5 | 39 | 5 | 10Ω~200KΩ |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## Power Ribbon Wire-wound Resistors-QR&QRZG Type

## 功率合金带绕线型 -QR&QRZG Type

QR Type (QR 型)




QRZG Type (QRZG 型)




| Type 类型 | Dimension ( 尺寸 )(mm) | | | | | | | | | | Resistance range 阻值范围 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | B | D±4 | E | F | G±2 | H1±2 | H2±2 | I±2 | J±1 | K±1 | |
| QR/QRZG120W | 115±2 | 36 | 143±2 | 173±2 | 28 | 34 | 64 | 16 | 6.3 | 27 | 0.2Ω~4Ω |
| QR/QRZG150W | 140±2 | 36 | 166±2 | 197±2 | 28 | 34 | 64 | 16 | 6.3 | 27 | 0.3Ω~5Ω |
| QR/QRZG180W | 165±2 | 36 | 193±2 | 223±2 | 28 | 34 | 64 | 16 | 6.3 | 27 | 0.3Ω~6Ω |
| QR/QRZG225W | 195±2 | 36 | 224±2 | 254±2 | 28 | 34 | 64 | 16 | 6.3 | 27 | 0.4Ω~8Ω |
| QR/QRZG300W | 254±2 | 36 | 282±2 | 312±2 | 28 | 34 | 64 | 16 | 6.3 | 27 | 0.5Ω~10Ω |
| QR/QRZG450W | 254±2 | 48 | 285±2 | 332±2 | 40 | 45 | 87 | 25 | 6.5 | 39 | 0.8Ω~15Ω |
| QR/QRZG600W | 330±3 | 48 | 364±3 | 410±3 | 40 | 45 | 87 | 25 | 6.5 | 39 | 1Ω~20Ω |
| QR/QRZG750W | 300±3 | 58 | 332±3 | 384±3 | 50 | 57 | 102 | 34 | 8 | 48 | 1Ω~75Ω |
| QR/QRZG1000W | 390±3 | 58 | 423±3 | 475±3 | 50 | 57 | 102 | 34 | 8 | 48 | 1Ω~100Ω |

## Ordering Procedure (Example: QRZG 225W ±5% 1.8Ω B/B)

## 订购方式 (例如: QRZG 225W ±5% 1.8Ω B/B)

**Q R Z G 0 0 J 0 1 8 J 2 2 5**

**Product Type ( 产品类型 ):**
QH00=QH Type
QL00=QL Type
QR00=QR Type
QRZG=QRZG Type

**Wattage ( 功率 ):**
00=for power rating over 100W, please indicate the power rating at the last 3 digits of the part No.
(00 = 功率超过 100 瓦 , 但请注明功率于料号最后三位数 )

**Tolerance (公差):**
J = ± 5%  K = 10%

**Resistance Value (阻值):**
**5%,10%(E-24 series):**
**5%,10%(E-24 series):**
The 1st digit is "0", the 2nd & 3rd digits are for the signifcant fgures of the resistance and the 4th indicate the numbers of zeros following;
**5%, 10% 产品 (E-24 系列阻值 ):**
第 1 位是 0, 第 2、3 位表示阻值的有效数 , 第 4 位表示有几个 0

**Additional information( 注 ):**
100=100W, 120=120W
150=150W, 180=180W
225=225W, 300=300W
450=450W, 600=600W
750=750W, 1KW=1000W

**Remark:** Please refer to page 141 for ordering guide.  注：下单请详见 P141 页说明 。

## Bilateral Cement Fixed Resistor-BCR Type
## 双体水泥固定电阻器 -BCR 型

- Small size & sturdy mechanically safe 尺寸小、机械性能安全
- High safety standard 安全系数高
- Application：Automobile and motorcycle 应用：汽车、摩托车






| Type 类型 | L1±0.5 | L2±1 | L3±0.5 | L4±1 | W1±0.5 | W2±1 | W3 | W4±1 | H1 Max. | H2+10/-0 | D1+0.5/-0 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| BCR20W+5W | 64 | 66 | 42 | 44 | 13 | 15 | 13±0.5 | 15 | 30 | 250 | 6.5 |

## Thermal Fuse Wire-wound Resistors-ASSY Type
## 热熔保险丝型绕线电阻器 -ASSY 型

- High quality non-flame coating 高品质阻燃性涂装
- Self fusing 自熔断
- High current load and pulse capacity 高电流的负荷和脉冲能力
- Application：Automobile 应用：汽车







### Derating Curve (降功率曲线)




| Type 类型 | L1±3 | L2±3 | W±3 | H(MAX) | T±0.2 | Resistance Range 阻值范围 |
|---|---|---|---|---|---|---|
| ASSY-4 Terminal | 74 | 43 | 39 | 13 | 0.8 | 0.1Ω~10Ω |
| ASSY-5 Terminal | 80 | 43 | 34 | 13 | 0.8 | 0.1Ω~10Ω |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## High Power Wire-wound Flat Aluminum Shell Fixed Resistors-HFWR Type
## 高功率绕线扁平铝壳电阻器 -HFWR 型

- Completely flame-retardant material 完全阻燃的材料
- Anti-vibration, high stability 优异的抗震性和稳定性
- Flat structure with great saving space 扁平式结构极大的节约空间
- Wire-wound process, good resistance to current impact
  绕线工艺，良好的耐电流冲击能力
- Application：Overload current protection of lithium battery pack in the start of new energy vehicle
  应用：新能源汽车启动时锂电池组的过载电流保护




| Type 类型 | L±1.0 | L1±0.5 | L2±0.3 | W±0.3 | W1±0.3 |
|---|---|---|---|---|---|
| HFWR90W | 70 | 53 | 39.7 | 51 | 41 |
| HFWR330W | 280 | 263 | 2*100 | 51 | 41 |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## Cement Thermal Fusible Resistors
## 水泥热熔保险丝电阻器

- Self-extinguishing 自熄灭
- Excellent flame & moisture resistance 优异的阻燃性和抗湿性
- Extremely small & sturdy mechanically safe 体积小且坚固安全
- Non-inductive type available 无感也可提供
- Circuit protection applied to industrial and motor control
  应用于工业和马达控制的电路保护
- Old Part.NO：PF2A~PF10D Series 旧料号PF2A~PF10D系列



| Type 类型 | FTR2~FTR10 |
|---|---|
| Thermal Cut-Off Temp. 动作温度 | 98℃ ~235℃ |
| Rated current 额定电流 | 2A or 10A |
| Rated voltage 额定电压 | AC 250V |
| Wire-wound Resistance Range 阻值范围 (±5%、±10%) | 0.22Ω~1.8KΩ |




## Vertical Type Shrapnel Fuse Resistors - PHF0 Type
## 立式弹片型保险丝电阻 - PHF0 型

- Elastic sheet metal, solder dot fuse, reliable circuit cut off function
  弹性金属片，锡点熔断型，可靠的电路切断功能
- Fusing Temperature 220±20℃ 熔断温度220±20℃
- Application: Over temperature protection of industrial power supply
  应用：工业电源部分的超温保护

| Type 类型 | L±1.0 | W±1.0 | H±1 | L1±3 | L2±1.5 | L3±0.5 | C±0.1 | e±0.1 | Φd±0.05 |
|---|---|---|---|---|---|---|---|---|---|
| PHF-2W | 25.0 | 9.0 | 10.0 | 38.0 | 13.0 | 4.5 | 3.0 | 0.9 | 0.75 |




## Array Type Cement Temperature Fusing Resistors - TFRC Type
## 排列式水泥温度保险丝电阻器 - TFRC 型

- Multi lead arrange encapsulation & space saving 多引线排列封装、节约空间
- Excellent flame &miosture resistance 良好的阻燃性、抗湿性
- Application: Over temperature protection of industrial power supply
  应用：工业电源部分的超温保护




| Type 类型 | Fusing Temp. 熔断温度 | Rated current 额定电流 | Rated voltage 额定电压 |
|---|---|---|---|
| TFRC-2W | 91℃ | 10A | 250V |




Remark: For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## Columnar Type Cement Fixed Resistors-QHO Type

## 圆柱状水泥电阻器 -QHO 型

- Circular ceramic 圆形瓷管外壳
- Excellent insulation and moisture resistance优良的绝缘性和耐湿性
- Winding process, good resistance to load绕线工艺，良好的耐负荷能力
- Application：Power supply of frequency converter
  应用：变频器的电源

| Type 类型 | L±1 | L1±3 | ΦD±1 | d±0.05 |
|---|---|---|---|---|
| QHO 4W | 43 | 30 | 8 | 0.75 |
| QHO 5W | 45 | 30 | 8 | 0.75 |
| QHO 7W | 50 | 30 | 9 | 0.75 |
| QHO 9W | 60 | 30 | 9 | 0.75 |
| QHO 11W | 65 | 30 | 9 | 0.75 |
| QHO 17W | 75 | 30 | 9 | 0.75 |

QHO-1




QHO-2




## Multi-Lead Wire-wound Fixed Resistors - KNHW Type

## 多引线型绕线固定电阻器 - KNHW 型

- All materials are inorganic and non-flammable
  所有的材料均为无机或非燃性的固体材料
- Super heat dissipation & High stability 散热性高，稳定性好
- Special design of Multi-lead wire easy to assembled on PCB
  特殊设计的多导线易于在PCB上安装
- Application: Charging or discharging resistance of electrical equipment such as elevator
  应用：电气设备如电梯的充电电阻或放电电阻

| Type 类型 | L±1 | A±1 | F±1 | P±1 | ΦD±1 | d±0.05 |
|---|---|---|---|---|---|---|
| KNHW10W | 45 | 10 | 15 | 12 | 11.5 | 1.0 |
| KNHW18W | 40 | 12 | 18 | 15 | 14.5 | 1.0 |
| KNHW25W | 50 | 12 | 18 | 15 | 14.5 | 1.0 |
| KNHW40W | 65 | 12 | 20 | 17 | 16.5 | 1.0 |




## High Power Flat Wire-wound Fixed Resistors - KNHB Type

## 高功率扁平型绕线固定电阻器

- All materials are inorganic and non-flammable
  所有的材料均为无机或非燃性的固体材料
- Can withstand High Voltage pulse in short-time 短时间可承受高电压脉冲
- Can use in single or in-piles 可单个或成堆使用
- Application: Charging or discharging resistance of electrical equipment such as elevator
  应用：电气设备如电梯的充电电阻或放电电阻

| Type 类型 | A±2 | B±1 | C±0.5 | D±1 | L±1 | N±2 |
|---|---|---|---|---|---|---|
| KNHB21W | 32 | 19 | 12 | 14 | 68 | 51 |
| KNHB31W | 51 | 19 | 12 | 14 | 87 | 70 |
| KNHB53W | 90 | 19 | 12 | 14 | 126 | 109 |
| KNHB68W | 120 | 19 | 12 | 14 | 156 | 140 |
| KNHB91W | 153 | 19 | 12 | 14 | 189 | 173 |




**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## High Power Wire-wound Flat Aluminum Shell Fixed Resistors - HPWR Type

## 高功率绕线扁平铝壳电阻器 - HPWR 型

- Anti-vibration, high stability 优异的抗震性和稳定性
- Easy to assembled on PCB 易于在PCB 上安装
- Application：Power supply of frequency converter
  应用：变频器的电源

| Type 类型 | L±1 | L1±0.5 | L2 $^{+20}_{-0}$ | W±0.5 | W1±0.2 | H±0.5 |
|---|---|---|---|---|---|---|
| HPWR 40W | 85 | 72 | 300 | 45 | 5.5 | 8.2 |




## High Power Wire-wound Iron Shell Fixed Resistors - HPWR Type

## 高功率绕线铁壳固定电阻器 - HPWR 型

| Type 类型 | L+0/-5 | L1±0.5 | W±0.5 | H±0.5 | L3±5 |
|---|---|---|---|---|---|
| HPWR110W | 105 | 91.5 | 44.6 | 11.5 | 300 |
| HPWR120W | 195 | 184 | 40 | 14 | 250 |
| HPWR220W | 200 | 187 | 44.6 | 11.5 | 250 |







## High Power Wire-wound Iron-Case Resistors - HAWF Type

## 高功率绕线型铁壳固定电阻器 - HAWF 型

- Anti-vibration, high stability 优异的抗震性和稳定性
- Excellent transient current impact capability, suitable for the start of the inverter under harsh conditions
  优良的瞬间电流冲击能力，适合变频器严苛条件下的启动
- Application: Frequency Conversion Equipment, such as Elevator, Freezer, Crane, Lift etc.
  应用: 各类变频设备中, 如电梯,冷柜, 起重机, 升降机等



| Type 类型 | L±1 | W±1 | H±1 | L1±1 |
|---|---|---|---|---|
| HAWF30W | 97 | 32 | 15 | 90.5 |
| HAWF40W | 85 | 32 | 20 | 20 |




**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

## High Power Wire-wound Aluminum Shell Resistance - HAWR Type

## 高功率绕线型铝壳电阻器 - HAWR 型

- Anti-vibration, high stability 优异的抗震性和稳定性
- Excellent transient current impact capability, suitable for the start of the inverter under harsh conditions
  优良的瞬间电流冲击能力，适合变频器严苛条件下的启动
- Application: Frequency Conversion Equipment, such as Elevator, Freezer, Crane, Lift etc.
  应用: 各类变频设备中, 如电梯,冷柜, 起重机, 升降机等




| Type 类型 | L1±1 | L2±2 | P±1 | W1±1 | W2±1 | W3±0.5 | W4±0.2 | D±0.2 | H±1 |
|---|---|---|---|---|---|---|---|---|---|
| **HAWR60W** | 100 | 75.5 | 90 | 30 | 28 | 16.5 | 4.5 | 4.6 | 16.5 |
| **HAWR80W** | 130.5 | 104.5 | 117.5 | 43 | 38.5 | 22 | 6.0 | 6.0 | 21 |
| **HAWR100W** | 130 | 110 | 118 | 42 | 39 | 22.5 | 6.0 | 6.0 | 20 |

**Remark:** For further information, please contact our sales team. 若需详细信息，请联系我司销售。

# Standard Packing of Cement Resistors - (1)
# 水泥电阻器包装规范 - (1)

## Type A Packing- 包装类型 A (mm)



Type-A1 plastic bag
塑料袋



Type-A2 paper tray
纸托盘




Inner box
内盒

| Type<br>类型 | Qty/Plastic Bag(PCS)<br>每塑料袋数量 | Qty/Inner Box(PCS)<br>每内盒数量 | Qty/Carton (PCS)<br>每外箱数量 | Carton Size<br>L×W×H(±5%) | Gross Wt.±2Kgs | Packing Type<br>包装类型 |
|---|---|---|---|---|---|---|
| **PRW Series** | | | | | | |
| **PRW 1W** | 10 | 500 | 3000 | 485×190×200 | 10.00 | Type A1 |
| **PRW 2W** | 10 | 400 | 2400 | 485×190×200 | 8.00 | Type A1 |
| **PRW 3W** | 10 | 500 | 3000 | 520×220×250 | 12.20 | Type A1 |
| **PRW 5W** | 10 | 400 | 2400 | 520×220×250 | 13.72 | Type A1 |
| **PRW 7W** | 10 | 300 | 1800 | 520×220×250 | 15.46 | Type A1 |
| **PRW 10W** | 10 | 250 | 1500 | 520×220×250 | 18.39 | Type A1 |
| **PRW 15W** | 10 | 70 | 420 | 510×200×250 | 8.20 | Type A1 |
| **PRW 20W** | 10 | 60 | 360 | 510×200×250 | 10.75 | Type A1 |
| **PRW 25W** | 10 | 60 | 360 | 510×200×250 | 11.22 | Type A1 |
| **PRWA Series** | | | | | | |
| **PRWA 5W** | 10 | 400 | 2400 | 520×220×250 | 15.00 | Type A1 |
| **PRWA 7W** | 10 | 240 | 1440 | 520×220×250 | 14.20 | Type A1 |
| **PRWA 10W** | 10 | 220 | 1320 | 520×220×250 | 16.30 | Type A1 |
| **PRWC Series** | | | | | | |
| **PRWC 3W** | 10 | 400 | 2400 | 485×190×200 | 7.30 | Type A1 |
| **PRWC 5W** | 10 | 400 | 2400 | 485×190×200 | 9.40 | Type A1 |
| **PRWC 7W** | 10 | 400 | 2400 | 520×220×250 | 14.00 | Type A1 |
| **PRWC-1 Series** | | | | | | |
| **PRC1 4W** | 50 | 500 | 3000 | 485×190×200 | 9.05 | Type A2 |
| **PRC1 5W** | 10 | 600 | 3600 | 485×190×200 | 13.45 | Type A1 |
| **PRC1 6W** | 40 | 400 | 2400 | 485×190×200 | 13.71 | Type A2 |
| **PRT Series** | | | | | | |
| **PRT 10W** | 10 | 200 | 1200 | 520×220×250 | 19.50 | Type A1 |
| **PRT 15W** | 5 | 150 | 900 | 520×220×250 | 22.00 | Type A1 |
| **PRT 20W** | 5 | 95 | 570 | 520×220×250 | 18.50 | Type A1 |
| **PRT 30W** | 5 | 45 | 270 | 520×220×250 | 21.40 | Type A1 |
| **PRT 40W** | 5 | 25 | 150 | 520×220×250 | 14.20 | Type A1 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
**注:** 以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

## Type A Packing 包装类型 A (mm)




| Dimension of Plastic Case (mm) | | | |
|---|---|---|---|
| Type | A | B | C |
| Type - B1 | 260 | 105 | 260 |
| Type - B2 | 300 | 100 | 210 |
| Type - B3 | 300 | 100 | 210 |




Inner Box of Plastic Case

| Type 类型 | Qty/Plastic Bag(PCS) 每塑料袋数量 | Qty/Inner Box(PCS) 每内盒数量 | Qty/Carton (PCS) 每外箱数量 | Carton Size L×W×H(±5%) | Gross Wt.±2Kgs | Packing Type 包装类型 |
|---|---|---|---|---|---|---|
| **PRM/FTR Series** | | | | | | |
| **PRM2W** | 10 (in Bag) | 700 | 4200 | 520×220×250 | 18.50 | Type A1 |
| **PRM3W** | 100 | 500 | 2000 | 535×270×220 | 14.20 | Type B1 |
| **PRM5W** | 100 | 500 | 2000 | 535×270×220 | 14.20 | Type B1 |
| **PRM7W** | 75 | 375 | 1500 | 435×305×215 | 17.42 | Type B2 |
| **PRM 10W** | 60 | 300 | 1200 | 435×305×215 | 18.12 | Type B3 |
| **PFA 10W** | 10 (in Bag) | 150 | 900 | 520×220×250 | 14.74 | Type A1 |
| **PRMA Series** | | | | | | |
| **PRMA 5W** | 100 | 500 | 2000 | 535×270×220 | 14.00 | Type B1 |
| **PRMA 10W** | 10 (in Bag) | 150 | 900 | 485×190×200 | 14.50 | Type A1 |
| **PFAS & PFAT Series** | | | | | | |
| **PFAS 2W** | 20 (in Bag) | 600 | 3600 | 485×190×200 | 7.10 | Type A1 |
| **PFAS 5W** | 20 (in Bag) | 500 | 3000 | 485×190×200 | 9.72 | Type A1 |
| **PFAS 7W** | 160 | 900 | 3600 | 435×305×215 | 16.20 | Type B1 |
| **PFAS 10W** | 10 (in Bag) | 500 | 3000 | 520×220×250 | 22.40 | Type A1 |
| **PFAT 5W** | 10 (in Bag) | 300 | 1800 | 485×190×200 | 13.20 | Type A1 |
| **PFAT 7W** | 10 (in Bag) | 250 | 1500 | 485×190×200 | 11.50 | Type A1 |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
**注:** 以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

# Standard Packing of Cement Resistors - (3)
## 水泥电阻器包装规范 - (3)

### Type B Packing-Plastic Case 包装类型 B - 塑料盒 (mm)

| Type 类型 | Qty/Plastic Bag(PCS) 每塑料袋数量 | Qty/Inner Box(PCS) 每内盒数量 | Qty/Carton (PCS) 每外箱数量 | Carton Size L×W×H(±5%) | Gross Wt.±2Kgs | Packing Type 包装类型 |
|---|---|---|---|---|---|---|
| **PRM/FTR Series** | | | | | | |
| **PRM2W / PF2** | 10(in Bag) | 700 | 4200 | 520×220×250 | 18.50 | Type A1 |
| **PRM3W / PF3** | 100 | 500 | 2000 | 535×270×220 | 14.20 | Type B1 |
| **PRM5W / PF5** | 100 | 500 | 2000 | 535×270×220 | 14.20 | Type B1 |
| **PRM7W / PF7** | 75 | 375 | 1500 | 435×305×215 | 17.42 | Type B2 |
| **PRM 10W** | 60 | 300 | 1200 | 435×305×215 | 18.12 | Type B3 |
| **PFA 10W** | 10(in Bag) | 150 | 900 | 520×220×250 | 14.74 | Type A1 |
| **PRMA Series** | | | | | | |
| **PRMA 5W** | 100 | 500 | 2000 | 535×270×220 | 14.00 | Type B1 |
| **PRMA 10W** | 10(in Bag) | 150 | 900 | 485×190×200 | 14.50 | Type A1 |
| **PFAS & PFAT Series** | | | | | | |
| **PFAS 2W** | 20(in Bag) | 600 | 3600 | 485×190×200 | 7.10 | Type A1 |
| **PFAS 5W** | 20(in Bag) | 500 | 3000 | 485×190×200 | 9.72 | Type A1 |
| **PFAS 7W** | 160 | 900 | 3600 | 435×305×215 | 16.20 | Type B1 |
| **PFAS 10W** | 10(in Bag) | 500 | 3000 | 520×220×250 | 22.40 | Type A1 |
| **PFAT 5W** | 10(in Bag) | 300 | 1800 | 485×190×200 | 13.20 | Type A1 |
| **PFAT 7W** | 10(in Bag) | 250 | 1500 | 485×190×200 | 11.50 | Type A1 |
| **PRU Series** | | | | | | |
| **PRU 10W** | 100 | 100 | 1000 | 560×305×310 | 12.50 | Type D |
| **PRU 15W** | 80 | 80 | 800 | 560×305×310 | 17.33 | Type D |
| **PRU 20W** | 60 | 60 | 600 | 560×305×310 | 17.85 | Type D |
| **PRU 30W** | 20 | 40 | 160 | 435×305×215 | 16.37 | Type D |
| **PRU 40W** | 20 | 20 | 160 | 435×305×215 | 16.37 | Type D |

**Note:** The above is recommended packaging, the actual packing method is in accordance with the order.
**注:** 以上为推荐包装方式，实际以工厂依订单情形的包装方式为准

| 测试项目 | 引用标准 | 测试方法 |
|---|---|---|
| **Temperature coefficient**<br>**温度系数** | **GB/T 5729 4.8**<br>**JIS-C-5201 4.8**<br>**IEC 60115-1 4.8** | Natural resistance change per temperature degree centigrade 实际阻值随温度变化的变化率：<br>$\frac{R_2-R_1}{R_1(t_2-t_1)}$ X $10^6$ (PPM / ℃)<br>$R_1$: Resistance value at room temperature 室温下的阻值 ($t_1$);<br>$R_2$: Resistance at test temperature (-55℃ or +155℃) 在 -55℃ 或者 +155℃ 温度下的阻值 ;<br>$t_1$: +25℃ or specified room temperature +25℃ 或者特殊要求的室内温度 ;<br>$t_2$: -55℃ or +155℃ test temperature -55℃ 或者 +155℃ 的测试温度。 |
| **Short-time overload**<br>**短时间过负荷** | **GB/T 5729 4.13**<br>**JIS-C-5201.4.13**<br>**IEC 60115-1 4.13** | Permanent resistance change after the application of a potential of 2.5 times RCWV or Max.Overload Votage whichever less for 5 seconds.<br>加 2.5 倍额定工作电压或最大过负荷电压 ( 取其低者 )，持续 5 秒钟，测阻值变化。 |
| **Insulation resistance**<br>**绝缘阻值** | **GB/T 5729 4.6**<br>**JIS-C-5201 4.6**<br>**IEC 60115-1 4.6** | 1. Chip Resistor：the measuring voltage shall be, measured with a direct voltage of (100±15)V or a voltage equal to the dielectric withstanding voltage, and appiy for 1 min.<br>2. TH Resistor: the measuring voltage shall be equal to the dielectric withstanding voltage for resistor with an isolation voltage ＜ 500V or (500±50)V DC, for resistors with an isolation voltage≥500V.<br>1. 贴片电阻：绝缘耐压＜ 100V，测试电压取绝缘耐压的电压；绝缘耐压 ≥100V，测试电压为 100±15VDC，1 分钟后量测阻值。<br>2. 插件电阻：绝缘耐压 ＜ 500V，测试电压取绝缘耐压的电压；绝缘耐压 ≥500V . 测试电压为 500±50VDC，1 分钟后量测阻值。 |
| **Dielectric Withstanding Voltage**<br>**绝缘耐压** | **GB/T 5729 4.7**<br>**JIS-C-5201 4.7**<br>**IEC 60115-1 4.7** | Resistor shall be clamped in the trough of 90° metallicV -block and shall be tested at AC potential respectively specified in the given list of each product type for 60-70 seconds.For Cement Fixed Resistors,the testing voltage is 1000V.<br>电阻固定在 90° 的 V 型槽中，根据不同产品规定交流电压，持续 60~70 秒，水泥型电阻电压设定为 1000V。 |
| **Pulse overload**<br>**脉冲过负荷** | **IEC 60115-1 4.39** | Rsistance change after 10000 cycles(1 second"ON",25 seconds"OFF") at 4 times of RCWV or Max.Overload whichever less.<br>10000 次循环后变化 (1 秒 " 通 "、25 秒断 )4 倍工作电压或最大工作电压 ( 取其最低者 )。<br>**Remark:** DIP resistor using 4 times of RCWV, Chip resistor using 2.5 times of RCWV **注：**传统电阻 :4×Ur, 晶片电阻 : 2.5×Ur |
| **Terminal strength**<br>**端子强度** | **GB/T 5729 4.16**<br>**JIS-C-5201 4.16**<br>**IEC 60115-1 4.16** | Direct Load: Resistance at a 2.5kg direct load for 10 seconds in the direction of the longitudinal axis of the terminal leads.<br>Twist Test: Terminal leads shall be bent through 90° at a point of about 6mm from the body of the resisitor and shall be rotated through 360° about the original axis of the bent terminal in alternating direction for a total of 3 rotations.<br>直接负荷：在电阻引线方向直接加 2.5 公斤力 10 秒。扭曲测试：两端导线折弯 90 度在熔点 6mm 处交替旋转 360 度 3 次。 |
| **Terminal strength**<br>**端子强度** | **GB/T 5729 4.16**<br>**JIS-C-5201 4.16**<br>**IEC 60115-1 4.16** | (Applicable for Resister Network 适用网络电阻)<br>Tensile：1KG,30 seconds /Bending:500g ,2 times 张力：1KG，30 秒 / 弯曲：500g，2 次。 |
| **Terminal bending**<br>**端子弯曲** | **GB/T 5729 4.33**<br>**JIS-C-5201 4.33**<br>**IEC 60115-1 4.33** | (Applicable for CHIP Resisters 适用晶片电阻)<br>Twist of Test Board:Y/X=3/90mm 60 seconds. 测试板弯曲：Y/X=3/90mm 60 秒。 |
| **Soldering heat**<br>**耐焊接热** | **GB/T 5729 4.18**<br>**JIS-C-5201 4.18**<br>**IEC 60115-1 4.18** | (Applicable for CHIP Resisters 适用晶片电阻)<br>Dip the resister into a temperature of 260±5℃ and hold it for a 10±1 seconds.<br>将电阻浸入到 260±5℃ 的锡炉中并保持 10 秒时间 |
| **Soldering heat**<br>**耐焊接热** | **GB/T 5729 4.18**<br>**JIS-C-5201 4.18**<br>**IEC 60115-1 4.18** | （Applicable forTH Resisters 适用插件电阻）<br>Permanent resister change when leads immersed to a point 2.0~2.5mm from the body in 260±5℃ solder 10±1 seconds .<br>锡炉温度 260±5℃，浸入深度：离本体导线根部约 2.0~2.5mm，处浸入时间 10±1 秒。 |
| **Solderability**<br>**可焊性** | **GB/T 5729 4.17**<br>**JIS-C-5201 4.17**<br>**IEC 60115-1 4.17** | The area covered with a new, smooth, clean, shiny and continuous surface free from concentrated pinholes. Temperature of solder: 245±3℃; Dwell time in solder: 2~3 seconds.<br>表面光滑、清洁、均匀、有光泽，锡炉温度：245±3℃；浸入时间：2~3 秒。 |
| **Resistance to solvent**<br>**耐溶剂** | **GB/T 5729 4.29**<br>**JIS-C-5201 4.29**<br>**IEC 60115-1 4.29** | Specimens shall be immersed in a bath of IPA completely for a 5±0.5 minutes using ultrasonic test equipment.<br>电阻浸入异丙醇超声波清洗 5±0.5 分钟。 |
| **Rapid change of temperature**<br>**温度快速变化** | **GB/T 5729 4.19**<br>**JIS-C-5201 4.19**<br>**IEC 60115-1 4.19** | 30 min at -55 ℃ and 30 min at 155℃; 100 cycles<br>-55 ℃ 温度放置 30min, 155 ℃ 温度放置 30min, 100 个循环； |
| **High Temperature Exposure**<br>**高温暴露** | **MIL-STD-202 108A** | Exposed to a temperature of 155±2℃ for 1000H.<br>在 155±2℃ 的环境下放置 1000H。 |
| **Low Temperature Storage**<br>**低温存放** | **IEC 60068-2-1 (Aa)** | Exposed to a temperature of -55±3℃ for 2H.<br>在 -55±3℃ 的环境下放置 2H。 |
| **Leaching**<br>**金属融出** | **J-STD-002 Test D** | Samples completely immersed for 30 sec in solder bath at 260℃, no visible damage.<br>样品浸入 260℃ 的焊锡炉 30S，无明显的损伤。 |
| **Load life in humidity**<br>**湿度寿命** | **GB/T 5729 4.24**<br>**JIS-C-5201 4.24**<br>**IEC 60115-1 4.24** | Resistance change after 1000 hours (1.5hours"ON", 0.5hours"OFF") at RCWV or Max.Working Voltage whichever less in a humidity test chamber controlled at 40±2℃ and 90~95% RH.<br>持续时间：1000h (1.5h "通"，0.5h "断")；试验温度：40±2℃；相对湿度： 90~95% RH；试验电压：额定工作电压或最大工作电压 ( 取其低者 )。 |
| **Load life**<br>**负载寿命** | **GB/T 5729 4.25.1**<br>**JIS-C-5201 4.25.1**<br>**IEC 60115-1 4.25.1** | Permanent Resistance change after 1000 hours operating at RCWV or Max.Working Voltage whichever less with duty cycle of 1.5 hours "ON", 0.5 hour "OFF" at 70±2℃ ambient.<br>持续时间：1000h (1.5h "通"，0.5h "断")；试验温度： 70±2℃；试验电压：额定工作电压或最大工作电压 ( 取其低者 )。 |
| **Accidental overload**<br>**意外过载** | **GB/T 5729 4.26**<br>**JIS-C-5201 4.26**<br>**IEC 60115-1 4.26** | Resistors shall resist flaming or arcing when overload up to 5,10,16,25,40,63,100 times power or 4times Max.Working Voltage , whichever less.<br>施加 5,10,16,25,40,63 和 100 倍额定功耗的过负荷，但所加的电压不超过 4 倍的最大工作电压，测试其阻燃性。 |

** *RCWV* = Rated Continuous Working Voltage 额定持续工作电压 = $\sqrt{\text{Rated Power} \times \text{Resistance Value}}$ 额定功率 × 阻值 the calculated value or the Max. Working Voltage whichever less. 计算值或该产品最大工作电压取其低者

# Standard Nominal Resistance Values
## 标准阻值



The below chart shows the nominal resistance value for each series. The values in the chart have been in this order using the approximate values that are based on the common ratios given in the following table:

下表列出每种系列的标准阻值，表中的阻值是按照通用倍率得出的接近阻值。

| Series 系 列 | Common Ratio 通用倍率 | Remarks 备注 |
|---|---|---|
| **E-6** | $\sqrt[6]{10}$ (1.46) | Rounded off to a 2-digit figure (2 位有效数字 ) |
| **E-12** | $\sqrt[12]{10}$ (1.21) | Rounded off to a 2-digit figure (2 位有效数字 ) |
| **E-24** | $\sqrt[24]{10}$ (1.10) | Rounded off to a 2-digit figure (2 位有效数字 ) |
| **E-96** | $\sqrt[96]{10}$ (1.02) | Rounded off to a 3-digit figure (3 位有效数字 ) |

| E-6 | E-12 | E-24 | E-96 |
|---|---|---|---|
| 1.0 | 1.0 | 1.0 | 1.00 |
| | | | 1.02 |
| | | | 1.05 |
| | | | 1.07 |
| | | 1.1 | 1.10 |
| | | | 1.13 |
| | | | 1.15 |
| | | | 1.18 |
| | 1.2 | 1.2 | 1.21 |
| | | | 1.24 |
| | | | 1.27 |
| | | | 1.30 |
| | | 1.3 | 1.33 |
| | | | 1.37 |
| | | | 1.40 |
| | | | 1.43 |
| 1.5 | 1.5 | 1.5 | 1.47 |
| | | | 1.50 |
| | | | 1.54 |
| | | | 1.58 |
| | | 1.6 | 1.62 |
| | | | 1.65 |
| | | | 1.69 |
| | | | 1.74 |
| | 1.8 | 1.8 | 1.78 |
| | | | 1.82 |
| | | | 1.87 |
| | | | 1.91 |
| | | 2.0 | 1.96 |
| | | | 2.00 |
| | | | 2.05 |
| | | | 2.10 |

| E-6 | E-12 | E-24 | E-96 |
|---|---|---|---|
| 2.2 | 2.2 | 2.2 | 2.15 |
| | | | 2.21 |
| | | | 2.26 |
| | | | 2.32 |
| | | 2.4 | 2.37 |
| | | | 2.43 |
| | | | 2.49 |
| | | | 2.55 |
| | 2.7 | 2.7 | 2.61 |
| | | | 2.67 |
| | | | 2.74 |
| | | | 2.80 |
| | | 3.0 | 2.87 |
| | | | 2.94 |
| | | | 3.01 |
| | | | 3.09 |
| 3.3 | 3.3 | 3.3 | 3.16 |
| | | | 3.24 |
| | | | 3.32 |
| | | | 3.40 |
| | | 3.6 | 3.48 |
| | | | 3.57 |
| | | | 3.65 |
| | | | 3.74 |
| | 3.9 | 3.9 | 3.83 |
| | | | 3.92 |
| | | | 4.02 |
| | | | 4.12 |
| | | 4.3 | 4.22 |
| | | | 4.32 |
| | | | 4.42 |
| | | | 4.53 |

| E-6 | E-12 | E-24 | E-96 |
|---|---|---|---|
| 4.7 | 4.7 | 4.7 | 4.64 |
| | | | 4.75 |
| | | | 4.87 |
| | | | 4.99 |
| | | 5.1 | 5.11 |
| | | | 5.23 |
| | | | 5.36 |
| | | | 5.49 |
| | 5.6 | 5.6 | 5.62 |
| | | | 5.76 |
| | | | 5.90 |
| | | | 6.04 |
| | | 6.2 | 6.19 |
| | | | 6.34 |
| | | | 6.49 |
| | | | 6.65 |
| 6.8 | 6.8 | 6.8 | 6.81 |
| | | | 6.98 |
| | | | 7.15 |
| | | | 7.32 |
| | | 7.5 | 7.50 |
| | | | 7.68 |
| | | | 7.87 |
| | | | 8.06 |
| | 8.2 | 8.2 | 8.25 |
| | | | 8.45 |
| | | | 8.66 |
| | | | 8.87 |
| | | 9.1 | 9.09 |
| | | | 9.31 |
| | | | 9.53 |
| | | | 9.76 |

**E-24 series standard resistance value & the codes to be used in the part No. system 2%, 5% & 10% tolerance (4 digits, start with "0"):**
**E-24 系列标准阻值和料号系统使用代码 ( 4 位 , 以 0 为首位 , 2%、5%、10% 公差 ):**

| Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1.0Ω | **010J** | 10Ω | **0100** | 100Ω | **0101** | 1.0KΩ | **0102** | 10KΩ | **0103** | 100KΩ | **0104** | 1.0MΩ | **0105** |
| 1.1Ω | **011J** | 11Ω | **0110** | 110Ω | **0111** | 1.1KΩ | **0112** | 11KΩ | **0113** | 110KΩ | **0114** | 1.1MΩ | **0115** |
| 1.2Ω | **012J** | 12Ω | **0120** | 120Ω | **0121** | 1.2KΩ | **0122** | 12KΩ | **0123** | 120KΩ | **0124** | 1.2MΩ | **0125** |
| 1.3Ω | **013J** | 13Ω | **0130** | 130Ω | **0131** | 1.3KΩ | **0132** | 13KΩ | **0133** | 130KΩ | **0134** | 1.3MΩ | **0135** |
| 1.5Ω | **015J** | 15Ω | **0150** | 150Ω | **0151** | 1.5KΩ | **0152** | 15KΩ | **0153** | 150KΩ | **0154** | 1.5MΩ | **0155** |
| 1.6Ω | **016J** | 16Ω | **0160** | 160Ω | **0161** | 1.6KΩ | **0162** | 16KΩ | **0163** | 160KΩ | **0164** | 1.6MΩ | **0165** |
| 1.8Ω | **018J** | 18Ω | **0180** | 180Ω | **0181** | 1.8KΩ | **0182** | 18KΩ | **0183** | 180KΩ | **0184** | 1.8MΩ | **0185** |
| 2.0Ω | **020J** | 20Ω | **0200** | 200Ω | **0201** | 2.0KΩ | **0202** | 20KΩ | **0203** | 200KΩ | **0204** | 2.0MΩ | **0205** |
| 2.2Ω | **022J** | 22Ω | **0220** | 220Ω | **0221** | 2.2KΩ | **0222** | 22KΩ | **0223** | 220KΩ | **0224** | 2.2MΩ | **0225** |
| 2.4Ω | **024J** | 24Ω | **0240** | 240Ω | **0241** | 2.4KΩ | **0242** | 24KΩ | **0243** | 240KΩ | **0244** | 2.4MΩ | **0245** |
| 2.7Ω | **027J** | 27Ω | **0270** | 270Ω | **0271** | 2.7KΩ | **0272** | 27KΩ | **0273** | 270KΩ | **0274** | 2.7MΩ | **0275** |
| 3.0Ω | **030J** | 30Ω | **0300** | 300Ω | **0301** | 3.0KΩ | **0302** | 30KΩ | **0303** | 300KΩ | **0304** | 3.0MΩ | **0305** |
| 3.3Ω | **033J** | 33Ω | **0330** | 330Ω | **0331** | 3.3KΩ | **0332** | 33KΩ | **0333** | 330KΩ | **0334** | 3.3MΩ | **0335** |
| 3.6Ω | **036J** | 36Ω | **0360** | 360Ω | **0361** | 3.6KΩ | **0362** | 36KΩ | **0363** | 360KΩ | **0364** | 3.6MΩ | **0365** |
| 3.9Ω | **039J** | 39Ω | **0390** | 390Ω | **0391** | 3.9KΩ | **0392** | 39KΩ | **0393** | 390KΩ | **0394** | 3.9MΩ | **0395** |
| 4.3Ω | **043J** | 43Ω | **0430** | 430Ω | **0431** | 4.3KΩ | **0432** | 43KΩ | **0433** | 430KΩ | **0434** | 4.3MΩ | **0435** |
| 4.7Ω | **047J** | 47Ω | **0470** | 470Ω | **0471** | 4.7KΩ | **0472** | 47KΩ | **0473** | 470KΩ | **0474** | 4.7MΩ | **0475** |
| 5.1Ω | **051J** | 51Ω | **0510** | 510Ω | **0511** | 5.1KΩ | **0512** | 51KΩ | **0513** | 510KΩ | **0514** | 5.1MΩ | **0515** |
| 5.6Ω | **056J** | 56Ω | **0560** | 560Ω | **0561** | 5.6KΩ | **0562** | 56KΩ | **0563** | 560KΩ | **0564** | 5.6MΩ | **0565** |
| 6.2Ω | **062J** | 62Ω | **0620** | 620Ω | **0621** | 6.2KΩ | **0622** | 62KΩ | **0623** | 620KΩ | **0624** | 6.2MΩ | **0625** |
| 6.8Ω | **068J** | 68Ω | **0680** | 680Ω | **0681** | 6.8KΩ | **0682** | 68KΩ | **0683** | 680KΩ | **0684** | 6.8MΩ | **0685** |
| 7.5Ω | **075J** | 75Ω | **0750** | 750Ω | **0751** | 7.5KΩ | **0752** | 75KΩ | **0753** | 750KΩ | **0754** | 7.5MΩ | **0755** |
| 8.2Ω | **082J** | 82Ω | **0820** | 820Ω | **0821** | 8.2KΩ | **0822** | 82KΩ | **0823** | 820KΩ | **0824** | 8.2MΩ | **0825** |
| 9.1Ω | **091J** | 91Ω | **0910** | 910Ω | **0911** | 9.1KΩ | **0912** | 91KΩ | **0913** | 910KΩ | **0914** | 9.1MΩ | **0915** |
| | | | | | | | | | | | | 10MΩ | **0106** |

**E-96 series standard resistance value & the codes to be used in the part No. system not over 1% tolerance (4 digits):**
**E-96 系列标准阻值和料号系统使用代码 (4 位 , 0.1%、0.25%、0.5%、1% 公差 ):**

| Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 10.0Ω | **I00J** | 17.8Ω | **178J** | 31.6Ω | **316J** | 56.2Ω | **562J** | 100Ω | **1000** | 178Ω | **1780** | 316Ω | **3160** | 562Ω | **5620** |
| 10.2Ω | **102J** | 18.2Ω | **182J** | 32.4Ω | **324J** | 57.6Ω | **576J** | 102Ω | **1020** | 182Ω | **1820** | 324Ω | **3240** | 576Ω | **5760** |
| 10.5Ω | **105J** | 18.7Ω | **187J** | 33.2Ω | **332J** | 59.0Ω | **590J** | 105Ω | **1050** | 187Ω | **1870** | 332Ω | **3320** | 590Ω | **5900** |
| 10.7Ω | **107J** | 19.1Ω | **191J** | 34.0Ω | **340J** | 60.4Ω | **604J** | 107Ω | **1070** | 191Ω | **1910** | 340Ω | **3400** | 604Ω | **6040** |
| 11.0Ω | **110J** | 19.6Ω | **196J** | 34.8Ω | **348J** | 61.9Ω | **619J** | 110Ω | **1100** | 196Ω | **1960** | 348Ω | **3480** | 619Ω | **6190** |
| 11.3Ω | **113J** | 20.0Ω | **200J** | 35.7Ω | **357J** | 63.4Ω | **634J** | 113Ω | **1130** | 200Ω | **2000** | 357Ω | **3570** | 634Ω | **6340** |
| 11.5Ω | **115J** | 20.5Ω | **205J** | 36.5Ω | **365J** | 64.9Ω | **649J** | 115Ω | **1150** | 205Ω | **2050** | 365Ω | **3650** | 649Ω | **6490** |
| 11.8Ω | **118J** | 21.0Ω | **210J** | 37.4Ω | **374J** | 66.5Ω | **665J** | 118Ω | **1180** | 210Ω | **2100** | 374Ω | **3740** | 665Ω | **6650** |
| 12.1Ω | **121J** | 21.5Ω | **215J** | 38.3Ω | **383J** | 68.1Ω | **681J** | 121Ω | **1210** | 215Ω | **2150** | 383Ω | **3830** | 681Ω | **6810** |
| 12.4Ω | **124J** | 22.1Ω | **221J** | 39.2Ω | **392J** | 69.8Ω | **698J** | 124Ω | **1240** | 221Ω | **2210** | 392Ω | **3920** | 698Ω | **6980** |
| 12.7Ω | **127J** | 22.6Ω | **226J** | 40.2Ω | **402J** | 71.5Ω | **715J** | 127Ω | **1270** | 226Ω | **2260** | 402Ω | **4020** | 715Ω | **7150** |
| 13.0Ω | **130J** | 23.2Ω | **232J** | 41.2Ω | **412J** | 73.2Ω | **732J** | 130Ω | **1300** | 232Ω | **2320** | 412Ω | **4120** | 732Ω | **7320** |
| 13.3Ω | **133J** | 23.7Ω | **237J** | 42.2Ω | **422J** | 75.0Ω | **750J** | 133Ω | **1330** | 237Ω | **2370** | 422Ω | **4220** | 750Ω | **7500** |
| 13.7Ω | **137J** | 24.3Ω | **243J** | 43.2Ω | **432J** | 76.8Ω | **768J** | 137Ω | **1370** | 243Ω | **2430** | 432Ω | **4320** | 768Ω | **7680** |
| 14.0Ω | **140J** | 24.9Ω | **249J** | 44.2Ω | **442J** | 78.7Ω | **787J** | 140Ω | **1400** | 249Ω | **2490** | 442Ω | **4420** | 787Ω | **7870** |
| 14.3Ω | **143J** | 25.5Ω | **255J** | 45.3Ω | **453J** | 80.6Ω | **806J** | 143Ω | **1430** | 255Ω | **2550** | 453Ω | **4530** | 806Ω | **8060** |
| 14.7Ω | **147J** | 26.1Ω | **261J** | 46.4Ω | **464J** | 82.5Ω | **825J** | 147Ω | **1470** | 261Ω | **2610** | 464Ω | **4640** | 825Ω | **8250** |
| 15.0Ω | **150J** | 26.7Ω | **267J** | 47.5Ω | **475J** | 84.5Ω | **845J** | 150Ω | **1500** | 267Ω | **2670** | 475Ω | **4750** | 845Ω | **8450** |
| 15.4Ω | **154J** | 27.4Ω | **274J** | 48.7Ω | **487J** | 86.6Ω | **866J** | 154Ω | **1540** | 274Ω | **2740** | 487Ω | **4870** | 866Ω | **8660** |
| 15.8Ω | **158J** | 28.0Ω | **280J** | 49.9Ω | **499J** | 88.7Ω | **887J** | 158Ω | **1580** | 280Ω | **2800** | 499Ω | **4990** | 887Ω | **8870** |
| 16.2Ω | **162J** | 28.7Ω | **287J** | 51.1Ω | **511J** | 90.9Ω | **909J** | 162Ω | **1620** | 287Ω | **2870** | 511Ω | **5110** | 909Ω | **9090** |
| 16.5Ω | **165J** | 29.4Ω | **294J** | 52.3Ω | **523J** | 93.1Ω | **931J** | 165Ω | **1650** | 294Ω | **2940** | 523Ω | **5230** | 931Ω | **9310** |
| 16.9Ω | **169J** | 30.1Ω | **301J** | 53.6Ω | **536J** | 95.3Ω | **953J** | 169Ω | **1690** | 301Ω | **3010** | 536Ω | **5360** | 953Ω | **9530** |
| 17.4Ω | **174J** | 30.9Ω | **309J** | 54.9Ω | **549J** | 97.6Ω | **976J** | 174Ω | **1740** | 309Ω | **3090** | 549Ω | **5490** | 976Ω | **9760** |

# Standard Nominal Resistance Values

## 标准阻值



| Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 | Value 阻值 | Code 代码 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1.00K | **1001** | 2.37K | **2371** | 5.62K | **5621** | 13.3K | **1332** | 31.6K | **3162** | 75.0K | **7502** | 178K | **1783** | 422K | **4223** |
| 1.02K | **1021** | 2.43K | **2431** | 5.76K | **5761** | 13.7K | **1372** | 32.4K | **3242** | 76.8K | **7682** | 182K | **1823** | 432K | **4323** |
| 1.05K | **1051** | 2.49K | **2491** | 5.90K | **5901** | 14.0K | **1402** | 33.2K | **3322** | 78.7K | **7872** | 187K | **1873** | 442K | **4423** |
| 1.07K | **1071** | 2.55K | **2551** | 6.04K | **6041** | 14.3K | **1432** | 34.0K | **3402** | 80.6K | **8062** | 191K | **1913** | 453K | **4533** |
| 1.10K | **1101** | 2.61K | **2611** | 6.19K | **6191** | 14.7K | **1472** | 34.8K | **3482** | 82.5K | **8252** | 196K | **1963** | 464K | **4643** |
| 1.13K | **1131** | 2.67K | **2671** | 6.34K | **6341** | 15.0K | **1502** | 35.7K | **3572** | 84.5K | **8452** | 200K | **2003** | 475K | **4753** |
| 1.15K | **1151** | 2.74K | **2741** | 6.49K | **6491** | 15.4K | **1542** | 36.5K | **3652** | 86.6K | **8662** | 205K | **2053** | 487K | **4873** |
| 1.18K | **1181** | 2.80K | **2801** | 6.65K | **6651** | 15.8K | **1582** | 37.4K | **3742** | 88.7K | **8872** | 210K | **2103** | 499K | **4993** |
| 1.21K | **1211** | 2.87K | **2871** | 6.81K | **6811** | 16.2K | **1622** | 38.3K | **3832** | 90.9K | **9092** | 215K | **2153** | 511K | **5113** |
| 1.24K | **1241** | 2.94K | **2941** | 6.98K | **6981** | 16.5K | **1652** | 39.2K | **3922** | 93.1K | **9312** | 221K | **2213** | 523K | **5233** |
| 1.27K | **1271** | 3.01K | **3011** | 7.15K | **7151** | 16.9K | **1692** | 40.2K | **4022** | 95.3K | **9532** | 226K | **2263** | 536K | **5363** |
| 1.30K | **1301** | 3.09K | **3091** | 7.32K | **7321** | 17.4K | **1742** | 41.2K | **4122** | 97.6K | **9762** | 232K | **2323** | 549K | **5493** |
| 1.33K | **1331** | 3.16K | **3161** | 7.50K | **7501** | 17.8K | **1782** | 42.2K | **4222** | l00K | **1003** | 237K | **2373** | 562K | **5623** |
| 1.37K | **1371** | 3.24K | **3241** | 7.68K | **7681** | 18.2K | **1822** | 43.2K | **4322** | 102K | **1023** | 243K | **2433** | 576K | **5763** |
| 1.40K | **1401** | 3.32K | **3321** | 7.87K | **7871** | 18.7K | **1872** | 44.2K | **4422** | 105K | **1053** | 249K | **2493** | 590K | **5903** |
| 1.43K | **1431** | 3.40K | **3401** | 8.06K | **8061** | 19.1K | **1912** | 45.3K | **4532** | 107K | **1073** | 255K | **2553** | 604K | **6043** |
| 1.47K | **1471** | 3.48K | **3481** | 8.25K | **8251** | 19.6K | **1962** | 46.4K | **4642** | 110K | **1103** | 261K | **2613** | 619K | **6193** |
| 1.50K | **1501** | 3.57K | **3571** | 8.45K | **8451** | 20.0K | **2002** | 47.5K | **4752** | 113K | **1133** | 267K | **2673** | 634K | **6343** |
| 1.54K | **1541** | 3.65K | **3651** | 8.66K | **8661** | 20.5K | **2052** | 48.7K | **4872** | 115K | **1153** | 274K | **2743** | 649K | **6493** |
| 1.58K | **1581** | 3.74K | **3741** | 8.87K | **8871** | 21.0K | **2102** | 49.9K | **4992** | 118K | **1183** | 280K | **2803** | 665K | **6653** |
| 1.62K | **1621** | 3.83K | **3831** | 9.09K | **9091** | 21.5K | **2152** | 51.1K | **5112** | 121K | **1213** | 287K | **2873** | 681K | **6813** |
| 1.65K | **1651** | 3.92K | **3921** | 9.31K | **9311** | 22.1K | **2212** | 52.3K | **5232** | 124K | **1243** | 294K | **2943** | 698K | **6983** |
| 1.69K | **1691** | 4.02K | **4021** | 9.53K | **9531** | 22.6K | **2262** | 53.6K | **5362** | 127K | **1273** | 301K | **3013** | 715K | **7153** |
| 1.74K | **1741** | 4.12K | **4121** | 9.76K | **9761** | 23.2K | **2322** | 54.9K | **5492** | 130K | **1303** | 309K | **3093** | 732K | **7323** |
| 1.78K | **1781** | 4.22K | **4221** | 10.0K | **1002** | 23.7K | **2372** | 56.2K | **5622** | 133K | **1333** | 316K | **3163** | 750K | **7503** |
| 1.82K | **1821** | 4.32K | **4321** | 10.2K | **1022** | 24.3K | **2432** | 57.6K | **5762** | 137K | **1373** | 324K | **3243** | 768K | **7683** |
| 1.87K | **1871** | 4.42K | **4421** | 10.5K | **1052** | 24.9K | **2492** | 59.0K | **5902** | 140K | **1403** | 332K | **3323** | 787K | **7873** |
| 1.91K | **1911** | 4.53K | **4531** | 10.7K | **1072** | 25.5K | **2552** | 60.4K | **6042** | 143K | **1433** | 340K | **3403** | 806K | **8063** |
| 1.96K | **1961** | 4.64K | **4641** | 11.0K | **1102** | 26.1K | **2612** | 61.9K | **6192** | 147K | **1473** | 348K | **3483** | 825K | **8253** |
| 2.00K | **2001** | 4.75K | **4751** | 11.3K | **1132** | 26.7K | **2672** | 63.4K | **6342** | 150K | **1503** | 357K | **3573** | 845K | **8453** |
| 2.05K | **2051** | 4.87K | **4871** | 11.5K | **1152** | 27.4K | **2742** | 64.9K | **6492** | 154K | **1543** | 365K | **3653** | 866K | **8663** |
| 2.10K | **2101** | 4.99K | **4991** | 11.8K | **1182** | 28.0K | **2802** | 66.5K | **6652** | 158K | **1583** | 374K | **3743** | 887K | **8873** |
| 2.15K | **2151** | 5.11K | **5111** | 12.1K | **1212** | 28.7K | **2872** | 68.1K | **6812** | 162K | **1623** | 383K | **3833** | 909K | **9093** |
| 2.21K | **2211** | 5.23K | **5231** | 12.4K | **1242** | 29.4K | **2942** | 69.8K | **6982** | 165K | **1653** | 392K | **3923** | 931K | **9313** |
| 2.26K | **2261** | 5.36K | **5361** | 12.7K | **1272** | 30.1K | **3012** | 71.5K | **7152** | 169K | **1693** | 402K | **4023** | 953K | **9533** |
| 2.32K | **2321** | 5.49K | **5491** | 13.0K | **1302** | 30.9K | **3092** | 73.2K | **7322** | 174K | **1743** | 412K | **4123** | 976K | **9763** |
| | | | | | | | | | | | | | | 1M | **1004** |

*** All values shown above are standard resistance values, other values could also be provided on a case to case basis (MOQ requested)*

*** 以上所有阻值都是标准阻值，其他阻值可以特别提供，但有相应 MOQ 之要求。*

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

The standard Part No. includes 14 digits with the following explanation ( 标准料号包括 14 位数字，注释如下 ):

1. 1st~4th digits ( 第 1 位 ~ 第 4 位 ):
   a) This is to indicate the SMD Resistor size. Example ( 表示晶片电阻的尺寸，例如 ): 1206, TC05 or HV03;
   b) For Resistor Network & Coated type, the 1st~3rd digits are to indicate the product type and the 4th digit is the special feature. Example: RNLA = Resistor Newtork Circuit A type; CFRF = Carbon Film Fixed Resistors Non-Flame type; MORI = Metal Oxide Film Fixed Resistor Non-Inductive type.
   网络电阻和涂装型电阻第 1 位到第 3 位表示产品类型，第 4 位表示特殊形态，如 : RNLA = 网络电阻 A 型 ; CFRF = 不燃性碳膜电阻器 ; MORI = 无感型金属氧化膜电阻器。
   c) For Cement Fixed Resistors, these 4 digits are to indicate the product type but if the product type has only 3 digits, the 4th digit will be "0". Example: PRW0=PRW type; PRWC=PRWC type.
   水泥型前 4 位表示产品类型，如果产品只有 3 个字母，第 4 位为 0，例：PRW0=PRW 型 ; PRWC=PRWC 型。

2. 5th~ 6th digits ( 第 5 位 ~ 第 6 位 ):
   a) This is to indicate the wattage or power rating. To distinguish the sizes and the numbers, the following codes are used, and please refer to the following chart for details: W = Normal Size; S = Small Size; U = Ultra Small Size; "1" ~ "G" to denotes "1" ~ "16" as Hexadecimal:
   表示产品标识功率，为区别不同尺寸，同时使用以下字母，如 :W = 正常尺寸 ; S = 小尺寸 ; U = 超小尺寸 ; "1" ~ "G" 代表 "1" ~ "16" 为 16 进制。

### 1/16W ~ 1/2W (<1W)

| Wattage 功率 | 1/2 | 1/3 | 1/4 | 1/5 | 1/6 | 1/7 | 1/8 | 1/9 | 1/10 | 1/11 | 1/12 | 1/13 | 1/14 | 1/15 | 1/16 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Normal Size 正常尺寸 | W2 | W3 | W4 | W5 | W6 | W7 | W8 | W9 | WA | WB | WC | WD | WE | WF | WG |
| Small Size 小尺寸 | S2 | S3 | S4 | S5 | S6 | S7 | S8 | S9 | SA | SB | SC | SD | SE | SF | SG |
| Ultra Small Size 超小尺寸 | U2 | U3 | U4 | U5 | U6 | U7 | U8 | U9 | UA | UB | UC | UD | UE | UF | UG |

### 1W ~ 16W (≥1W)

| Wattage 功率 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Normal Size 正常尺寸 | IW | 2W | 3W | 4W | 5W | 6W | 7W | 8W | 9W | AW | BW | CW | DW | EW | FW | GW |
| Small Size 小尺寸 | 1S | 2S | 3S | 4S | 5S | 6S | 7S | 8S | 9S | AS | BS | CS | DS | ES | FS | GS |
| Ultra Small Size 超小尺寸 | 1U | 2U | 3U | 4U | 5U | 6U | 7U | 8U | 9U | AU | BU | CU | DU | EU | FU | GU |

   b) For power rating less than 1W, the 5th digit will be the letters W, S or U to represent the size required & the 6th digit will be a number or a letter code. Example: WA = 1/10W; U2 = 1/2W-SS ( 功率小于 1 瓦 , 第 5 位用 W, S 或 U 表示尺寸要求，第 6 位将是数字或字母，例 : WA = 1/10W; U2 = 1/2W-SS.).
   c) For power rating of 1W to 16W, the 5th digit will be a number or a letter code and the 6th digit will be the letters of W, S or U. Example: AW = 10W; 3S = 3W-S.
   当功率为 1 到 16 瓦 , 第 5 位将是数字或字母，第 6 位是 W, S or U. 例 : AW = 10W; 3S = 3W-S.
   d) For power rating between 20W to 99W, the 5th & 6th digits will show the whole numbers of the power rating itself. Example: 20 = 20W; 75 = 75W.
   当功率在 20 瓦 ~99 瓦之间第 5 位至第 6 位全部表示功率。例 : 20 = 20W; 75 = 75W.
   e) For power rating of 100W & over, the 5th & 6th digits will be indicated with "00" and the actual wattage being indicated at the last 3 digits (12th~14th) of the Part No.
   当大于 100 瓦时第 5 位和第 6 位表示为 "00" 实际功率表示在料号最后 3 位 (12 位 ~ 14 位 )
   f) For special power ratings, the following codes are to be used ( 特殊功率用下列数字表示 ):
      1). WH = 1/32W (10P8 Chip Network 网络电阻 )
      2). 07 = 3/4WS [Chip 2010 size ( 晶片 2010 尺寸 )]
      3). 04 = 0.4W-SS (0.4 watt Ultra Small size 超小尺寸 )
      4). 06 = 0.6W-S (0.6 watt Small size 小尺寸 )
      5). 2A = 2.5W  6). 6A = 6.5W  7). WK= 2/3W
      8). 1A =1.5W  9). 1.25W =1Q
   g) For Resistor Network, since the power rating is fixed as 1/8W for A circuit & 1/5W for B circuit, the 5th & 6th digit is to be used to denote the number of pins required. Example: 09 = 9pins; 12 = 12pins. ( 网络电阻功率固定为 1/8W 或 1/5W，故第 5 位和第 6 位用来表示所需要的 pins 数 . 例 : 09 = 9pins; 12 = 12pins.)
   h) For Jumper Wires the 5th & 6th digits will be indicated with "00" .( 跳线电阻的第 5 位、第 6 位用 "00" 来表示 )
   i) For Thin Film Chip Resistors, these 2 digits will be used to indicated the requested Temperature coefficient:
   对於薄膜晶片电阻产品 , 这两位用来表示产品的温度系数要求 :
      1). 05 = 5PPM  2). 10 = 10PPM  3). 15 = 15PPM  4). 25 = 25PPM  5). 50 = 50PPM

3. The 7th digit is to denote the Resistance Tolerance. The following letter code is to be used for indicating the standard Resisance Tolerance. As for Metal Film Fixed Resistor products, it is also to denote the standard PPM as follows ( 第 7 位表示阻值误差。下列数码用来表示标准误差，用于金属膜产品时，同时用来表示标准 PPM，如下 ):

| | | |
|---|---|---|
| **B** = ±0.1% (15PPM) | **G** = ±2% (100PPM) | **W** = ±0.05% |
| **C** = ±0.25% (25PPM) | **J** = ±5% (200PPM) | **L** = ±0.01% |
| **D** = ±0.5% (50PPM) | **K** = ±10% | |
| **F = ±1% (50PPM)** | | |

*Remark: if it is not one of the above standard "tolerance-TCR", the requirement should be clearly stated when placing order. Example: ±1% (25PPM), the 7th digit still shows "F" but separately note the requirement of "25PPM"*

*注 : 如果一个不是上述标准 " 公差 -PPM" 的要表示清楚 例 : ±1% (25PPM), 第 7 位要标示 "F" 并另注 "25PPM"*

4. The 8th to 11th digits is to denote the Resistance Value ( 第 8 位 ~ 第 11 位表示阻值 ):

a) For the standard resistance values of E-24 series in 5% & 10% tolerance, the 8th digit is "0", the 9th & 10th digits are to denote the significant figures of the resistance and the 11th digit is the number of zeros following ( 对于 E-24 系列的 5%、10% 产品，第 8 位数是 0，第 9 位数和第 10 位数表示阻值的有效数，第 11 位表示有几个 0 ).

b) For the standard resistance values of E-96 series in ≤2% tolerance, the 8th digit to the 10th digits are to denote the significant figures of the resistance and the 11th digit is the number of zeros following ( 对于 E-96 系列 ≤2% 的产品，第 8 位数到第 10 位数表示阻值的有效数，第 11 位数表示有几个 0).

c) For the code to the significant figures to E-24 & E-96 series, please refer to page 170 & 171 of the standards Resistance Value list.( 有效数 E-24 和 E-96 系列 , 请参考 170 页和 171 页标准阻值表 )

d) The following numbers and the letter codes is to be used to indicate the number of zeros in the 11th digit:
以下数字及字母用来表示第 11 位数有几个 0:

| | | | | | | |
|---|---|---|---|---|---|---|
| $0 = 10^0$ | $1 = 10^1$ | $2 = 10^2$ | $3 = 10^3$ | $4 = 10^4$ | $5 = 10^5$ | $6 = 10^6$ |
| $J = 10^{-1}$ | $K = 10^{-2}$ | $L = 10^{-3}$ | $M = 10^{-4}$ | $N = 10^{-5}$ | $P = 10^{-6}$ | |

e) For Cement Resistors the 8th digit will be coded with "W" or "P" to denote Wire-wound type or Power Film type respectively of the Cement Fixed Resistor proudct. The 9th to 11th please refer to point 4.a ( 水泥电阻第 8 位数 "W" 或 "P" 用来表示绕线型或切割型，第 9 位数到第 11 位数请参考 4.a)
Example ( 例 ):

| E-24 series 系列 | E-96 series 系列 | Cement Resistors 水泥型固定电阻值 |
|---|---|---|
| 0120 = 12 ohm | 1210 = 121 ohm | W120 = 12 ohm Wire-wound type 绕线型 |
| 0123 = 12K ohm | 1302 = 13K ohm | W12J = 1.2 ohm Wire-wound type 绕线型 |
| 012J = 1.2 ohm | 196J = 19.6 ohm | P273 = 27 kohm Powe Film type 切割型 |

5. The 12th, 13th & 14th digits ( 第 12 位数、13 位数和 14 位数 ):

a) The 12th digit is to denote the Packaging type with the following codes ( 第 12 位数表示包装方式，采用如下代码 ):
A = Tape / Box (Ammo Pack) [ 编带 / 盒装（带装）] C = Bulk in Cassette (for Chip product)[ 散装盒（晶片产品）]
B = Bulk / Box ( 散装 / 盒装 ) T = Tape / Reel ( 编带 / 卷装 ) P = Tape / Box of PT-26 product [ 编带 / 盒装（PT-26 产品）]

b) The 13th digit is normally to indicate the Packing Quantity of Tape/Box or Tape/Reel packaging types. Except for Chip products Bulk packing, this digit should be filled "0" or other products with "Bulk/Box packaging requirement. The following letter codes is to be used for some packaging quantities ( 第 13 位数一般表示包装数量对于 T/B 或 T/R 型，除了晶片散装外，其他产品的散装包装用 "0" 表示数量。下列字母说明包装数量 ).
A = 500pcs ( 只 ) B = 2,500pcs ( 只 ) C = 10,000pcs ( 只 ) N = 12,500pcs ( 只 ) E = 15,000pcs ( 只 )
D = 20,000pcs ( 只 ) G = 25,000pcs ( 只 ) L = 45,000pcs ( 只 ) H = 50,000pcs ( 只 ) J = 60,000pcs ( 只 )
Example ( 例 ):

| CHIP product ( 晶片产品 ) | Other products ( 其它产品 ) |
|---|---|
| TD = T/R-20,000 | A5 = T/B-5,000 |
| TE = T/R-15,000 | TB = T/R-2,500 |
| T4 = T/R-4,000 | B0 = B/B ( 可提供标准包装 ) |

c) For the Forming type products, the 13th & 14th digits are used to denote the forming types of the product with the following letter codes
( 对于成型产品第 13 位数和第 14 位数用来表示成型产品，如下字母表示 ):
MF = M type with Flattened lead wire (M 型打扁加工 ) F0 = F type 型
MK = M type with Kinked lead wire (M 型打弯加工 ) F1 = F1 type 型
ML = M type with normal lead wire (M 型加工 ) F2 = F2 type 型
MC = M type with kinked lead wire (M 型打弯加工 ) F3 = F3 type 型

d) For power rating over 100watt, the 12th to the 14th digits are to denote the actual wattage of the products
( 当功率超过 100W 时，它的第 12 位数到 14 位数用来表示产品的实际功率 ):
Example ( 例 ): 100 = 100watt ( 瓦 ) 150 = 150watt ( 瓦 ) 225 = 225watt ( 瓦 )

e) For some products, the 14th digit alone can use to denote special features or additional information with the following codes
( 对于某些产品第 14 位可以显示特性和附加信息，如下字母 ):
P = Panasert type (Panasert 型 ) 1 = Avisert 1 type (Avisert 1 型 ) 2 = Avisert 2 type (Avisert 2 型 )
3 = Avisert 3 type (Avisert 3 型 ) A = CO 1/4W - A type ( 切割型 CO 1/4W-A 型 ) B = CO 1/4W - B type ( 切割型 CO 1/4W-B 型 )
E = used to denote the "Environment Protection, lead Free type" of SMD category resistors (now, this became the Standard type of SMD)
( 晶片电阻，晶片排阻及网络电阻器 " 环保无铅型 ")

f) For some products, the 14th digit alone can use to denote special features or additional information with the following codes
( 对于某些产品第 14 位可以显示特性和附加信息，如下字母 ):
B=1/32W G=1/16W F=1/10W G=1/8W H=1/6W J=1/4W K=1/3W M=1/2W
N=3/4W P=1W S=Special

## *4* Band Color Code (available for CFR, MOR, KNP & 2% or 5% of MF products)

## 4 道色码 ( 适用于 CFR, MOR, KNP & 2% 或 5% of MF 产品 )

| 1st Band 第一道 | |
|---|---|
| Black 黑 | = 0 |
| Brown 棕 | = 1 |
| Red 红 | = 2 |
| Orange 橙 | = 3 |
| Yellow 黄 | = 4 |
| Green 绿 | = 5 |
| Blue 蓝 | = 6 |
| Violet 紫 | = 7 |
| Gray 灰 | = 8 |
| White 白 | = 9 |

| 2nd Band 第二道 | |
|---|---|
| Black 黑 | = 0 |
| Brown 棕 | = 1 |
| Red 红 | = 2 |
| Orange 橙 | = 3 |
| Yellow 黄 | = 4 |
| Green 绿 | = 5 |
| Blue 蓝 | = 6 |
| Violet 紫 | = 7 |
| Gray 灰 | = 8 |
| White 白 | = 9 |

| 3rd Band 第三道 | |
|---|---|
| Black 黑 | = Multiply by 乘积倍数 1 ($10^0$) |
| Brown 棕 | = Multiply by 乘积倍数 10 ($10^1$) |
| Red 红 | = Multiply by 乘积倍数 100 ($10^2$) |
| Orange 橙 | = Multiply by 乘积倍数 1,000 ($10^3$) |
| Yellow 黄 | = Multiply by 乘积倍数 10,000 ($10^4$) |
| Green 绿 | = Multiply by 乘积倍数 100,000 ($10^5$) |
| Blue 蓝 | = Multiply by 乘积倍数 1,000,000 ($10^6$) |
| Violet 紫 | = Multiply by 乘积倍数 10,000,000 ($10^7$) |
| Gold 金 | = Multiply by 乘积倍数 0.1 ($10^{-1}$) |
| Silver 银 | = Multiply by 乘积倍数 0.01 ($10^{-2}$) |

| 4th Band 第四道 | |
|---|---|
| Red 红 | = ±2% |
| Gold 金 | = ±5% |
| Silver 银 | = ±10% |

## *5* Band Color Code (available for MF 1% & FRN Proudcts)

## 5 道色码 ( 适用于 MF 1% & FRN 产品 )

| 1st Band 第一道 | |
|---|---|
| Black 黑 | = 0 |
| Brown 棕 | = 1 |
| Red 红 | = 2 |
| Orange 橙 | = 3 |
| Yellow 黄 | = 4 |
| Green 绿 | = 5 |
| Blue 蓝 | = 6 |
| Violet 紫 | = 7 |
| Gray 灰 | = 8 |
| White 白 | = 9 |

| 2nd Band 第二道 | |
|---|---|
| Black 黑 | = 0 |
| Brown 棕 | = 1 |
| Red 红 | = 2 |
| Orange 橙 | = 3 |
| Yellow 黄 | = 4 |
| Green 绿 | = 5 |
| Blue 蓝 | = 6 |
| Violet 紫 | = 7 |
| Gray 灰 | = 8 |
| White 白 | = 9 |

| 3rd Band 第三道 | |
|---|---|
| Black 黑 | = 0 |
| Brown 棕 | = 1 |
| Red 红 | = 2 |
| Orange 橙 | = 3 |
| Yellow 黄 | = 4 |
| Green 绿 | = 5 |
| Blue 蓝 | = 6 |
| Violet 紫 | = 7 |
| Gray 灰 | = 8 |
| White 白 | = 9 |

| 4th Band 第四道 | |
|---|---|
| Black 黑 | = Multiply by 乘积倍数 1 ($10^0$) |
| Brown 棕 | = Multiply by 乘积倍数 10 ($10^1$) |
| Red 红 | = Multiply by 乘积倍数 100 ($10^2$) |
| Orange 橙 | = Multiply by 乘积倍数 1,000 ($10^3$) |
| Yellow 黄 | = Multiply by 乘积倍数 10,000 ($10^4$) |
| Green 绿 | = Multiply by 乘积倍数 100,000 ($10^5$) |
| Blue 蓝 | = Multiply by 乘积倍数 1,000,000 ($10^6$) |
| Violet 紫 | = Multiply by 乘积倍数 10,000,000 ($10^7$) |
| Gold 金 | = Multiply by 乘积倍数 0.1 ($10^{-1}$) |
| Silver 银 | = Multiply by 乘积倍数 0.01 ($10^{-2}$) |

| 5th Band 第五道 | |
|---|---|
| Violet | = ±0.1% |
| Blue | = ±0.25% |
| Green | = ±0.5% |
| Brown | = ±1% |

## Ceramic Rods For Resistors ( 电阻器用陶瓷基体 )

| | | | |
|---|---|---|---|
| | Ceramic Rod ( 瓷棒 ) | 146 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |

## Capped & Sorted Ceramic Rod ( 组帽棒 )

| | | | |
|---|---|---|---|
| | White Capped Ceramic Rod ( 组帽瓷棒 ) | 148 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| | Carbon Film Capped Ceramic Rod ( 碳膜组帽棒 ) | 150 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| | Metal Film Capped Ceramic Rod ( 金属膜组帽棒 ) | 152 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| | Metal Oxide Film Capped Ceramic Rod ( 金属氧化膜组帽棒 ) | 154 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| | Capped Metal Glaze Film Rod ( 玻璃釉膜组帽棒 ) | 156 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16 |
| | Capped Chemical Deposited Film Rod ( 化学沉积膜组帽棒 ) | 158 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.0×10, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| | Zero Ohm Rod ( 零歐姆棒 ) | 160 | 1.3×2.7, 1.7×5.2 |

## Tin-Plated Steel Cap ( 镀锡铁帽 )

| | | | |
|---|---|---|---|
| | Tin-Plated Steel Cap ( 镀锡铁帽 ) | 162 | Ø1.26, Ø1.64, Ø1.95, Ø2.45, Ø2.90, Ø3.41, Ø3.91, Ø4.90, Ø6.90 |

## Ceramic Case ( 瓷壳 )

| | | | |
|---|---|---|---|
| | PRW series Case (PRW 系列瓷壳 ) | 163 | 2W, 3W, 5W, 7W, 10W, 15W, 20W, 25W |
| | PRM series Case (PRM 系列瓷壳 ) | 163 | 2W, 3W, 5W, 7W, 10W, 15W, 20W, 25W |
| | PRV series Case (PRV 系列瓷壳 ) | 163 | 3W, 5W, 7W, 10W, 15W, 20W |
| | PRT series Case (PRT 系列瓷壳 ) | 163 | 10W, 15W, 20W, 30W, 40W |
| | PFA series Case (PFA 系列瓷壳 ) | 163 | 2W, 3W, 5W, 7W, 10W |

## Packing ( 包装 )

| | | |
|---|---|---|
|  | Ceramic Rod ( 瓷棒 ) | 165 |
| | Filmed & Capped Rod ( 组帽棒 ) | 165 |
| | Zero Ohm Rod ( 零欧姆棒 ) | 166 |
| | Tin-Plated Steel Cap ( 铁帽 ) | 166 |

# Material Characteristics Of Ceramics Rods
# 陶瓷棒特性表



| Material 材质 | | Alumina 氧化铝瓷 | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Product Code 产品代号 | | FS-25 | FS-55 | FS-70 | FS-75 | FS-80 | FS-85 | FS-92 | FS-98 |
| Chemical Analysis 主成份 | | $AL_2O_3$ 25% | $AL_2O_3$ 55% | $AL_2O_3$ 70% | $AL_2O_3$ 75% | $AL_2O_3$ 80% | $AL_2O_3$ 85% | $AL_2O_3$ 92% | $AL_2O_3$ 98% |
| Appearance 外观 | | Dense 致密质 | Dense 致密质 | Dense 致密质 | Dense 致密质 | Dense 致密质 | Dense 致密质 | Dense 致密质 | Dense 致密质 |
| Color 呈色 | | White 白色 | White 白色 | White 白色 | White 白色 | White 白色 | White 白色 | White 白色 | White 白色 |
| Features 特征 | | Good Heat Resistance, High Thermal Conductivity 耐热性优良，热传导性高 | | | | | | | |
| Main Use 主要用途 | | Wire-wound Resistor 绕线电阻器用 | | | | | | | |
| | | | | Film Resistor 膜式电阻器用 | | | | | |
| | | | | | | | Small-size & High power resistor 大功率小型化电阻器用 | | |
| Water Absorption 吸水率 | % | ≤ 0.02 | ≤ 0.02 | ≤0.01 | ≤0.01 | ≤0.01 | ≤0.01 | < 0.02 | < 0.02 |
| Bulk Density 体积密度 | g / $cm^3$ | ≥2.3 | ≥2.8 | ≥3.1 | ≥3.2 | ≥3.2 | ≥3.45 | ≥3.6 | ≥ 3.8 |
| Thermal Expansion Coefficient 热膨胀系数 | $\times10^{-6}$/°C (20-500°C) | > 4.0 | > 5.5 | > 6.1 | > 6.7 | > 7.0 | > 7.3 | > 7.0 | > 7.7 |
| Thermal Conductivity 热传导率 | Cal/ cm.sec. °C | > 0.003 | > 0.008 | > 0.011 | > 0.020 | > 0.015 | > 0.023 | > 0.040 | > 0.050 |
| Dielectric Strength 绝缘强度 | KV/mm | > 9 | > 10 | > 10 | > 10 | > 10 | > 10 | > 10 | > 10 |
| Dielectric Constant 绝缘常数 | 1MHZ | 9.5 | 9.5 | 9.5 | 9.5 | 9.5 | 9.5 | 9.5 | 9.5 |
| Loss Rate 损失率 | 1MHZ | < 0.001 | < 0.001 | < 0.001 | < 0.001 | < 0.001 | < 0.0001 | 0.0001 | 0.0001 |
| Anti-cross break strength 抗折力 | Kg | > 9 | > 10 | > 12 | > 12 | > 16 | > 16 | > 16 | > 16 |

# Ceramic Rod
# 瓷棒

## Feature ( 特性 )

- Aluminum Content 70%, 80%, 85%. (70%, 80%, 85% 含铝量瓷棒 )
- Electronic Ceramic parts in superior performance. ( 属于优良的电子陶瓷产品 )
- Suitable for producing in different types of resistance film.
  ( 适合生产各种膜层的电阻 )




## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | D 直径 | L 长度 | R | |
|---|---|---|---|---|---|
| | | | | ( Ra MIN 最小 ) | ( Rb MAX 最大 ) |
| 1 | 1.3×2.7 | 1.30±0.02 | 2.7±0.1 | 0.15 | 0.45 |
| 2 | 1.7×5.2 | 1.70±0.03 | $5.2^{+0.1}_{-0.2}$ | 0.20 | 0.65 |
| 3 | 1.7×5.5 | 1.70±0.03 | 5.5±0.2 | 0.20 | 0.65 |
| 4 | 1.7×6.0 | 1.70±0.03 | 6.0±0.2 | 0.20 | 0.65 |
| 5 | 2.0×7.5 | $2.00^{+0.04}_{-0.03}$ | 7.5±0.2 | 0.25 | 0.75 |
| 6 | 2.0×8.0 | 2.00±0.03 | 8.0±0.2 | 0.25 | 0.75 |
| 7 | 2.5×8.0 | 2.50±0.04 | 8.0±0.2 | 0.28 | 0.80 |
| 8 | 3.0×8.0 | 3.00±0.04 | 8.0±0.2 | 0.30 | 1.00 |
| 9 | 3.0×10 | 3.00±0.04 | 10.0±0.3 | 0.30 | 1.00 |
| 10 | 3.5×10 | $3.50^{+0.04}_{-0.05}$ | 10.0±0.3 | 0.30 | 1.00 |
| 11 | 4.0×14 | 4.00±0.05 | 14.0±0.3 | 0.35 | 1.20 |
| 12 | 5.0×16 | 5.00±0.05 | 16.0±0.3 | 0.45 | 1.40 |
| 13 | 7.0×23 | 7.00±0.07 | 23.0±0.5 | 0.75 | 2.00 |

**Remark:** any special dimensions (4.0×12, 4.0×22, 4.0×39....) and Aluminum Content can be produced according to customer's request.
**备注 :** 特殊规格的尺寸 (4.0×12, 4.0×22, 4.0×39.....) 及公差和含铝量可以按客户的要求来生产。

## Specification ( 产品规格 )

| Type （瓷 类） | Size （规 格） |
|---|---|
| FS-25 FS-55 FS-70 | 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| FS-75 FS-80 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |
| FS-85 RS-92 FS-98 | 1.3×2.7, 1.7×5.2, 1.7×5.5, 1.7×6.0, 2.0×7.5, 2.0×8.0, 2.5×8.0, 3.0×8.0, 3.5×10, 4.0×14, 5.0×16, 7.0×23 |

## Ordering Procedure (Example:OPD217520000FS)

**订购方式 ( 例如: 膜层用 1.7×5.2 80% 瓷棒 )**




Remark: can produce other Alumina content product according to customer's request.
备注 : 可根据客户的要求订制其他含铝量的产品 .

# Capped Ceramic Rod
## 组帽瓷棒

## Feature ( 特性 )

- Aluminum Content 70%, 80%, 85% (70%, 80%, 85% 含铝量白瓷棒 )
- Electronic Ceramic parts in superior performance ( 属于优良的电子陶瓷产品 )
- Suitable for producing in different types of Wire-wound resistors ( 适合生产绕线电阻 )




1. Ceramic (瓷棒 )
2. Cap (iron) (铁帽 . 铁 )
3. Cap (copper) (铁帽 . 铜层 )
4. Cap (tin) (铁帽 . 锡层 )

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | Capped Ceramic Rod 压帽瓷棒 | | MIN PULLING FORCE 最小拉力 (KG) |
|---|---|---|---|---|
| | | D 直径 | L 长度 | |
| 1 | 1.3×2.7 | 1.54~1.66 | 2.86~3.16 | 2 |
| 2 | 1.7×5.2 | 2.03~2.17 | 5.36~5.76 | 3 |
| 3 | 1.7×5.5 | 2.03~2.17 | 5.66~6.16 | 3 |
| 4 | 1.7×6.0 | 2.03~2.17 | 6.16~6.66 | 3 |
| 5 | 2.0×7.5 | 2.33~2.58 | 7.66~8.27 | 5 |
| 6 | 2.0×8.0 | 2.33~2.57 | 8.16~8.77 | 5 |
| 7 | 2.5×8.0 | 2.82~3.08 | 8.16~8.77 | 6 |
| 8 | 3.0×8.0 | 3.32~3.58 | 8.16~8.77 | 6 |
| 9 | 3.0×10 | 3.32~3.58 | 10.06~10.89 | 6 |
| 10 | 3.5×10 | 3.81~4.08 | 10.06~10.89 | 6 |
| 11 | 4.0×14 | 4.31~4.59 | 14.06~14.89 | 6 |
| 12 | 5.0×16 | 5.41~5.59 | 16.16~16.89 | 6 |
| 13 | 7.0×23 | 7.39~7.61 | 22.96~24.09 | 6 |

## Ordering Procedure (Example: OSC14014000000)

**订购方式 ( 例如 :4.0×14 规格 70% 组帽瓷棒 )**

O S C 1 4 0 1 4 0 0 0 0 0 0

Product Name
表示品名 :
OS= Ceramic Rod for Wire-wound
绕线用瓷棒

Type 表示类别 :
C= Capped Ceramic Rod 组帽

Alumina Content
表示瓷棒含铝量 :
1=Alumina ( 含铝量 ) 70%
2=Alumina ( 含铝量 ) 80%
3=Alumina ( 含铝量 ) 85%
4=Alumina ( 含铝量 ) 25%
5=Alumina ( 含铝量 ) 55%
6=Alumina ( 含铝量 ) 75%
7=Alumina ( 含铝量 ) 92%
8=Alumina ( 含铝量 ) 98%

Size of Rod 表示瓷棒规格 :

| | |
|---|---|
| 1327=1.3×2.7 | 1752=1.7×5.2 |
| 1755=1.7×5.5 | 1760=1.7×6.0 |
| 2075=2.0×7.5 | 2080=2.0×8.0 |
| 2580=2.5×8.0 | 3080=3.0×8.0 |
| 3010=3.0×10 | 3510=3.5×10 |
| 4014=4.0×14 | 5016=5.0×16 |
| 7023=7.0×23 | |

0=Standard 标准品

**Remark:** can produce other Alumina content product according to customer's request.
备注 : 可根据客户的要求订制其他含铝量的产品 .

# Technical parameter of Capped Rods in various film

## 各类膜层组帽棒技术参数



| Type<br>膜层类型 | Characteristic<br>膜层特点 | Resistance range<br>电阻值范围 (Ω) | T.C.R.<br>电阻温度系数<br>(ppm/°C ) | Limit of short time over load<br>短时间过载变化率 |
|---|---|---|---|---|
| Film ceramic rods of carbon film resistor<br>碳膜 | Conductive film made of high-heat temperature decompose carbon material<br>高温热分解碳质导电膜层<br>Ceramic rod with high-conduction material<br>高导热材料基体<br>Low cost<br>低成本 | 1Ω ~2.5Ω<br>2.6Ω ~800Ω<br>801Ω ~5KΩ<br>5.1KΩ ~ 120KΩ | ±300<br>±450<br>0 ~ -700<br>0 ~ -1500 | ≦ (1%+0.05Ω) |
| Film ceramic rods of metal film resistor<br>金属膜 | Vacuum sputtering film ceramic rod adopted<br>采用真空溅射完成膜层<br>Ceramic rod with high-conduction material<br>高导热材料基体<br>Low current noise & T.C.R.<br>低电流噪声、低电阻温度系数<br>Wide resistance range:1Ω ~20KΩ<br>电阻值范围可达 :1Ω ~20KΩ | 0.5Ω ~20KΩ | ±15<br>±25<br>±50 | ≦ (0.5%+0.05Ω) |
| Film ceramic rods of metal oxide film resistor<br>金属氧化膜 | Conductive film made of metal oxide fired at high temperature<br>金属氧化物高温烧成膜层<br>Good overload capacity<br>具有高温负荷能力<br>Ceramic rod with high-conduction material<br>高导热材料基体 | 2Ω ~500Ω | ±350 | Normal size<br>正常尺寸<br>≦ (1%+0.05Ω)<br>Small size<br>小尺寸≦ (2%+0.05Ω) |
| Film ceramic rods of Chemical Deposited Film resistors 化学沉积膜 | Conductive film made of chemical plated metal<br>化学镀金属导电膜层<br>Ceramic rod with high-conduction material<br>高导热材料基体<br>Low cost<br>低成本 | 0.02Ω ~1.3Ω | ±200 | Normal size<br>正常尺寸<br>≦ (1%+0.05Ω)<br>Small size<br>小尺寸≦ (2%+0.05Ω) |
| Film ceramic rods of Metal Glaze film resistors<br>玻璃釉膜 | Conductive film made of high temperature<br>高温烧成贵金属氧化物导电膜层<br>With high overload capacity<br>具有高过负荷能力<br>Wide resistance range:15Ω ~2.5MΩ<br>阻值范围 :15Ω ~2.5MΩ<br>Small T.C.R.: ±100~200ppm/°C<br>温度系数小 :±100~200ppm/°C | 15Ω ~1.3MΩ | ±100<br>±200 | ≦ (1%+0.05Ω) |
| OΩ resistors<br>零欧电阻 | Conductive film made of chemical plated copper<br>化学镀铜导电膜层<br>Ceramic rod with high-conduction material<br>高导热材料基体<br>Low cost<br>低成本 | ≦ 50mΩ | / | / |

# Carbon Film Capped Ceramic Rod

## 碳膜组帽棒

## Feature ( 特性 )

- Filming in CVD technology ( 采用 CVD 技术成膜 )
- Low cost, good performance at High Frequency ( 低成本 , 高频特性好 )
- Wide IRV range, can be sorted accurately ( 初值范围宽 , 并可以精准分类 )




1. Ceramic ( 瓷棒 )
2. Film ( 膜层 )
3. Cap (iron) （铁帽 . 铁 )
4. Cap (copper) （铁帽 . 铜层 )
5. Cap (tin) （铁帽 . 锡层 )

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | Uncapped Filming Rod 着膜棒 | | Capped Filming Rod 组分品 | | MIN PULLING FORCE 最小拉力 (KG) |
|---|---|---|---|---|---|---|
| | | D 直径 | L 长度 | D 直径 | L 长度 | |
| 1 | 1.3×2.7 | 1.30±0.02 | 2.7±0.1 | 1.54~1.66 | 2.86~3.16 | 2 |
| 2 | 1.7×5.2 | 1.70±0.03 | $5.2^{+0.1}_{-0.2}$ | 2.03~2.17 | 5.36~5.76 | 3 |
| 3 | 1.7×5.5 | 1.70±0.03 | 5.5±0.2 | 2.03~2.17 | 5.66~6.16 | 3 |
| 4 | 1.7×6.0 | 1.70±0.03 | 6.0±0.2 | 2.03~2.17 | 6.16~6.66 | 3 |
| 5 | 2.0×7.5 | $2.00^{+0.04}_{-0.03}$ | 7.5±0.2 | 2.33~2.58 | 7.66~8.27 | 5 |
| 6 | 2.0×8.0 | 2.00±0.03 | 8.0±0.2 | 2.33~2.57 | 8.16~8.77 | 5 |
| 7 | 2.5×8.0 | 2.50±0.04 | 8.0±0.2 | 2.82~3.08 | 8.16~8.77 | 6 |
| 8 | 3.0×8.0 | 3.00±0.04 | 8.0±0.2 | 3.32~3.58 | 8.16~8.77 | 6 |
| 9 | 3.0×10 | 3.00±0.04 | 10.0±0.3 | 3.32~3.58 | 10.06~10.89 | 6 |
| 10 | 3.5×10 | $3.50^{+0.04}_{-0.05}$ | 10.0±0.3 | 3.81~4.08 | 10.06~10.89 | 6 |
| 11 | 4.0×14 | 4.00±0.05 | 14.0±0.3 | 4.31~4.59 | 14.06~14.89 | 6 |
| 12 | 5.0×16 | 5.00±0.05 | 16.0±0.3 | 5.41~5.59 | 16.16~16.89 | 6 |
| 13 | 7.0×23 | 7.00±0.07 | 23.0±0.5 | 7.39~7.61 | 22.96~24.09 | 6 |

## IRV (Initial Resistance Value) Range ( 初值范围 )

| | | | | | |
|---|---|---|---|---|---|
| 1Ω-2Ω | 8Ω-13Ω | 60Ω-100Ω | 500Ω-800Ω | 4KΩ-7KΩ | 30KΩ-60KΩ |
| 1.5Ω-2.5Ω | 10Ω-20Ω | 80Ω-130Ω | 600Ω-900Ω | 5KΩ-10KΩ | 40KΩ-80KΩ |
| 2Ω-3.5Ω | 15Ω-25Ω | 100Ω-200Ω | 800Ω-1.3KΩ | 6KΩ-12KΩ | 50KΩ-100KΩ |
| 3Ω-5Ω | 20Ω-30Ω | 150Ω-250Ω | 1KΩ-2KΩ | 8KΩ-16KΩ | 60KΩ-120KΩ |
| 4Ω-7Ω | 30Ω-50Ω | 200Ω-400Ω | 1.5KΩ-2.5KΩ | 10KΩ-20KΩ | |
| 5Ω-8Ω | 40Ω-60Ω | 300Ω-500Ω | 2KΩ-4KΩ | 15KΩ-30KΩ | |
| 6Ω-10Ω | 50Ω-80Ω | 400Ω-600Ω | 3KΩ-5KΩ | 20KΩ-40KΩ | |

## Ordering Procedure (Example: CRC11752100200)

**订购方式 ( 例如: CR 70% 1.7×5.2 10-20E)**



# Metal Film Capped Ceramic Rod
## 金属膜组帽棒

## Feature ( 特性 )

- Filming in PCD technology. ( 采用 PCD 成膜技术 ).
- Excellent Temperature coefficient, very low current noise. ( 温度系数范围低 , 电流噪声小 ).
- Wide IRV range, suitable to produce high precision product. ( 初值范围宽 , 适用于生产高精度产品 )




1. Ceramic ( 瓷棒 )
2. Film ( 膜层 )
3. Cap (iron) （铁帽 . 铁 )
4. Cap (copper) （铁帽 . 铜层 )
5. Cap (tin) （铁帽 . 锡层 )

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | Uncapped Filming Rod 着膜棒 | | Capped Filming Rod 组分品 | | MIN PULLING FORCE 最小拉力 (KG) |
|---|---|---|---|---|---|---|
| | | D 直径 | L 长度 | D 直径 | L 长度 | |
| 1 | 1.3x2.7 | 1.30±0.02 | 2.7±0.1 | 1.54~1.66 | 2.86~3.16 | 2 |
| 2 | 1.7x5.2 | 1.70±0.03 | $5.2^{+0.1}_{-0.2}$ | 2.03~2.17 | 5.36~5.76 | 3 |
| 3 | 1.7x5.5 | 1.70±0.03 | 5.5±0.2 | 2.03~2.17 | 5.66~6.16 | 3 |
| 4 | 1.7x6.0 | 1.70±0.03 | 6.0±0.2 | 2.03~2.17 | 6.16~6.66 | 3 |
| 5 | 2.0x7.5 | $2.00^{+0.04}_{-0.03}$ | 7.5±0.2 | 2.33~2.58 | 7.66~8.27 | 5 |
| 6 | 2.0x8.0 | 2.00±0.03 | 8.0±0.2 | 2.33~2.57 | 8.16~8.77 | 5 |
| 7 | 2.5x8.0 | 2.50±0.04 | 8.0±0.2 | 2.82~3.08 | 8.16~8.77 | 6 |
| 8 | 3.0x8.0 | 3.00±0.04 | 8.0±0.2 | 3.32~3.58 | 8.16~8.77 | 6 |
| 9 | 3.0x10 | 3.00±0.04 | 10.0±0.3 | 3.32~3.58 | 10.06~10.89 | 6 |
| 10 | 3.5x10 | $3.50^{+0.04}_{-0.05}$ | 10.0±0.3 | 3.81~4.08 | 10.06~10.89 | 6 |
| 11 | 4.0x14 | 4.00±0.05 | 14.0±0.3 | 4.31~4.59 | 14.06~14.89 | 6 |
| 12 | 5.0x16 | 5.00±0.05 | 16.0±0.3 | 5.41~5.59 | 16.16~16.89 | 6 |
| 13 | 7.0x23 | 7.00±0.07 | 23.0±0.5 | 7.39~7.61 | 22.96~24.09 | 6 |

## IRV (Initial Resistance Value) Range ( 初值范围 )

| | | | | | |
|---|---|---|---|---|---|
| 0.5Ω-0.8Ω | 4Ω-7Ω | 20Ω-30Ω | 100Ω-200Ω | 600Ω-900Ω | 4KΩ-7KΩ |
| 0.8Ω-1.3Ω | 5Ω-8Ω | 30Ω-50Ω | 150Ω-250Ω | 800Ω-1.3KΩ | 5KΩ-10KΩ |
| 1Ω-2Ω | 6Ω-10Ω | 40Ω-60Ω | 200Ω-400Ω | 1KΩ-2KΩ | 6KΩ-12KΩ |
| 1.5Ω-2.5Ω | 8Ω-13Ω | 50Ω-80Ω | 300Ω-500Ω | 1.5KΩ-2.5KΩ | 8KΩ-16KΩ |
| 2Ω-3.5Ω | 10Ω-20Ω | 60Ω-100Ω | 400Ω-600Ω | 2KΩ-4KΩ | 10KΩ-20KΩ |
| 3Ω-5Ω | 15Ω-25Ω | 80Ω-130Ω | 500Ω-800Ω | 3KΩ-5KΩ | |

## Ordering Procedure (Example: MFC11752101201)

**订购方式 ( 例如: MF 70% 1.7×5.2 100-200Ω)**



# Metal Oxide Film Capped Ceramic Rod

## 金属氧化膜组帽棒

## Feature ( 特性 )

- Conductive Film Layer produced under High Temperature ( 高温烧成导电膜层 )
- Good Performance under High Temperature environment ( 高温负荷能力强 )
- First Choice for Power type resistor materials ( 功率型产品优选原料 )




1. Ceramic ( 瓷棒 )
2. Film ( 膜层 )
3. Cap (iron) （铁帽 . 铁 )
4. Cap (copper) （铁帽 . 铜层 )
5. Cap (tin) （铁帽 . 锡层 )

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | Uncapped Filming Rod 着膜棒 | | Capped Filming Rod 组分品 | | MIN PULLING FORCE 最小拉力 (KG) |
|---|---|---|---|---|---|---|
| | | D 直径 | L 长度 | D 直径 | L 长度 | |
| 1 | 1.3×2.7 | 1.30±0.02 | 2.7±0.1 | 1.54~1.66 | 2.86~3.16 | 2 |
| 2 | 1.7×5.2 | 1.70±0.03 | $5.2^{+0.1}_{-0.2}$ | 2.03~2.17 | 5.36~5.76 | 3 |
| 3 | 1.7×5.5 | 1.70±0.03 | 5.5±0.2 | 2.03~2.17 | 5.66~6.16 | 3 |
| 4 | 1.7×6.0 | 1.70±0.03 | 6.0±0.2 | 2.03~2.17 | 6.16~6.66 | 3 |
| 5 | 2.0×7.5 | $2.00^{+0.04}_{-0.03}$ | 7.5±0.2 | 2.33~2.58 | 7.66~8.27 | 5 |
| 6 | 2.0×8.0 | 2.00±0.03 | 8.0±0.2 | 2.33~2.57 | 8.16~8.77 | 5 |
| 7 | 2.5×8.0 | 2.50±0.04 | 8.0±0.2 | 2.82~3.08 | 8.16~8.77 | 6 |
| 8 | 3.0×8.0 | 3.00±0.04 | 8.0±0.2 | 3.32~3.58 | 8.16~8.77 | 6 |
| 9 | 3.0×10 | 3.00±0.04 | 10.0±0.3 | 3.32~3.58 | 10.06~10.89 | 6 |
| 10 | 3.5×10 | $3.50^{+0.04}_{-0.05}$ | 10.0±0.3 | 3.81~4.08 | 10.06~10.89 | 6 |
| 11 | 4.0×14 | 4.00±0.05 | 14.0±0.3 | 4.31~4.59 | 14.06~14.89 | 6 |
| 12 | 5.0×16 | 5.00±0.05 | 16.0±0.3 | 5.41~5.59 | 16.16~16.89 | 6 |
| 13 | 7.0×23 | 7.00±0.07 | 23.0±0.5 | 7.39~7.61 | 22.96~24.09 | 6 |

## IRV (Initial Resistance Value) Range ( 初值范围 )

| | | | |
|---|---|---|---|
| 2Ω-3.5Ω | 8Ω-13Ω | 40Ω-60Ω | 150Ω-250Ω |
| 3Ω-5Ω | 10Ω-20Ω | 50Ω-80Ω | 200Ω-400Ω |
| 4Ω-7Ω | 15Ω-25Ω | 60Ω-100Ω | 300Ω-500Ω |
| 5Ω-8Ω | 20Ω-30Ω | 80Ω-130Ω | |
| 6Ω-10Ω | 30Ω-50Ω | 100Ω-200Ω | |

## Ordering Procedure (Example: MOC11752101201)

**订购方式 ( 例如: MO 70% 1.7×5.2 100-200Ω)**



# Metal Glaze Capped Ceramic Rod
## 玻璃釉膜组帽棒

## Feature ( 特性 )

- Good performance against Humidity environment ( 耐湿特性好 )
- Wide IRV range, can be sorted accurately
  ( 初值范围宽 , 并可以精准分类 )
- Best choice for Anti-surge product （抗浪涌型产品的优选原料 )




1. Ceramic ( 瓷棒 )
2. Film ( 膜层 )
3. Cap (iron) （铁帽 . 铁 )
4. Cap (copper) （铁帽 . 铜层 )
5. Cap (tin) （铁帽 . 锡层 )

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | Uncapped Filming Rod 着膜棒 | | Capped Filming Rod 组分品 | | MIN PULLING FORCE 最小拉力 (KG) |
|---|---|---|---|---|---|---|
| | | D 直径 | L 长度 | D 直径 | L 长度 | |
| 1 | 1.3×2.7 | 1.30±0.02 | 2.7±0.1 | 1.54~1.67 | 2.86~3.16 | 2 |
| 2 | 1.7×5.2 | 1.70±0.03 | $5.2^{+0.1}_{-0.2}$ | 2.03~2.18 | 5.36~5.76 | 3 |
| 3 | 1.7×5.5 | 1.70±0.03 | 5.5±0.2 | 2.03~2.18 | 5.66~6.16 | 3 |
| 4 | 1.7×6.0 | 1.70±0.03 | 6.0±0.2 | 2.03~2.18 | 6.16~6.66 | 3 |
| 5 | 2.0×7.5 | $2.00^{+0.04}_{-0.03}$ | 7.5±0.2 | 2.33~2.73 | 7.66~8.27 | 5 |
| 6 | 2.0×8.0 | 2.00±0.03 | 8.0±0.2 | 2.33~2.60 | 8.16~8.77 | 5 |
| 7 | 2.5×8.0 | 2.50±0.04 | 8.0±0.2 | 2.82~3.11 | 8.16~8.77 | 6 |
| 8 | 3.0×8.0 | 3.00±0.04 | 8.0±0.2 | 3.32~3.60 | 8.16~8.77 | 6 |
| 9 | 3.0×10 | 3.00±0.04 | 10.0±0.3 | 3.32~3.60 | 10.06~10.89 | 6 |
| 10 | 3.5×10 | $3.50^{+0.04}_{-0.05}$ | 10.0±0.3 | 3.81~4.10 | 10.06~10.89 | 6 |
| 11 | 4.0×14 | 4.00±0.05 | 14.0±0.3 | 4.31~4.67 | 14.06~14.89 | 6 |
| 12 | 5.0×16 | 5.00±0.05 | 16.0±0.3 | 5.41~5.62 | 16.16~16.89 | 6 |

## IRV (Initial Resistance Value) Range ( 初值范围 )

| | | | | |
|---|---|---|---|---|
| 15Ω-25Ω | 200Ω-400Ω | 3KΩ-5KΩ | 40KΩ-80KΩ | 500KΩ-800KΩ |
| 20Ω-30Ω | 300Ω-500Ω | 4KΩ-7KΩ | 50KΩ-100KΩ | 600KΩ-900KΩ |
| 30ΩE-50Ω | 400Ω-600Ω | 5KΩ-10KΩ | 60KΩ-120KΩ | 800KΩ-1.3MΩ |
| 40Ω-60Ω | 500Ω-800Ω | 6KΩ-12KΩ | 80KΩ-160KΩ | |
| 50Ω-80Ω | 600Ω-900Ω | 8KΩ-16KΩ | 100KΩ-200KΩ | |
| 60Ω-100Ω | 800Ω-1.3KΩ | 10KΩ-20KΩ | 150KΩ-300KΩ | |
| 80Ω-130Ω | 1KΩ-2KΩ | 15KΩ-30KΩ | 200KΩ-400KΩ | |
| 100Ω-200Ω | 1.5KΩ-2.5KΩ | 20KΩ-40KΩ | 300KΩ-500KΩ | |
| 150Ω-250Ω | 2KΩ-4KΩ | 30KΩ-60KΩ | 400KΩ-700KΩ | |

## Ordering Procedure (Example: MGC32580104204)

**订购方式 ( 例如: MG 85% 2.5×8.0 100-200KΩ)**



# Chemical Nickel - Plating Film Capped Ceramic Rod
## 化学沉积膜组帽棒

## Feature ( 特性 )

- Conductive layer (Ni) deposited by Chemical method ( 化学镀镍形成导电膜层 )
- Extremely Low Resistance value ( 超低阻值 )
- Specially used for Low Resistance range product ( 其他膜层低阻部分的替代品 )




1. Ceramic ( 瓷棒 )
2. Film ( 膜层 )
3. Cap (iron) （铁帽 . 铁 )
4. Cap (copper) （铁帽 . 铜层 )
5. Cap (tin) （铁帽 . 锡层 )

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | Uncapped Filming Rod 着膜棒 | | Capped Filming Rod 组分品 | | MIN PULLING FORCE 最小拉力 (KG) |
|---|---|---|---|---|---|---|
| | | D 直径 | L 长度 | D 直径 | L 长度 | |
| 1 | 1.3×2.7 | 1.28~1.33 | 2.7±0.1 | 1.54~1.67 | 2.86~3.16 | 2 |
| 2 | 1.7×5.2 | 1.67~1.74 | $5.2^{+0.1}_{-0.2}$ | 2.03~2.18 | 5.36~5.76 | 3 |
| 3 | 1.7×5.5 | 1.67~1.74 | 5.5±0.2 | 2.03~2.18 | 5.66~6.16 | 3 |
| 4 | 1.7×6.0 | 1.67~1.74 | 6.0±0.2 | 2.03~2.18 | 6.16~6.66 | 3 |
| 5 | 2.0×7.5 | 1.97~2.19 | 7.5±0.2 | 2.33~2.73 | 7.66~8.27 | 5 |
| 6 | 2.0×8.0 | 1.97~2.06 | 8.0±0.2 | 2.33~2.60 | 8.16~8.77 | 5 |
| 7 | 2.5×8.0 | 2.46~2.57 | 8.0±0.2 | 2.82~3.11 | 8.16~8.77 | 6 |
| 8 | 3.0×8.0 | 2.96~3.06 | 8.0±0.2 | 3.32~3.60 | 8.16~8.77 | 6 |
| 9 | 3.0×10 | 2.96~3.06 | 10.0±0.3 | 3.32~3.60 | 10.06~10.89 | 6 |
| 10 | 3.5×10 | 3.45~3.56 | 10.0±0.3 | 3.81~4.10 | 10.06~10.89 | 6 |
| 11 | 4.0×14 | 3.95~4.13 | 14.0±0.3 | 4.31~4.67 | 14.06~14.89 | 6 |
| 12 | 5.0×16 | 4.95~5.08 | 16.0±0.3 | 5.41~5.62 | 16.16~16.89 | 6 |
| 13 | 7.0×23 | 6.93~7.10 | 23.0±0.5 | 7.39~7.64 | 22.96~24.09 | 6 |

## IRV (Initial Resistance Value) Range ( 初值范围 )

| | | |
|---|---|---|
| 0.02Ω-0.03Ω | 0.10Ω-0.20Ω | 0.80Ω-1.3Ω |
| 0.03Ω-0.05Ω | 0.20Ω-0.30Ω | 1.0Ω-2.0Ω |
| 0.05Ω-0.07Ω | 0.30Ω-0.50Ω | |
| 0.07Ω-0.10Ω | 0.50Ω-0.80Ω | |

## Ordering Procedure (Example: CNC1401480L13K)

**订购方式 ( 例如: CN 70% 4.0×14 0.08-0.13Ω)**



# 0Ω Resistor
## 0Ω 电阻

## Feature ( 特性 )

- Conductive layer formed by Copper Plating (or Tin plating) process ( 电镀铜层或锡层作为导电膜层 )
- Resistance value can be lowest to mini ohm range ( 阻值可低至 mΩ)
- Ceramic rod core or Alloy rod core ( 陶瓷棒或合金棒作为基体材料 )




1. Ceramic (瓷棒 )
2. Film (膜层 )
3. Cap (iron) (铁帽 . 铁 )
4. Cap (copper) (铁帽 . 铜层 )
5. Cap (tin) (铁帽 . 锡层 )

## Copper Film Ceramic Rod 镀铜瓷棒 ( 单位: mm)

| NO | Size 规格 | Copper Film Ceramic Rod 镀铜瓷棒 | | Copper Film Capped Ceramic Rod 镀铜组帽棒 | |
|---|---|---|---|---|---|
| | | D 直径 | L 长度 | D 直径 | L 长度 |
| 1 | 1.3x2.7 | 1.30±0.02 | 2.7±0.1 | 1.60~1.70 | 2.89~3.14 |
| 2 | 1.7x5.2 | 1.70±0.03 | $5.2^{+0.1}_{-0.2}$ | 2.09~2.21 | 5.39~5.74 |

Tinned Iron Rod ( 镀锡铁棒 )




1.Fe 铁棒 2.Cu 铜层 3.Sn 锡层

## Tinned Iron Rod ( 镀锡铁棒 ) ( 单位: mm)

| NO | Size 规格 | Tinned Iron Rod 镀锡铁棒 | |
|---|---|---|---|
| | | D 直径 | L 长度 |
| 1 | 1.3x2.7 | 1.50 ± 0.05 | 3.00 ± 0.05 |
| 2 | 1.7x5.2 | 2.00 ± 0.05 | 5.60 ± 0.05 |

## IRV (Initial Resistance Value) Range ( 初值范围 )

Standard resistance value <=50mE, other value or special structure can be specially provided
标准品阻值 ≤50mΩ, 其他阻值或特殊结构的要求可以特别提供

## Ordering Procedure (Example: ZOC11752000000)

**订购方式 ( 例如: ZO 70% 1.7×5.2 0Ω)**




## OrderingProcedure (Example: TOE01327000000)

**订购方式 ( 例如 :0Ω 1.3×2.7 镀锡铁棒 )**



# Tin-Plated Steel Cap
## 铁帽

## Feature ( 特性 )

- Suitable for many different kinds of Electronic parts ( 适用各类电子产品 )
- Full series in different size ( 规格齐全 )
- Surface treatments in Tin & Copper Plating ( 表面经过镀铜镀锡处理 )




1.Fe 铁
2.Cu 铜层
3.Sn 锡层

## Dimension ( 尺寸 ) ( 单位: mm)

| NO | Size 规格 | ØD 直径 | Ød 内径 | H 高度 | R(Max. 最大 ) | t±0.02 |
|---|---|---|---|---|---|---|
| 1 | 1.26 × 0.95 | 1.62±0.02 | 1.265±0.02 | 0.95±0.02 | 0.15 | 0.15 |
| 2 | 1.64 × 1.42 | 2.10±0.02 | 1.64±0.02 | 1.42±0.04 | 0.20 | 0.20 |
| 3 | 1.95 × 1.74 | 2.51±0.02 | 1.93±0.02 | 1.74±0.03 | 0.25 | 0.25 |
| 4 | 1.95 × 1.85 | 2.51±0.02 | 1.93±0.02 | 1.85±0.03 | 0.25 | 0.25 |
| 5 | 2.45 × 1.95 | 3.00±0.02 | 2.44±0.02 | 1.95±0.05 | 0.25 | 0.25 |
| 6 | 2.90 × 2.00 | 3.50±0.03 | 2.92±0.02 | 2.00±0.05 | 0.25 | 0.25 |
| 7 | 2.90 × 2.10 | 3.50±0.03 | 2.92±0.02 | 2.10±0.05 | 0.25 | 0.25 |
| 8 | 3.41 × 2.35 | 4.00±0.03 | 3.41±0.02 | 2.35±0.05 | 0.25 | 0.25 |
| 9 | 3.91 × 2.35 | 4.50±0.03 | 3.91±0.03 | 2.35±0.05 | 0.25 | 0.25 |
| 10 | 4.90 × 2.85 | 5.48±0.02 | 4.88±0.03 | 2.85±0.05 | 0.25 | 0.25 |
| 11 | 6.90 × 3.45 | 7.50±0.02 | 6.90±0.03 | 3.45±0.05 | 0.25 | 0.25 |

## Ordering Procedure (Example: TOCA12600000FS)
## 订购方式 ( 例如: 镀锡铁帽 Ø1.26)

**T O C A 1 2 6 0 0 0 0 0 F S**

- **T O** — Product Name 表示品名 : TO= 镀锡 (Sn)
- **C** — Type 表示类别 : C= Cap 铁帽
- **A** — Thickness 表示厚度 A=0.15mm 厚 B=0.20mm 厚 C=0.25mm 厚
- **1 2 6 0** — Size 表示铁帽尺寸 :
  1260= Ø1.26 / 1640 = Ø1.64
  1950 = Ø1.95 / 2450= Ø 2.45
  2900 = Ø2.90 / 3910 = Ø3.91
  4900 = Ø4.90 / 6900= Ø6.90
- **0 0 0 0** — 0000 for Steel Cap product. Can indicate the specified height in case for non-standard cap 无需描述添 0 补足 ---0000 指定高度 , 例 : 1900--- H1.90mm
- **F S** — FS= For reference 特殊标志

Remark: Special size can be provided according to customer's request
备注 : 特殊尺寸可以按客户的要求订制

## Feature ( 特性 )

- Superior Talc Material ( 优质滑石瓷原料 )
- Full series in different size ( 规格齐全 )
- Hot-briquetting & Dry-pressing two different process ( 热压和干压两种成形方式 )

## Type & Dimension ( 类型及尺寸 ) ( 单位: mm)

| Type ( 类型 ) | | 功率 | 2W | 3W | 5W | 7W | 10W | 15W | 20W | 25W | 30W | 40W |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | PRW | L 长 | 18 | 22 | 22 | 35 | 49 | 49 | 60 | 64 | - | - |
| | | W 宽 | 7 | 8 | 10 | 10 | 10 | 12.5 | 14.5 | 14.5 | - | - |
| | | H 高 | 7 | 8 | 9 | 9 | 9 | 11.5 | 13.5 | 13.5 | - | - |
|  | PRM | L 长 | 20 | 25 | 25 | 38 | 50 | - | 45 | - | - | - |
| | | W 宽 | 11.5 | 12.5 | 12.5 | 12.5 | 12.5 | - | 20 | - | - | - |
| | | H 高 | 7.5 | 8.5 | 9 | 9 | 9 | - | 13.5 | - | - | - |
|  | PRV | L 长 | - | 22 | 27/25 | 35 | 48 | 48 | 63 | - | - | - |
| | | W 宽 | - | 10 | 10 | 10 | 10 | 12.5 | 12.5 | - | - | - |
| | | H 高 | - | 9 | 9 | 9 | 9 | 11.5 | 13.5 | - | - | - |
| | PRT | L 长 | - | - | - | - | 48 | 48 | 63 | - | 75 | 90 |
| | | W 宽 | - | - | - | - | 10 | 12.5 | 12.5 | - | 19 | 19 |
| | | H 高 | - | - | - | - | 9 | 11.5 | 13.5 | - | 19 | 19 |
|  | PFA | L 长 | 13 / 26 | 13 / 26 | 14 / 26 | 26 | 26 | - | - | - | - | - |
| | | W 宽 | 5 | 5 | 5 | 5 | - | - | - | - | - | - |
| | | H 高 | 8.5 / 9 | 13.5 / 13 | 18 | 20 | 18 | - | - | - | - | - |

Remark: Special type and dimension can be orded by customer's request.
备注 : 特殊尺寸可以按客户的要求订制

## Performance Specifications ( 性能 )

| Item | 项目 | Unit 单位 | Specification 标准 |
|---|---|---|---|
| Bulk Density | 体积密度 | $g/cm^3$ | ≥ 2.8 |
| Flexural Strength | 抗折强度 | MPa | 139 |
| Coefficient of Linear Thermal Expansion | 线膨胀系数 (20~100°C) | $\times10^{-6}$/°C | 7.3 |
| Permittivity | 介电常数 (1MHz 20°C) | F/M | 6.2 |
| Dielectric Loss Tangent | 介质损耗角正切值 | $\times10^{-4}$ | 13 |
| Volume Resistivity | 体积电阻率 (100°C) | Ω.cm | ≥ $10^{12}$ |
| Dielectric Strength | 击穿强度 | K v /mm | ≥ 20 |

## Ordering Procedure (Example: CK0PRW0000500FS)

**订购方式 ( 例如 :PRW5W 瓷壳 )**






| Packing ( 标准包装方式 ) | | | | | | |
|---|---|---|---|---|---|---|
| Tpye ( 类 型 ) | | Size ( 尺寸 ) (mm) | | | Quantity ( 数量 ) (KPCS) | |
| Aluminum Content ( 瓷棒 ) | | | | | | |
| | | A | B | C | 袋 | 盒 |
| 1 | 1.3 × 2.7 | 25 | 20 | 45 | 600 | 1800 |
| 2 | 1.7 × 5.2 | 25 | 20 | 45 | 200 | 600 |
| 3 | 1.7 × 5.5 | 25 | 20 | 45 | 200 | 600 |
| 4 | 1.7 × 6.0 | 25 | 20 | 45 | 200 | 600 |
| 5 | 2.0 × 7.5 | 25 | 20 | 45 | 100 | 300 |
| 6 | 2.0 × 8.0 | 25 | 20 | 45 | 100 | 300 |
| 7 | 2.5 × 8.0 | 25 | 20 | 45 | 60 | 180 |
| 8 | 3.0 × 8.0 | 25 | 20 | 45 | 40 | 120 |
| 9 | 3.0 × 10 | 25 | 20 | 45 | 40 | 120 |
| 10 | 3.5 × 10 | 25 | 20 | 45 | 25 | 75 |
| 11 | 4.0 × 14 | 25 | 20 | 45 | 12.5 | 37.5 |
| 12 | 5.0 × 16 | 25 | 20 | 45 | 7.5 | 22.5 |
| 13 | 7.0 × 23 | 25 | 20 | 45 | 2.5 | 7.5 |
| Capped Ceramic Rod ( 组帽棒 ) | | | | | | |
| 1 | 1.3 × 2.7 | 25 | 20 | 45 | 600 | 1800 |
| 2 | 1.7 × 5.2 | 25 | 20 | 45 | 200 | 600 |
| 3 | 1.7 × 5.5 | 25 | 20 | 45 | 200 | 600 |
| 4 | 1.7 × 6.0 | 25 | 20 | 45 | 200 | 600 |
| 5 | 2.0 × 7.5 | 25 | 20 | 45 | 100 | 300 |
| 6 | 2.0 × 8.0 | 25 | 20 | 45 | 100 | 300 |
| 7 | 2.5 × 8.0 | 25 | 20 | 45 | 60 | 180 |
| 8 | 3.0 × 8.0 | 25 | 20 | 45 | 40 | 120 |
| 9 | 3.0 × 10 | 25 | 20 | 45 | 40 | 120 |
| 10 | 3.5 × 10 | 25 | 20 | 45 | 25 | 75 |
| 11 | 4.0 × 14 | 25 | 20 | 45 | 12.5 | 37.5 |
| 12 | 5.0 × 16 | 25 | 20 | 45 | 7.5 | 22.5 |
| 13 | 7.0 × 23 | 25 | 20 | 45 | 2.5 | 7.5 |

| Packing ( 标准包装方式 ) | | | | | | |
|---|---|---|---|---|---|---|
| Tpye ( 类 型 ) | Size ( 尺寸 ) (mm) | | | | Quantity ( 数量 ) (KPCS) | |
| Zero Ohm product ( 0Ω 产品 ) | | | | | | |
| Copper plated 0 ohm in Ceramic core 镀铜瓷棒 | 1.3 × 2.7 | 25 | 20 | 45 | 600 | 1800 |
| Tin plated 0 ohm in Ceramic core 镀铜瓷棒 | 1.7 × 5.2 | 25 | 20 | 45 | 200 | 600 |
| Copper plated 0 ohm in Steel core 铁棒鍍銅鍍錫 | 1.3 × 2.7 | 25 | 20 | 45 | 300 | 900 |
| Tin plated 0 ohm in Steel core 铁棒鍍銅鍍錫 | 1.7 × 5.2 | 25 | 20 | 45 | 100 | 300 |
| Tin-Plated Steel Cap ( 铁帽 ) | | | | | | |
| 1 | 1.26 × 0.95 | 25 | 20 | 45 | 1800 | 5400 |
| 2 | 1.64 × 1.42 | 25 | 20 | 45 | 900 | 2700 |
| 3 | 1.95 × 1.85 | 25 | 20 | 45 | 600 | 1800 |
| 4 | 2.45 × 1.95 | 25 | 20 | 45 | 250 | 750 |
| 5 | 2.90 × 2.10 | 25 | 20 | 45 | 200 | 600 |
| 6 | 3.41 × 2.35 | 25 | 20 | 45 | 150 | 450 |
| 7 | 3.91 × 2.35 | 25 | 20 | 45 | 120 | 360 |
| 8 | 4.90 × 2.85 | 25 | 20 | 45 | 80 | 240 |
| 9 | 6.90 × 3.45 | 25 | 20 | 45 | 40 | 120 |



## Technology Description ( 技术说明 )

厚声采用半导体薄膜创新观念，开发直接电镀铜 (Direct Plating Copper, DPC) 陶瓷基板制程，完美的结合陶瓷散热及金属之特性。此制程利用溅镀及曝光显影方式在陶瓷基板上刻划出各种各样的电路图形，在经由电镀方式不仅可使金属与陶瓷两种不同属性之物质相互紧密结合，线路亦不易脱落 ( 结合力佳 )。透过微显技术线路位置可更准确，线距更缩小之优点。主要应用于高亮度高功率 LED、微波无线通信、太阳能组件及半导体设备等领域。

Uni-Royal using the semiconductor thin-film innovative idea to develop the Direct Plating Copper (DPC) manufacturing process, in order to perform the excellent properties of metal and ceramic. This process developed by sputtering and exposure procedure to produce a wide variety of circuit pattern, by plating integrated the metal and ceramic properties, which the metallized metal will not be easy to peel off (good adhesion). Through this technology, the line position can be more accurately, and more narrow margin of line. Application mainly used in high brightness and high power LED, microwave radio Communication (Wireless) and semiconductor equipment, solar cell and other fields.

## Thin Film Structures 薄膜结构




① Substrate 基板
② Sputter layer 溅镀层
③ Conductive layer 导电层
④ Surface Coating 表面金属层



## Thin Film Technology Feature ( 薄膜技术特征 )

- ✓ 采用薄膜工艺制程获得精准的线路
- ✓ 优化的使用散热陶瓷材料特性
- ✓ 高热可靠性，能承受 300℃ 1min 热板测试
- ✓ 良好的热结合力，可达拉力 1Kg 以上
- ✓ 优异的导通性能，阻抗 ≤0.1E
- ✓ 可按客户要求进行设计
- ✓ 高散热系数材料远优于 PCB 和 LTCC
- ✓ 高热稳定性远优于铝基板
- ✓ 符合 ROHS 要求

- ✓ Thin-film process to obtain accurate of line
- ✓ Optimize the best used of thermal properties of ceramic
- ✓ High reliability , withstand 300 ℃ within 1
- ✓ Good thermal adhesion, tensile reach > 1kg up
- ✓ Excellent conduction performance, impedance under controlled within 0.1E
- ✓ According to customer requirements, OEM available
- ✓ Highly dissipation coefficient than PCB and LTCC
- ✓ Highly heat stability superior than aluminum substrate
- ✓ ROHS compliant for global application

## Process Capability 制程能力

| Item 项目 | Reference Range 参考范围 |
|---|---|
| Material 材质 | $AL_2O_3$、ALN |
| Dimension & Thickness 尺寸厚度 | Sheet size 4.5"114.3x114.3mm 0.38mm, 0.5mm, 1.0mm |
| Set-PIN 上机孔 | Φ1、1.3、1.5、1.8、2mm Depending on the client machine 取决于客户机台 |
| VIA diameter 导通孔径 | 75~150μm Depending on the customer requirement 依客户需求 |
| Line spacing 线路间距 | The smallest diameter of up to 60μm 最小线径可达 60μm |
| Plate margins 板边距 | Sheet design set aside a minimum of 3mm 基板设计预留最小 3mm |
| Copper Thickness 镀层厚度 | Cu 30~75μm |
| Surface Coating 表面处理 | Electronless Gold/Silver 化学镀 ( 金 / 银 )、Eletrolytic Gold/Silver 电镀 ( 金 / 银 )、OSP Antioxidant treatment 抗氧化处理 |

## Reliability Test ( 可靠性测试 )

| NO | Item 项目 | Parameter 测试参数 | Specification 测试规范 |
|---|---|---|---|
| 1 | Adhesion test 附着力试验 | 1. Temp: RT 温度: RT<br>2. Tool: 3M 600# 工具: 3M 600#<br>3. Time adhesive 30 seconds 持续粘合 30 秒<br>4. Angle:180° 角度 : 180° | • The extensor must be no separate 镀层没有被分离 |
| 2 | Thermal Test 热板试验 | 1. Temp:300°C 温度 : 300°C<br>2. Times:1min 时间 :1 分钟 | • No yellowing、blisters 未黄变、起泡现象 |
| 3 | 耐热持久性试验 Thermal durability test | 1. Temp:150°C 温度 : 150°C<br>2. Times:3 hours 时间 :3 小时 | • test before-and-after 试验前后<br>• 尺寸形变量 ≤1%<br>• Size shape variables are 1% or less<br>• 导通阻抗恒低于 5mE<br>• Conduction resistance constant below 5 mE |

## Reference Pattern (Thin-Film) 参考设计图形 ( 薄膜 )

TYPE 1






28×13=364 PCS

TYPE 2






27×20=540 PCS

* Product drawing for reference only 产品图片仅供参考
* Custom Design Circuit could be available on a case to case basis. ( 可按客户特殊要求定制 )

## Ceramic Processing Parts ( 陶瓷加工件 )

- ✓ 优异的加工精准度
- ✓ 高绝缘性能及机械性能强度
- ✓ 客制化服务，可按客户要求进行加工
- ✓ 精密研磨，表面粗化处理等
- ✓ 适用于 LED 照明、汽车组件等产品加工

- ✓ Superior processing of accuracy
- ✓ High performance of insulation and mechanical properties
- ✓ Customized design services, OEM available
- ✓ Precision grinding, coarsening treatment of surface
- ✓ It's suitable for LED lighting, automotive components and other products processing







## Storage conditions ( 储存条件 )

- ✓ Store under 25±5℃,50±10% RH when sealed ( 密封保存 )
- ✓ The expiration date is less than 3 months when unsealed ( 不开封产品保质期在 3 个月以内 )
- ✓ Store under 25±5℃,50±10%RH when unsealed ( 开封产品的储存条件 )
- ✓ Please store unsealed package in airtight containers and try to used within 3 days ( 已开封产品请于 3 日内使用完，并在一个密闭容器内开封 )

# Ordering Procedure

## 订购方式

**Example:** Open version of 3535 model type , Alumina sheet size 4.5" (114.3x114.3x0.5mm), via hole 75μm, total thickness 0.65mm, Gold (Au) thickness ≥0.03μm

**例如：**公版 1 3535 规格 氧化铝基板尺寸 4.5 寸 (114.3x114.3x0.5mm), 孔径要求 75μm 总厚要求 0.65mm 金 ≥0.03μm



# Uni-Royal

# 厚聲集團


台湾总部
新竹县湖口乡新竹工业园区

泰国生产基地
**ROYAL ELECTRONIC FACTORY (THAILAND) CO., LTD**
**20/1-2 Moo 2，Klong Na, Muang, Chachoengsao 24000, Thailand**
**Tel: +66 3882 2404 ~ 2408**
**Email: info@royalohm.com**

昆山生产基地 & 销售基地
昆山厚声电子工业有限公司
中国江苏省昆山市经济技术开发区龙腾路 88 号
**Tel: +86 512 5763 1411 ~ 1433**
**Email: localsales@uniohm.com　globalsales@uniohm.com**

厦门生产基地 & 销售基地
厦门火炬高新区翔安（产业园区）赤埔路 301 号
**Tel: +86 592 708 0691**
**Email：sales01@aeonohm.com**

深圳销售基地
广东省深圳市宝安区西乡镇黄麻布第二工业区 & 九围工业区
**Tel: +86 755 2997 5889　Email: sales-sz@uniohm.com**
**Tel: +86 755 6186 1798　Email: neil@royalohm.com.cn**

| Resistors<br>电阻成品 | Material<br>电子材料 | Heat Dissipation Substrate<br>散热基板 |
|---|---|---|

ROYALOHM　uniohm U Need it!　FOSS　aeon

## 厚声集团 Uni-Royal Group

**厚声国际贸易 (昆山) 有限公司**
**Uniroyal Electronics Global Co., Ltd.**
中国江苏省昆山市经济技术开发区龙腾路88号
88th LongTeng Road, Economic & Technical Development Zone, Kunshan, Jiangu, China, 215 334
+86 512 5763 1400 / 1411 /1422 /1433
markering@uni-royal.cn

**厚声国际贸易 (昆山) 有限公司 深圳分公司**
**Uniroyal Electronics Global Co., Ltd. Shenzhen Branch**
中国广东省深圳市宝安区福海街道桥头社区福永街道同泰时代中心501
501, TongTai Times, Fuyong Street., Qiaotou Community, Fuhai Street, Bao'An District,
Shenzhen, Guangdong, China, 518 000
+86 755 2748 4698 Ext 6033
Info-sz@royalohm.com.cn

**厚声国际贸易 (昆山) 有限公司 厦门分公司**
**Uniroyal Electronics Global Co., Ltd. Xiamen Branch**
中国福建省厦门市火炬高新区（翔安）产业区赤埔路301号
301 Chi-pu Road, Xiamen Torch (Xiang'an) Industrial Zone, Xiamen, Fujian, China, 361 101
+86 592 7080 109
sales@aeonohm.com

**厚声工业股份 (泰国) 有限公司**
**Royal Electronic Factory (Thailand) Co., Ltd.**
20/1-2 Moo 2, Klong Na, Muang, Chachoengsao, Thailand 24000
+66 3882 2404 to 2408
export@royalohm.com

**厚声科技股份 (泰国) 有限公司**
**Royal Technology (Thailand) Co., Ltd.**
35 Moo.4, Don-sai, Banpho, Chachoengsao, Thailand 24140
+66 3809 0921 to 0924
info@royalohm.com

**www.uni-royal.cn**