



TABLE 1



SEC. A-A



注記

1. 嵌合相手品番 : 7282-5073-70 (7C82-5073-70)
2. 適用端子品番 : 7116-4220-08 (7B16-4220-08)
3. 適用ゴム品番 : 7158-3070-80 (7B58-3070-80)
7158-3121-80 (7B58-3121-80)
4. () 内品番は、エアバッグ (A/B) 回路及び特別管理回路に使用する時に適用すること。

NOTES

1. MATING PART NO. : 7282-5073-70 (7C82-5073-70)
2. APPLICABLE TERMINAL NO. : 7116-4220-08 (7B16-4220-08)
3. APPLICABLE RUBBER STOPPER NO. : 7158-3070-80 (7B58-3070-80)
7158-3121-80 (7B58-3121-80)
4. PART NUMBERS IN PARENTHESIS SHALL BE USED FOR AIR BAG (A/B) CIRCUITS AND OTHER CIRCUITS DESIGNATED FOR SPECIAL MONITORING.

LET	DATE	REVISION RECORD	NO.	CHKD
GENERAL TOLERANCE				
10MAX	50MAX	100MAX	2500VR	ANGLE
A	±0.15	±0.2	±0.3	±0.5
B	±0.2	±0.3	±0.55	±0.95
C	±0.3	±0.5	±0.8	±1.4
SPECIFIED				
MASS				
g				

SUB ASSEMBLY PART NO. AND CH. CODE		NO.	PART NO. AND CH. CODE	MATERIAL	COLOR	QTY.
7283-5073-70 ETC. (7C83-5073-70.国)		1	SEE TABLE 2	HPA	SEE TABLE 2	1
		2	7158-4410 (7B58-4410)	HPA	NATURAL	1
		3	7137-2770-80 (7B37-2770-80)	SILICONE RUBBER	BROWN	1
		4	SEE TABLE 2	HPA	SEE TABLE 2	1
		5	7144-1679 (7B44-1679)	STAINLESS STEEL		2

TABLE 2

SUB ASSEMBLY PART NO. AND CH. CODE		PART NO. AND CH. CODE	COLOR
7283-5073-70.国 (7C83-5073-70.国)		7183-5073-70 (7B83-5073-70)	YELLOW
		7158-7110-70 (7B58-7110-70)	YELLOW
		7183-5073-30.国 (7B83-5073-30.国)	BLACK

CUSTOMER		MATERIAL SPEC.		TREAT. & FIN.	
CUSTOMER PART NO.		SEE TABLE 1		ISSUE MARK	
OFFICE		NAME		A/B 1.0III(040III) 2P SEALED CONNECTOR	
VENDOR		TRIAL PART NO.		HOUSING FEMALE SUB ASSEMBLY	
DWG TYPE		DWG DATE		PART NO. 7283-5073-70 ETC. (7C83-5073-70.国)	
R		96.08.20		CH. CODE 2/1 3	
APPROVED		CHECKED		DESIGN DRAWN	
E. SUZUKI		A. GELVERO		DWG NO. 7283-5073-70:R	
96.03.21		04.05.25		SET DWG NO.	
96.03.21		04.05.25		YAZAKI CORPORATION	