

Illuminated pushbutton Ø 22 mm silver contact

82-6151.2133.B001



<https://eao.com/p/82-6151.2133.B001>

Your product:



82-6151.2133.B001
Illuminated pushbutton Ø
22 mm silver contact

FRONT

Front bezel shape:	flush
Front bezel material:	Stainless steel

MOUNTING

Mounting cut-out:	Ø 22 mm
--------------------------	---------

OPERATING-/INDICATION PART

Illumination colour:	Green
Lens colour:	Silver
Lens optics:	opaque
Symbol:	ON/OFF
Lens material:	Stainless steel
Lens shape:	flush
Shape of illumination:	Ring
Lens illumination:	illuminative

ELECTRICAL CHARACTERISTICS

Operating voltage:	12 V AC/DC
Electrical lifetime:	50 000 cycles of operation
Thermal current I_{th}:	5 A
Contacts:	1 C
Pollution degree:	2, according to EN IEC 60947-1

Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground		
Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15		
Voltage	Current		
24 VAC	1 A		
35 VAC	1 A (M12 versio		
110 VAC	1 A		
220 VAC	0.5 A		
Switch rating DC service categorie DC-13 (Silver contacts)			
Voltage	Current		
24 VDC	0.7 A		
35 VDC	0.5 A (M12 vers		
110 VDC	0.2 A		
220 VDC	0.1 A		
according to UL 508 (Silver contacts) $\cos\phi$ 0,75 ... 0,8			
Voltage	Current		
120 VAC	5 A		
240 VAC	3 A		
24 VAC	1 A		
Rated Operational Voltage Ue:	250 VAC		
Rated insulation voltage Ui:	250 V		

MECHANICAL CHARACTERISTIC

Switching system:	Snap-action switching element
Operating force:	4 N ... 7 N
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Mechanical lifetime:	500 000 cycles of operation
Tightening torque:	0.5 ... 0.6 Nm
Weight:	0.018 kg
Operating Travel:	ca. 3 mm
Contact material:	Silver
Switching action:	Maintained

AMBIENT CONDITION

Operating temperature:	- 30 °C ... + 70 °C
IP front protection:	IP65, IP67
Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Storage temperature:	- 40 °C ... + 80 °C
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Vibration resistance:	

10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

CERTIFICATE

Conformities: CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)


Approbations: CB, CCC, C UL, UL

OTHER


Short Description: Illuminated pushbutton Ø 22 mm silver contact, Maintained, 12 V AC/DC, 1 C, Soldering terminal, 2.8 x 0.5 mm, Stainless steel, Green, ON/OFF, Silver

Kind of illumination: Single-LED


Mounting cut-outs:



Component layouts:



Dimension drawings:



A = Solder terminal
B = Screw terminal

Wiring diagrams:

