


## HiPerFET™ Power MOSFET Q2-Class

## IXFN70N60Q2


N-Channel Enhancement Mode  
Avalanche Rated, Low  $Q_g$ , Low Intrinsic  $R_g$   
High  $dV/dt$ , Low  $t_{rr}$



$$\begin{aligned} V_{DSS} &= 600V \\ I_{D25} &= 70A \\ R_{DS(on)} &\leq 88m\Omega \\ t_{rr} &\leq 250ns \end{aligned}$$

| Symbol     | Test Conditions                                                    | Maximum Ratings |            |
|------------|--------------------------------------------------------------------|-----------------|------------|
| $V_{DSS}$  | $T_J = 25^\circ C$ to $150^\circ C$                                | 600             | V          |
| $V_{DGR}$  | $T_J = 25^\circ C$ to $150^\circ C$ , $R_{GS} = 1M\Omega$          | 600             | V          |
| $V_{GSS}$  | Continuous                                                         | $\pm 30$        | V          |
| $V_{GSM}$  | Transient                                                          | $\pm 40$        | V          |
| $I_{D25}$  | $T_C = 25^\circ C$                                                 | 70              | A          |
| $I_{DM}$   | $T_C = 25^\circ C$ , Pulse Width Limited by $T_{JM}$               | 280             | A          |
| $I_A$      | $T_C = 25^\circ C$                                                 | 70              | A          |
| $E_{AS}$   | $T_C = 25^\circ C$                                                 | 5               | J          |
| $dV/dt$    | $I_S \leq I_{DM}$ , $V_{DD} \leq V_{DSS}$ , $T_J \leq 150^\circ C$ | 20              | V/ns       |
| $P_D$      | $T_C = 25^\circ C$                                                 | 890             | W          |
| $T_J$      |                                                                    | -55 ... +150    | $^\circ C$ |
| $T_{JM}$   |                                                                    | 150             | $^\circ C$ |
| $T_{stg}$  |                                                                    | -55 ... +150    | $^\circ C$ |
| $T_L$      | 1.6mm (0.062 in.) from Case for 10s                                | 300             | $^\circ C$ |
| $V_{ISOL}$ | 50/60Hz, RMS $t = 1min$                                            | 2500            | V~         |
|            | $I_{ISOL} \leq 1mA$ $t = 1s$                                       | 3000            | V~         |
| $M_d$      | Mounting Torque                                                    | 1.5/13          | Nm/lb.in.  |
|            | Terminal Connection Torque                                         | 1.3/11.5        | Nm/lb.in.  |
| Weight     |                                                                    | 30              | g          |

miniBLOC, SOT-227 B  
E153432



G = Gate                      D = Drain  
S = Source

Either Source terminal at miniBLOC can be used  
as Main or Kelvin Source

### Features

- Double Metal Process for Low Gate Resistance
- miniBLOC, with Aluminium Nitride Isolation
- Avalanche Rated
- Low Package Inductance
- Fast Intrinsic Rectifier

### Applications

- DC-DC Converters
- Switched-Mode and Resonant-Mode Power Supplies
- DC Choppers
- Pulse Generators

### Advantages

- Easy to Mount
- Space Savings
- High Power Density


| Symbol       | Test Conditions<br>( $T_J = 25^\circ C$ , Unless Otherwise Specified) | Characteristic Values |      |                    |
|--------------|-----------------------------------------------------------------------|-----------------------|------|--------------------|
|              |                                                                       | Min.                  | Typ. | Max.               |
| $BV_{DSS}$   | $V_{GS} = 0V$ , $I_D = 1mA$                                           | 600                   |      | V                  |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$ , $I_D = 8mA$                                       | 3.0                   |      | 5.5 V              |
| $I_{GSS}$    | $V_{GS} = \pm 30V$ , $V_{DS} = 0V$                                    |                       |      | $\pm 200$ nA       |
| $I_{DSS}$    | $V_{DS} = V_{DSS}$ , $V_{GS} = 0V$<br>$T_J = 125^\circ C$             |                       |      | 50 $\mu A$<br>3 mA |
| $R_{DS(on)}$ | $V_{GS} = 10V$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1                   |                       |      | 88 m $\Omega$      |

| Symbol       | Test Conditions<br>( $T_J = 25^{\circ}\text{C}$ , Unless Otherwise Specified)                                                               | Characteristic Values |      |                      |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------|----------------------|
|              |                                                                                                                                             | Min.                  | Typ. | Max.                 |
| $g_{fs}$     | $V_{DS} = 10\text{V}$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1                                                                                  | 36                    | 50   | S                    |
| $C_{iss}$    | $V_{GS} = 0\text{V}$ , $V_{DS} = 25\text{V}$ , $f = 1\text{MHz}$                                                                            | 1340                  | 12   | nF                   |
| $C_{oss}$    |                                                                                                                                             |                       | 345  | pF                   |
| $C_{rss}$    |                                                                                                                                             |                       |      | pF                   |
| $t_{d(on)}$  | <b>Resistive Switching Times</b><br>$V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 35\text{A}$<br>$R_G = 1\Omega$ (External) | 26                    | 26   | ns                   |
| $t_r$        |                                                                                                                                             |                       | 25   | ns                   |
| $t_{d(off)}$ |                                                                                                                                             |                       | 60   | ns                   |
| $t_f$        |                                                                                                                                             |                       | 12   | ns                   |
| $Q_{g(on)}$  | $V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 0.5 \cdot I_{D25}$                                                            | 265                   | 265  | nC                   |
| $Q_{gs}$     |                                                                                                                                             |                       | 57   | nC                   |
| $Q_{gd}$     |                                                                                                                                             |                       | 120  | nC                   |
| $R_{thJC}$   |                                                                                                                                             | 0.05                  | 0.14 | $^{\circ}\text{C/W}$ |
| $R_{thCS}$   |                                                                                                                                             |                       |      | $^{\circ}\text{C/W}$ |

## Source-Drain Diode

| Symbol   | Test Conditions<br>( $T_J = 25^{\circ}\text{C}$ , Unless Otherwise Specified)                         | Characteristic Values |      |               |
|----------|-------------------------------------------------------------------------------------------------------|-----------------------|------|---------------|
|          |                                                                                                       | Min.                  | Typ. | Max.          |
| $I_S$    | $V_{GS} = 0\text{V}$                                                                                  |                       |      | 70 A          |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$                                                           |                       |      | 280 A         |
| $V_{SD}$ | $I_F = I_S$ , $V_{GS} = 0\text{V}$ , Note 1                                                           |                       |      | 1.5 V         |
| $t_{rr}$ | $I_F = 25\text{A}$ , $-di/dt = 100\text{A}/\mu\text{s}$<br>$V_R = 100\text{V}$ , $V_{GS} = 0\text{V}$ | 1.2                   | 8.0  | 250 ns        |
| $Q_{RM}$ |                                                                                                       |                       |      | $\mu\text{C}$ |
| $I_{RM}$ |                                                                                                       |                       |      | A             |

## SOT-227B Outline



| SYM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 1.240  | 1.255 | 31.50       | 31.88 |
| B   | .307   | .323  | 7.80        | 8.20  |
| C   | .161   | .169  | 4.09        | 4.29  |
| D   | .161   | .169  | 4.09        | 4.29  |
| E   | .161   | .169  | 4.09        | 4.29  |
| F   | .587   | .595  | 14.91       | 15.11 |
| G   | 1.186  | 1.193 | 30.12       | 30.30 |
| H   | 1.496  | 1.505 | 38.00       | 38.23 |
| J   | .460   | .481  | 11.68       | 12.22 |
| K   | .351   | .378  | 8.92        | 9.60  |
| L   | .030   | .033  | 0.76        | 0.84  |
| M   | .496   | .506  | 12.60       | 12.85 |
| N   | .990   | 1.001 | 25.15       | 25.42 |
| O   | .078   | .084  | 1.98        | 2.13  |
| P   | .195   | .235  | 4.95        | 5.97  |
| Q   | 1.045  | 1.059 | 26.54       | 26.90 |
| R   | .155   | .174  | 3.94        | 4.42  |
| S   | .186   | .191  | 4.72        | 4.85  |
| T   | .968   | .987  | 24.59       | 25.07 |
| U   | -.002  | .004  | -0.05       | 0.1   |

Notes1: Pulse Test,  $t \leq 300\mu\text{s}$ ; Duty Cycle,  $d \leq 2\%$ .


## Ordering Information

The IXFN70N60Q2 is also available with brass capture nuts in place of the normal Zinc coated steel capture nuts. The ordering part number is IXFN70N60Q2-BN.


IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

|                                                                                  |           |           |           |           |              |              |              |              |              |             |
|----------------------------------------------------------------------------------|-----------|-----------|-----------|-----------|--------------|--------------|--------------|--------------|--------------|-------------|
| IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665    | 6,404,065 B1 | 6,683,344    | 6,727,585    | 7,005,734 B2 | 7,157,338B2 |
|                                                                                  | 4,850,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123 B1 | 6,534,343    | 6,710,405 B2 | 6,759,692    | 7,063,975 B2 |             |
|                                                                                  | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728 B1 | 6,583,505    | 6,710,463    | 6,771,478 B2 | 7,071,537    |             |


**Fig. 1. Output Characteristics**  
@ 25°C




**Fig. 2. Extended Output Characteristics**  
@ 25°C




**Fig. 3. Output Characteristics**  
@ 125°C




**Fig. 4.  $R_{DS(on)}$  Normalized to 0.5  $I_{D25}$  Value vs. Junction Temperature**









**Fig. 5.  $R_{DS(on)}$  Normalized to 0.5  $I_{D25}$  Value vs.  $I_D$**



**Fig. 6. Drain Current vs. Case Temperature**



**Fig. 7. Input Admittance**

**Fig. 8. Transconductance**

**Fig. 9. Source Current vs. Source-To-Drain Voltage**

**Fig. 10. Gate Charge**

**Fig. 11. Capacitance**

**Fig. 12. Maximum Transient Thermal Impedance**




---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).