

1	2	3	4	5	6	7																														
E				<table><tr><td>SIGN</td><td>DATE</td><td>DESCRIPTION</td><td>APPROVER</td></tr><tr><td>△</td><td>10/20'08</td><td>Add APPROVAL: : CQC</td><td>Kind</td></tr><tr><td>△</td><td>12/05'12</td><td>Change the screw plating specification</td><td>Jacky</td></tr><tr><td>△</td><td>12/05'12</td><td>Change the dimensional tolerance</td><td>Jacky</td></tr><tr><td>△</td><td>12/12'13</td><td>Add the view</td><td>Jacky</td></tr><tr><td>△</td><td>12/12'13</td><td>Change the withstand voltage and current</td><td>Jacky</td></tr><tr><td colspan="4"></td><td colspan="2">THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!</td></tr></table>		SIGN	DATE	DESCRIPTION	APPROVER	△	10/20'08	Add APPROVAL: : CQC	Kind	△	12/05'12	Change the screw plating specification	Jacky	△	12/05'12	Change the dimensional tolerance	Jacky	△	12/12'13	Add the view	Jacky	△	12/12'13	Change the withstand voltage and current	Jacky					THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!		E
				SIGN	DATE	DESCRIPTION	APPROVER																													
				△	10/20'08	Add APPROVAL: : CQC	Kind																													
				△	12/05'12	Change the screw plating specification	Jacky																													
				△	12/05'12	Change the dimensional tolerance	Jacky																													
△	12/12'13	Add the view	Jacky																																	
△	12/12'13	Change the withstand voltage and current	Jacky																																	
				THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!																																
D	MATERIALS ELECTRICAL RATED VOLTAGE & CURRENT: cULus 250 V, 10 A / CQC 250 V, 9A△5 WITHSTAND VOLTAGE: AC 2000 V/Min INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C SCREW TORQUE VALUE: 5.3 Lb-In. WIRE RANGE: 22 - 18 AWG 1) MOLDED PARTS: Thermoplastic, UL 94 V-0 BLACK 2) TERMINAL: BRASS, 0.8t, Tin PLATED △ 3) TERMINAL SCREWS: STEEL, M3 △ APPROVAL: PART NO.: Critical dimension:		D																																	
	C	YK 223 xx 0 x x 00G NO. OF POLES 02: 2 POLES 03: 3 POLES 04: 4 POLES ... 30: 30 POLES G: RoHS compliant (lead<4%) In copper Alloy MARK 0: "@" MARK 1: "ANY" MARK TERMINAL & SCREW PLATED 0: TERMINAL & SCREW: G/F △ 1: TERMINAL: G/F, SCREW: Zinc 2: TERMINAL: Sn, SCREW: G/F △ 3: TERMINAL: Sn, SCREW: Zinc		C																																
		B			△ 4		B																													
	A	Dim A Dim B 6.35 12.7			N = Number of poles△ Dim A=Nx6.35+1.0 Dim B=(N-1)x6.35 <table><tr><td>Poles</td><td>Tol.</td><td>Dim A&B</td></tr><tr><td>2-5p</td><td>±0.20</td><td></td></tr><tr><td>6-10p</td><td>±0.25</td><td></td></tr><tr><td>11-16p</td><td>±0.35</td><td></td></tr><tr><td>17-24p</td><td>±0.40</td><td></td></tr><tr><td>25-30p</td><td>±0.50</td><td></td></tr></table>		Poles	Tol.	Dim A&B	2-5p	±0.20		6-10p	±0.25		11-16p	±0.35		17-24p	±0.40		25-30p	±0.50		A											
Poles		Tol.	Dim A&B																																	
2-5p	±0.20																																			
6-10p	±0.25																																			
11-16p	±0.35																																			
17-24p	±0.40																																			
25-30p	±0.50																																			
1	2	3	4	5	6	7																														

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

<u>YK2230203000G</u>	<u>YK2230303000G</u>	<u>YK2230403000G</u>	<u>YK2230503000G</u>	<u>YK2230603000G</u>	<u>YK2230703000G</u>
<u>YK2230803000G</u>	<u>YK2230903000G</u>	<u>YK2231003000G</u>	<u>YK2231103000G</u>	<u>YK2231203000G</u>	<u>YK2231303000G</u>
<u>YK2231403000G</u>	<u>YK2231503000G</u>	<u>YK2231603000G</u>	<u>YK2231703000G</u>	<u>YK2231803000G</u>	<u>YK2231903000G</u>
<u>YK2232003000G</u>	<u>YK2232103000G</u>	<u>YK2232203000G</u>	<u>YK2232303000G</u>	<u>YK2232403000G</u>	<u>YK2232503000G</u>
<u>YK2232603000G</u>	<u>YK2232703000G</u>	<u>YK2232803000G</u>	<u>YK2232903000G</u>	<u>YK2233003000G</u>	