





PART NUMBER	LED COLOR
597-3005-502F,507F	RED (630nm)
597-3035-502F,507F	RED (620nm)
597-3045-502F,507F	RED-ORANGE
597-3205-502F,507F	ORANGE
597-3405-502F,507F	YELLOW
597-3505-502F,507F	YELLOW-GRN





ABSOLUTE MAXIMUM RATINGS AT 25°C						
LED COLOR	POWER DISSIPATON (mW)	FORWARD CURRENT (mA)	PEAK FORWARD CURRENT (mA)	REVERSE VOLTAGE (V)	OPERATING TEMPRATURE (°C)	STORAGE TEMPRATURE (°C)
RED (630nm)	84	35	100	5	-40 TO +100	-40 TO +100
RED (620nm)						
RED-ORANGE						
ORANGE	87	35	100	5	-40 TO +100	-40 TO +100
YELLOW						
YELLOW-GREEN						

OPERATING CHARACTERISTICS AT 25°C							
LED COLOR	IF (mA)	LUMINOUS INTENSITY (mcd)		DOMINANT WAVELENGTH (nm)			FORWARD VOLTAGE
		MIN	TYP	MIN	TYP.	MAX	
RED (630nm)	20	71	90	627	630	633	2 @ IF=20mA
RED (620nm)		90	112	617	620	623	
RED-ORANGE		112	140	612	615	618	
ORANGE		180	224	603	605	607	2.1 @ IF=20mA
YELLOW		56	71	588	590	592	
YELLOW-GREEN		56	71	569	571	573	



Mark	Meanings	Conditions
TS _{max}	Maximum of pre-heating temperature	180°C
TS _{min}	Minimum of pre-heating temperature	140°C
t _s	Time from T _{min} to T _{max}	Over 60sec.
T _L	Reference temperature	230~250°C
t _L	Retention time for T _L	Within 40sec.
T _P	Peak temperature	250°C(Max)
t _p	Time for peak temperature	Within 10sec.
ΔT _R /Δt	Temperature rising rate	Under 3°C/sec.
ΔT _D /Δt	Temperature decreasing rate	Over -3°C/sec.

RECOMMENDED RoHS SOLDER PROFILE



ATTENTION:
OBSERVE PRECAUTIONS FOR
HANDLING ELECTROSTATIC
SENSITIVE DEVICES

NOTES:

- DIALIGHT P/N: 597-3XX5-50XF
SUFFIX -502F FOR 20 PCS ON A SAMPLE TAPE STRIP
SUFFIX -507F FOR 7" DIAMETER REEL, PACKAGED 3000 PCS PER REEL.
- LABELING FOR REEL AND OUTSIDE OF ALUMINUM FOIL BAG:
DIALIGHT P/N, QUANTITY PER REEL, DATE CODE, INTENSITY BIN CODE,
LOT NUMBER AND COUNTRY OF ORIGIN.
- TAPE AND REEL LEDS MAY REQUIRE RE-TAPING AFTER TWELVE MONTHS.
- ESD WITHSTAND VOLTAGE 4000V MAX ACC. TO JS-001-2014
- MSL LEVEL 3

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT CORP. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT CORP.		
DIALIGHT CORP. INTERNAL REFERENCE ONLY - 3D MODEL : 5975006507F-0		
SCALE: 25.000	DRAWING NUMBER	REV
ALL DIM'S IN: INCHES (MM)	C-18369	A
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE	SM LED 0603 PACKAGE
FRACTIONS: ±1/64	TITLE	SINGLE INTENSITY BIN
DECIMALS (.XX): ±.01	MATERIAL	
DECIMALS (.XXX): ±.005		
DECIMALS (.XXXX): ±.0005		
ANGLES: ±1°		
FINISH	Dialight	
FSCM 83330	1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727 (732) 919-3119 www.dialight.com	
SHEET 1 OF 1	FAMILY TABLE:	