








- NOTE
- 1 REFERENCE IS A.
 - 2 LEAD CO-PLANARITY SHALL BE 0.1 MAX.
 - 3 THICKNESS OF SUPPORTING TAPE SHALL BE 0.188(7.5mil) MIN.



RECOMMENDED LAND PATTERN, METAL MASK(FREE)



RECOMMENDED METAL MASK THICKNESS: t=0.15

5	BRASS	TIN PLATING 1#MIN OVER NICKEL 1#MIN			
4	BRASS	TIN PLATING 1#MIN OVER NICKEL 1#MIN	9	(CONNECTOR)	
3	PHOSPHOR BRONZE	GOLD PLATING 0.05#MIN OVER NICKEL 1#MIN	8	POLYSTYRENE	
2	LCP	(BLACK) UL94V-0	7	POLYESTER	
1	LCP	(GRAY) UL94V-0	6	POLYSTYRENE	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm					
SCALE 5 : 1		COUNT	DESCRIPTION OF REVISIONS		
APPROVED : RI. TAKAYASU		09.10.19	DESIGNED		
CHECED : HS. SAKAMOTO		09.10.19	CHECKED		
DESIGNED : MK. YASUMI		09.10.17	DATE		
DRAWN : MK. YASUMI		09.10.17			
DRAWING NO. EDC3-327247-01			PART NO. FH28D-20(10)SB-1SH(C05)		
CODE NO. CL586-1863-0-05			1/2		

Sep.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

