


## Specifications

## 备注 (Remark)

1. 材料 (MATERIAL)  
 胶芯: PA6T+30%G. F UL94V-0, 颜色: 黑色.  
 Housing: PA6T+30%G. F UL94V-0, Color: Black  
 端子: 黄铜, 镀底30μ, 表面镀普金  
 Contact: brass, GOLD PLATING OVER ALL  
 30μ NICKEL UNDERPLATING OVER ALL

## 2. 特性 (characteristics):




额定电流: 3 AMP  
 Rating Current: 3 AMP.  
 接触阻抗: 20 mΩ MAX.  
 Contact Resistance: 20 mΩ MAX.  
 绝缘阻抗: 1000 MΩ MIN.  
 Insulating Resistance: 1000 MΩ MIN.  
 耐电压: AC 500V/分钟.  
 Withstanding Voltage: AC 500V/Minute.  
 温度范围: -40° C to +105° C  
 Temperature Range: -40° C to +105° C



## Ordering Information

F185-12 15 A0 B SY E 1

NO. OF PINS PER ROW	Contact Plating	INSULATOR MATERIAL	PACKING
2~40P	Full Of Gold	Semi-gold	A:PE Bag
	A0=0.8u"	B0=0.8u"	B:Tape & Reel
	A1=1u"	B1=1u"	C:Tube
	A2=1.5u"	B2=1.5u"	D:Tube+CAP
	A3=2u"	B3=2u"	E:Tray
	A4=3u"	B4=3u"	
	A5=5u"	B5=5u"	
	A6=10u"	B6=10u"	
	A7=15u"	B7=15u"	
	A8=20u"	B8=20u"	
	A9=30u"	B9=30u"	
	S1=Ordinary Tin Plated		
	S2=Matte Tin Plated		
	S3=Tin-plated High-temperature		



东莞市宇熙精密连接器有限公司  
Dongguan Yuxi Electronic Co., Ltd.

F185-1215A0BSYE1

2.54排母8.5mm塑高 2\*15P 180度 Y型 PA6T料 镀普金

RoHS COMPLIANT	客编:
注 意 事 项	1. 带序号为必检尺寸 2. 带*为重点检验尺寸 2. 保持力测试: 0.5kg Min (公司标准)

				OPERATION		SCALE		Fit	Yxcon www.yxcon.com	伍思远 2023.07.13	PART NO.	TITLE:	Customer No.
				X.X	±0.25	UNIT	MM						
A0	2023.07.13	/	新版发行	X.XX	±0.20	SHEET	A4	DESIGN					
REV	DATE	SYMBOL	MODIFICATION DESCRIPTION	X.XXX	±0.10	Angle	±3°	CHECK	李青杰				
				DIM	TOL	PROJ.		APPROVE	2023.07.13				