

修 订	标 记	修 改 描 要	签 名	日 期
REV	AO	REVISION DESCRIPTION	SIGNATURE	DATE
		NEW DWG		2016-03-12

SPECIFICATIONS

Current Rating: 3Amps
Insulator resistance: 5000 Megchms min.
Dielectric Withstanding: AC 500V
Operating Temperature: $-40^{\circ}\sim +105^{\circ}\text{C}$
Contating Material: phosphor Bronze
or brass
Insulator Material: PA6T
Plating: Gold flash
UNSPECIFIED TOLERANCE: ± 0.20

Dimen Sions List

Contacts Per Row	A	B	Contacts Per Row	A	B
2*02	2.54	1.27	2*22	27.94	26.67
2*03	3.81	2.54	2*23	29.21	27.94
2*04	5.08	3.81	2*24	30.48	29.21
2*05	6.75	5.08	2*25	31.75	30.48
2*06	7.62	6.35	2*26	33.02	31.75
2*07	8.89	7.62	2*27	34.29	33.02
2*08	10.16	8.89	2*28	35.56	34.29
2*09	11.43	10.16	2*29	36.83	35.56
2*10	12.70	11.43	2*30	38.70	36.83
2*11	13.97	12.70	2*31	39.37	38.10
2*12	15.24	13.97	2*32	40.64	39.37
2*13	16.51	15.24	2*33	41.91	40.64
2*14	17.78	16.51	2*34	43.18	41.91
2*15	19.05	17.78	2*35	44.45	43.18
2*16	20.32	19.05	2*36	45.72	44.45
2*17	21.59	20.32	2*37	46.99	45.72
2*18	22.86	21.59	2*38	46.99	54.61
2*19	24.13	22.66	2*39	49.53	48.26
2*20	25.40	24.13	2*40	50.80	49.53
2*21	26.67	25.40	2*50	63.5	62.23



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

电话: 0755-23304126 传真: 0755-29940187

-TOLERANCES-
UNLESS OTHERWISE SPECIFIED
公差参数表



TITLE:
产品名称: 1.27X1.0双排直插排针L7.2/2.4

X.X ± 0.30 X.X* $\pm 3^{\circ}$

APPD:
核准:

PART NO:
产品编号: HDGC127-PZ2-n

X.XX ± 0.20 X.XX* $\pm 2^{\circ}$

CHECK:
校对: 王建业

DATE SCALE UNIT CODE NUMBER

X.XXX ± 0.10 X.XXX* $\pm 1^{\circ}$

DRAW:
绘图: 黄艳兰

2016-03-12 1:1 mm A001

PCB LAYOUT