



1. FIGURE AND DIMENSIONS (视图及尺寸)



Main technical indicators (主要技术指标)	
1. Mating (插拔次数)	5000
2. Working Temperature (温度)	-20~+105°
3. IP Rating (防护级别)	IP 50
4. Diameter of socket end(插头端直径)	ø 0. 9
5. Rated voltage (额定电压)	1250V
6. Rated Current (额定电流)	10A
7. Shell material (壳体材质)	PC
8. Pin Material (插针材料)	Copper alloy gold plating(铜合金镀金)
9. Insulation resistance (绝缘电阻)	>100MΩ
10. Insulator material (绝缘体材料)	L: PPS, P: PEEK
11. Salt spray test (盐雾测试)	> 72H



Sum up (总结)	
Series (系列)	MI9
Shell style/model (外壳样式/型号)	LPAG: Straight plug, cable collet and nut for fitting a bend relief直塞、电缆夹头和螺母，用于安装弯曲凸起
Button (按键)	3 button(3个按键)
Termination type (终止类型)	Male solder (公焊锡)
Line diameter awg(线材直径)	22AWG-14AWG
Matching parts(配件)	-
14. Nut color (螺母颜色)	G=灰色/J=黄色/A=蓝色/N=黑色/R=红色/V=绿色/B=白色

版本				TITLE	DRAWING NO.	REV.		
REVA4								
REVA3								
REVA2								
REVA1								
DRAW		DATE		PART NO.	UNIT	mm		
CHECK		DATE					SCALE	Free
APPR'D		DATE						
USE				KKB INDUSTRIAL PRECISION CO., LIMITED				
				A0				
				