



## General Description

This product family offers state of the art performance. It is designed for high frequency applications where high efficiency and high reliability are required.



TO-247-2L  
Package

## Features

- Low conduction loss due to low  $V_F$
- Extremely low switching loss by tiny  $Q_c$
- Highly rugged due to better surge current
- Industrial standard quality and reliability



## Applications

- UPS
- Power Inverter
- High performance SMPS
- Power factor correction

Ordering Part Number	Package	Marking
HC3D50170H	TO-247-2L	HC3D50170H



## Absolute Maximum Ratings ( $T_j = 25^\circ\text{C}$ )

Parameter		Symbol	Value	Unit
Reverse voltage (repetitive peak)		$V_{RM}$	1700	V
Reverse voltage (DC)		$V_R$	1700	V
Continuous forward current ( $T_c=145^\circ\text{C}$ )		$I_F$	50 <sup>*1</sup>	A
Surge non-repetitive forward current	PW=10ms sinusoidal, $T_j=25^\circ\text{C}$	$I_{FSM}$ <sup>*2</sup>	150	A
	PW=10ms sinusoidal, $T_j=150^\circ\text{C}$		110	A
	PW=10μs square, $T_j=25^\circ\text{C}$		630	A
$i^2t$ value	1 ≤ PW ≤ 10ms, $T_j=25^\circ\text{C}$	$\int i^2 dt$ <sup>*2</sup>	120	$\text{A}^2\text{s}$
	1 ≤ PW ≤ 10ms, $T_j=150^\circ\text{C}$		60	$\text{A}^2\text{s}$
Junction temperature		$T_j$	175	$^\circ\text{C}$
Range of storage temperature		$T_{stg}$	-55 to +175	$^\circ\text{C}$

\*1 Limited by  $T_j$  \*2 Assumes  $Z_{th(j-a)}$  of 0.16  $^\circ\text{C}/\text{W}$  or less. (Pulse Width = 8.3ms)



**Electrical characteristics ( $T_j = 25^\circ\text{C}$ )**

Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
DC blocking voltage	$V_{DC}$	$I_R = 0.3\text{mA}$	1700	-	-	V
Forward voltage	$V_F$	$I_F = 50\text{A}, T_j = 25^\circ\text{C}$	-	1.65	1.95	V
		$I_F = 50\text{A}, T_j = 150^\circ\text{C}$	-	2.5	-	V
		$I_F = 50\text{A}, T_j = 175^\circ\text{C}$	-	2.8	-	V
Reverse current	$I_R$	$V_R = 1700\text{V}, T_j = 25^\circ\text{C}$	-	5	300	$\mu\text{A}$
		$V_R = 1700\text{V}, T_j = 150^\circ\text{C}$	-	110	-	$\mu\text{A}$
		$V_R = 1700\text{V}, T_j = 175^\circ\text{C}$	-	250	-	$\mu\text{A}$
Total capacitance	C	$V_R = 1\text{V}, f = 1\text{MHz}$	-	3100	-	pF
		$V_R = 1700\text{V}, f = 1\text{MHz}$	-	170	-	pF
Total capacitive charge	$Q_C$	$V_R = 800\text{V}, di/dt = 500\text{A}/\mu\text{s}$	-	158	-	nC
Switching time	$t_C$	$V_R = 800\text{V}, di/dt = 500\text{A}/\mu\text{s}$	-	39	-	ns

**Electrical characteristic curves**

Fig.1  $V_F - I_F$  Characteristics




Fig.2  $V_F - I_F$  Characteristics






Fig.3  $V_R$  -  $I_R$  Characteristics




Fig.4  $V_R$ - $C_t$  Characteristics





Fig.5 Surge non-repetitive forward current vs. Pulse width (Sinusoidal waveform)\*



\* Assumes  $Z_{\text{th(j-a)}}$  of 0.38  $^\circ\text{C}/\text{W}$  or less.  
(Pulse Width = 8.3ms)

Fig.6 Typical capacitance store energy







Fig.7 Equivalent forward current curve



$$V_F = V_{th} + R_{diff} I_F$$

$$V_{th} (T_j) = a_0 + a_1 T_j$$
$$R_{diff} (T_j) = b_0 + b_1 T_j + b_2 T_j^2$$

Symbol	Typical Value	Unit
$a_0$	9.21E-01	V
$a_1$	-1.52E-03	V/°C
$b_0$	1.20E-02	Ω
$b_1$	8.13E-05	Ω/°C
$b_2$	5.64E-07	Ω/°C <sup>2</sup>




$T_j$  in °C; -55 °C <  $T_j$  < °C ;  $I_F$  < 100A



## Package Dimensions

Package TO-247-2L

Unit:mm



	Min	Nom	Max		Min	Nom	Max
A	4.70	5.00	5.20	E1	13.06	13.26	13.56
A1	2.30		2.50	E2	4.90	5.00	5.10
A2	1.90	2.00	2.10	E3	1.50	1.60	1.70
b	1.10	1.20	1.30	e	5.34	5.44	5.54
b2		2.00		L	19.80	20.00	20.32
				L1		4.17	4.50
C	0.5	0.6	0.7	P	3.50	3.60	3.70
D	20.8	20.95	21.1	P1	7.00	7.19	7.40
D1		16.55		S	6.04	6.15	6.3
D2	0.95	1.17	1.35				
E	15.48	15.88	16.28				



### **Attention**

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.