







REV.	ECN NO.	DESCRIPTION	DATE	DESIGN


Part No	Pin	A	B
A254E1L1-2R2P12	2	2.5	7.5
A254E1L1-2R3P12	3	5.0	10.0
A254E1L1-2R4P12	4	7.5	12.5
A254E1L1-2R5P12	5	10.0	15.0
A254E1L1-2R6P12	6	12.5	17.5
A254E1L1-2R7P12	7	15.0	20.0
A254E1L1-2R8P12	8	17.5	22.5
A254E1L1-2R9P12	9	20.0	25.0
A254E1L1-2R10P12	10	22.5	27.5
A254E1L1-2R11P12	11	25.0	30.0
A254E1L1-2R12P12	12	27.5	32.5
A254E1L1-2R13P12	13	30.0	35.0
A254E1L1-2R14P12	14	32.5	37.5
A254E1L1-2R15P12	15	35.0	40.0
A254E1L1-2R16P12	16	37.5	42.5
A254E1L1-2R17P12	17	40.0	45.0



适用线路板(PCB LAYOUT)

序号	品名	材质
1	HA2.5 胶芯	PA66 UL94V-2 Red
2	HA2.5 直针 端子	Copper Alloy/ Tin Plating

Technical Index:
 1. Temperature range: -25°C~85°C.
 2. Rated voltage: 250V DC/AC(rms).
 3. Rated current: 3.0A.
 4. Contact resistance: ≤20mΩ.
 5. Withstanding voltage: 1000V AC/minute.
 6. Insulation resistance: ≥1000MΩ.

TOLERANCE		 深圳聚兴泰电子科技有限公司 Shenzhen Juxingtai Electronic Technology Co., Ltd	
X.X:±0.35	X.X':±3"	PART NO.	TITLE: Socket-type terminal Vertical plug
X.XX:±0.25	X.XX':±2"	A254E1L1-2RXP12	
X.XXX:±0.15		DESIGN: Ethan	MANUFACTURE DWG
UNITS	mm	CHED: Olvia	
MATERILA	---	APPD: Ava	
FINISH	---		 SCALE N:A SHEET 1/1