

P-DI GY - Isolating plugs



3047390
<https://www.phoenixcontact.com/pc/products/3047390>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Isolating plugs, depth: 23.1 mm, width: 3.5 mm, height: 10.8 mm, color: gray

Your advantages

- Can be used in all ...-TG disconnect terminal blocks from the CLIPLINE complete system
- The P-DI isolating plug can be easily removed to release the connection and then "parked" back to front in the disconnect zone

Commercial data

Item number	3047390
Packing unit	50 pc
Minimum order quantity	50 pc
Product key	BE2ZWX
GTIN	4046356140225
Weight per piece (including packing)	0.694 g
Weight per piece (excluding packing)	0.629 g
Customs tariff number	85366990
Country of origin	CN

P-DI GY - Isolating plugs



3047390

<https://www.phoenixcontact.com/pc/products/3047390>

Technical data

Product properties

Product type	Knife
--------------	-------

Dimensions

Width	3.5 mm
Height	10.8 mm
Depth	23.1 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V2
Insulating material	PA
Static insulating material application in cold	-40 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

P-DI GY - Isolating plugs

3047390

<https://www.phoenixcontact.com/pc/products/3047390>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3047390>

	CSA Approval ID: 2030668			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	-	15 A	-	-

	EAC Approval ID: RU C-DE.BL08.B.00511
---	--

	BV Approval ID: 25278/C1 BV
---	--------------------------------

P-DI GY - Isolating plugs



3047390
<https://www.phoenixcontact.com/pc/products/3047390>

Classifications

ECLASS

ECLASS-11.0	27141190
ECLASS-12.0	27141190
ECLASS-13.0	27141190

ETIM

ETIM 9.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

P-DI GY - Isolating plugs



3047390
<https://www.phoenixcontact.com/pc/products/3047390>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com