

Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°c to +105°c

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PA6T
Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)

Dimension antitheses list			
ITEM	PA	PC	L
Standard	4.00	2.40	8.90
Alternate			

PZ 254 - * - N - Z - * - **

No. of Rows 1=Single Row 2=Dual Row	No. of Pins 2~40Pin	Type Z=直插 D=贴片 S=立贴 PS=插贴	Length (产品长度)	Contact G0:Gold G1:1μ" Gold G2:3μ" Gold G3:5μ" Gold G4:10μ" Gold G5:15μ" Gold G6:30μ" Gold S0:Gold S1:Tin	Plating Flash Flash Gold Gold Gold Gold Gold Flash/Tin
---	------------------------	---------------------------------------	------------------	--	--

			GENERAL TOLERANCE		制 图 DRAWING	 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM	TOL	审 核 CHECK				
			X. X	±0.30	批 准 APPROVAL	产 品 名 称 TITLE	2.54双排 直排针(塑高2.5)	版 本 REV.	A
1	初版发行		X. XX	±0.20	比 例 SCALE	产 品 料 号 PART NO.	P2254-2-N-Z-2.5-XX(PA4.0,PC2.4)	单 位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日 期 MODIFY DATE	Angle	±3.0°	投 影 Projection	材 料 MATERIAL		页 次 SHEET	1/1