



Product Overview Momentary Action Switches

www.schurter.com/en/pg09

	Type	Function	IEC max Voltage Current	Number of Poles Illumination	Contact Material	Protection class
	LDT/LDS Frontpanel Switch / Momentary or Latching, Medium Stroke, 10 mm	N.O.	- 200 mA	-	-	-
	MTG Printmount Switch Short Stroke 12.7 mm	N.O.	- 125 mA	non-illuminated	Ag / Au	IP 40
	PTS Switch for Public Transport Systems	-	60 / 50 VAC/DC 250 mA	Ring Illumination	-	-
	6x6 mm tact switches Print and SMD Switch 6x6	N.O.	- 50 mA	non-illuminated	-	IP 40
	PMS Push button for PCB mounting	N.O.	42 VDC 50 mA	non-illuminated	Au	IP 40 and IP 67
	SMS Print and SMD Switch Short Stroke 11.4 mm	N.O.	42 VDC 50 mA	non-illuminated	-	IP 40 and IP 67
	MCS 18 Print Membrane Switch Printmount Short Stroke 18mm	N.O.	- 125 mA	-	Ag / Au	IP 65
	SDK Printmount Switch, Medium Stroke, 7.5 mm	N.O. / N.C.	48 VDC AC: 2 A / DC: 1.2 A	non-illuminated	Ag / Au	-
	MCS 18 Front Membrane Switch Frontpanel Short Stroke 18 mm	N.O.	- 125 mA	-	Ag / Au	-