

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 10mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

| 编 号      | 尺寸 (mm) |       |
|----------|---------|-------|
|          | A       | B     |
| XHB-2AW  | 2.50    | 7.50  |
| XHB-3AW  | 5.00    | 10.00 |
| XHB-4AW  | 7.50    | 12.50 |
| XHB-5AW  | 10.00   | 15.00 |
| XHB-6AW  | 12.50   | 17.50 |
| XHB-7AW  | 15.00   | 20.00 |
| XHB-8AW  | 17.50   | 22.50 |
| XHB-9AW  | 20.00   | 25.00 |
| XHB-10AW | 22.50   | 27.50 |
| XHB-11AW | 25.00   | 30.00 |
| XHB-12AW | 27.50   | 32.50 |
| XHB-13AW | 30.00   | 35.00 |
| XHB-14AW | 32.50   | 37.50 |
| XHB-15AW | 35.00   | 40.00 |
| XHB-16AW | 37.50   | 42.50 |
|          |         |       |

|                   |            |              |  |     |              |                      |  |         |  |                                                                                       |  |     |  |
|-------------------|------------|--------------|--|-----|--------------|----------------------|--|---------|--|---------------------------------------------------------------------------------------|--|-----|--|
| GENERAL TOLERANCE |            | 制 图          |  | 林月旺 |              | 料 号<br>PART NO.      |  | XHB-NAW |  | 版 本<br>REV.                                                                           |  | A   |  |
| X.±0.25           | X.±2°      | 审 核          |  | 李攀进 |              | 品 名<br>TITLE         |  | 带扣直针座   |  | 页 次<br>SHEET                                                                          |  | 1/1 |  |
| .X±0.20           | .X°±1°     | 核 准          |  | 罗观彬 |              | 客 户 料 号<br>CUTL. NO. |  |         |  |  |  | G   |  |
| .XX±0.15          | .XX°±0.5°  |              |  |     |              | 富 港 电 子              |  |         |  |                                                                                       |  |     |  |
| .XXX±0.10         | .XXX°±0.5° | 单 位<br>UNITS |  | MM  | 比 例<br>SCALE |                      |  |         |  |                                                                                       |  |     |  |