

1		2		3		4		5		6							
芯位排布						芯数	3	4	4D	5B	6	8					
						额定电流/电压	3A/60V	3A/60V	4A/60V	3A/30V	1.5A/30V	1.5A/30V					
						额定脉冲电压	1500V	1500V	1500V	800V	800V	800V					
						绝缘阻抗 (MΩ)	≥100	≥100	≥100	≥100	≥100	≥100					
						接触阻抗 (MΩ)	≤ 5	≤ 5	≤ 5	≤ 5	≤ 5	≤ 5					
P.C.B开孔尺寸																	
面板开孔尺寸																	
						技术参数											
						连接方式: 螺纹连接											
						接线方式: 焊板											
						污染等级: 3											
						温度范围: -40°C ~ +80°C											
						防护等级: IP67											
						插拔周期: ≥500											
6 插板式母针直针镀金						pc	3~8	GENERAL TOLERANCE (UNLESS SPECIFIED)		绘图 DWN		W. M 2024. 8. 26					
5 丁腈橡胶 φ9*φ6*1.5黑色						pc	1	≤10 ±0.1		确认 CHK							
4 圆形螺母黄铜 M10*0.75螺纹 (M8板后母座螺母) 亮镍						pc	1	<10~≤20 ±0.2		核准 APVD		品名 TITLE		M8板后安装孔型金属插座 插板式 锁板牙M10*0.75			
3 M8螺纹式板后, 母座铜外壳 锁板牙M10*0.75						pc	1	<20~≤50 ±0.5				品号 PART NO					
2 M8 孔型胶芯长体带倒角 黑色						pc	1	Angle ±1°		单位 UNIT		MM	版本 REV	A	型号 DRAWING NO	M8-Sx-GPFM10	
1 丁腈橡胶 φ7*φ5.4*0.8黑色						pc	1			尺寸 SIZE		A4	页码 SHEET	1 OF 1			
No. Specification						Unit	Q'ty	视角 THIRD ANGLE									
1		2		3		4		5		6							