







PCB LAYOUT

NOTES:

ELECTRICAL:

1. VOLTAGE RATING :125 VAC RMS.
2. CURRENT RATING :1.5 AMP.
3. CONTACT RESISTANCE :30 MILLIOHMS MAX.
4. INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
5. DIELECTRIC STRENGTH :1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

1. HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
2. CONTACT MATERIAL :PHOSPHOR BRONZE $\phi 0.46$ mm.
3. PLATING :GOLD PLATING OVER NICKEL.
4. OPERATING :750 CYCLES MIN.
5. SHIELDING :0.23mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.
6. PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

1. Temperature Range : -25°C~+85°C
2. Relative Humidity : 90~95% (40±2°C)

TOLERANCE TABLE	
.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	Ckmtw 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD			
CHECKED:	DATE:	TITLE: RJ45-8P/8C 53A 弯插 半屏蔽 无耳H:18.5 黑色			
DRAWN: SXA	DATE: 2018-03-05	PART. NO.	R-RJ45R08P-B010		
		UNIT	mm	SCALE	free
		FILE NO.	Ckmtw-RJ45-0409	REV.	A HY04