



AMPHENOL PART NUMBER CONFIGURATION

U77 - C X 1 1 X - X X 1 X

PORTS _____

2 = 1X2 (2 PORTS)
4 = 1X4 (4 PORTS)
6 = 1X6 (6 PORTS)

REAR PINS OPTION _____

0 = STANDARD
4 = REAR PRESS FIT PINS

PACKAGING FOR CAGE _____

1 = TRAY PACKAGING
DUST COVER OPTION
0 = NO DUST COVER
D = WITH DUST COVER

PLATING _____

1 = TIN PLATING
2 = NICKEL PLATING

MATERIAL (RoHS COMPLIANCE):

CAGE:
COPPER ALLOY

PLATING OPTION 1:
100 μ [2.54 μ m] MIN. TIN
PLATING OVER 50 μ (1.27 μ m)
MIN. NICKEL UNDER PLATING.

PLATING OPTION 2:
100 μ [3.81 μ m] MIN. NICKEL
PLATING.

LIGHT PIPE:
CLEAR POLYCARBONATE.

BRACKET FOR LIGHT PIPE:
STAINLESS STEEL.

DUST COVER:
THERMOPLASTIC, COLOR BLACK.

PACKAGING:
TRAY PACKAGING FOR ALL

TEMPERATURE RANGE:
-40°C TO +85°C

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION
MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING
PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

REVISIONS			
SYM	ZONE	ECN, ERN NO.	DATE APPRD.
F		UPDATED (NEW PAGE)	JUN08/08
G		DUST COVER OPTION ADDED	JUL08/09

THIS IS A CAD DRAWING. DO NOT MANUALLY REVISE.

DRAWN J.SI	DATE 2006/02/16	Amphenol Canada Corp.		
DESIGNED J.SI	2006/02/16			
CHECKED X	X			
DWG. APPRD.				
ENG. REL. NO.		TITLE SFP 1XN CAGE, PRESS FIT PINS WITH LIGHT PIPE (SHIP LOOSE) DUST COVER OPTION (SHIP LOOSE)		
REF.	X	DWG. A	DRAWING NO. P-U77-CX11X-XX1X G	
DIMENSIONS ARE IN mm [INCHES]	CODE ID. NO. 03554	SCALE 1:1	WT. ----- SURF. ----- SHEET 1 OF 8	