


Description

The IS280-4x series combine two AlGaAs infrared emitting diodes as the emitter which is optically coupled to a silicon planar phototransistor detector in a plastic SO16 package.

With the robust coplanar double mold structure, IS280-4x series provide the most stable isolation feature.


Features

- High isolation 3750 VRMS
- CTR flexibility available see order information
- AC input with transistor output
- Operating temperature range - 55 °C to 110 °C
- REACH compliance
- Halogen free
- MSL class 1
- Regulatory Approvals
 - UL - UL1577
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC - GB4943.1, GB8898
 - cUL- CSA Component Acceptance Service Notice No. 5A



Applications

- Switch mode power supplies
- Programmable controllers
- Household appliances
- Office equipment



ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNIT	NOTE
INPUT				
Forward Current	I_F	± 60	mA	
Peak Forward Current	I_{FP}	± 1	A	1
Input Power Dissipation	P_I	100	mW	
OUTPUT				
Collector - Emitter Voltage	V_{CEO}	80	V	
Emitter - Collector Voltage	V_{ECO}	6	V	
Collector Current	I_C	50	mA	
Output Power Dissipation	P_O	150	mW	
COMMON				
Total Power Dissipation	P_{tot}	200	mW	
Isolation Voltage	V_{iso}	3750	Vrms	2
Operating Temperature	T_{opr}	-55~110	°C	
Storage Temperature	T_{stg}	-55~125	°C	
Soldering Temperature	T_{sol}	260	°C	

Note 1. 100μs pulse, 100Hz frequency

Note 2. AC For 1 Minute, R.H. = 40 ~ 60%

ELECTRICAL OPTICAL CHARACTERISTICS at $T_a=25^\circ C$


PARAMETER	SYMBOL	MIN	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
INPUT							
Forward Voltage	V_F	-	-	1.4	V	$IF=10mA$	
Input Capacitance	C_{in}	-	10	-	pF	$V=0, f=1kHz$	
OUTPUT							
Collector Dark Current	I_{CEO}	-	-	100	nA	$V_{CE}=20V, IF=0$	
Collector-Emitter Breakdown Voltage	BV_{CEO}	80	-	-	V	$IC=0.1mA, IF=0$	
Emitter-Collector Breakdown Voltage	BV_{ECO}	6	-	-	V	$IE=0.1mA, IF=0$	
TRANSFER CHARACTERISTICS							
Current Transfer Ratio	280-4	CTR	50	-	600	% $IF=1mA, V_{CE}=5V$	
	280-4GB		100	-	600		
CTR Symmetry		0.7	-	1.3		$IF=\pm 1mA, V_{CE}=5V$	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	-	0.07	0.2	V	$IF=20mA, IC=1mA$	
Isolation Resistance	R_{ISO}	10^{12}	10^{14}	-	Ω	$DC500V, 40 \sim 60\% R.H.$	
Floating Capacitance	C_{IO}	-	0.4	1	pF	$V=0, f=1MHz$	
Response Time (Rise)	tr	-	7	18	μs	$V_{CE}=2V, IC=2mA$	3
Response Time (Fall)	tf	-	9	18	μs		3

Note 3. Fig.12&13


Note 4. Fig.14

CHARACTERISTIC CURVES


**Fig.1 Forward Current
vs. Ambient Temperature**




**Fig.2 Collector Power Dissipation
vs. Ambient Temperature**




**Fig.3 Forward Current
vs. Forward Voltage**




**Fig.4 Collector Dark Current
vs. Ambient Temperature**




**Fig.5 Collector Current
vs. Collector-emitter Voltage**



**Fig.6 Collector Current
vs. Collector-emitter Voltage**





CHARACTERISTIC CURVES






Fig.7 Normalized Current Transfer Ratio vs. Forward Current**Fig.8 Normalized Current Transfer Ratio vs. Ambient Temperature****Fig.9 Collector-emitter Saturation Voltage vs. Ambient Temperature****Fig.10 Switching Time vs. Load Resistance**



Fig.11 Frequency Response



TEST CIRCUITS

Fig.12 Test Circuits of Response Time




Fig.13 Curves of Response Time







Fig.14 Test Circuits of Frequency Response






PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)




Recommended Solder Mask (Dimensions in mm unless otherwise stated)






CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option T1



Description	Symbol	Dimension mm (inch)
Tape Width	W	16 ± 0.3 (0.63)
Pitch of Sprocket Holes	P0	4 ± 0.1 (0.15)
Distance of Compartment to Sprocket Holes	F	7.5 ± 0.1 (0.295)
Distance of Compartment to Compartment	P2	2 ± 0.1 (0.079)
	P1	12 ± 0.1 (0.47)



ORDERING AND MARKING INFORMATION

MARKING INFORMATION



AHP4 :Part Number

I: denotes Company Abbr.

Y: denotes 1 digit Year code, Y=Year
(A-2010, B-2011, …, K-2020, L-2021)

WW: denotes 2 digit Week code

ORDERING INFORMATION

IS280-4x

IS – Series Abbr.

280-4 – Part Number

X – Rank (None/GB)


PACKING QUANTITY

Option	Quantity	Quantity – Inner box	Quantity – Outer box
T1	2000 Units/Reel	4 Reels/Inner box	5 Inner box/Outer box = 20k Units




REFLOW INFORMATION

REFLOW PROFILE




IPC-020d-5-1

Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T_{smin})	100	150°C
Temperature Max. (T_{smax})	150	200°C
Time (t_s) from (T_{smin} to T_{smax})	60-120 seconds	60-120 seconds
Ramp-up Rate (t_L to t_p)	3°C/second max.	3°C/second max.
Liquidous Temperature (T_L)	183°C	217°C
Time (t_L) Maintained Above (T_L)	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (t_p) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (T_p to T_L)	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.



TEMPERATURE PROFILE OF SOLDERING WAVE SOLDERING (JESD22-A111 COMPLIANT)



HAND SOLDERING BY SOLDERING IRON

Soldering Temperature	$380+0/-5^{\circ}\text{C}$
Soldering Time	3 sec max.

- One time soldering is recommended for all soldering method.
- Do not solder more than three times for IR reflow soldering.

DISCLAIMER

- ASG is continually improving the quality, reliability, function and design. ASG reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- ASG makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, ASG disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular purpose. The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death. Please contact ASG sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify ASG's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.