

Technical drawing of a rectangular plate with dimensions 10.2 and 5.6. A table to the right lists pin configurations (9P to 2P) and their corresponding dimensions (DIM. A and DIM. B). The 5P configuration is highlighted in red.

9P	40.64	45.72
8P	35.56	40.64
7P	30.48	35.56
6P	25.4	30.48
5P	20.32	25.4
4P	15.24	20.32
3P	10.16	15.24
2P	5.08	10.16
NUMBER OF PINS	DIM. A	DIM. B



适应基板厚度：1.2mm~1.6mm
温度范围：-25℃~85℃
额定电压：250V AC/DC
额定电流：7A
接触电阻：≤0.01Ω
绝缘电阻：≥1000MΩ
耐压：1500V AC/minute

- 1) 材质:见附表;
- 2) 电镀:见附表;
- 3) 塑件表面平整、光洁、无毛刺、气泡、烧焦、变形、浇口无拉伤、多料或缺料等不良现象;
- 4) 端子表面无氧化、电镀不良等现象。



深圳市韩下电子有限公司

DRAW :	黄彬	2021-06-16	TITLE: 插件针座		DRAW NAME: HX-CH5.08-5PZZ		
DESIGN:							
CHECK:	张伟	2021-06-16	SERIES: 1501 SERIES		DRAW NO.		
APPROVED	罗小春	2021-06-16	P/N:				
CUSTOMER DRAWING			REV. 1.00	SCALE N/A	UNIT: mm	SHEET: 1/1	