

[illegible]

NOTES1:

UL Standard

1.

2.Torque value: M2.5, 3.54Lb.in

3.Wire range: 28~12AWG

IEC Standard

2. Torque value: M2.5, 0.4Nm

3.wire range: $0.2 \sim 2.5 \text{ mm}^2$

NOTES2:

1.Housing: PA66 (UL94V-0)

2.Cover: PA66 (UL94V-0)

3.Cage: Brass (Ni Plated)

4.Clamp: Copper alloy (Ni Plated)

5.Screw1: Steel (M2.5,Zn Plated)

6.Screw2: Steel (M2.5,Zn Plated)

NOTES3:

1.Pitch: 7.62mm Poles: 02-24P

2.Stripping length: 7-8mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4.RoHS Compliance

How to order

MX2EDGKM	-	7.62	-	XXP	-	XXXX	-	X	-	X	-	X
产品型号		间距		板数		颜色:		01:常规颜色				A-Z其他定制
				灰色:GY		橙色:OE		02-99:				0:Y一字螺丝
				蓝色:BU		红色:RD		定制颜色				1:S十字螺丝
				黑色:BK		透明色:TT						2:P平头十字螺丝
				绿色:GN		黄色:YW						CU:铜方块
				透明色:TT		白色:WE						FE:铁方块

Pitch Range In mm			Nominal Dimension Range In mm					—		
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	0.1/10		
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°		

ITEM	NAME OF PART		NO. OF PART	Q'TY	MATERIAL		NOTE	
DWG.	CKK	DATE	23.06.20	UNITS	MM	SHEET/OF	1/1	A
CHK.		DATE		SCALE	1 : 1	A4		
APP.		DATE		NAME	MX2EDGKM-7.62-XXP			
 CIXI MAIXU ELECTRONICS CO., LTD. 慈溪迈旭电子有限公司				DWGNO.				