



Technical Index:

1. Temperature range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$.
2. Rated voltage: 600V, AC, DC.
3. Rated current: 5.0A AC, DC.
4. Contact resistance: $\leq 20\text{m}\Omega$.
5. Withstanding voltage: 1500V AC/minute.
6. Insulation resistance: $\geq 1000\text{M}\Omega$.

REV.	ECN NO.	DESCRIPTION	DATE	DESIGN

型号	CKT	A	B
A300E1W2-2B2P12	2*1	0.00	6.00
A300E1W2-2B4P12	2*2	3.00	9.00
A300E1W2-2B6P12	2*3	6.00	12.00
A300E1W2-2B8P12	2*4	9.00	15.00
A300E1W2-2B10P12	2*5	12.00	18.00
A300E1W2-2B12P12	2*6	15.00	21.00
A300E1W2-2B14P12	2*7	18.00	24.00
A300E1W2-2B16P12	2*8	21.00	27.00
A300E1W2-2B18P12	2*9	24.00	30.00
A300E1W2-2B20P12	2*10	27.00	33.00
A300E1W2-2B22P12	2*11	30.00	36.00
A300E1W2-2B24P12	2*12	33.00	39.00

2	端子Contact	黄铜	N*1	表面镀锡
1	基座Wafer	PA66(UL94 V-0)	1	黑色
序号	名称	材料	数量	备注

TOLERANCE

X.X	± 0.20	X.*	$\pm 10^{\circ}$	深圳聚兴泰电子科技有限公司 Shenzhen Juxingtai Electronic Technology Co., Ltd	PART NO.	A300E1W2-2BXP12	TITLE:	MX3.0MM 双排直针带扣带定位柱
.XX	± 0.10	.X*	$\pm 8^{\circ}$		DESIGN:	Ethan	MANUFACTURE DWG	
.XXX	± 0.05	.XX*	$\pm 5^{\circ}$		CHED:	Olvia		
UNITS	mm	APPD:	Ava				SCALE	SHEET
MATERILA	---						N:A	1/1
FINISH	---							

PCB.WELDING DRAWING (TOLERANCE: ± 0.05)