





ROHS



RECOMMENDED PCB LAYOUT
(TOLERANCE:±0.05)

1,ELECTRICAL SPECIFICATIONS:

- 1.1 Rated current and voltage(额定电流):
3A 250V AC(r.m.s)
- 1.2 Dielectric Withstanding Voltage(耐电压) :
1000V AC for one minute
- 1.3 Contact Resistance(接触电阻) :
<20mΩ
- 1.4 Insulation Resistance(绝缘电阻) :
>1000MΩ
- 1.5 Operating Temperature(工作温度) :
-40℃ ~ 105℃

2,MATERIAL SPECIFICATION:

- 2.1 Insulator Material(绝缘体材质):
High Temperature Plastic ,
UL94V-0
- 2.2 Contact Material(端子材质):
Brass

PART NO. LEGEND:

Female Header	FP	6	D	04	S	-A	1	Y	28-B	Packing: B:BOX
Pitch:6=2.54mm										Contact Plating : 1;G/F 7:tin all over
Plastic Height: D=3.50mm										Insulator Material: A:PBT
NO of Contacts: 4										Series No: S

DRAWING:
Hu yatao

CHECKED:
Tony

APPROVAL:
Yang jie

GENERAL TOLERANCE


.X:=±0.30 .X':=±2°
.XX:=±0.20 .XX':=±1°
.XXX:=±0.10 .XXX':=±0.5°

UNIT: MM

PROJECTION:

SCALE: N/A

SHEET: 1/1



CHIN-BAN
electronics (H.K.) co., ltd

DESCRIPTION:
2.54mm Pitch Female Header Double Row DIP180°

PART NO: FP6D04S-A1Y28-B

REV:1.0

CUSTOMER NO:

SIZE: A4