


Features


- SOD-723 package

Marking Code : T4



SOD-723

SOD-723



DIMENSIONS (mm are the original dimensions)

UNIT	A	b _p	c	D	E	H _E	L _p
mm	0.55 0.49	0.32 0.25	0.15 0.08	1.05 0.95	0.65 0.55	1.45 1.35	0.27 0.13

Absolute Maximum Ratings (T_a = 25 °C)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V _{RM}	100	V
Reverse Voltage	V _R	100	V
Average Rectified Forward Current	I _{F(AV)}	150	mA
Non-repetitive Peak Forward Surge Current at t = 1 μs	I _{FSM}	2	A
Power Dissipation	P _{tot}	210	mW
Thermal Resistance from Junction to Ambient Air	R _{θJA}	312	°C/W
Junction Temperature	T _j	150	°C
Storage Temperature Range	T _{stg}	- 65 to + 150	°C

1N4148G

Characteristics at $T_a = 25\text{ }^{\circ}\text{C}$

Parameter	Symbol	Min.	Max.	Unit
Reverse Breakdown Voltage at $I_R = 1\text{ }\mu\text{A}$	$V_{(BR)R}$	100	-	V
Forward Voltage at $I_F = 10\text{ mA}$ at $I_F = 50\text{ mA}$ at $I_F = 150\text{ mA}$	V_F	- - -	0.855 1 1.25	V
Peak Reverse Current at $V_R = 75\text{ V}$ at $V_R = 20\text{ V}$ at $V_R = 75\text{ V}$, $T_J = 150\text{ }^{\circ}\text{C}$ at $V_R = 25\text{ V}$, $T_J = 150\text{ }^{\circ}\text{C}$	I_R	- - - -	1 100 50 30	μA nA μA μA
Total Capacitance at $V_R = 0\text{ V}$, $f = 1\text{ MHz}$	C_T	-	8	pF
Reverse Recovery Time at $I_{rr} = 0.1 \times I_R$, $I_F = I_R = 10\text{ mA}$, $R_L = 100\text{ }\Omega$	t_{rr}	-	4	ns

RATING AND VCHARACTERISTIC CURVES(1N4148G)

