

Crystal Unit

YSX221SL Small Size




Applications

- Smart Wearable
- TWS
- IOT

Features

- Dimensions: 2.50 x 2.05 x 0.55mm
- Standard Frequency: 12 ~ 54MHz

- High Precision and Tight Frequency Stability
- Excellent Heat Resistance and Environmental Characteristics



Specifications (规格参数)

Item	Symbol	Specifications
Nominal Frequency Range 额定频率范围	f _{nom}	12 ~ 54MHz, or specify
Vibration Mode 震动模式	-	AT Fundamental
Load Capacitance 负载电容	CL	8pF, 10pF, 20pF, or specify
Frequency Tolerance 频率偏差 (at 25°C)	f _{tol}	±10ppm, ±20ppm, or specify
Frequency Versus Temperature Characteristics 频率-温度特性	f _{tem}	±20ppm, or specify
Operating Temperature 工作温度	T _{use}	-40~+85°C, or specify
Storage Temperature 储存温度	T _{stg}	-55~125°C
Shunt Capacitance 静态电容	C0	3pF Max
Level of Drive 激励电平	DL	10~200μW Max (100μW typical)
Aging 老化(at 25°C)	f _{age}	±3ppm/year Max

Equivalent Series Resistance (等效串联电阻(ESR))

YSX221SL	
12 ~ 14MHz	150Ω Max
15 ~ 30MHz	100Ω Max
31 ~ 48MHz	60Ω Max
49 ~ 54MHz	50Ω Max

Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)
Top View: 2.5±0.1 x 2.05±0.1 mm, Marking area. Side View: 0.55±0.10 mm height. Bottom View: 0.9 x 0.7 mm pads, pins #1, #2, #3, #4.	Top View Crystal Connection: Pins #1, #2, #3, #4, GND. Top View Suggested Layout: Pad dimensions 1.0, 0.85, 1.0 mm; pad spacing 0.9, 0.65, 0.9 mm.